MILITARY SPECIFICATION

SIMULATOR, TARGET KILL, PARTS FOR AND LOADING, ASSEMBLING AND PACKING

This specification is approved for use within the US Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification contains requirements not covered by the drawings and provides quality assurance provisions for the fabrication of parts for and loading, assembling and packing for one type of simulator designated as Simulator, Target Kill .

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specification and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-P-116	- Preservation - Packaging, Methods of
MIL-A-48078	- Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Center, Attn: AMSMC-QA, Dover, New Jersey 07801-5001 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1370

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:39Z
Check the source to verify that this is the current version before use.

MIL-STD-331	- Fuze and Fuze Components, Environmental and Performance Test For
MIL-STD-810	- Environmental Test Method
MIL-STD-1234	- Pyrotechnics, Sampling, Inspection and Testing

2.1.2 Other Government documents, drawing and publications. The following other Government documents, drawings and publications forms a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

US ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

PRODUCT AND PACKAGING DRAWINGS

9390392	- Simulator, Target Kill Assembly
9395639	- Packing and Marking for Box, Fiberboard, For Simulator, Target Kill
9395638	- Packing and Marking for Box, Packing, For Simulator, Target Kill

(Copies of specifications, standards, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer).

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Materials. Materials and parts shall be in accordance with applicable drawings, specifications and standards.

3.2 Assembly. The Target Kill Simulator shall comply with all requirements specified on Drawing (dwg.) 9390392, all associated drawings, and with all requirements specified in applicable specifications and standards.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:39Z
Check the source to verify that this is the current version before use.

3.3 Functioning (Ambient temperature, 21 ± 3°C, 70 ± 5oF, Hot 51.5 ± 3°C, 125 ± 5°F, Cold -32 ± 3°C, -25 ± 5°F), The assembly shall function and comply with the following requirements after conditioning at specified temperature.

3.3.1 Visual signature. The Black Smoke Kill Indicator shall produce a cloud of dense black smoke for 2.0 minutes minimum (Min.) and 3.5 minutes maximum (MAX.) in a low wind condition (1 - 5 knots).

3.3.2 Functioning time. The time from application of twenty-four (24) plus or minus (±) two (2) Volts Direct Current (VDC), with minimum ignition current of 3.0 milliwatt seconds/ohm, to initiation of the assembly shall not be greater than 0.20 seconds.

3.4 Environmental conditions.

3.4.1 Low temperature. The simulators shall be capable of withstanding low temperature conditions as specified in 4.5.4.1 and meeting the performance requirements when test fired.

3.4.2 High and ambient temperature. The simulators shall be capable of withstanding high temperature conditions as specified in 4.5.4.2 and meeting the performance requirements when test fired.

3.4.3 Leak test. The cartridge shall not leak when tested as specified in 4.5.4.3. Leakage shall constitute a failure.

3.4.4 Leakage test. The simulators shall be capable of withstanding exposure to the leakage test as specified in 4.5.4.4 and meeting the performance requirements when test fired.

3.4.5 Jumble. The simulator shall comply with the following requirements when tested as specified in para. 4.5.4.6.

a. The simulator shall not function during test.

b. There shall be no powder leakage.

c. The simulator components shall not separate during test.

3.5 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:39Z
Check the source to verify that this is the current version before use.

3.6 Workmanship. All parts and assemblies shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, crazes, porosity, warpage, burn marks, blisters, excess flash, scratches, dirt, grease and other defects and foreign matter which would affect appearance or serviceability. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. All required markings shall be neat, legible and sharply defined. All packing components shall be dry.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. First Article Inspection

b. Quality Conformance Inspection

4.3 First article inspection

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2 and 4.3.3. The first article sample shall consist of the following items in sample quantities as indicated:

Part Description	Drawings
Match and Cable Assembly	9354515
Plug, Electrical Assembly	9342154
Cap, Short Circuit	9342157
Container	9390379
Simulator Target Kill Assembly	9390392
Interface, Igniter Assembly	12556037
Composition, Black Smoke	9390395
Composition, Ignition	9390396
Marking Drawings	9390398

4.3.2 Inspections to be performed. See MIL-A-48078 and Table 1 specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:39Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-70536(AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
	Simulator, Target Kill Assembly				See below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Interface, Igniter Assembly (Dwg. 12556037)				
	Examination for defects	32		3.2	4.4.2.1
	Resistance test	32		3.2	4.5.3.3
	Container (Dwg. 9390379)				
	Examination for defects	32		3.2	4.4.2.2
	Cap, Short Circuit (Dwg. 9342157)				
	Examination for defects	32		3.2	4.4.2.3
	Plug, Electrical Assembly (Dwg. 9342154)				
	Examination for defects	32		3.2	4.4.2.4
	Match and Cable Assembly (Dwg. 9354515)				
	Examination for defects	32		3.2	4.4.2.5
	Composition, Black Smoke (Dwg. 9390395)				
	Examination for defects	32		3.2	4.4.2.6

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T03:39Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-70536(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
	Simulator, Target Kill Assembly				See below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Composition, Ignition (Dwg. 9390396)				
	Examination for defects	32		3.2	4.4.2.7
	Simulator, Target Kill Assembly (Dwg. 9390392)				
	Examination for defects	32		3.2	4.4.2.8
	Non-Sequential Test				
	Leakage Test +70 ± 5°F	1Box		3.4.4	4.5.4.4
	Sequential Test				
	Leak test +70 ± 5°F	128		3.4.3	4.5.4.3
	Jumble	32		3.4.5	4.5.4.6
	Hot	32	Note 1	3.4.2	4.5.4.2, 4.5.3
	Cold	32	Note 1	3.4.1	4.5.4.1, 4.5.3
	Ambient	32	Note 1	3.4.2	4.5.4.2, 4.5.3

NOTES:

1. Cold minus 25 ± 5°F, Ambient 70 ± 5°F, Hot +125 ± 5°F.

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T03:39Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of Simulator Assemblies shall contain:

a. Parts of one kind from one manufacturer.

b. Electric match from not more than one lot interfix number from one manufacturer.

co Composition ingredients from not more than one lot or batch.

4.4.2 Examination. - See MIL-A-48078.

a. Sampling plans . Unless otherwise specified in the Classification of Defects and Test tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 202640-23T03:39Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-70536(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Interface, Igniter Assembly				12556037
					NEXT HIGHER ASSEMBLY 9390392
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Glue, hot melt missing or improper		0.40%	3.2	Visual
102	Knot missing		0.40%	3.2	Visual
103	Distance from knot to match head improper		0.40%	3.2	Gage
104	Primer paste not applied properly		0.40%	3.2	Visual
105	Resistance test		0.40%	3.2	4.5.3.3
Minor					
201	Poor workmanship		1.0%	3.6	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:39Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-70536(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.2	Container				9390379
					NEXT HIGHER ASSEMBLY 9390392
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Inside diameter		0.40%	3.2	Gage
Minor 201	Poor workmanship		1.0%	3.6	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:39Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-70536 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.3	Cap, Short Circuit				9342157
					NEXT HIGHER ASSEMBLY 9390398
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Inside dimension (width) of cap opening, min.		0.40%	3.2	Gage
102	Depth of cap opening		0.40%	3.2	Gage
103	True position of clip		0.40%	3.2	Gage
Minor					
201	Poor workmanship		1.0%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:39Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-70536 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Plug, Electrical Assy				9342154
					NEXT HIGHER ASSEMBLY 9390392
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Thickness of body, max. (Datum B)		0.40%	3.2	Gage
102	Width of body, max. (Datum A)		0.40%	3.2	Gage
103	Threaded insert missing or damaged		0.40%	3.2	Visual
104	True position of threaded insert (2)		0.40%	3.2	Gage
105	Insert below flush of surface X		0.40%	3.2	Gage
Minor					
201	Poor Workmanship		1.0%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:39Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-70536(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.5	Match and Cable Assembly		9354515
			NEXT HIGHER ASSEMBLY 9390392

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Match insecure or improperly assembled (soldered)		0.40%	3.2	Visual/Manual
102	Resistance of asssembly		0.40%	3.2	4.5.3.3
Minor					
201	Poor workmanship		1.0%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:39Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-70536(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9390395
4.4.2.6	Composition, Black Smoke				NEXT HIGHER ASSEMBLY 9390392
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Composition analysis	30	0-1	3.2	4.4.4
102	Moisture content		0-1	3.2	4.5.2.2/4.4.3.1
Minor	None defined				

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:39Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-70536(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.7	Composition, Ignition	1 OF 1	9390396
			NEXT HIGHER ASSEMBLY: 9390392

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Composition analysis	30	0-1	3.2	4.4.4
102	Moisture content		0-1	3.2	4.5.2.1/4.4.3.1
Minor	None defined				

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:39Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-70536(AP)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.8	Simulator, Target Kill Assembly				9390392
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Sealant not 360° around plug and container		0.40%	3.2	Visual
102	Wire not flat or outside closure plug		0.40%	3.2	Visual
103	Tape strip (2) not secure or missing		0.40%	3.2	Visual/Manual
104	Coating compound at top not complete or missing		0.40%	3.2	Visual
105	Leak Test	182	0-1	3.4.3	4.5.4.3
106	Leakage Test - Packaged +70 ± 10°F	1 box		3.4.4	4.5.4.4
107	Jumble	32	0-1	3.4.5	4.5.4.6
108	High Temperature	50	Note 1	3.4.2	4.5.4.2, 4.5.3
109	Low Temperature	50	Note 1	3.4.1	4.5.4.1, 4.5.3
110	Ambient	50		3.4.2	4.5.4.2, 4.5.3
111	Height of assembly max		0.40%	3.2	Gage
Minor					
201	Poor workmanship		1.0%	3.6	Visual

NOTES: 1. Cold minus 25 + 5°F, Ambient 70 + 5°F, Hot +125 ± 5°. To be conditioned for six (6) hours (min.) and fired within five (5) minutes of removal from temperature chamber.

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T03:39Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-70536(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.9	Sealed Packed Barrier Bag (Prior to Packing Into Box)				9395639
					NEXT HIGHER ASSEMBLY 9395638
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Waterproofness of bag destroyed by rupture, puncture, or separation of seal		0.40%	3.2	Visual
102	Heat seal of barrier bag incorrect	10	0-1	3.2	4.5.4.5
103	Leakage test	15/ sub pack	0-1	3.4.4	4.5.4.4
Minor					
201	Heat seal of bag located so that two subsequent seals cannot be made		0.65%	3.2	Visual
202	Marking on bag missing, misleading or unidentifiable		0.65%	3.2	Visual
203	Poor workmanship		1.0%	3.6	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:39Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-70536(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.10	Box, Fiberboard, For Target Kill Assembly (Prior to Sealing Top in Flaps)				9395639
					NEXT HIGHER ASSEMBLY 9395638
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Component(s) missing		0.40%	3.2	Visual
102	Filler(s) missing or inadequate		0.40%	3.2	Visual
103	Packaging components obviously damp or wet		0.40%	3.2	Visual/Manual
Minor					
201	Label missing		0.65%	3.2	Visual
202	Marking incorrect, misleading or unidentifiable		0.65%	3.2	Visual
203	Poor workmanship		1.0%	3.6	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T03:39Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-70536 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.11	Box, Wood, Packing, For Target Kill Assembly				9395638
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Strapping missing, broken or loose		0.40%	3.2	Visual/Manual
102	Box broken or split		0.40%	3.2	Visual
103	DOT symbol misleading or unidentifiable		0.40%	3.2	Visual
Minor					
201	Marking incomplete or incorrect		0.65%	3.2	Visual
202	Hardware improperly engaged		0.65%	3.2	Visual
203	Strapping improperly assembled		0.65%	3.2	Visual
204	Metallic Seal missing, unsealed or improperly positioned		0.65%	3.2	Visual
205	Contents loose		0.65%	3.2	Manual
206	Poor workmanship		1.0%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:39Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection tables.

4.4.3.1 Moisture Content (see Table II) - Major Defects

TABLE II - Moisture Content

Composition, ignition	(see Dwg. 9390396)
Composition, Black smoke	(see Dwg. 9390395)
Paper and paper products	(see 3.3.1)

The Contractor shall provide adequate controls to insure that the materials comply with the requirements. For verification, the contractor shall select and subject to test, one sample of each material from each eight (8) hours production. If a composite sample exceeds the requirement, that quantity or sub-lot material represented by the sample shall not be used in loading and packing, the remaining unloaded and unpacked material shall not be used in production, and the loaded and packed simulators shall be rejected. Test shall be performed as specified in 4.5.2.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the Paragraph Reference/Inspection Method column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.2 herein.

4.4.5 Functioning test

4.4.5.1 High and ambient temperature. Beginning with the first lot produced and continuing until three (3) consecutive lots have complied with the acceptance criteria of 4.4.2.8, fifty (50) simulator assemblies shall be selected from each lot for test. The lot shall be rejected if four (4) or more major defects occur. After three (3) consecutive lots have met the acceptance criteria, thirty-two (32) simulators shall be selected from each lot for test. The lot shall be rejected if three (3) or more major defects occur, and lot sampling shall revert to fifty (50) samples per lot.

4.4.5.2 Cold temperature Beginning with the first lot produced and continuing until three (3) consecutive lots have complied with the acceptance criteria of 4.4.2.8, fifty (50) simulator assemblies shall be selected from each lot for test. The lot shall be rejected if six (6) or more major defects occur. After three (3) consecutive lots have met the acceptance criteria, thirty-two (32) simulators shall be selected from each lot for test. The lot shall be rejected if four (4) or more major defects occur, and lot sampling shall revert to fifty (50) samples per lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:39Z
Check the source to verify that this is the current version before use.

4.5 Methods of inspection.

4.5.1 Dimensional control of molded or plastic parts. In place of normal sampling and inspections associated with the Classification of Defects, and after a curing time for the parts has been approved (see Note 1) a sample of three (3) parts (as molded) from each cavity shall be fully inspected dimensionally to qualify a new or reworked cavity for use in production. Each molded part shall carry the individual cavity identification. As a control of each cavity during production, the above quantity of parts from each cavity shall be inspected for at least the defects listed in paragraphs 4.4.2.1, after continuous production of each 5,000 parts or at the end of each week, whichever occurs first. Of the three (3) samples, one (1) sample shall be the last part produced. If any defective parts are found during qualification of the cavity, the cavity producing the defective part will not be used in production. If any defective parts are found when inspection is performed for the control of the cavity, the cavity producing the defective part shall be removed from production. Further, that portion of production since the last control check shall be returned to the contractor for inspection for each separate type of defect according to MIL-STD-105, using an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. All cavities removed from production because of some fault, may, after reworking be returned to production providing they pass the qualification test above. The contractor may request a change of inspection frequency providing he presents objective evidence to the Contracting Officer to substantiate the request. Contractor design of gages and test equipment required to perform the inspections listed herein shall be submitted per 6.3 for approval prior to manufacture of equipments The noted subparagraphs identify those items and minimum inspections subject to the requirements of this paragraph.

NOTE 1: In establishing a curing time, dimensionally check ten (10) parts from each cavity at periodic intervals (e.g. every 30, 60, etc. reins.) until dimensional stability is attained. The curing time will be from the time the part comes out of the mold until dimensional stability is attained. The inspection data used in determing the curing time shall be sent to ARDC, Dover, New Jersey 07801-5001, ATTN: AMSMC-QAT-M(D) . If there is a change in material or cycle time, or if a cavity is reworked, or a new cavity is used, a new curing time shall be established and approved.

4.5.2 Moisture content.

4.5.2.1 Composition, ignition. The method of determining the percentage of moisture in the igniter composition shall be in accordance with Method 101.2 of MIL-STD-1234 except that the sample shall be heated until a constant weight is obtained in lieu of four hours. Observation shall be made for compliance with the applicable requirement.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:39Z
Check the source to verify that this is the current version before use.

4.5.2.2 Composition, black smoke. The method of determining the percentage of moisture in the black smoke composition shall be in accordance with method 101.2.1 of MIL-STD-1234. Observation shall be made for compliance with the applicable requirement.

4.5.3 Functioning. (Ambient temperature, 21 ± 3°C, 70 ± 5°F, Hot, 51.5 ± 3°C, 125 ± 5°F, Cold, -32 ± 3°C, -25 ± 5°F). The simulator assemblies shall be conditioned for 6 hours min. at the specified temperatures and fired within 5 minutes after removal from the conditioning chamber. The simulator shall be held in a rigid support and fired by means of an approved power source in accordance with 3.3.2. (Destructive test)

4.5.3.1 Visual signature. Measurement shall be made from a side position to the longitudinal axis of the simulator with an approved method in accordance with para. 4.4.4. Observation shall be made for compliance with the applicable requirement.

4.5.3.2 Functioning time. The time from initiation of the VDC shall be measured with approved metering equipment in accordance with para. 4.4.4. The assembly shall be observed for compliance with the requirements of 3.3.2.

4.5.3.3 Resistance test. (Dwg. 9354515) The match and cable assembly shall be tested for the specified resistance with inspection equipment approved in accordance with para. 4.4.4. Observation shall be made for compliance with applicable requirements. (Non-Destructive Test)

4.5.4 Environmental tests. Environmental testing shall be conducted to determine compliance with the requirements of 3.4.

4.5.4.1 Low temperature. This test shall be conducted in accordance with Method 502.2, Procedure I of MIL-STD-810, except that the simulator shall be exposed to a temperature of -25 ± 5°F until thermal stabilization is reached and maintained for a period of 6 hours (min.); then the simulator shall be test fired. When necessary, the test specimens may be removed from the conditioning cabinet, set up, and fired within a period of time not to exceed 5 minutes. Observation shall be made for compliance with the applicable requirement.

4.5.4.2 High and ambient temperature. This test shall be conducted in accordance with Method 501.2, Procedure I of MIL-STD-810 except that the simulator shall be exposed to a temperature of 125 ± 5° and ambient temperature of 70 ± 5°F until thermal stabilization is reached, and maintained at that

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:39Z
Check the source to verify that this is the current version before use.

temperature for a period of 6 hours (min.). Then the simulator shall be test fired. When necessary, the test specimens may be removed from the conditioning cabinet, set up, and fired within 5 minutes. Observation shall be made for compliance with the applicable requirement.

4.5.4.3 Leak test. The test shall be performed in accordance with the procedure specified in para. 4.4.3.1 and 4.4.3.2 of MIL-P-116H. Test samples shall be tested at a differential pressure of 1.3 P.S.I for 30 seconds minimum. (Non-Destructive Test)

4.5.4.4 Leakage test. The test shall be performed in accordance with the procedure specified in para. 4.4.3.1 and 4.4.3.2 or 4.4.3.6 of MIL-P-116H. After the test, the seal shall be examined for compliance with the requirements of 3.4.4. (Non-Destructive Test)

4.5.4.5 Heat seal of barrier bag. The test shall be performed in accordance with the procedure specified in para. 4.4.4.3 of MIL-P-116H. After the test, the seal shall be examined for compliance with the applicable requirements (Destructive Test).

4.5.4.6 Jumble. The simulator assemblies shall be tested in accordance with procedures specified in MIL-STD-331, Test 102, except that the duration of the test shall be a minimum of 20 minutes. The assemblies and equipment shall be observed for compliance with 3.4.5 (Destructive Test) l

5. PACKAGING

5.1 Packaging. Packaging shall be in accordance with drawing 9395639.

5.2 Packing. Packing shall be in accordance with drawing 9395638.

5.3 Marking. Marking shall be in accordance with drawings 9395638 and 9395639.

6. NOTES

6.1 Intended use. The components covered by this specification are intended for use on the Simulator, Target Kill Assembly.

6.2 Ordering data. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:39Z
Check the source to verify that this is the current version before use.

6.3 Submission of inspection equipment for design approvals. See MIL-A-48078. Submit designs as required to: Commander, US Army Armament Research, Development and Engineering Center, ATTN: AMSMC-QAT-I (D), Dover, NJ 07801-5001.

6.4 Distribution of ammunition data cards. Distribution of data cards include the following: Commander, US Army Armament Research, Development and Engineering Center, ATTN: AMSMC-QAT-M(D), Dover, NJ 07801-5001.

6.5 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research, Development and Engineering Center (ARDEC), may also include drawings prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal (ARRADCOM) or Picatinny Arsenal drawings. Technical data orginally prepared by these activities is now under the cognizance of ARDEC.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1370-A196)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:39Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:39Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
US ARMY ARMAMENT RSCH DEV & ENGR CENTER
ATTN: AMSMC-QA
DOVER, NJ 07801 5001

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:39Z
Check the source to verify that this is the current version before use.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-S-70536	SIMULATOR, TARGET KILL, PARTS FOR AND LOADING, ASSEMBLING & PACKING

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*. _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 202640-23T03:39Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:39Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:39Z
Check the source to verify that this is the current version before use.