MILITARY SPECIFICATION

BAG, PROPELLING, CHARGE, M67, EMPTY

1. SCOPE

1.1 This specification covers the empty bags for the Charge, Propelling, M67.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

UU-T-106	-	Tape, Pressure-Sensitive Adhesive, Masking, Paper
PPP-B-26	-	Bag, Plastic, Polyethylene
PPP-B-636	-	Box, Fiberboard
PPP-T-45	-	Tape, Gummed, Paper Reinforced and Plain, For Sealing and Securing

MILITARY

MIL-A-2550	-	Ammunition and Special Weapons, General Specification for

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-109	-	Quality Assurance Terms and Definitions
MIL-STD-1168	-	Lot Numbering of Ammunition
MIL-STD-1169	-	Packaging, Packing and Marking for Shipment of Inert Ammunition Components
MIL-STD-1235	-	Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

FSC: 1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:46Z
Check the source to verify that this is the current version before use.

DRAWINGS

ARMY

9271883 - Bag, Propelling, M67

PUBLICATIONS

ARMY

ET-9271883

Equipment Tabulation

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

3. REQUIREMENTS

3.1 Material.-Materials shall be in accordance with applicable drawings and specifications.

3.2 Bags.-The bags shall comply with all requirements specified on Drawing (dwg.) 9271883, as applicable, and with all requirements specified in the applicable specification.

3.3 Weight Classification.-All bags shall be classified and marked in weight zones of .005 ounces.

3.4 Workmanship.-All bags shall be fabricated and finished in a thorough, workmanlike manner. All bags shall be free of dirt, grease and other foreign material.

3.5 First article inspection.-This specification makes provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract (See 6.1).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order,

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:46Z
Check the source to verify that this is the current version before use.

the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL-STD-109 in order to define the terms used herein. The provisions of Specification MIL-A-2550 shall apply.

4.1.1 Submission of product.-At the time each completed lot of items deliverable under the contract is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all of the quality assurance provisions specified in this specification.

b. Drawing and specification number and date, together with an identification and date of changes thereto.

c. A statement that all material purchased by the contractor meets requirements, when such material is controlled by Government or commercial specifications referenced in any of the contractual documents, and that certificates of conformance are on file and available for review.

d. Number of items in the lot.

e. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 First Article Inspection

4.2.1 Submission.-The contractor shall submit a first article sample as designated by the contracting officer for evaluation in accordance with the provisions of 4.2.2. The first article sample shall consist of twenty-five assemblies and twenty-five each of every component which have been produced by the contractor or furnished by a supplier, and which have been manufactured using the same production processes, procedures

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:46Z
Check the source to verify that this is the current version before use.

and equipment which will be used in fulfilling the contract. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as will be used in regular production. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract and submit a record of this inspection with the sample, including statements of findings for materials, processes and tests. A sample containing known defects will not be submitted unless specifically authorized by the contracting officer. A first article sample, or portion thereof, as directed by the contracting officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days, or whenever a change occurs in manufacturing process, material used, drawing or specification such as to significantly affect product uniformity as determined by the Government.

4.2.2 Inspections to be performed.-Assemblies and components will be subjected by the Government to any or all of the examinations or tests specified in 4.3.2 or 4.3.3 of this specification and any or all requirements of the applicable drawings.

4.2.3 Rejection.-If any assembly or component fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of an assembly or component to comply with any of the stated requirements.

4.3 Inspection provisions

4.3.1 Lot formation.-The term "lot" as used throughout this specification refers to an inspection lot, which is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance of the lot with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn, and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision, and complies with the provisions for submission of product as specified in MIL-STD-105. Changes to the process, specification or drawing not affecting safety, performance, interchangeability or storage, as determined by the Government, shall not be deemed to alter the homogeneity of an inspection lot. All material

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:46Z
Check the source to verify that this is the current version before use.

submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein regardless of the type of sampling procedure which is being applied to determine conformance with requirements. Lot numbering, as required, shall be in accordance with MIL-STD-1168. Each lot shall contain cloth from one manufacturer.

4.3.2 Examination.-The examinations listed in the following subparagraphs shall be performed on inspection lots (See 4.3.1) of the components or assemblies designated in the applicable paragraph headings. Inspection for critical defects (and major defects, when so specified) shall be 100 percent. Sampling plans for major and minor defects shall be in accordance with MIL-STD-105, except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the Government. Instead of applying the AQL's designated herein to the groups of major and minor defects listed, the contractor may elect to apply AQL's to individual defects using an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. When this method is elected, it shall be applied to all of the major and minor defects listed in the applicable subparagraph of this section, except where 100 percent inspection is specified, and be documented as part of the contractor's inspection system. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.3.4.

4.3.2.1 Bag (See dwg. 9271883).

Categories	Defects	Method of Inspection
Critical:	None defined.	
Major:	None defined.	
Minor:	AQL 2.50 percent	
201.	Length of bag	Scale
202.	Width of bag	Scale
203.	Distance from edge to seam	Scale
204.	Position of cross seam	Scale
205.	Any seam or opening incompletely stitched	Visual
206.	Seam puckered	Visual
207.	Foil missing or improperly assembled (applicable to increment 5 only)	Visual
208.	Evidence of poor workmanship (See 3.4)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:46Z
Check the source to verify that this is the current version before use.

4.3.2.2 Box, prior to closing (see 5.2.1)

Categories	Defects	Method of Inspection
Critical: None defined.		
Major: None defined.		
Minor:	AQL 1.5 percent	
	201. Any opening in liner	Visual
	202. Liner not closed	Visual
	203. Size of bags incorrect	Visual

4.3.3 Testing

4.3.3.1 Weight classification, Minor Defect, (See 3.3).-All bags shall be weighed and classified in groups of .005 ounces.

4.3.4 Inspection equipment.-Equipment Tabulation number ET-9271883 identifies the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in 6.2.

4.3.4.1 Government rights to documentation.-Inspection equipment drawings and lists provided and revised in accordance with the requirements of the ET may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey and whenever inspection equipment drawings are needed.

4.3.4.2 Government use of contractor's inspection and test equipment.-The contractor shall make available to the Government all inspection and test equipment necessary for determining conformance with contract requirements. Personnel for operating the equipment, and verification of its accuracy, shall be supplied by the contractor for the performance of examination or test by the Government.

5. PREPARATION FOR DELIVERY

5.1 Packaging

5.1.1 Level C.-Like-size bags shall be stacked flat in bundles of 1000 bags. A plain paperboard pad consisting of commercial chipboard, minimum .040 inch thickness, shall be placed on the bottom and top of each bag stack. The length and width of the pad shall be equal to the outside length and width of the bags.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:46Z
Check the source to verify that this is the current version before use.

A length of Kraft paper, minimum 30 pound basic weight, shall be encircled around each stack of bags to provide a secure bundle. The width of the paper wrap shall be equal to the width of the bags to be wrapped and shall be secured with UU-T-106 masking tape or commercial cellophane tape, minimum 1 inch width.

5.2 Packing

5.2.1 Level C.-Like-size bags bundled as required shall be packed in a PPP-B-636 Type CF, Class Domestic, Variety SW, Grade 200 fiber box complete with polyethylene liner conforming to PPP-B-26, for a Type I or II Grade A, Style 2 bag. Number of bags per box size of liner and box shall be as follows:

Bag Number	Bundles Per Box	Approx. Box Size (Inches)*	Approx. Liner Size (Inches) Inside Dim When Opened
1 & 6	2	10 1/2 x 9 3/16 x 15 5/8	10 3/4 x 9 7/16 x 26 1/2
2, 3 & 4	6	16 7/8 x 9 3/16 x 15 5/8	17 1/8 x 9 7/16 x 26 1/2
5	4	16 1/8 x 9 3/16 x 15 5/8	16 3/8 x 9 7/16 x 26 1/2
7	2	13 1/2 x 9 3/16 x 15 5/8	13 3/4 x 9 7/16 x 26 1/2

*Box and liner size may be adjusted to conform to variation in bag size.

Filler sheets consisting of plain fiberboard of the same bursting strength as that of the box and equal in size to the inside length and width of the box less 1/4 inch, shall be inserted between the stacks of bags and liner as required to provide a tight pack. Additional filler sheets equal to the inside length of the box less 1/8 inch shall be placed on top of the bags as required for a tight pack. The liner shall be closed by a wire tie. Fiber boxes shall be closed and secured by application of a PPP-T-45, Type III, Class 2, Grade B, 2-inch wide gummed Kraft tape over the full length of all top and bottom seams of the box with approximately 2-inch extension of tape around all corners and onto the end panels of the box.

5.3 Marking.-Each bundle of bags and each fiber box shall be marked in accordance with MIL-STD-1169, requirements for Level C shipments.

6. NOTES

6.1 Ordering data.-Procurement documents shall specify the following:

a. Title, number and date of this specification.
b. First article sample.
c. Provisions for submission of first article sample.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:46Z
Check the source to verify that this is the current version before use.

6.2 Inspection equipment.-The contractor shall design inspection equipment as required by the inspection Equipment Lists (EL) referenced on the applicable ET in accordance with the instructions of paragraphs 6.2.1 through 6.2.5.

6.2.1 Inspection equipment lists (EL).-Inspection Equipment Lists indicate the availability of inspection equipment designs by showing in the "number" column of the list of inspection equipment (Form SMUPA-1010) the numbers of drawings or Federal stock numbers of existing equipment designs, or codes as indicated in paragraph 6.2.2. Design action required of the contractor is described in paragraphs 6.2.3 and 6.2.4. The contractor will be required to prepare detailed drawings in accordance with 6.2.4 for all the equipment coded as "Contractor Design" in the number column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.2.5.

6.2.2 Inspection equipment list codes.-The inspection equipment defined in 6.2.3 and 6.2.4 will be designated in the EL by the following codes:

CD - Contractor design on controlled contractor format and/or commercial equipment.

MU - Army design, mandatory for use.

6.2.3 Army designs.-Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for an item of inspection equipment. Army designs fall into two basic classifications: Mandatory (designated "MU") and non-mandatory (indicated by drawing or Federal Stock Number). When an inspection equipment list references mandatory Army designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with non-mandatory designs, and with the approval of the Government, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor-prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.2.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:46Z
Check the source to verify that this is the current version before use.

6.2.4 Contractor designs.-Contractor designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finish, notes, operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Unless otherwise specified, contractor designs may be developed on the format the contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above, subject to the following controls: All submitted contractor designs shall conform to MIL-D-1000, Category E, Form 2. Legibility and reproducibility shall permit conventional making of clearly understandable, high contrast reproductions. Contractors shall submit three copies of final designs as a flat set. Designs shall be submitted for approval as specified in 6.2.5.

6.2.5 Submission of contractor designs.-All submitted designs shall contain a reference to the applicable paragraph and defect contained in Section 4 of this specification and the appropriate component or assembly drawing number and revision letter to which the specific design applies. Unless otherwise specified on the EL, all designs of equipment for inspection of defects classified as critical and major shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-QA-A-A. All other designs of inspection equipment shall be approved by the inspection element of the agency administering the contract; submission shall be as directed by the contracting officer. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will be accomplished normally within one month after receipt.

Custodian:
ARMY-MU

Preparing Activity:
ARMY-MU

Project Number: 1315-A-001

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:46Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:46Z
Check the source to verify that this is the current version before use.