MILITARY SPECIFICATION

DISPENSER, MINE: ANTI-TANK

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers an anti-tank (AT) mine dispenser for operation with a military wheeled or tracked cargo vehicle of 2-1/2 ton or larger capacity. The dispenser will dispense Type M-15 AT mines on or beneath the surface of the ground. This dispenser is a component of the Anti-tank Mine Dispensing System, M57.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

Military

| | |
|---|---|
| MIL-P-514 | - Plates, Identification, Instruction and Marking, Blank. |
| MIL-T-704 | - Treatment and Painting of Materiel. |
| MIL-G-3859 | - Grease Guns, Hand-Operated, Lever, Push and Screw Type. |
| MIL-G-10924 | - Grease, Automotive and Artillery. |
| MIL-A-52759 | - Anti-Tank Mine Dispensing System, Packaging of. |

FSC 1095

Source: https://assist.dla.mil -- Downloaded: 202640-22T21:33Z
Check the source to verify that this is the current version before use.

STANDARDS

Military

| | |
|---|---|
| MIL-STD-105 | - Sampling Procedures and Tables for Inspection by Attributes. |
| MIL-STD-209 | - Slinging and Tiedown Provisions for Lifting and Tying Down Military Equipment. |
| MIL-STD-781 | - Reliability Tests: Exponential Distribution. |

DRAWINGS

ME

| | |
|---|---|
| TA13218E6986 | - Dispenser, Mine: Anti-Tank. |

(Copies of specifications, standards, and drawings, required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)

Boiler and Pressure Vessel Code, Section IX, Welding Qualifications

(Application for copies should be addressed to the American Society of Mechanical Engineers, 345 East 47th Street, New York, NY 10017.)

AMERICAN WELDING SOCIETY

B3.0 - Standard Qualification Procedure

(Application for copies should be addressed to American Welding Society, 2501 Northwest Seventh Street, Miami, FL 33125.)

NATIONAL BUREAU OF STANDARDS

Handbook H28 - Screw-Thread Standards for Federal Services

(Application for copies should be addressed to the Superintendant of Documents, Government Printing Office, Washington, DC 20402.)



Source: https://assist.dla.mil -- Downloaded: 202610-22T21:33Z
Check the source to verify that this is the currentversion before use.

SOCIETY OF AUTOMOTIVE ENGINEERS (SAE)

SAE Handbook

(Application for copies should be addressed to Society of Automotive Engineers, Two Pennsylvania Plaza, New York, NY 10001.)

3. REQUIREMENTS

3.1 Description. The mine dispenser (hereinafter called "dispenser") shall be in accordance with Top Assembly TA13218E6986 and as specified herein.

3.1.1 Drawings. The drawings forming a part of this specification are end product drawings. No deviation from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Any data (e.g. shop drawings, layouts, flow sheets, processing procedures, etc.) prepared by the supplier or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or his designated representative.

3.2 First article (preproduction model). The supplier shall furnish one or more dispensers for examination and testing within the time frame specified (see 6.2), to prove to starting production that his production methods will produce dispensers that comply with the requirements of this specification. Examination and tests shall be as specified in section 4 and unless otherwise specified herein, all examinations and tests shall be conducted by the supplier subject to surveillance and approval by the Government (see 6.3). When specified (see 6.2), the Government will conduct any or all of the preproduction examination and tests, as specified (see 6.2).

3.3 Initial production inspection. When specified (see 6.2), the supplier shall furnish to the Government one or more dispensers for inspection as specified in 4.4.

3.4 Material. Material shall be as specified herein and on the applicable drawings. Materials not specified shall be selected by the supplier and shall be subject to all the provisions of this specification.



Source: https://assist.dla.mil -- Downloaded: 202640-22T21:33Z
Check the source to verify that this is the currentversion before use.

3.5 Threaded parts. All screw threads shall be in accordance with H28, unless otherwise specified on the applicable drawings.

3.6 Safety. Nonfunctional sharp edges, projecting points and excessive length of fastening devices shall be avoided.

3.7 Maintainability. All major assemblies and installed attachments shall be accessible for servicing, repair, and replacement. Any maintenance operation performed on the dispenser during testing shall be accomplished by one person using common maintenance tools normally available and the tools furnished with the dispenser. None of the major assemblies or components of the dispenser shall require replacement, rebuild, or overhaul during the test, except that a damaged plow blade, broken or stretched tow beam weak-link, or shear pin may be replaced. The ratio of active maintenance manhours (including both scheduled and unscheduled maintenance) expended during the test to the total dispenser operating time shall be not more than 0.04. Prior to the start of testing, the supplier shall furnish a maintenance schedule and operating and maintenance procedures.

3.8 Reliability. The specified Mean-Time-Between-Failure (MTBF) shall be 102 hours when tested as specified in 4.6.2.4.

3.9 Mobility characteristics. When tested as specified in 4.6.2.1, the dispenser shall perform without malfunction, damage, or permanent deformation to any of its components.

3.10 Dispensing. When tested as specified in 4.6.2.2, the mine dispenser shall dispense mines without overturning the mines at speeds up to 3 mph while being towed by a suitable truck.

3.10.1 Chute operation. With the moldboard and upper chute at the correct angle, the mines shall drop freely through the chute and shall land with the top facing up.

3.11 Tow beam breakaway device. The dispenser shall be equipped with an aluminum "weak-link" attached to the front of the tow beam and the lunette shaft by means of two studs as shown on the applicable drawings. The link shall fail under a tensile force of 10,000 pounds plus or minus 800 pounds.

3.12 Lubrication. All surfaces requiring lubrication shall be provided with a means for lubricating.



Source: https://assist.dla.mil -- Downloaded: 202610-22T21:33Z
Check the source to verify that this is the current version before use.

3.12.1 Lubrication fittings. Lubrication fittings shall be located as shown on the applicable drawings and shall be accessible to a hand-operated grease gun conforming to MIL-G-3859, Type I.

3.12.2 Grease lubrication. All grease lubrication shall be with grease conforming to MIL-G-10924. The dispenser shall be assembled, run-in, tested, and delivered with this grease. Lubrication fittings shall be cleaned and dried prior to lubrication. The moldboards shall be heavily coated with grease.

3.12.3 Oil lubrication. All blades, linkages, hinges, and latches shall be cleaned and coated with lubricating oil.

3.13 Identification and instruction plates. The dispensers shall be equipped with identification and instruction plates as shown on the applicable drawings.

3.14 Treatment and painting. Unless otherwise specified on the drawings, the portions of the dispenser normally painted shall be cleaned, treated, and painted in accordance with MIL-T-704, Type A, Color No. 24087.

3.15 Government-loaned property. The following property in the quantities indicated will be loaned by the Government (see 6.4):

| Description | Identification | Quantity |
|---|---|---|
| Mine, AT, Inert | M-15 | 50 |
| Booster, Inert | M120 | 75 |
| Fuse, AT, Inert | M603 | 75 |
| Ring, Retainer, for M120 Booster | - | 75 |

3.16 Interchangeability. All parts having the same part number shall be functionally and dimensionally interchangeable. Interchangeable parts are defined as two or more parts possessing such functional and physical characteristics as to be equivalent in performance and durability and capable of being exchanged one for the other without alteration of the parts themselves or of adjoining parts except for adjustment, and without selection for fit or performance.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:33Z
Check the source to verify that this is the current version before use.

3.17 Lifting and tiedown provisions. The equipment shall be provided with lifting and tiedown provisions conforming to MIL-STD-209. A diagram showing the lifting provisions and lifting slings shall be inscribed on a plate conforming to MIL-P-514, Type III, Composition A, securely fastened to the unit with the lifting capacity of each attachment and the required length and size of each sling marked thereon.

3.18 Workmanship.

3.18.1 Castings and forgings. All parts, components, and assemblies of the dispensers which include castings and forgings shall be clean of harmful extraneous material such as sand, dirt, pits, sprues, scale, and flux. Rework shall be limited to procedures which do not reduce strength or affect function.

3.18.2 Metal fabrication. Metal used in fabrication shall be free from kinks and sharp bends. The straightening of material shall be done by methods that will not cause injury to the material. Corners shall be square and true. Flame cutting, using tips suitable for the thickness of the steel, may be employed instead of shearing and sawing. All bends shall be made with controlled means to insure uniformity of size and shape. Precaution shall be taken to avoid overheating.

3.18.3 Welding. The surfaces of parts to be welded shall be free from rust, scale, paint, grease, mill scale that can be removed by chipping and wire brushing, and other foreign matter. Welds shall transmit stress without permanent deformation or failure when the parts connected by the welds are subjected to proof and service loading. Parent materials, weld filler materials, and fabrication techniques shall be as required to enable the dispenser to conform to the examination and test requirements specified in section 4. Parts to be joined by fillet welds shall be brought into as close contact as possible and in no event shall be separated by more than 3/16 inch, unless appropriate bridging techniques are used. Unless otherwise specified (see 6.2), the welding process used in fabrication of the dispenser shall be at the option of the supplier.

3.18.4 Welders. Before assigning any welder to manual welding work covered by this specification, the supplier shall provide the contracting officer with certification that the welder has passed qualification tests as prescribed by either of the following listed codes for the type of welding operations to be performed and that such qualification is effective as defined by the particular code:

Standard Qualification Procedure of the American Welding Society.
Welding Qualifications of the ASME.

Suppliers who only make horizontal welds need not qualify welders for "all position welding." Subject to approval by the Government, supplier's



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:33Z
Check the source to verify that this is the current version before use.

standard welder qualification may be substituted in lieu of the above codes provided that the supplier's procedure is equivalent to the above codes. The supplier shall be responsible for determining that automatic welder equipment operators are capable of producing quality welds.

3.18.5 Welding practices.

(a) Preheat of materials being welded, and maximum interpass temperature during welding, shall be in accordance with the supplier's recommendations.
(b) Tack welds shall be subject to the same quality requirements as final welds.
(c) Work shall be positioned for flat welding whenever practicable.
(d) Procedures and sequences shall be such that distortion and shrinkage will be held to a minimum. When straightening is required, caution shall be exercised to insure that the straightening process does not weaken the part and dispenser.

3.18.6 Weld quality.

(a) The supplier shall be responsible for determining the inspections needed to insure that, when the welded parts are assembled together to make the dispenser, the dispenser shall conform to the inspection requirements specified in section 4.
(b) All weldments shall be free of slag, flux, weld spatter, and other impurities detrimental to both the appearance and strength of the weldment.
(c) Undercut in weldments shall be held to a minimum but shall not be more than 1/32-inch deep.

3.18.7 Bolted connections. Boltholes shall be accurately formed and shall have the burrs removed. Washers or lockwashers shall be provided where necessary. Matching thread areas securing bolts conforming to SAE J429 or capscrews shall be of sufficient strength to withstand the tensile strength of the bolt. All fasteners shall be correctly torqued and shall have full thread engagement. Bolts shall not protrude more than two full threads.

3.18.8 Riveted connections. Rivets shall fill the holes completely. The upset rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the member, and shall be in accordance with SAE J492.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:33Z
Check the source to verify that this is the current version before use.

3.18.9 Machine work. Tolerances and gages for metal fits shall conform to the limits specified on the applicable drawings and to the standards of the industry.

## 4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. The supplier is responsible for insuring that components and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards.

4.1.2 Disassembly inspection. Failure of any test by the preproduction model shall be cause for disassembly, in the presence of a Government representative, of the preproduction model to the extent necessary to determine the cause of the failure. Each disassembled part shall be examined in detail for compliance with this specification and referenced drawings in regard to materials, dimensions, tolerances, and workmanship. Parts not complying with such requirements shall be rejected.

4.1.3 Parts and components. Parts and components detailed on the drawings shall be inspected in accordance with the Supplementary Quality Assurance Provisions (SQAP) shown on the drawings. The drawings specify the characteristics requiring SQAP inspection, the sampling plan, and the basis for acceptance and rejection (see 6.5 and 6.6).

4.2 Classification of inspection. Inspection shall be classified as follows:

(a) Preproduction inspection (see 4.3).
(b) Initial production inspection (see 4.4).
(c) Quality conformance inspection (see 4.5).
(d) Inspection comparison (see 4.7).
(e) Inspection of preparation for delivery (see 4.8).



Source: https://assist.dla.mil -- Downloaded: 202610-22T21:33Z
Check the source to verify that this is the current version before use.

4.3 Preproduction inspection.

4.3.1 Examination. The preproduction dispenser shall be examined as specified in 4.6.1. Presence of one or more defects shall be cause for rejection.

4.3.2 Tests. The preproduction dispenser shall be tested as specified in 4.6.2.1, 4.6.2.2, and 4.6.2.3. Failure of any test shall be cause for performing the inspection specified in 4.1.2.

4.4 Initial production inspection. When specified (see 3.3), one or more initial production dispensers will be selected at random by the Government from the dispensers being produced from production tooling and shall be examined as specified in 4.6.1 and tested as specified in 4.6.2.3 and 4.6.2.4 to determine conformance to the requirements of this specification. The inspection will be performed by the Government at a site selected by the Government. Acceptance of an initial production dispenser shall not exclude the remaining dispensers from the quality conformance inspection and acceptance provisions specified in section 4. In addition to any test specified as part of the initial production test, the Government reserves the right to conduct any and all other tests contained in this specification as part of the initial production test and failure of such additional tests shall have the same effect as failure of those tests specified as initial production tests.

4.4.1 Inspection failure. Failure of an initial production dispenser to meet any requirement specified herein during and as a result of the examination and tests specified in 4.4 shall be cause for rejection of the initial production dispenser(s) and shall be cause for refusal by the Government to continue acceptance of production dispensers until evidence has been provided by the supplier that corrective action has been taken to eliminate the deficiencies. Correction of such deficiencies shall be accomplished by the supplier at no cost to the Government on dispensers previously accepted and produced under the contract. Any deficiencies found as a result of the initial production inspection will be considered prima facie evidence that all dispensers accepted prior to the completion of initial production inspection are similarly deficient unless evidence to the contrary is furnished by the supplier and such evidence is acceptable to the contracting officer.

4.5 Quality conformance inspection.

4.5.1 Sampling. Sampling for examination and tests shall be in accordance with MIL-STD-105, Inspection Level II.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:33Z
Check the source to verify that this is the current version before use.

4.5.2 Examination.

4.5.2.1 Individual. Each dispenser shall be examined for the critical defects specified in 4.6.1. Presence of a critical defect shall be cause for rejection.

4.5.2.2 Samples. Samples selected in accordance with 4.5.1 shall be examined for the major and minor defects specified in 4.6.1. Acceptable Quality Level (AQL) shall be 2.5 percent defective for major defects and 6.5 percent defective for minor defects.

4.5.3 Tests.

4.5.3.1 Samples. Samples selected in accordance with 4.5.1 shall be tested as specified in 4.6.2.1, 4.6.2.2, and 4.6.2.3. AQL shall be 2.5 percent defective.

4.6 Inspection procedure.

4.6.1 Examination. The dispenser shall be examined for the following defects:

Critical

1. Chute dimensions not as shown on the applicable drawings, not uniform between dispensers, or not within allowable cumulative tolerance.
2. Flow blades not as shown on the applicable drawing; hole alignment uniformity not as specified.

Major

101. Any part or component not in accordance with SQAP requirements as shown on the drawings.
102. Components missing or not as specified.
103. Welding not as specified.
104. Moldboard not as shown on the drawings.
105. Moldboard smoothness not as specified.
106. Moldboards not correctly welded to the side plate; weld not ground smooth.



Source: https://assist.dla.mil -- Downloaded: 20261O-22T21:33Z
Check the source to verify that this is the current version before use.

107. Top moldboard surface painted or not greased.
108. Leveling jack gears keyway not as shown on the drawings; gear housing covers not correctly sealed.
109. Electric wiring not protected or not tied as shown on the applicable drawing.
110. Service, stop and tail lights not as specified.
111. Tow beam breakaway device not as specified.
112. Lubrication and grease fittings not as specified; dispenser not lubricated as specified.
113. Parts having the same part number not interchangeable.
114. Workmanship not as specified.
115. Lifting and tiedown provisions not as specified.

Minor

201. Identification and instruction plates missing or not as specified.
202. Treatment and painting not as specified.

4.6.2 Tests.

4.6.2.1 Mobility. The dispenser shall be towed under each of the following conditions:

(a) Cross-country operation. Over open, rolling, hilly, or cross-country terrain at speeds up to 5 mph, with average speed of 4 mph, for a distance of 6 miles.
(b) Unimproved road operation. Over unimproved roads at speeds up to 15 mph, with average speed of 10 mph for 5 miles.
(c) Highway operation. Over smooth, hard-surfaced roads at speeds up to 35 mph, with average speed of 30 mph, for 30 miles.

Nonconformance to 3.9 shall constitute failure of this test.

4.6.2.2 Dispensing. After satisfactorily completing the mobility test of 4.6.2.1, the dispenser shall dispense mines without overturning the mines at speeds up to 3 mph at an average continuous speed of 1-1/2 mph. Mines shall be dispensed at a rate of one mine every 300 feet under the following conditions:



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:33Z
Check the source to verify that this is the current version before use.

(a) On the surface of cross-country terrain.
(b) At any depth up to 6 inches in bare or grassy soil having a California Bearing Ratio (CBR) of from 2 to 12; the soil may be dry, moist or wet. The dispenser plow shall lift the soil, place the mine under the soil, and return the soil to its original position with a minimum of disturbance.

The dispensing time shall be 3 hours with 4-1/2 miles of dispensing, of which not more than 50 percent shall be surface dispensing.

4.6.2.2.1 Chute operation. With the moldboard at the correct angle, drop the mines through the chute.

4.6.2.2.2 Failure criteria. Inability of the dispenser to dispense mines as specified in 4.6.2.2, inability of the mines to drop freely through the chute, mines landing overturned, or nonconformance to 3.10 shall constitute failure of this test.

4.6.2.3 Tow beam breakaway. Three tow beam breakaway devices shall be subjected to a tensile force of 10,000 lbs plus or minus 800 lbs. Failure of any device to break shall constitute failure of the test.

4.6.2.4 Reliability. Using the MTBF specified in 3.8, the dispenser shall be tested as specified herein with "accept" and "reject" criteria in accordance with MIL-STD-781, Test Plan IV A. The dispensers shall be considered to have passed the test if the test times and failures fall within the "accept" region and considered to have failed if the test times and failures fall within the "reject" region of Test Plan IV A, and testing shall be terminated. If the assessment falls within the "continue test" region, multiples of the previous testing shall be performed until an "accept" or "reject" assessment is achieved. No more than two test items will be used as the sample for conduct of this reliability test.

4.6.2.4.1 Reliability performance. Test the dispenser as specified in 4.6.2.1 and 4.6.2.2. This cycle of testing shall be repeated until an "accept" or "reject" decision is reached in accordance with 4.6.2.4. A failure is defined as any malfunction which cannot be corrected within 30 minutes by adjustment, repair, or replacement using the tools supplied with the dispenser, and which causes or may cause:



Source: https://assist.dla.mil -- Downloaded: 202610-22T21:33Z
Check the source to verify that this is the current version before use.

(a) Failure to commence operation, cessation of operation, or degradation of performance below levels specified herein.
(b) Damage to the dispenser by continued operation.
(c) Safety hazards to personnel.

Dependant failures and failures resulting from operator error shall be excluded. Nonconformance to 3.8 shall constitute failure of this test.

4.6.2.5 Maintainability. During the testing specified in 4.6.2.4.1, an evaluation shall be made of the total active maintenance man-hours, the total dispenser operating time, the maintenance schedule, and the operator and maintenance procedures. Failure of the dispenser to be properly maintained or nonconformance to 3.7 shall constitute failure of this test.

4.6.2.6 Lifting and tiedown attachments. Pull test the lifting and tiedown attachments in accordance with MIL-STD-209. Nonconformance to 3.17 shall constitute failure of this test.

4.7 Inspection comparison. The Government may select dispensers at any time during the contract production period and subject these dispensers to the examination specified in 4.6.1 and the tests specified in 4.6.2.3 and 4.6.2.4 to determine conformance to the requirements of this specification. The inspection will be performed by the Government, at a site selected by the Government, on units selected at random from those which have been accepted by the Government and will not include the previously inspected preproduction model and initial production dispensers. In addition to any test specified as part of the inspection comparison, the Government reserves the right to conduct any and all other tests contained in this specification as part of the inspection comparison and failure of such additional tests shall have the same effect as failure of those tests specified as inspection comparison.

4.7.1 Inspection failure. Failure of any inspection comparison dispensers to meet any requirement specified herein during and as a result of the examination and tests specified in 4.7 shall be cause for rejection of the inspection comparison dispensers and shall be cause for refusal by the Government to continue acceptance of production dispensers until evidence has been provided by the supplier that corrective action has been taken to eliminate the deficiencies. Correction of such deficiencies shall be accomplished by the supplier at no cost to the Government on dispensers previously accepted and produced under the contract. Any deficiencies found as a result of the inspection comparison will be considered prima facie evidence that all dispensers accepted prior to the completion of inspection comparison are similarly deficient unless evidence to the contrary is furnished by the supplier and such evidence is acceptable to the contracting officer.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:33Z
Check the source to verify that this is the current version before use.

4.8 Inspection of preparation for delivery. The preservation, packaging, packing, and marking shall be examined and tested in accordance with MIL-A-52759.

5. PREPARATION FOR DELIVERY

5.1 Preservation, packaging, packing, and marking. The dispenser shall be preserved, packaged, packed, and marked in accordance with MIL-A-52759. Preservation and packaging shall be level A or C, and packing shall be level A or C, as specified (see 6.2).

6. NOTES

6.1 Intended use. The mine dispenser is intended for laying M15 anti-tank mines while being towed behind a military wheeled or tracked cargo vehicle of 2-1/2 ton or larger capacity.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Time frame required for submission of preproduction model and number of models required (see 3.2).
(c) When the Government will conduct any or all of the preproduction model examination and tests. When the Government will conduct some but not all of the preproduction examination and tests, the contracting officer should specify which examination and tests will be conducted by the Government and which examination and tests shall be conducted by the supplier (see 3.2).
(d) When initial production inspection is required, and number of dispensers to be furnished, when applicable (see 3.3).
(e) When welding process will not be at the option of the supplier (see 3.17.3).
(f) Level of preservation and packaging and level of packing required (see 5.1).

6.3 Preproduction model. Any changes or deviations of production dispensers from the approved preproduction model during production will be subject to the approval of the contracting officer. Approval of the preproduction model will not relieve the supplier of his obligation to furnish dispensers conforming to this specification.



Source: https://assist.dla.mil -- Downloaded: 202610-22T21:33Z
Check the source to verify that this is the current version before use.

6.4 Government-loaned property. The contracting officer should arrange to loan the property specified in 3.15.

6.5 Supplementary Quality Assurance Provisions (SQAP). The contracting officer should require the supplier to maintain records of all SQAP inspections. A suggested paragraph is as follows:

> "The supplier shall maintain complete records of all examinations and tests performed to verify the requirements of classified SQAP characteristics. The records shall include, as a minimum, lot size, sample size, drawing requirements, actual measurement, number and type of deficiencies found, quantity approved, quantity rejected, corrective action taken when applicable.

6.6 Definitions.

6.6.1 Supplementary Quality Assurance Provisions (SQAP). A SQAP is a contractual requirement that supplements section 4 of the specification. SQAP indicates the minimum requirements which must be inspected on the product drawings to verify the design objectives of the product and assure interchangeability of repair parts.

6.7 Data requirements. The contracting officer should include requirements for such data as technical publications, instructional materials, illustrated parts lists, and supplier's maintenance and operation manual to be furnished with each dispenser.

6.8 Provisioning. The contracting officer should include provisioning requirements for repair parts and maintenance tools as necessary (including any special tools), and instructions on shipment of dispensers.

Custodian:

Army - ME

Preparing activity:

Army - ME

Project No. 1095-A069



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:33Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
U. S. ARMY MOBILITY EQUIPMENT
RESEARCH, DEVELOPMENT
CENTER
FORT BELVOIR, VIRGINIA 22060

OFFICIAL BUSINESS

AMSME-RZD-S

POSTAGE AND FEES PAID
DOD-314

COMMANDER
U. S. ARMY MOBILITY EQUIPMENT
RESEARCH, DEVELOPMENT CENTER
ATTN: AMSME-RZD-S
FORT BELVOIR, VIRGINIA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:33Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION MIL-D-52784(ME) - DISPENSER, MINE: ANTI-TANK

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1426
11 Oct 72 (Rev)

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:33Z
Check the source to verify that this is the current version before use.