MILITARY SPECIFICATION

FUZE, DEMOLITION KIT, M1134A2 LOADING ASSEMBLING, AND PACKING

This Specification is approved for use within the U. S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification contains requirements not normally covered by the drawings, and provides quality assurance provisions for the loading, assembling, and packing of one type of fuze designated as Fuze, Demolition Kit, M1134A2.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-A-48078	Ammunition, Standard Quality Assurance Provisions, General Specification For.

STANDARDS

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Armament,Munitions and Chemical Command, Attn. AMSMC-QA, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1375
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

MIL-STD-331 Fuze and Fuze Components, Environmental and perfomance tests for

2.1.2 Other Government documents, drawings, and publications. The following other Government documents drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

U.S. ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

PRODUCT AND PACKAGING DRAWINGS

8799682 - Carton, Packing, Ammunition, for Fuze.
8799683 - Container, Fiberboard, Ammunition, for Fuze, Demolition Kit, M1134A2.
9370065 - Fuze, Demolition Kit, M1134A2 Loading Assembly.

(Copies of specifications, standards, handbooks, drawings, publications and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence. Nothing in this specification however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with applicable drawings and specifications.

3.2 Fuze. The loaded fuze shall comply with all requirements specified on Drawing (Dwg.) 9370065, all associated drawings, and with all requirements specified in applicable specifications.

3.3 Twelve meter drop test. The fuze shall conform with the requirements of MIL-STD-331 test 103.1 when tested as specified in 4.5.3.

3.4 Leak test. The complete fuze shall show no evidence of leakage when tested as specified in 4.5.2.

3.5 Explosive functioning. The fuze shall function satisfactorily when tested as specified in 4.5.9.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

3.6 Jolt test. The fuze shall conform with the requirements of MIL-STD-331 test 101.2, when tested as specified in 4.5.3.

3.7 Jumble test. The fuze shall conform with the requirements of MIL-STD-331 test 102.1 when tested as specified in 4.5.5.

3.8 Drop test 1.5 meter. The fuze shall conform with the requirements of MIL-STD-331 test 111.1 criteria B and shall be fully functional when tested as specified in 4.5.6.

3.9 Temperature and humidity. The fuze shall conform with the requirements of MIL-STD-331 test 105.1 when tested as specified in 4.5.7.

3.10 Transportation vibration-temperature. The fuze shall conform with the requirements of specified in MIL-STD-331A test 119 when tested as specified in 4.5.8.

3.11 Workmanship. All parts shall be loaded and assembled in a thorough workmanlike manner. They shall be clean and free of burrs, distortion, dirt, grease, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any of the parts nor shall the parts be contaminated by the cleaning agent. Surface coatings shall be continuous except for a few light scratches not exposing base metal. All required markings shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contrsactor is responsible for the performance of all inspecition requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsiblity for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspection. The following types of inspection shall be conducted on this item:

a. First article inspection.

b. Quality conformance inspection.

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated:

Part Description	Drawing	Quantity
Rotor Lead Assembly	9370098	20
Rotor Assembly Loaded	9370096	5
Booster Lead Assembly	9370113	20
Retainer Rotor Loaded Assembly	9370112	5
Fuze, Demolition Kit, M1134A2 Loading Assembly (prior to crimping)	9370065	30
Fuze, Demolition Kit, M1134A2 Loading Assembly	9370065	150

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS MIL-F-70757 (AR)

PARAGRAPH	TITLE		1 SHEET 2 OF		DRAWING NUMBER See-Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Rotor Lead Assembly (Dwg. 9370098)				
	Examination for defects	20		3.2	4.4.2.1
	Specific gravity test	20		3.2	4.5.1
	Rotor Assembly Loaded (Dwg. 9370096)				
	Examination for defects	5		3.2	4.4.2.2
	Booster Lead Assembly (Dwg. 9370113)				
	Examination for defects	20		3.2	4.4.2.3
	Specific gravity test	20		3.2	4.5.1
	Retainer Rotor Loaded Assembly (Dwg. 9370112)				
	Examination for defects	5		3.2	4.4.2.4

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

TABLE I First article inspection.

CLASSIFICATION OF DEFECTS & TESTS MIL-F-70757 (AR)

PARAGRAPH	TITLE		2 SHEET 2 OF		DRAWING NUMBER See Below
					NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Fuze, Demolition Kit, M1134A2 Loading Assembly (prior to crimping) (Dwg. 9370065)				
	Examination for defects	30		3.2	4.4.2.5
	Fuze, Demolition Kit, M1134A2 Loading Assembly (Dwg. 9370065)				
	Examination for defects	150		3.2	4.4.2.6
	Leak test	20	Note 1	3.4	4.5.2
	Twelve meter drop test	10	Note 1	3.3	4.5.3
	Jolt test	10		3.6	4.5.4
	Jumble test	10		3.7	4.5.5
	Drop test, 1.5 meter	20		3.8	4.5.6
	Temperature and humidity test	30		3.9	4.5.7
	Transportation vibration-temperature	30		3.10	4.5.8
	Explosive functioning	120	Note 1	3.5	4.5.9

NOTES: 1. Sample units for the leak test and 12 meter drop test shall not be subjected to explosive functioning test.

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of Demolition Kit Fuzes shall contain:

a. Fuze metal part assemblies of one lot number from one supplier.

b. Composition A5 from not more than one lot or, if made in-house, from not more than one batch or homogeneous blend of batches.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70757 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Rotor lead assembly	1 OF 1	9370098
			NEXT HIGHER ASSEMBLY: 9370096

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length, base to shoulder, max.		0.40%	3.2	Gage
102	Diameter		0.40%	3.2	Gage
103	Charge above flush		0.40%	3.2	Gage
104	Specific gravity incorrect	20-0-1		3.2	4.5.1
Minor					
201	Poor workmanship		1.00%	3.11	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 — Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70757 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9370096
4.4.2.2	Rotor assembly, Loaded				NEXT HIGHER ASSEMBLY 9370065
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Rotor lead cup missing (2 places)		0.40%	3.2	Visual
102	Lead cup cover above flush (2 places)		0.40%	3.2	Gage
103	Lead cup cover improperly staked (2 places)		0.40%	3.2	Visual
Minor					
201	Poor workmanship		1.00%	3.11	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70757 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Booster lead assembly	1 OF 1	9370113
			NEXT HIGHER ASSEMBLY: 9370112

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length, base to shoulder max.		0.40%	3.2	Gage
102	Diameter		0.40%	3.2	Gage
103	Charge above flush		0.40%	3.2	Gage
104	Specific gravity incorrect	20-0-1		3.2	4.5.1
Minor					
201	Poor workmanship		1.00%	3.11	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 — Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET	DRAWING NUMBER
4.4.2.4	Retainer, Rotor Loaded Assembly		1 OF 1	9370112
				NEXT HIGHER ASSEMBLY: 9370065

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Booster lead assembly missing (2 places)		0.40%	3.2	Visual
102	Lead cup cover above flush (2 places)		0.40%	3.2	Gage
103	Stake missing or improper (2 places)		0.40%	3.2	Visual
104	Adhesive missing or improperly applied (2 places)				
Minor					
201	Poor workmanship		1.00%	3.11	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70757 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Fuze, Demolition Kit, M1134A2 Loading Assembly prior to crimping				9370065
					NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Any component missing, damaged or improperly assembled		0.40%	3.2	Visual
102	Screw(s) fastening the retainer assembly missing or loose		0.40%	3.2	Manual
Minor					
201	Poor workmanship		1.00%	3.11	Visual

COVER:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70757 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.6	Fuze, Demolition Kit, M1134A2 Loading Assembly	1 OF 1	9370065
			NEXT HIGHER ASSEMBLY: --

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Shear pin missing		100%	3.2	Visual
2	Red warning stencil (or decal) missing or illegible		100%	3.2	Visual
3	Indicator not visible		100%	3.2	Visual
Major					
101	Torque of nut		0.40%	3.2	Gauge
102	Leak test	32-0-1		3.4	4.5.2
103	Explosive functioning	30-1-2		3.5	4.5.3
104	Crimp missing or improper		0.40%	3.2	Visual
Minor					
201	Dust Cap Missing		0.40%	3.2	Visual
202	Protective coating damaged		0.65%	3.2	Visual
203	Poor workmanship		1.00%	3.11	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70757 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.7	Inner carton, sealed				8799632
					NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Contents loose		0.40%	3.2	Manual
Minor 201	Marking misleading, missing or unidentifiable		0.65%	3.2	Visual
202	Poor workmanship		1.00%	3.11	Visual

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70757 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.8	Barrier bag, sealed				8799682
					NEXT HIGHER ASSEMBLY
					--
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Area for subsequent seals missing		0.40%	3.2	Visual
102	Air not exhausted		0.40%	3.2	Visual
103	Carton corners not blunted		0.40%	3.2	Visual/Manual
Minor					
201	Marking incorrect, incomplete, or illegible		0.65%	3.2	Visual
202	Poor workmanship		1.00%	3.11	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 — Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70757 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.9	Outer carton, sealed	1 OF 1	8799682
			NEXT HIGHER ASSEMBLY: --

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Carton damaged		0.40%	3.2	Visual
102	Contents loose		0.40%	3.2	Manual
103	Closing flaps insecure		0.40%	3.2	Manual
Minor					
201	Marking incorrect, incomplete, or illegible		0.65%	3.2	Visual
202	Poor workmanship		1.00%	3.11	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70757 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.10	Shipping container	1 OF 1	8799683
			NEXT HIGHER ASSEMBLY: --

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Carton damaged		0.40%	3.2	Visual
102	Contents loose when tilted		0.40%	3.2	Manual
103	Closing flaps not secure		0.40%	3.2	Manual
Minor					
201	Marking missing, misleading or unidentifiable		0.65%	3.2	Visual
202	Poor workmanship		1.00%	3.11	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in Table I herein.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the 'Paragragh Reference/Inspection Method' column starting with 4.4.2.1 . The contractor shall submit, inspection equipment designs for approval, in accordance with the terms of the contract. See section 6 of MIL-A-48078 and 6.3 herein.

4.5 Methods of inspection.

4.5.1 Specific gravity of booster lead and rotor lead assemblies. The sample shall be weighed and the weight recorded as A. The exposed explosive surface of each lead assembly shall be coated with a thin coat of molten wax. After the wax has solidified, the sample shall be weighed and the weight recorded as B. A 50 cubic centimeter (cc) pycnometer (specific gravity bottle) shall be filled with distilled water at 20, plus or minus 2 degrees centigrade (C.) and weighed. The weight of the empty pycnometer shall be substracted from the water filled pycnometer and this weight difference recorded as D. The sample shall be transferred to the pycnometer, all air bubbles shall be removed, water (at 20 degrees C. plus or minus 2 degrees C.) shall be added, if necessary, to fill the pycnometer and the pycnometer and contents weighed. The weight of the empty pycnometer shall be subtracted from the preceding weight determination and the result recorded as E. The explosive and wax shall be removed from the lead cups (toluene followed by acetone with a final washing in toluene is suggested) and the clean cups shall be weighed, the weight shall be recorded as F and the cups transferred to the pycnometer. With approximately 35 cc of water in the pycnometer, the water and lead cups shall be boiled under vacuum to remove all air bubbles. The pycnometer and its contents shall be cooled to 20 degrees C., plus or minus 2 degrees C., distilled water at the same temperature added to fill the pycnometer and weighed. The weight of the empty pycnometer shall be subtracted from the preceding weight determination and the result recorded as G. Weight B shall be subtracted from weight E and this difference subtracted from weight D, this result shall be recorded as J. Weight B shall be subtracted from weight A and the difference shall be divided by the specific gravity of the wax at 20 degrees C. plus or minus 2 degrees C. The result of the preceding calculation shall be recorded as K. Weight F shall be subtracted from weight A and this result shall be recorded as L.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

The specific gravity of the explosive shall be calculated as follows:

$$\text{Specific gravity} = \frac{L}{H - (J + K)}$$

where:
L = weight of explosive in grams
H = weight of water displaced by loaded, waxed sample in grams which is equivalent to volume in cubic centimeters.
J = weight of water displaced by empty lead cups in grams which is equivalent to volume in cubic centimeters.
K = weight of water displaced in grams is equivalent to volume of wax in cubic centimeters.

4.5.2 Leak test. The fuze assembly shall be tested utilizing the applicable procedure specified in MIL-STD-331 Test 118 Bubble Method. Any fuze assembly which fails to comply with the applicable requirement shall be classified defective.
(Destructive test)

4.5.3 Twelve meter drop test. The fuze assembly shall be tested utilizing the applicable procedure specified in MIL-STD-331 test 119. Any fuze assembly which fails to comply with the applicable requirement shall be classified defective.

4.5.4 Jolt test. The fuze assembly shall be tested utilizing the procedure specified in MIL-STD-331 Test 101.2. Any fuze assembly which fails to comply with the applicable requirement shall be classified defective.

4.5.5 Jumble test. The fuze assembly shall be tested utilizing the procedure specified in MIL-STD-331 Test 102.1. Any fuze assembly which fails to comply with the applicable requirement shall be classified defective.

4.5.6 Drop test (1.5 meter). The fuze assembly shall be tested utilizin the procedure specified in MIL-STD-331 Test 111.1. Any fuze assembly which fails to comply with the applicable requirements shall be classified defective.

4.5.7 Temperature and humidity. The fuze assembly shall be tested utilizing the procedure specified in MIL-STD-331 Test 105.1. Any fuze assembly which fails to comply with the applicable requirement shall be classified defective.

4.5.8 Transportation vibration-temperature. The fuze assembly shall be tested utilizing the applicable procedure specified in MIL-STD-331 Test 119. Any fuze assembly which fails to comply with the applicable requirement shall be classified defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

4.5.9 Explosive functioning. The fuze shall be held firmly in a fixture or clamp with the longitudinal axis of the fuze held horizontally. Two pieces of 100 grain detonating cord approximately 12 inches long with relays (see dwg. 8847494) attached to one end of each shall be positioned to align the relay end of the detonating cord with the booster charges in the fuze and firmly held to leave a minimum gap 1/16 inch between the fuze container surface and the end of the relay. An external electrical power source of 22 volts direct current shall be connected to the pins of the external connector through an open switch. The arming pin assembly shall be retracted completely and the switch to the external electrical power source closed. The fuze shall be classified defective if one or both detonating cords fail to function completely.(Destructive test)

4.5.10 Forty foot drop test. The unarmed fuze shall be assembled to the approved test equipment and submitted to the required free fall. Observation shall be made for exterior damage likely to cause a malfunction. Any unit which either detonates, burns, or becomes armed shall be classified as defective. The fuze shall be safe to handle and dispose of following this test. (Destructive test)

5. PACKAGING

5.1 Preservation and packaging.

5.1.1 Level A. The fuze shall be preserved, packaged and marked in accordance with dwg. 8799682.

5.2 Packing.

5.2.1 Level A. The packaged fuze shall be packed and marked in accordance with dwg. 8799683.

6. NOTES

6.1 Intended use. The item covered by this specification is intended to be used as a Demolition Fuze with other demolition items.

6.2 Ordering dates. See MIL-A-48078.

6.3 Submission of inspection equipment designs for approval. See MIL-A-48078. Submit equipment designs as required to Commander, ARDEC, ATTN: AMSMC-QAT-I, Picatinny Arsenal, New Jersey 07806-5000. This address will be specified on the Contract Data Requirement List, DD Form 1423 in the contract. Unless otherwise specified, data item DI-R-1714 will apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

6.4 Army designs. Army designed inspection equipment is not mandatory for use. The contractor may design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.

6.5 Drawings. Drawings listed in Section 2 of this specification under the heading of U.S. Army Armament Research and Development Center (ARDEC) may also include drawings prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, ARRADCOM or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARDEC.

6.6 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

6.7 Subject term (key word) listing.

Fuze
Demolition kit

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1375-A391)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-F-70757	FUZE, DEMOLITION KIT, M1134A2 LOADING ASSEMBLING, AND PACKING

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
ARDEC
ATTN: AMSMC-QA
PICATINNY ARSENAL, NJ 07806-5000

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.