# MILITARY SPECIFICATION

## PROJECTILE, 8 INCH, HE: M509A1 ADAPTER FOR

This specification is approved for use by the US Army Armament Research and Development Command and is available for use by all Departments and Agencies of the Department of Defense.

## 1. SCOPE

1.1 This specification contains requirements, quality assurance provisions and packaging for one type of component designated as Adapter, for use with Projectile, 8 Inch, HE: M509A1.

## 2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

| | |
|---|---|
| TT-C-490 | - Cleaning Methods and Pretreatment of Ferrous Surfaces for Organic coatings |
| TT-I-1795 | - Ink, Marking Stencil, Opaque, for Porous Surfaces (Wood Boxes, Fiber Cartons, etc.) |
| PPP-B-636 | - Box, Fiberboard |

FSC: 1320

**Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.**

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:13Z
Check the source to verify that this is the current version before use.

PPP-F-320 - Fiberboard; Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes
PPP-T-76 - Tape, Pressure-Sensitive, Adhesive Paper, (For Carton Sealing)

MILITARY

MIL-B-117 - Bags and Sleeves, Interior Packaging
MIL-H-6875 - Heat Treatment of Steels (Aircraft Practice, Process for)
MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification for

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-410 - Nondestructive Testing Personnel Qualification and Certification

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS (See 6.7)

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

B-9210129 - Adapter

(Copies of specifications, standards, handbooks, drawings, and publications required by suppliers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officier).

2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the reference cited herein, the text of this specification shall take precedence.

2.2 Other publications.- The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on the date of invitation for bids or request for proposal shall apply.

AMERICAN SOCIETY FOR TESTING AND MATERIALS

ASTM E 8 - Standard Methods of Tension Testing of Metallic Materials



Source: https://assist.dla.mil -- Downloaded: 202610-22T19:13Z
Check the source to verify that this is the current version before use.

ASTM E 18 - Standard Test Methods for Rockwell Hardness and Rockwell Superficial Hardness of Metallic Materials

(Application for copies should be addressed to: American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pa. 19103).

3. REQUIREMENTS

3.1 Material.- Materials shall be in accordance with the applicable drawing and specifications.

3.2 Adapter.- The adapter shall comply with all requirements specified on Drawing (Dwg) B-9210129, and with all requirements specified in applicable specifications.

3.3 Identification and segregation of adapters.- All adapters submitted to the Government shall by recognizable as to homogeneity in accordance with the provisions of 4.4.1.

3.4 Written heat treatment process controls for maximizing homogeneity of adapters.- The contractor shall briefly describe his entire heat treatment process and, using MIL-H-6875 as a guide, fully describe the controls to be employed which shall include, as a minimum, all the checkpoints referenced in 6.6. The written plan shall be submitted to the address specified (See 6.4) for Government approval. Such approval shall be limited to the controls to be employed and not to the overall heat treatment process, nor shall such approval relieve the contractor, in any way, of the responsibility for producing acceptable adapters.

3.5 First article inspection.- This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract. (See 4.3).

3.6 Verification of heat treatment.- Each adapter after completing the heat treating operation shall be inspected/tested for verification of the heat treatment process. This inspection/test shall meet, as a minimum, the requirements of para. 4.4.2.2, 4.5.4 and associated documents (e.g. dwg. B9210129).

3.7 Workmanship.- All adapters shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust, corrosion products, and other foreign matter. The cleaning method used shall not be injurious to any parts, nor shall the parts be contaminated by the cleaning agents. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings (See 5.3) shall be neat and sharply defined.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.

## 4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions.- Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078(PA) shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections.- The following types of inspection shall be conducted on this item:

a. First Article Inspection
b. Quality Conformance Inspection

4.3 First article inspection

4.3.1. Submission.- The contractor shall submit a first article sample as designated by the contracting officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

| PART DESCRIPTION | DRAWINGS | QUANTITY |
|---|---|---|
| Adapters (with protective finish) | 9210129 | 50 |
| Adapters (without protective finish) | 9210129 | 50 |

4.3.2 Inspections to be performed.- See MIL-A-48078 (PA) and Table 1 herein.

4.3.3 Rejection.- See MIL-A-48078 (PA).



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

## CLASSIFICATION OF DEFECTS & TESTS

MIL-P-48094B (AR)

| PARAGRAPH CATEGORY | TITLE / EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | DRAWING NUMBER / NEXT HIGHER ASSEMBLY / PARAGRAPH REFERENCE /INSPECTION METHOD |
|---|---|---|---|---|---|
| | Adapter | | SHEET 1 OF 1 | | 9210129 |
| | Adapter (without protective finish) | | | | |
| | Hardness test | 40 | — | 3.2 | 4.5.1 |
| | Longitudinal force test | 40 | — | 3.2 | 4.5.2 |
| | Examination for defects | 50 | — | 3.2 | 4.4.2.1 |
| | Adapter (with protective finish) | | | | |
| | Examination for defects | 50 | — | 3.2 | 4.4.2.2 |

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.

4.4 QUALITY CONFORMANCE INSPECTION

4.4.1 Inspection lot formation.- Inspection lots shall comply with the lot formation provisions of MIL-A-48078 (PA).

4.4.1.1 Heat treatment lot (identity and formation).- A heat treatment lot shall consist of adapters from the same mill heat of material, that have been heat treated by the same overall process (including the normalizing and/or stress relief phases when part of the contractor's overall heat treatment process) using the same quench bath, and in the same furnace for each of all phases of the overall heat treatment process. Each heat treatment lot shall be properly identified and segregated from other heat treatment lots. In addition, each heat treatment lot shall consist of one or more identified and segregated heat treatment batches formed in accordance with the provisions of 4.4.1.2.

4.4.1.2 Heat treatment batch (identity and formation).- A heat treatment batch shall consist of adapters from the same heat treatment lot that have been heat treated at the same time in the same furnace and quench bath for each of all phases of the entire heat treatment process.

When a continuous-type furnace is used for one or more, but not all, phases of the overall heat treatment process, the quantity of adapters processed through that furnace for each four (4) hours' production, or portion thereof, shall be considered as a quantity of adapters heat treated at the same time for that particular phase or phases of the overall heat treatment process.

When a continuous-type furnace is used for all phases of the entire heat treatment process, including the normalizing and/or stress relief phases when part of the contractor's overall heat treatment process, and quenching is performed in the same bath, each four (4) hours' production or portion thereof shall represent a heat treatment batch.

Each heat treatment batch shall be identified and segregated from all other heat treatment batches. One or more heat treatment batches, properly identified and segregated, may be associated with the same heat treatment lot providing the provisions of 4.4.1.1 are applicable.

4.4.1.3 Contractor's identification system for heat-treated adapters.- The method of control for heat treatment lot and heat treatment batch identification formation, in accordance with the provisions of 4.4.1.1 and 4.4.1.2, shall be documented by the contractor and submitted to the address specified in 6.4 for approval by the Government. (See 3.3).

4.4.2 Examination.- See MIL-A-48078 (PA).

a. Sampling plans.- Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.



Source: https://assist.dla.mil -- Downloaded: 202610-22T19:13Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

## CLASSIFICATION OF DEFECTS & TESTS

MIL-P-48094B (AR)

| PARAGRAPH | TITLE | SHEET | DRAWING NUMBER |
|---|---|---|---|
| 4.4.2.1 | Adapter (without protective finish) | OF | 9210129 |
| | | | NEXT HIGHER ASSEMBLY |

| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
|---|---|---|---|---|---|
| Critical | None defined | | | | |
| Major | | | | | |
| 101 | Hardness | 150 | a | 3.2 | 4.5.1 |
| 102 | Longitudinal force | 25 | b | 3.2 | 4.5.2 |
| 103 | Total length | | 0.40% | 3.2 | Gage |
| 104 | Perpendicularity of faces (2) to outside diameter | | 0.40% | 3.2 | Gage |
| 105 | Inside diameter | | 0.40% | 3.2 | Gage |
| 106 | True position of inside diameter | | 0.40% | 3.2 | Gage |
| 107 | Chamfer missing | | 0.40% | 3.2 | Visual |
| Minor | | | | | |
| 201 | Evidence of poor workmanship | | 0.65% | 3.7 | Visual |

NOTES:
a. Accept on 0, reject on 1 defect.
b. No defective allowed.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T19:13Z
Check the source to verify that this is the current version before use.

# CLASSIFICATION OF DEFECTS & TESTS

MIL-P-48094B (AR)

| PARAGRAPH | TITLE | | SHEET | OF | DRAWING NUMBER |
|---|---|---|---|---|---|
| 4.4.2.2 | Adapter (with protective finish) | | | 1 | 9210129 |
| | | | | | NEXT HIGHER ASSEMBLY |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | | | | | |
| 1 | Verification of heat treatment | | 100% | 3.6 | 4.5.4 |
| Major A | | | | | |
| 101 | Phosphate coating weight | a | a | 3.2 | 4.5.3 |
| 102 | Outside diameter | | 0.40% | 3.2 | Gage |
| Minor | | | | | |
| 201 | Evidence of poor workmanship | | 0.65% | 3.7 | Visual |

NOTES: (a)Sampling and acceptance/rejection shall be in accordance with TT-C-490. (Except that coating weight shall be as specified on dwg. 9210129).

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

## CLASSIFICATION OF DEFECTS & TESTS

MIL-P-48094B (AR)

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| 4.4.2.3 | Box Inner, Sealed (Prior to placing in Barrier Bag) | | | | See Section 5 |
| | | | | | NEXT HIGHER ASSEMBLY |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | None defined | | | | |
| Major | | | | | |
| 101 | Box damaged exposing contents | | 0.40% | 3.2 | Visual |
| 102 | Sealing strip missing, incomplete or badly wrinkled | | 0.40% | 3.2 | Visual |
| 103 | Corner not blunted | | 0.40% | 3.2 | Visual |
| Minor | | | | | |
| 201 | Contents loose | | 0.65% | 3.2 | Manual |
| 202 | Marking misleading or unidentifiable | | 0.65% | 3.2 | Visual |

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete



Source: https://assist.dla.mil -- Downloaded: 2026-02-22T19:13Z
Check the source to verify that this is the current version before use.

# CLASSIFICATION OF DEFECTS & TESTS

MIL-P-48094B (AR)

| PARAGRAPH | TITLE | SHEET | DRAWING NUMBER |
|---|---|---|---|
| 4.4.2.4 | Barrier Bag, Sealed | 1 OF 1 | See Section 5 |
| | | | NEXT HIGHER ASSEMBLY |

| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
|---|---|---|---|---|---|
| Critical | None defined | | | | |
| Major 101 | Waterproofness destroyed by separation of heat seal, or tear, rip or puncture | | 0.40% | 3.2 | Visual |
| Minor 201 | Marking on bag misleading or unidentifiable | | 0.65% | 3.2 | Visual |

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.

## CLASSIFICATION OF DEFECTS & TESTS



| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| 4.4.2.5 | Box, Outer, Sealed | | | | See Section 5 |
| | | | | | NEXT HIGHER ASSEMBLY |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | None defined | | | | |
| Major | | | | | |
| 101 | Contents loose | | 0.40% | 3.2 | Manual |
| 102 | Box damaged exposing contents | | 0.40% | 3.2 | Visual |
| 103 | Sealing tape missing, incomplete, or badly wrinkled | | 0.40% | 3.2 | Visual |
| Minor | | | | | |
| 201 | Marking misleading or unidentifiable, including incorrect color code | | 0.65% | 3.2 | Visual |
| 202 | Label missing or badly wrinkled (when applicable) | | 0.65% | 3.2 | Visual |

NOTES:





Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.

4.4.3 Testing.- Testing is described in the First Article and Quality Conformance Inspection Tables.

4.4.4 Inspection equipment.- The inspection equipment required to perform the examinations and tests prescribed herein is described in the Paragraph Reference/Inspection Method column in the tables starting with Paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Test methods and procedures

4.5.1 Hardness (prior to application of protective finish).- One hundred fifty (150) adapters shall be randomly selected from each heat treatment batch, as determined by the provisions of 4.4.1.2, and subjected to this test. Prior to performing this test, each adapter shall be suitably marked with an identification number. The test shall be performed as specified in ASTM E 18-74, using the standard penetrator for the specified hardness scale. The body shall be supported on the inside diameter using a Wilson Gooseneck Anvil No. 7803, or equivalent, with a mandrel not less than one (1) inch in diameter. Three (3) readings shall be taken near mid-length on the cylindrical surface approximately 120° apart. Each reading shall be recorded and, in addition, the average of the three readings shall be computed and recorded with the identification number of that adapter. A tabulation of the test results shall be prepared for each heat treatment batch of each heat treatment lot. The twenty-five (25) adapters having the lowest average hardness shall be subjected to the longitudinal force test of 4.5.2. Those adapters not selected for the longitudinal force test and which meet the hardness requirement specified on the applicable drawing may be returned to the heat treatment batch.

4.5.2 Longitudinal force (prior to application of protective finish).- The sample to be subjected to this test shall be the twenty-five (25) adapters having the lowest average hardness in the sample previously subjected to the hardness test of 4.5.1. The longitudinal force test shall be performed with the adapter mounted in a test fixture and the load applied in accordance with the applicable drawing. Equipment and test fixturing for this test shall be approved in accordance with 4.4.4. The instructions in 6.5 of this specification shall be used to determine the longitudinal compression force for each adapter. A tabulation of the test results by adapter identification number as established in 4.5.1 shall be prepared for each heat treatment batch of each heat treatment lot. A copy of the tabulated test results shall be submitted to the address specified in 6.4. The heat treatment batch represented by the sample shall be rejected if any adapter in the sample fails to comply with the minimum longitudinal strength requirement specified on the adapter drawing. This is a destructive test. Adapters subjected to this test shall not be returned to any heat treatment lot or batch.



Source: https://assist.dla.mil -- Downloaded: 202610-22T19:13Z
Check the source to verify that this is the currentversion before use.

4.5.3 Phosphate coating weight.- Testing shall be performed in accordance with TT-C-490.

4.5.4 Verification of heat treatment of adapter.- This inspection, performed immediately prior to packaging, shall employ the eddy current or any other equivalent method approved by the procurement agency. The processes, equipment and calibration procedures used in performing this test and the standards applied shall be documented and have prior written approval of the procurement agency. In addition, after approval has been granted, the contractor shall make no changes in equipment or procedures without prior written approval by the procurement agency. All equipment employed shall be capable of performing this inspection accurately and consistently and shall be calibrated on an approved periodic basis. All personnel operating and calibrating this equipment shall be qualified and certified in accordance with MIL-STD-410.

Any adapter which fails to meet the requirements specified in para. 3.7 shall be classed defective and removed from the lot. When verification indicates that the eddy current equipment is performing incorrectly, those adapters processed since the last satisfactory verification shall be retested.

In addition, all inspection equipment used to perform this test shall be in accordance with paragraph 4.4.4.

## 5. PACKAGING

5.1 Preservation (level A and B) - One hundred and fifty (150) adapters, (Dwg. B-9210129), shall be preserved and packaged in six (6) layers in a "B" flute, RSC style, Type CF, SW Variety, Grade 175 min., domestic class fiberboard box in accordance with PPP-B-636. Inside dimensions of fiber box shall be 8-7/16" x 8-7/16" x 8-11/16" high (Tolerance: ± 1/16"). Each of the six layers shall be composed on a .06 thick commercial chipboard partition in a 5 x 5 cell pattern. The size of each cell of the partitions shall be 1-9/16 inches square. Six (6) partitions shall be snug-fit in fiber box.

Adapters shall be placed in each cell of the partition. Commercial chipboard fillers 8" x 8" x .06" shall be placed between each layer and additional fillers placed on top as required to insure tight packing.

Maximum moisture content of paper products used shall not exceed 9 percent prior to packaging.

The fiber box shall be sealed with a center sealing strip, 2" width, PPP-T-76, pressure tape. The corners of the fiber box shall be blunted. The packed fiber box shall be placed in a Type 1, Class E, MIL-B-117 barrier bag. Prior to sealing bag, exhaust all excess air. Size of bag to be: 18-1/4" min. x 20 x 1/2" min.



Source: https://assist.dla.mil -- Downloaded: 202640-22T19:13Z
Check the source to verify that this is the current version before use.

5.2 Packing

5.2.1 Level A - Level A packing shall be the same as Level B except that a wooden box complying with MIL-B-46506, MIL-A-2427, PPP-B-601, or PPP-B-621 shall be substituted for the fiberboard box specified for Level B. Sealing will be IAW requirements for the box selected.

5.2.2 Level B - One (1) sealed fiber box, inside sealed barrier bag, shall be placed in an RSC type, "B" flute, Type CF, SW Variety, Grade 175 min., domestic class fiberboard box in accordance with PPP-B-636. Inside dimensions of this outer fiber box shall be: 9" x 9" x 10-3/8" high. Insert end, side and top fillers as required for tight packing. Size of fillers shall be:

End side 8-1/2 x 9-1/2 x .06 inches

Top 8-1/2 x 8-1/2 x .06 inches

Filler material to be comercial chipboard. Outer fiber box to be sealed in accordance with closure requirements of PPP-B-636.

5.3 Marking

5.3.1 Inner box - Marking of fiber box (inner) and bag to be with black stencil ink, TT-I-1795. A label may be used on the fiber box. Size of letters: 1/8" min. Marking on fiber box to appear on one top flap, centrally located. Marking on bag to be so positioned that it appears on top of fiber box. Marking to be as follows:

"150-ADAPTER P/N 9210129
LOT NO._____ DATE PACKED _____"

Date not required when included in Lot Number.

5.3.2 Outer box.- Marking of outer fiber box to be same as that marked on inner fiber box. ICC marking is not required.

5.4 Shipping.- When shipments of more than one lot are made at one time, such as in a carload, each lot shall be kept separate and the division between lots clearly indicated to prevent mixing in transit.

6. NOTES

6.1 Intended use.- This item is intended for use with the Projectile, 8 Inch, HE, M509A1.

6.2 Ordering data.- See MIL-A-48078 (PA).

6.3 Submission of inspection equipment designs for approval.- See MIL-A-48078. Submit equipment designs as required to Commander, US Army ARRADCOM, ATTN: DRDAR-QAR-I, Dover, New Jersey 07801.



Source: https://assist.dla.mil -- Downloaded: 202610-22T19:13Z
Check the source to verify that this is the current version before use.

6.4 Submission of contractor's identification system, and written plan of heat treatment process control for heat-treated adapters.- These documents shall be submitted for approval to Commander, US Army ARRADCOM, ATTN: DRDAR-LCU-SS.

6.5 Determination of longitudinal compressive offset force.- This value shall be determined by applying a load to the adapter until failure occurs while obtaining a diagram of "applied force (lbs.) vs. length reduction (inches)". A straight line shall then be constructed parallel to and offset by .0028 inches taken along the length reduction axis, from the straight (linear) portion of the diagram. The constructed line shall be extended until it intersects the upper non-linear portion of the diagram. The corresponding value of force thus obtained shall represent the longitudinal compressive force at .0028 inches offset for that adapter. The magnification used for the deflection axis shall be 100X.

The method described is similar to that described in ASTM E 8-69, except that substitution has been made for stress, strain and % offset.

6.6 Contractor's written control procedure for the overall heat treatment process.- The contractor shall prepare a written plan to be implemented for control of his overall heat treatment process to facilitate homogeneity of the heat-treated adapters. The written plan shall specifiy, as a minimum, controls and procedures for the following:

a. Heat treatment temperature tolerance.- The maximum temperature deviation to be permitted from the pre-determined temperature for all phases in the heat treatment process, including the permitted temperature range of the quench medium before and during the quench operation.

b. Preheat.- The temperature and method of preheat, including designation of the phase(s), to which the method shall apply.

c. Confirmation of accuracy of temperature-measuring instruments.- The method, location, and frequency basis for obtaining temperature checks of all the temperature-recording instruments of all the heat-treatment phases.

d. Check for detrimental surface effects due to salt or gaseous contamination.- The test method, criteria, frequency basis, and heat-treatment phase source for determining the presence of detrimental surface effects.

e. Elapsed time between hardening and quench phases.- The maximum time interval to be permitted and the method of checking, from the end of the hardening phase to complete submersion in quench medium.



Source: https://assist.dla.mil -- Downloaded: 202610-22T19:13Z
Check the source to verify that this is the current version before use.

f. Elapsed time between quench and tempering phases.- The maximum time interval to be permitted between these phases, and the method of checking, including temperature of the adapters prior to tempering.

g. Prevention of mixing non or partially heat-treated adapters with those fully heat treated.- Procedures shall specify steps taken to preclude such mixing of adapters caused by sticking in handling containers, in-process inspections, poor housekeeping, or any other condition by which mixing of adapters may occur.

h. Records.- The storage of permament records, available for Government review, of the time-temperature cycle for all phases of the heat-treatment process and for the items in (b) through (g) above. The procedure shall provide for the identification of such records by heat-treatment batch and lot number as applicable.

6.7 Drawings.- Drawings listed in Section 2 of this specification under the headings US Army Armament Research and Development Command (ARRADCOM) may also include drawings prepared by and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARRADCOM.

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project Number: 1320-A613



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

**INSTRUCTIONS:** This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

**NOTE:** This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-P-48094B PROJECTILE, 8 INCH, HE; M509A1 ADAPTER FOR

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ *HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?* ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

| SUBMITTED BY *(Printed or typed name and address — Optional)* | TELEPHONE NO. |
|---|---|
| | DATE |

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.