MILITARY SPECIFICATION

PRESS, "H" FRAME, VERTICAL, HYDRAULIC, ELECTRIC MOTOR DRIVEN

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type of floor mounting, electric motor driven, "H" frame, hydraulic press with equipment and accessories specified herein.

1.2 Classification. This specification covers presses of the following sizes. The size press to be furnished shall be as specified (see 6.2.1 and table I).

Size 1 - 25 ton capacity.
Size 3 - 40 ton capacity.
Size 4 - 50 ton capacity.
Size 5 - 60 ton capacity.
Size 6 - 75 ton capacity.
Size 7 - 80 ton capacity.
Size 8 - 100 ton capacity.
Size 10 - 150 ton capacity.
Size 11 - 200 ton capacity.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specification and standards. The following specification and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solication.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Defense Industrial Plant Equipment Center, ATTN: DIPEC-SSG, Memphis, TN 38114-5051, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document of by letter.

AMSC N/A FSC 3442
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:40Z
Check the source to verify that this is the current version before use.

SPECIFICATION

MILITARY

MIL-M-18058 - Machinery, Metal and Woodworking, Packaging of.

STANDARDS

FEDERAL

FED-STD-H28 - Screw Thread Standards for Federal Services.

FED-STD-376 - Preferred Metric Unit for General use by the Federal Government.

2.1.2 Other Government documents. The following other Government document forms a part of this specification to the extent specified herein. Unless otherwise specified, the issue shall be that in effect on the date of the solicitation.

U. S. DEPARTMENT OF LABOR

29 CFR, CHAPTER XVII, PART 1910 - Occupational Safety and Health Standards.

(Copies of specifications, standards, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment document which is current on the date of the solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM D 3951 - Standard Practice for Commerical Packaging.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race St., Philadelphia, PA 19103-1187.)

JOINT INDUSTRIAL COUNCIL (JIC)

JIC H-1 - Hydraulic Standards for Industrial Equipment and General Purpose Machine Tools.

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:40Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the Joint Industrial Council, 7901 Westpark Drive, McLean, VA 22101-4269.)

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)

NFPA 79 - Electrical Standard for Industrial Machinery.

(Application for copies should be addressed to the National Fire Protection Association, Batterymarch Park, Quincy, MA 02269-9101.)

(Nongovernment standards and other publications are normally available from the organizations which prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order (see 6.2.1), a sample shall be subjected to first article inspection (see 4.4 and 6.3).

3.2 Design. The press shall be new and of the "H" frame type design capable of performing pressing operations in accordance with the requirements specified herein. The press shall be designed for floor mounting and shall consist basically of a frame, worktable, hydraulic head assembly, hydraulic system, electric motor pumping unit, and controls. The press shall include all components, parts, and features necessary to meet the performance requirements specified herein. All parts subject to wear, breakage, or distortion shall be accessible for adjustment, replacement, and repair.

3.2.1 Dimensional systems. Unless otherwise specified, either the U.S. Customary System of Units (US) or the International System of Units (SI) shall be used in the design and construction of the press. When only one dimensional system is acceptable, the particular system required shall be as specified (see 6.2.1). In this specification, all dimensions, measurements, sizes, and capacities are given in US units. These dimensions may be converted to SI units through the use of the conversion factors and methods specified in FED-STD-376.

3.2.1.1 Measuring and indicating device calibrations. Unless otherwise specified, either the U.S. Customary System of Units (US) or the International System of Units (SI) shall be used to graduate measuring and indicating devices such as scales, depth stops, carriage stops, dial indicators, pressure gauges, temperature indicators, and other similar devices. When

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:40Z
Check the source to verify that this is the current version before use.

only one system of graduation is acceptable, the particular graduation required shall be as specified (see 6.2.1). Regardless of the measurement system used, all measuring and indicating devices on the press shall be graduated in the same system.

3.2.2 Reclaimed materials. The press may contain reclaimed materials provided such materials will not jeopardize the intended use and performance of the press. The reclaimed materials shall have been reprocessed, remanufactured, or recycled in a manner which will restore them to the same chemical composition and physical properties as the materials originally selected for use on the press.

3.2.3 Energy efficiency. The press and its components that directly consume energy in normal operaton shall be designed and constructed for the highest degree of energy efficiency as governed by the latest developments available within the industry.

3.2.4 Controls. The press shall be equipped with all controls required for complete control of pressing operations. The controls shall provide for rapid advancement of the ram to, and retraction from, the workpiece. Ram speed shall be controllable from zero to maximum rated speed for all operating conditions. All operating controls shall be located convenient to the operator at his normal work station.

3.2.5 Safety and health requirements. Covers, guards, or other safety devices shall be provided for all parts of the press that present safety hazards. The safety devices shall not interfere with the operation of the press. The safety devices shall prevent unintentional contact with the guarded part, and shall be removable to facilitate inspection, maintenance, and repair of the parts. All parts, components, mechanisms, and assemblies furnished on the press, whether or not specifically required herein, shall comply with all of the requirements of CFR 29, Chapter XVII, Part 1910 that are applicable to the press itself. The press shall be equipped with all point-of-operation guarding normally furnished as standard on the manufacturer's commercial press supplied to the commercial market. If specific point-of-operation guarding is required, the procuring activity should specify the exact configuration of the guard required because the guard configuration is dependent on the size and configuration of the workpieces. The above, and any other additional safety and health requirements should be specified in detail (see 6.2.1).

3.2.6 Environmental protection. The press shall be so designed and constructed that, under the operating, service, transportation, and storage conditions described herein, the press shall not emit materials hazardous to the ecological system as prohibited by Federal, state, or local statutes in effect at the point of installation.

3.2.7 Interchangeability. All parts shall be manufactured to definite dimensions and tolerances that will permit installation of replacement parts without modification of the part or press.

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:40Z
Check the source to verify that this is the currentversion before use.

3.3 Construction. The press shall be constructed of parts which are new, without defects, and free of repairs. The structure shall be capable of withstanding all forces encountered during operation of the press at its maximum rating and capacity without permanent distortion.

3.3.1 Castings and forgings. All castings and forgings shall be free from defects such as scale and mismatching. Processes such as welding, peening, plugging, or filling with solders or pastes shall not be used on castings or forgings to reclaim any defective components for use on the press. Such processes may be used only for enhancing surface finish and appearance.

3.3.2 Welding, brazing, or soldering. Welding, brazing, or soldering shall be employed only where specified in the original design. None of these processes shall be employed as a repair measure for any defective part.

3.3.3 Fastening devices. All screws, pins, bolts, and other fasteners shall be installed in a manner to prevent change of tightness. Fastening devices subject to removal or adjustment shall not be swaged, peened, staked, or otherwise permanently installed.

3.3.4 Surfaces. All surfaces shall be clean and free of sand, dirt, fins, sprues, flash, scale, flux, and other harmful or extraneous materials. All edges shall be either rounded or beveled unless sharpness is required to perform a necessary function. Except as otherwise specified herein, the condition and finish of all surfaces shall be in accordance with the manufacturer's commercial practice.

3.3.5 Painting. Unless otherwise specified (see 6.2.1), the press shall be painted in accordance with the manufacturer's standard commercial practice and color.

3.3.6 Threads. All threaded parts used on the press and its related attachments and accessories shall conform to FED-STD-H28.

3.4 Components. The press shall consist of not less than the following components.

3.4.1 Frame. The press shall be of the "H" frame type, fabricated of structural steel sections. The side members shall be rigidly joined together by three or more crossmembers. The upper crossmember shall serve as the headrail to support the hydraulic head assembly. The center crossmember shall serve as the worktable. As applicable the headrail and worktable vertical travel shall conform to table I. The headrail, and all other crossmembers shall provide rigidity to the frame and maintain parallelism of the side members. The frame shall be supported by a base of adequate length and strength to provide stability during loading at maximum capacity. The frame shall have sufficient accuracy and rigidity to maintain the ram axis perpendicular to the worktable within an accuracy of 0.050 inch per foot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:40Z
Check the source to verify that this is the current version before use.

TABLE I. Size and capacities.

Size	Rated tonnage	Width between frame side-rails, (inches)	Width between table channels (max arbor size) (inches)	Distance, ram nose to table (inches)	Vertical travel of table or headrail (inches)	Ram piston travel (inches)	Ram speeds (inch per minute)	
							No load	Full load
1	25	30	7	40	35	7	28	12
3	40	30	7	40	36	7	17	8
4	50	32	7	40	35	7	15	6
5	60	40	7	36	36	7	10	6
6	75	44	8	36	30	10	10	6
7	80	48	8	36	32	7	10	5
8	100	48	10	36	36	14	7	3
10	150	48	10	30	20	14	5	3
11	200	48	18	30	24	14	4	2

NOTE: Requirements are not less than those shown.

3.4.1.1 Frame siderails and support pins. The siderails shall be either of the open type or closed type. The siderails shall have a series of equally spaced holes to provide movement of the headrail or worktable. The press siderail holes shall allow either the headrail, or the worktable, or both to be raised or lowered. The hole spacing shall provide a minimum distance between the ram nose and the worktable in accordance with the requirements of table I. The siderails shall support a mechanically operated hoist for raising and lowering the headrail or worktable, as applicable. A set of steel pins shall be provided for supporting the headrail or worktable to the siderails. The pins shall be shaped for easy insertion and removal from the holes. The total shear strength of the pin set shall be not less than double the tonnage rating of the press. The table and table support pins shall be capable of withstanding the bending stresses encountered when operating at the rated press tonnage without permanent deformation of the table support pins. The pin hole spacing in all members shall be of sufficient accuracy to insure that all pins support equal loads when the pressing force is centered between the headrail and the worktable. The width of the press between the frame siderails shall conform to the requirements of table I.

3.4.1.2 Worktable. Unless otherwise specified, a standard type worktable shall be furnished. When specified (see 6.2.1), a roll out worktable shall be furnished in lieu of the standard table.

3.4.1.2.1 Standard worktable. The standard worktable shall be designed to directly support the workpiece or the work support devices. The width between the worktable channels shall conform to the requirements of table I.

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:40Z
Check the source to verify that this is the current version before use.

3.4.1.2.2 Roll out worktable. The roll out worktable, when furnished, shall be provided with tracks mounted to the frame. The roll out worktable shall be easily rolled into and out of its normal work position below the ram axis in order to facilitate loading of the workpiece. The roll out worktable shall be provided with a locking or clamping device for locking the worktable in position below the ram assembly for pressing operations.

3.4.1.2.3 Work support device. The press shall have two work support plates that rest on the table channels to support flat workpieces. The work support plates shall be movable along the entire width of the table to provide the necessary support for any workpiece within the size range of the machine. The upper surface of the plates shall be flat and the bottom surface shall have a tongue, step, shoulder, or other means to hold the plates in alignment to prevent the plates from sliding off the table, but allow free sliding motion on the table channel surface. In addition, a pair of V-block type work support plates, suitable for supporting a round bar during straightening operations, shall be furnished with each press. A single pair of invertable blocks suitable for supporting flat workpieces on one side, and supporting round bars on the other side, may be supplied in lieu of the two pairs of supports required above.

3.4.2 Hydraulic system. The hydraulic system shall consist essentially of a fluid reservoir, a electric motor powered hydraulic pump, pressure release valve, pressure gauge, hydraulic controls, and necessary piping, hoses, and fittings. The hydraulic system design shall enable the ram to exert any tonnage up to 110 percent of the maximum rated tonnage specified in table I. All components in the hydraulic system shall have a safe working pressure rating of not less than the pressure that can be exerted by the pump. The system shall have a pressure relief valve, or similar device, to prevent loading the press beyond 110 percent of its rated tonnage. Means shall also be provided to prevent extension of the ram beyond its normal "end-of-stroke" position. All components in the system shall be sealed to prevent fluid leakage when the system is operating at full rated tonnage capacity.

3.4.2.1 Fluid reservoir. The fluid reservoir shall be capable of holding not less than 1-1/4 times the volume of fluid required to fill the hydraulic system and force the ram to the bottom of its stroke. If the hydraulic reservoir is pressurized during any part of the operating cycle, such as for rapid ram advance, the reservoir shall have a safe operating pressure rating of not less than twice the pressure that can be imposed on the interior of the reservoir.

3.4.2.2 Hydraulic pump. The hydraulic pump shall be of the electric motor powered positive displacement type and shall have a pressure and volumetric capacity that will enable the ram to exert 110 percent rated press tonnage and to comply with the ram travel speed requirements of table I. If a reciprocating pump is furnished, the pump shall be either of the doubleacting type or of the multi-cylinder, single-acting type. Pressure and displacement fluctuations shall be minimized to the extent that there is no observable variation in ram speed when the pump is operation and a pressing operation is

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:40Z
Check the source to verify that this is the currentversion before use.

in progress. The pump, or some other part of the hydraulic circuit, shall have a pressure release valve that allows pressure to be released to the reservoir, and allows the ram to be returned to the top-of-stroke position.

3.4.2.3 Pressure gauge. The hydraulic system shall include a pressure gauge calibrated to indicate ram force. The gauge shall be legible from the operator's normal work station, and shall not be obstructed by any part of the press.

3.4.2.4 Air bleeding. The hydraulic system shall be either selfbleeding or shall have provisions for bleeding air from the system after the system is filled. After the system is bled, it shall remain free of air under all conditions of operation except draining and refilling of the system.

3.4.2.5 Hydraulic head assembly. The hydraulic head assembly shall contain the hydraulic cylinder, ram piston, ram, or a ram extension mechanism. The hydraulic pump may be mounted directly on the head assembly, or may be mounted at any convenient operaing position on the press frame. Unless otherwise specified, the head assembly may be either fixed to the center of the headrail or laterally adjustable along the entire operating width of the headrail. When only one type of head assembly is acceptable, the particular type required shall be as specified (see 6.2.1). The movable type head assembly shall be provided with a means for securely clamping or locking the head assembly at any adjusted position within its range of movement. The movable type head assembly shall be capable of performing full rated tonnage pressing operations with the head assembly at any position within its range of travel without deformation of any component or structural member. All components in the hydraulic system shall conform to JIC H-1 Standards.

3.4.2.6 Cylinder and ram. The cylinder and ram shall be capable of exerting 100 percent of the full rated press tonnage without damage or permanent deformation. Means shall be provided for rapidly advancing the ram nose to contact the workpiece prior to the pressing operation and for rapidly retracting the ram to the top-of-stroke position after completion of the pressing operation. The ram piston travel and ram speed shall conform to table I.

3.4.2.7 Rapid ram advance system. The ram shall have provisions for rapidly advancing the ram to contact the workpiece prior to the pressing operation. Rapid advance may be accomplished by utilizing hydraulic pressure acting directly or indirectly on the ram piston. The average rapid advance speed (total ram stroke length in inches divided by total time in minutes to make full stroke) shall conform to the requirements in table I.

3.4.2.8 Ram retraction. The press shall have means for retracting the ram to the top of stroke position after completion of a pressing operation and after actuation of the pressure release valve. Pressure release and ram retraction shall be accomplished by operating a single control.

3.4.3 Electrical system. Unless otherwise specified (see 6.2.1), the electrical system shall conform to NFPA 79. Each press shall draw all of its electrical power from a single 230/460 volt, 3 phase, 60 Hz circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:40Z
Check the source to verify that this is the current version before use.

Each press shall have a fused safety disconnect switch or circuit breaker. The press shall be initially wired for operation on 460 volts. An identified terminal for grounding the press when it is installed shall be mounted in or near the disconnect switch. The terminal shall be suitable for connecting the size grounding conductor specified in NFPA 79 for the disconnect fuse rating.

3.4.3.1 Solid state components. Solid state design shall be used throughout the press for electronic components.

3.4.3.2 Control circuit voltage. The control circuits shall be isolated from the input electric power supply by a low voltage transformer having a secondary voltage no greater than 120 volts.

3.4 Size and capacity. Unless otherwise specified (see 6.2.1), the size and capacity of the press shall be not less than those specified in table I for the press size specified.

3.5 Performance. The press shall be capable of performing routine pressing operations within its rated tonnage capacity. The press shall be capable of exerting a force equal to 110 percent of its maximum rated tonnage capacity without permanent distortion, or other damage, to any component.

3.5.1 Additional performance requirements. Performance features required in addition to, or in lieu of, the requirements herein shall be as specified and fully described (see 6.2.1).

3.6 Standard equipment. Unless otherwise specified all standard equipment normally furnished with the manufacturer's standard commercial press shall be furnished. When specified (see 6.2.1), required additional equipment shall be furnished and fully described.

3.7 Optional equipment. Optional equipment shall be furnished as specified and shall be fully described (see 6.2.1).

3.8 Repair parts. Repair parts shall be furnished as specified (see 6.2.1).

3.9 Marking on plates and charts. All words on plates and charts shall be in the English language. Characters shall be engraved, etched, embossed, or stamped in boldface on a contrasting background.

3.9.1 Nameplate. A nameplate shall be securely attached to each press. The nameplate shall contain the information listed below. If the press is a special model, the model designation shall include the model of the basic standard press and a suffix identified in the manufacturer's permanent records. The captions listed may be shortened or abbreviated, provided the entry for each caption is clear as to its identity.

Nomenclature
Manufacturer's name

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:40Z
Check the source to verify that this is the current version before use.

Manufacturer's model designation
Manufacturer's serial number
Power input (volts, total amps, phase, frequency)
Rated press tonnage.
Contract Number or Order Number
National Stock Number or Plant Equipment Code
Date of manufacture

3.10 Technical data. When technical data is required it shall be furnished in accordance with the requirements of the contract. All technical data furnished shall be written in the English language.

3.11 Workmanship. Workmanship of the press and accessories shall be of a quality equal to that of the manufacturer's commercial equipment of the type specified herein.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does is commit the Government to acceptance of defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).

b. Quality conformance inspection (see 4.5).

4.3 Inspection conditions. Unless otherwise specified herein, all inspections, tests, and examinations shall be performed in the manufacturer's designated indoor test area under the ambient temperature, the relative humidity, and the air pressure existing inside the building at the time the inspections, tests, and examinations are performed.

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:40Z
Check the source to verify that this is the currentversion before use.

4.4 First article inspection. When first article inspection is require, it shall be applied to the first article submitted in accordance with 3.1. Unless otherwise specified (see 6.2.1), first article inspection shall consist of the examination in 4.6 and all tests in 4.7. Failure of the item to pass the first article examination and all tests shall be cause for rejection.

4.5 Quality conformance inspection. A quality conformance inspection shall be applied to each item prior to being offered for acceptance under the contract. Unless otherwise specified (see 6.2.1), quality conformance inspection shall consist of the examination in 4.6, the test in 4.7.1, and the inspection in 4.8. Failure of the item to pass the examination, the test, and the inspection shall be cause for rejection.

4.6 Examination. The press shall be visually examined to determine compliance with all requirements of this specification.

4.7 Tests.

4.7.1 Operational test. The press shall be operated and cycled at no load for not less than 10 minutes. Proper operation of all controls, motors, pumps, adjusting mechanisms, and accessories shall be verified during the trial period.

4.7.2 Performance test. The press shall be loaded and checked for proper operation when loaded to 110 percent of maximum rated capacity. The press shall retain the load for a period of not less than one hour. During and after testing, the press shall be examined for permanent distortion, breakage, hydraulic leaks, and any other evidence of nonconformance to this specification.

4.8 Packaging inspection. Packaging of each item shall be inspected to determine compliance with the requirements of section 5.

5. PACKAGING

5.1 Preservation, packing, and marking. Unless otherwise specified, preservation, packing, and marking shall be in accordance with ASTM D 3951. When specified (see 6.2.1), level A preservation, level A or level B packing, and marking shall be accomplished in accordance with MIL-M-18058.

6. NOTES

6.1 Intended use. Presses covered by this specification are for use in production, repair, and maintenance shops.

6.2 Ordering data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:40Z
Check the source to verify that this is the current version before use.

a. Title, number, and date of this specification.

b. Size required (see 1.2 and table I).

c. First article, if required (see 3.1).

d. If press is required to be configured in a specific dimensional system (US or SI), state required system (see 3.2.1).

e. If measuring and indicating devices are required to be graduated in a specific measurement system (US or SI), state required system (see 3.2.1.1).

f. Additional safety and health requirements, if required (see 3.2.5).

g. Painting, if different (see 3.3.5).

h. Roll out worktable, if required (see 3.4.1.2).

i. Specify either fixed or adjustable workhead, if required (see 3.4.2.5).

j. Electrical system and input power, if different (see 3.4.3).

k. Size and capacity, if different (see 3.4).

l. Additional performance features, if required (see 3.5.1).

m. Standard equipment, if different (see 3.6).

n. Specify and fully describe optional equipment, if required (see 3.7).

o. Specify repair parts, if required (see 3.8).

p. First article inspection, if different (see 4.4).

q. Quality conformance inspection, if different (see 4.5).

r. If preservation, packing, and marking in accordance with MIL-M-18058 is required, specify level required (see 5.1).

6.2.2 Contract data requirements. Required technical data such as operators manuals, parts lists, wiring diagrams, foundation and anchor bolt plans, and acceptance test reports should be specified on a DD Form 1423, Contract Data Requirements List, incorporated into the contract.

6.3 First article. When first article inspection is required, the item to be tested should be the first item offered for acceptance under the contract. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examination, test, and approval of the first article.

Source: https://assist.dla.mil -- Downloaded: 202640-23T04:40Z
Check the source to verify that this is the current version before use.

6.4 Cross-reference of classification changes. Machine classification changes from previous issues of this specification are as follows:

MIL-P-80128	MIL-P-80128A	MIL-P-80128B	MIL-P-80128C
Size 1	Size 1	Size 1	Size 1
Size 2	Size 2	deleted	
Size 3	Size 3	Size 3	Size 3
Size 4	Size 4	Size 4	Size 4
Size 5	Size 5	Size 5	Size 5
Size 6	Size 6	Size 6	Size 6
Size 7	Size 7	Size 7	Size 7
Size 8	Size 8	Size 8	Size 8
Size 9	Size 9	deleted	
Size 10	Size 10	Size 10	Size 10
Size 11	Size 11	Size 11	Size 11

6.5 Subject term (key words) listing.

Hydraulic presses
Machine presses
Metal working
Pressing
Rams
Straightening

6.6 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodians:
Army - AL
Navy - SH
Air Force - 99

Review activities:
Air Force - 84
DLA - GS

User activities:
Army - AR
Navy - AS, OS, MC

Preparing activity:
DLA-IP

(Project 3442-0043)

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:40Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-P-80128C	Press "H" Frame, Vertical, Hydraulic, Electric Motor Driven

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:40Z
Check the source to verify that this is the current version before use.