
FED SUP CLASS
5935



ALTERNATE CENTER
HOLE CONSTRUCTIONS

DESIGN STANDARD FOR USE WITH MIL-C-28748/3.

MS Part No. MS18178-1 - Suitable for all applications
MS Part No. MS18178-2 - For long jackscrews and hood only (thru-hole alternate construction)

© denotes change

APPROVED 20 December 1965 REVISED (A) 20 May 1970 (B) 23 June 1972 (C) 18 March 1985

Navy - EC Air Force - 11 Army - CR	International interest	TITLE Insert (insulator), rectangular connector, electrical, 34 (size 16 and 20 crimp removable) pin contacts	MILITARY STANDARD MS18178
Preparing activity: DLA - ES	SUPERSEDES MIL-C-28748		PAGE 1 OF 2

DD FORM 672 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

5935-3480-9

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:16Z
Check the source to verify that this is the current version before use.

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

User activities: Army - ME, AM, AR; Navy - MC, OS; Air Force -

Review activities: Army - MI, AT; Navy - AS, SH; Air Force - 11; DLA-ES

FED. SUP CLASS 5935

INCHES	MM
.002	0.05
.005	0.13
.010	0.25
.016	0.41
.075	1.91
.09	2.29
.090	2.29
.110	2.79
.118	3.00
.143	3.63
.150	3.81
.180	4.57
.195	4.95
.234	5.94
.260	6.60
.370	9.40
.375	9.53
.468	11.68
.511	12.98
.750	19.05
1.050	26.67
1.200	30.48
1.376	34.95
1.688	42.88
2.000	50.80

NOTES:
1. Dimensions are in inches.
2. Unless otherwise specified, tolerance is ±.015 (0.38 mm).
3. Metric equivalents are given for general information only.
4. Tolerance between any two adjacent contact centers shall be ±.004 (0.10 mm). Tolerance between any two contact centers, other than adjacent contacts, shall be ±.006 (0.15 mm).
5. Contact identification may be located on either side of the contact hole but shall appear on the front and rear of each insert.
6. For design feature purposes, this standard takes precedence over procurement documents referenced herein.
7. Referenced documents shall be of the issue in effect on date of invitation for bid.
8. (C) Designed for use with MIL-C-39029/34 contacts.
9. Contact hole details shall be in accordance with MIL-C-28748.
10. The maximum insertion and withdrawal force (connector assembly) shall be 42.5 pounds.
11. Insert material shall be in accordance with MIL-C-28748.

APPROVED 20 December 1965 REVISED (A) 20 May 1970 (B) 23 June 1972 (C) for changes see page 2 of 2

P A Navy - EC Other Cus AF-85 Army - CR	International interest	TITLE Insert (insulator), rectangular connector, electrical, 34 (size 16 and 20 crimp removable) pin contacts	MILITARY STANDARD MS18178
Procurement Specification MIL-C-28748		SUPERSEDES	PAGE 2 OF 2

DD FORM 1 MAY 73 672 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

5935-3480-9

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:16Z
Check the source to verify that this is the current version before use.