
AMSC N/A
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

REVIEWER ACTIVITIES: ARMY - ME, NAVY - OS, AIR FORCE - 82

USER ACTIVITIES: ARMY - MD, DH, NAVY - MS

FED. SUP CLASS
6640



MATERIAL: The bath shall be made of all stainless steel in accordance with ASTM Specification A167.

DESIGN: The bath shall have a built-in compressor for providing mechanical refrigeration and maintaining constant temperature for cooling. The bath shall operate from -15 to 100°C with a temperature ... rmity of ±0.2°C and shall include the following equip... steel pump, heater, circulating coils and bath ... d is a single dial control to adjust the ... meter with the range of -30 ... e 406 mm wide x 568 mm deep

CANCELLED

CANCELLED AFTER 23 OCT 1991

NO SUPERSEDING STANDARD

... c, 351.6 @ 0°C)

... quid: 300 mm W x 34 mm D
... pth: 140 mm
Co... sor, HP (W): .25 (186.5)
Refrigerant (freon): F12
Power required: 115V, 60Hz, 1250H

All electrical components shall conform to the standards of Underwriters Laboratories, Incorporated.

NOTE: Items differing from this Military Standard by minor variations in design or dimensions are considered standard under this document, provided such variations do not affect performance and are not in conflict with the material requirements specified herein.

APPROVED 30 JUN 1983 REVISED (A) 23 OCT 1991

(A) CANCELLATION

P.A. EA	INTERNATIONAL INTEREST	TITLE CIRCULATOR, REFRIGERATED BATH, LABORATORY	MILITARY STANDARD MS36414
Other Cust MS 99			
Procurement Specifications NONE	SUPERSEDES		SHEET 1 OF 1

DD FORM 1 MAY 73 672 (COORDINATED) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE CANCELLATION

Project Number 6640-1736-0

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:40Z
Check the source to verify that this is the current version before use.