AMSC A
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

USER ACTIVITIES: ARMY - CM, MD, MI
NAVY - MS

REVIEWER ACTIVITIES: ARMY - ME
AIR FORCE - 82

FED. SUP CLASS
6640



PART NUMBER	NOMINAL OVERALL DIMENSIONS (MM)		
	LENGTH	WIDTH	HEIGHT
MS36594-1	300	300	

MATERIAL: All steel components shall be i- unless otherwise specified.

Platform s- industrial spon-

Spr- Federal Spec-

Base - sphalt varni-

Housin- -- steel sheet with protect-

DESIGN: Platform -completely, and permanently covered on the exposed - with rubber, and have a 3 mm raised edge.

Platform shall be attached by four vertical springs connected to the corners of a metal base enclosed in the metal housing.

Motor shall be continuous duty, 115V, AC or DC universal type, 1/30 hp with a worm reduction gear.

Controls shall be mounted on the front of the housing. The speed control shall operate from a range of 70 to 210 oscillations/min. Positions 90, 110, 170, and 180 shall be numbered.

The speed governor shall be calibrated at 90 at 180 oscillations/min to eliminate speed changes due to variation in load or voltage.

Automatic cutoff timing device shall consist of an adjustable mounted pointer on a dial graduated in 0.5 minute increments from 0 to 25 minutes, with every 5 minute interval numbered.

Apparatus shall operate independently of the automatic cutoff timing device when in the "on" position, and operate on the timing device when in the "off" position.

When specified, the shaking machine shall conform to the electro-magnetic characteristic requirements and test limits as specified in MIL-STD-461.

(B) CANCELLATION

CANCELLED
CANCELLED AFTER 3 SEP 1991
NO SUPERSEDING STANDARD

APPROVED 15 April 1970 REVISED (A) 8 NOV 1983 (B) 3 SEP 1991

P.A.	INTERNATIONAL INTEREST	TITLE	MILITARY STANDARD
EA		SHAKING MACHINE, LABORATORY, ROTATING TYPE	MS36594
Other Cust MS 99			
Procurement Specifications MIL-S-003678	SUPERSEDES:		SHEET 1 OF 2

DD FORM 1 MAY 72 672 (COORDINATED) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE CANCELLATION

Project Number 6640-1734-02

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:44Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS
6640

All electrical components shall conform to the standards of Underwriters Laboratories, Incorporated.

NOTES:

1. Shaker shall accommodate up to 27 slides of 7.6 cm L x 5 cm W size. For microscope slides, see MS36331.

2. Items differing from this Military Standard by minor variations in design or dimensions are considered standard under this document, provided such variations do not affect performance and are not in conflict with the material requirements specified herein.

3. For design feature purposes, this standard takes precedence over procurement documents referenced herein.

4. Referenced documents shall be of the issue in effect on date of invitations for bid.

5. FSCM: 22527.

APPROVED 3 SEP 1991
REVISED (A) 8 NOV 1983 (B)

USER ACTIVITIES:

REVIEWER ACTIVITIES:

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A.	INTERNATIONAL INTEREST	TITLE	MILITARY STANDARD
EA		SHAKING MACHINE, LABORATORY, ROTATING TYPE	MS36594
Other Cust MS 99			
Procurement Specifications MIL-S-003678	SUPERSEDES:		SHEET 2 OF 2

DD FORM 1 MAY 73 672 (COORDINATED) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE Project Number 6640-1734-02

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:44Z
Check the source to verify that this is the current version before use.