FED. SUP CLASS
9530





TABLE I. DASH NUMBERS.

| DASH NO | A | TEMPER |
|---|---|---|
| 001 | .375 | 1/2 H |
| 003 | .375 | H |
| 005 | .406 | 1/2 H |
| 007 | .438 | H |
| 009 | .438 | 1/2 H |
| 011 | .469 | 1/2 H |
| 013 | .500 | 1/2 H |
| 015 | .500 | H |
| 017 | .562 | H |
| 019 | .562 | 1/2 H |
| 021 | .625 | 1/2 H |
| 023 | .625 | H |
| 025 | .688 | 1/2 H |
| 027 | .750 | 1/2 H |
| 029 | .750 | H |
| 031 | .812 | 1/2 H |
| 033 | .875 | H |
| 035 | .875 | 1/2 H |
| 037 | 1.000 | 1/2 H |
| 039 | 1.000 | H |
| 041 | 1.062 | 1/2 H |
| 043 | 1.125 | H |
| 045 | 1.125 | 1/2 H |
| 047 | 1.188 | 1/2 H |
| 049 | 1.250 | H |
| 051 | 1.250 | 1/2 H |
| 053 | 1.312 | 1/2 H |
| 055 | 1.375 | 1/2 H |
| 057 | 1.438 | 1/2 H |
| 059 | 1.500 | H |
| 061 | 1.500 | 1/2 H |
| 063 | 1.562 | 1/2 H |
| 065 | 1.625 | 1/2 H |
| 067 | 1.688 | 1/2 H |
| 069 | 1.750 | H |
| 071 | 1.750 | 1/2 H |
| 073 | 1.875 | 1/2 H |
| 075 | 2.000 | H |
| 077 | 2.000 | 1/2 H |
| 079 | 2.125 | 1/2 H |
| 081 | 2.250 | 1/2 H |
| 083 | 2.375 | 1/2 H |
| 085 | 2.500 | H |
| 087 | 2.500 | 1/2 H |
| 089 | 2.625 | 1/2 H |
| 091 | 2.750 | 1/2 H |
| 093 | 3.000 | 1/2 H |
| 095 | 3.000 | H |
| 097 | 3.250 | H |
| 099 | 3.250 | 1/2 H |
| 101 | 3.500 | H |
| 103 | 3.500 | 1/2 H |
| 105 | 3.750 | H |
| 107 | 3.750 | 1/2 H |
| 109 | 4.000 | H |
| 111 | 4.000 | 1/2 H |
| 113 | 6.000 | 1/2 H |

USER ACTIVITIES:

REVIEWER ACTIVITIES:
AIR FORCE - 84
DLA-IS

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

APPROVED 25 OCT 84
REVISED

| P.A. | INTERNATIONAL INTEREST | TITLE | MILITARY STANDARD |
|---|---|---|---|
| Other Cust MR SH 99 | | BAR, METAL, ROUND, COPPER BASE ALLOY 360 | MS52017 |
| PROCUREMENT SPECIFICATION QQ-B-626 | SUPERSEDES: | | PAGE 1 OF 2 |

DD FORM 1 MAY 73 672-1 (COORDINATED) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE 9530-0290

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:17Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

1. MATERIAL. COPPER BASE ALLOY 360 (UNS C36000), AS SPECIFIED IN PROCUREMENT DOCUMENT.
2. LENGTH. STANDARD LENGTH OF ROUND BAR IS 10 FEET MINIMUM, 12 FEET MAXIMUM.
3. FORMING PROCESS. COLD WORKED - CODE "C".
4. PART NUMBER. THE PART NUMBER CONSISTS OF THE BASIC MS NUMBER, PLUS A FORMING PROCESS CODE, PLUS A DASH NUMBER FROM TABLE I.

EXAMPLE: MS52107C001

- C001 — DASH NUMBER FROM TABLE I
- C — COLD WORKED (SEE REQUIREMENT 3)
- MS52107 — BASIC MS NUMBER

5. MARKING. COPPER AND COPPER BASE ALLOYS SHALL BE MARKED IN ACCORDANCE WITH FED-STD-185 WITH THE EXCEPTION THAT A PART NUMBER FROM THIS MILITARY STANDARD SHALL BE INCLUDED AS PART OF THE IDENTIFICATION MARKING.

NOTES:

1. ALL DIMENSIONS ARE IN INCHES.
2. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BIDS, OR REQUEST FOR PROPOSAL, EXCEPT THE REFERENCED ADOPTED INDUSTRY DOCUMENTS SHALL GIVE THE DATE OF THE ISSUE ADOPTED.
3. FOR DESIGN FEATURE PURPOSES THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.

USER ACTIVITIES:
REVIEWER ACTIVITIES:
AIR FORCE-84
DLA-IS

APPROVED 25 OCT 84 REVISED

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

| P.A. MR / Other Cust SH 99 | INTERNATIONAL INTEREST | TITLE: BAR, METAL, ROUND, COPPER BASE ALLOY 360 | MILITARY STANDARD MS 52017 |
|---|---|---|---|
| PROCUREMENT SPECIFICATION: QQ-B-626 | SUPERSEDES: | | PAGE 2 OF 2 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:17Z
Check the source to verify that this is the current version before use.