INCH-POUND


MS90558F
30 April 2009
SUPERSEDING
MS90558E
3 January 2003

DETAIL SPECIFICATION SHEET

CONNECTOR, PLUG, ELECTRICAL, WALL MOUNTING, (WITH COUPLING RING) CLASS L, (EQUIPMENT)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-22992.




Inches	mm
.005	.127
.010	.254
.011	.279
.031	.787
.062	1.57
.312	7.92

FIGURE 1. Receptacle

AMSC N/A

FSC 5935


Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:39Z
Check the source to verify that this is the current version before use.



Inches	mm
.312	7.92
.187	4.75
.010	.254
.001	.047

FIGURE 1. Receptacle - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:39Z
Check the source to verify that this is the current version before use.



Inches	mm
.101	2.56
.094	2.39
.067	1.70
.031	.79
.005	.127

FIGURE 1. Receptacle - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:39Z
Check the source to verify that this is the current version before use.

Contact size	Z dia	V dia wire sealing range
4 / 0	.614 (15.60) / .624 (15.85)	.700 (17.78) / .790 (20.07)
2 / 0	.520 (13.21) / .530 (13.46)	.530 (13.46) / .655 (16.64)
1 / 0-1	.471 (11.96) / .481 (12.22)	.457 (11.61) / .585 (14.86)
4	.339 (8.61) / .349 (8.86)	.356 (9.04) / .430 (10.92)
6	.292 (7.42) / .302 (7.67)	.300 (7.62) / .360 (9.14)

Shell size	C ± .047			F + .016 - .000	J ± .016	K ± .005	W ± .031
	Phase	Neutral	Ground				
28	.196 (4.98)	.078 (1.98)	.078 (1.98)	2.639 (67.03)	1.370 (34.80)	1.557 (39.55)	1.062 (26.97)
32	.196 (4.98)	.078 (1.98)	.078 (1.98)	2.639 (67.03)	1.370 (34.80)	1.557 (39.55)	1.062 (26.97)
44	.196 (4.98)	.078 (1.98)	.547 (13.89)	2.998 (76.15)	1.589 (40.36)	1.776 (45.11)	1.281 (32.54)
48	.196 (4.98)	.078 (1.98)	.547 (13.89)	2.998 (76.15)	1.589 (40.36)	1.776 (45.11)	1.281 (32.54)
52	.196 (4.98)	.078 (1.98)	.547 (13.89)	2.998 (76.15)	1.589 (40.36)	1.776 (45.11)	1.281 (32.54)

FIGURE 1. Receptacle- Continued.


Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:39Z
Check the source to verify that this is the current version before use.

Shell size	A Thread class 2B	G dia + .006 - .010	H + .001 - .010	L ± .031	M ± .047	N + .011 - .020	Q dia max
28	2.000-.1428P-.2857L	1.938 (49.23)	1.812 (46.02)	.959 (24.36)	.328 (8.33)	2.000 (50.80)	2.312 (58.72)
32	2.250-.1428P-.2857L	2.188 (55.58)	2.062 (52.37)	.959 (24.36)	.328 (8.33)	2.250 (57.15)	2.562 (65.07)
44	3.000-.1428P-.2857L	3.062 (77.77)	2.812 (71.42)	1.021 (25.93)	.390 (9.91)	3.125 (79.38)	3.531 (89.69)
48	3.250-.1428P-.2857L	3.312 (84.12)	3.062 (77.77)	1.021 (25.93)	.390 (9.91)	3.375 (85.73)	3.781 (96.04)
52	3.500-.1428P.2857L	3.562 (90.47)	3.312 (84.12)	1.021 (25.93)	.390 (9.91)	3.625 (92.08)	4.016 (102.01)

Shell size	R (BSC)	S + .021 - .020	T ± .005	AA dia + .006 - .005	XX dia + .001 - .010	YY dia + .010 - .001
28	1.844 (46.84)	2.375 (60.33)	.177 (4.50)	1.672 (42.47)	1.522 (38.66)	1.370 (34.80)
32	2.062 (52.37)	2.625 (66.68)	.209 (5.31)	1.922 (48.82)	1.772 (45.01)	1.620 (41.15)
44	2.812 (71.42)	3.375 (85.73)	.281 (7.14)	2.672 (67.87)	2.522 (64.06)	2.296 (58.32)
48	3.000 (76.20)	3.625 (92.08)	.281 (7.14)	2.891 (73.43)	2.725 (69.22)	2.551 (64.80)
52	3.156 (80.16)	3.875 (98.43)	.281 (7.14)	3.141 (79.78)	2.975 (75.57)	2.801 (71.15)

FIGURE 1. Receptacle - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:39Z
Check the source to verify that this is the current version before use.



Nongrounding assemblies: finish N

Shell size	Shell main key positions
	2 wire
	28 V dc
28	N (105°)
32	N (105°)
44	N (105°)
48	N (105°)
52	N (105°)

FIGURE 1. Receptacle - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:39Z
Check the source to verify that this is the current version before use.

Grounding assemblies: finish C

Shell size	Shell main key positions						
	60 Hz & 400 Hz (see note 1)						
	1 ∅			3 ∅			3 ∅ (see note 2)
	2 wire		3 wire	4 wire			3 wire
	120 V	240V	120/240 V	120/208 V	240/416 V	277/480 V	450/480 V
28	4 (120°)	5 (135°)	4 (120°)	4 (120°)	5 (135°)	6 (150°)	---------
32	4 (120°)	5 (135°)	4 (120°)	4 (120°)	5 (135°)	6 (150°)	---------
44	4 (120°)	---------	4 (120°)	4 (120°)	5 (135°)	6 (150°)	1 (60°)
48	--------	---------	4 (120°)	4 (120°)	5 (135°)	6 (150°)	---------
52	--------	---------	4 (120°)	4 (120°)	5 (135°)	6 (150°)	---------

NOTES:
1. Discrimination of 60 Hz & 400 Hz assemblies is accomplished by alternate positioning of inserts. See applicable insert drawing for keying.
2. For Navy ground support equipment use only. Arrangement 44-51, 44-52 and 44-56 are not applicable.
3. Shell main key positions 2 and 3 not used.
4. Dimensions are in inches. Metric equivalents are given for information only.
5. For protective cover, see MS90564.


FIGURE 1. Receptacle - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:39Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Mates with plugs shown on standard MS90557.
The PIN shall include the size, finish, shell key alternate position.
Inserts and contacts are removable.
For final installation contacts will be assembled in all insert holes.
Shell and nut finish shall be designated by the letter C (conductive) or N (non-conductive).
Normal key position. For alternate key positions see figure 1.
For insert arrangement, see MS90565, MS90567, MS14054, MS14055, and MS14057.
Covers specified in MS90564 shall be supplied with connector.

Part or Identifying Number (PIN) example:



Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Reference documents. In addition to MIL-DTL-22992, this document references the following:

MS14054
MS14055
MS14057
MS90557
MS90564
MS90565
MS90567

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:39Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army – CR
Navy – EC
Air Force – 85
DLA – CC

Preparing activity:
DLA – CC

Review activities:
Army – AR, MI
Navy – AS, CG, MC, OS
Air Force – 19, 99

(Project 5935–2008-087)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:39Z
Check the source to verify that this is the current version before use.