MIL-B-51254(MU)
AMENDMENT 3
7 October 1987
SUPERSEDING
AMENDMENT 2
2 February 1987

MILITARY SPECIFICATION

BREATHING APPARATUS, OXYGEN GENERATING, M20

This amendment forms a part of MIL-B-51254(MU), dated 12 December 1966, and is approved for use within the Chemical Research, Development and Engineering Center, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1:

Under "SPECIFICATIONS" "FEDERAL" delete the following:

"NN-P-00515 - Plywood, Container Grade.
PPP-B-566 - Boxes, Folding, Paperboard.
PPP-B-665 - Boxes; Paperboard, Metal Stayed (Including Stay Material)."

Under "SPECIFICATIONS" "FEDERAL" add the following:

"L-P-378 - Plastic Sheet and Strip, Thin Gauge, Polyolefin.
PPP-B-26 - Bag, Plastic, Polyethylene.
PPP-T-60 - Tape: Pressure-Sensitive, Adhesive, Waterproof, For Packaging.
PPP-F-320 - Fiberboard; Corrugated and Solid Sheet Stock (Container Grade); and Cut Shapes.
QQ-S-781 - Strapping, Steel, Flat and Seals."

Under "SPECIFICATIONS" "MILITARY" delete the following:

"MIL-P-116 - Preservation, Methods of."

PAGE 2

2.2: Delete in its entirety.

AMSC N/A

FSC 4240

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:54Z
Check the source to verify that this is the current version before use.

PAGE 4

3.1.7: Delete "two type I canisters and one type II canister (see 3.1.9)." and substitute "three type A-3 canisters (see 3.1.9)."

3.1.9: Delete paragraph and substitute "Each apparatus shall be provided with three type A-3 canisters conforming to MIL-C-17671."

3.1.12: Delete paragraph and substitute with the following:

"3.1.12 Hood. One hood supplied as an accessory shall be Mine Safety Appliance Co. part no. D304157."

PAGE 6

4.2.1, line 1: Add "packaged" before "preproduction".

4.2.2.1: Change to read as follows:

"Packaged sample apparatus shall be examined in accordance with the classification of defects (4.3.3.3(b)). After completion of the packaging inspection, the sample apparatus shall then be examined in accordance with the classification of defects (4.3.3.3(a))."

4.2.2, line 1: Add "packaged" before "apparatus".

4.3.2.1: Change to read as follows:

"Sampling for examination and test of item, and the packaging thereof, shall be conducted in accordance with MIL-STD-105."

PAGE 7

4.3.3.1: Delete in its entirety and substitute the following:

"Sample apparatus, unit packed in accordance with 5.1, shall be examined and tested in accordance with defects listed in 4.3.3.3(b) and MIL-STD-105. After completion of the packaging inspection, the sample apparatus shall then be examined and tested in accordance with the classification of defects (4.3.3.3(a)) and MIL-STD-105. MIL-STD-289 and MIL-STD-407 shall apply as visual inspection guides for rubber sheet material and rubber molded items."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:54Z
Check the source to verify that this is the current version before use.

PAGE 8

4.3.3.3(b):

Change title to read "Packaging inspection (section 5)."

Under Major Defects, delete text in its entirety and substitute the following:

"101	Unit container not as specified or damaged (3.1.7)
102	Shipping container not as specified or damaged
103	Closure of unit pack or shipping container not as specified
104	Carrying case not enclosed in polyethylene wrap or bag as specified
105	Cushioning, blocking, or bracing missing or insufficient to make a tight unit pack or pack
106	Marking of unit or shipping container not as specified"

PAGES 9 AND 10

Section 5: Delete in its entirety and substitute the following:

"5. PACKAGING

5.1 Unit packing, level A. No preservative compounds or oils shall be applied to any portion of the breathing apparatus. The breathing apparatus, consisting of a facepiece and hose assembly, back-carry harness assembly, breathing bag assembly, anti-fogging kit, hood, canisters, spanner wrench and technical publications shall be placed inside the carrying case (see 3.1.7) in such a manner to prevent damage to the rubber components of the breathing apparatus. Internal cushioning, blocking, or bracing shall be used as necessary to prevent movement of the breathing apparatus or components within the carrying case. The cover shall be secured with the fasteners provided. The case shall be either enclosed in a wrap of polyethylene conforming to L-P-378, type II (folded ends taped with tape conforming to PPP-T-60, type IV), or in a polyethylene bag conforming to PPP-B-26, type II, style 1 or 2, 0.004 inch thick material. The bag, if used, shall be closed as follows: Style 1 bags shall be either heat sealed in accordance with the bag manufacturers recommendation, or the open end taped with tape conforming to PPP-T-60, type IV. Style 2 bags shall be closed with wire tie provided.

5.2 Packing. Level shall be specified (see 6.2).

5.2.1 Level A. The breathing apparatus, unit packed as specified in 5.1, shall be packed in an overseas type, style optional, class A, cleated plywood box conforming to PPP-B-601. The box shall be minimum cube to contain the unit packed breathing apparatus. Filler pads conforming to PPP-F-320, grade W5c or

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:54Z
Check the source to verify that this is the current version before use.

W6C, shall be used as necessary to ensure a tight pack. The box shall be closed and strapped in accordance with the appendix to PPP-B-601. Strapping and seals shall conform to QQ-S-781 (Strapping - type I (Regular Duty), Finish B, Grade 2 and Seals - type D, styles I or IV, finish B, Grade 2).

5.2.2 Level B. The breathing apparatus, unit packed as specified in 5.1, shall be packed in a weather resistant fiberboard box conforming to PPP-B-636, variety SW, grade V3C, type 1 load. The box shall be minimum cube to contain the unit packed breathing apparatus. Filler pads fabricated of the same material as the box, or filler pads specified in 5.2.1, shall be used as necessary to ensure a tight pack. The box shall be closed in accordance with the Method V closure requirements and reinforced using nonmetallic strapping as tape banding in accordance with the reinforcing requirements in the appendix to PPP-B-636.

5.3 Marking. In addition to any special marking required by the contract or order, unit packs (5.1) and shipping containers (5.2) shall be marked in accordance with MIL-STD-129. Shelf life code markings shall be applied.

5.4 Repair parts. When the components of this item are procured for storage and issue as a repair part, packaging shall be specified in their applicable Special Packaging Instruction (SPI), which is identified by the part number preceded by "P".

PAGE 11

6.4: Delete paragraph in its entirety.

6.5: Delete paragraph in its entirety.

Custodian:

Army - EA

Preparing activity:

Army - EA

Project No. 4240-A932

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:54Z
Check the source to verify that this is the current version before use.