INCH-POUND
MIL-DTL-81530B(OS)
24 August 2000
SUPERSEDING
MIL-I-81530A(AS)
6 May 1987

DETAIL SPECIFICATION

IGNITION ELEMENT, ELECTRIC, MARK 11 MOD 0

This specification is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification establishes requirements for the Electric Ignition Element Mark 11 Mod 0 (see 6.1).

2. Applicable Documents.

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents specified in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications and standards. The following specifications and standards form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

DEPARTMENT OF DEFENSE

MIL-I-23659 Initiators, Electric, Design and Evaluation of

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Indian Head Division, Naval Surface Warfare Center, Standardization Team (Code 840M), 101 Strauss Avenue, Indian Head, MD 20640-5035 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document, or by sending a letter.

AMSC N/A FSC 1377

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:38Z
Check the source to verify that this is the current version before use.

STANDARDS

DEPARTMENT OF DEFENSE

DOD-STD-2101	Classification of Characteristics

(Unless otherwise indicated, copies of federal and Department of Defense specifications and standards are available from Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.2.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

Naval Air Systems Command (Code Ident 30003)

DL546659	Ignition Element, Electric, Mark 11 Mod 0
DL613457	Firing Test Fixture, Ignition Element (Output and Electrical Functioning)
838AS100	Propellant, Double Base

(Application for copies should be addressed to Commander, Naval Surface Warfare Center, Indian Head Division, 101 Strauss Avenue, Data Control Branch (Code 8410), Indian Head, MD 20640-5035.)

2.3 Non-Government publications and drawings. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI)/AMERICAN SOCIETY FOR QUALITY CONTROL (ASQC)

ASQC Z1.4	Sampling Procedures and Tables for Inspection by Attributes (DoD adopted)

(Application for copies should be addressed to the American Society for Quality Control, PO Box 3005, 611 E. Wisconsin Ave., Milwaukee, WI 53201-4606)

2.4 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:38Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 General. The Mk 11 Mod 0 Ignition Element covered by this specification shall be manufactured in accordance with DL 546659 and all documents listed thereon.

3.1.1 First article. When specified in the contract or purchase order (see 6.2), a sample shall be subjected to the first article inspection (see 4.2.1 and 6.4). Unless otherwise specified by the procuring activity, a first article sample of 146 ignition elements shall be manufactured using the same methods and procedures proposed for the production lot. The sample shall be tested as specified in 4.3.2 and is the purpose of determining that the contractor, prior to starting production, is capable of producing items which comply with the technical requirements of the contract. When the ignition element is being manufactured as an integral part of a procured cartridge, the first article and production lot testing of the Mk 11 is not required.

3.2 Material. All materials used in the manufacture of the ignition elements shall conform strictly with the specifications referred to on the respective Bureau of Naval Weapons drawings unless specific approval in writing covering a departure therefrom has been obtained from the Naval Air Systems Command prior to manufacture. When alternate materials or methods of manufacture are specified on the drawings, the bidder's selections shall be clearly stated in the proposal.

3.3 Primary Components. For the purpose of this specification the loaded spacer charge, Drawing 2302165, is defined as a primary component. See 4.3.3.

3.4 Cleaning and condition of parts. All parts shall be free of chips, dirt, grease, rust and all other foreign materials. There shall be no burrs nor other imperfections in manufacture which would harmfully affect either the assembly or the functioning of the product. The cleaning methods which are used shall not be injurious to any of the parts nor shall the parts be contaminated by the cleaning agents which are used.

3.5 Explosive components, volatiles. The primer composition, Drawing 2519878, shall have a maximum moisture content of 0.5% at time of loading as determined in 4.6.1. After consolidation of the primer composition in the loaded spacer, Drawing 2302165, the loaded spacer shall be dried at +100°F to +120°F for a minimum of 16 hours. After removal of the units from the drying equipment, if more than 4 hours elapse before their assembly into ignition elements, the units shall be dried at +100°F to +120°F for a minimum of 4 hours immediately prior to their being assembled into ignition elements.

3.6 Insulation resistance. Prior to assembly of bridgewires, the insulation resistance shall not be less than 50 megohms at a relative humidity of less than 80 percent when measured in accordance with 4.6.2.

3.7 Bridgewire (Soldering).

3.7.1 Bridgewire assembly, decontamination. All assemblies shall be cleaned and inspected as stated in 4.6.3.

3.8 Igniter assembly, loading. The consistency of the ignition charge and the loading procedure shall be regulated to secure an ignition charge which is free from internal voids while avoiding damage to the bridgewire. The ignition charge shall fill the cavity such that the charge is flush with the top of the cavity and the bridgewire is completely covered. All external surfaces of the igniter assembly shall be free from any of the ignition charge. When necessary, external surfaces may be cleaned of ignition charge by

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:38Z
Check the source to verify that this is the current version before use.

means of a cloth wet with butyl acetate. The charged igniter assembly shall be dried at a temperature of +100°F to +120°F for a minimum of 12 hours. After removal of the units from the drying equipment, if more than 4 hours elapse before their assembly into ignition elements the units shall be dried at +100°F to +120°F for a minimum of 4 hours immediately prior to their being assembled into ignition elements.

3.8.1 Ignition charge. The ignition charge shall be compounded by an improved method which contains the weight composition of nonvolatile constituents prescribed on Drawing 1558439. The finished ignition charge when ready for buttering into the igniter assembly shall be uniformly mixed slurry in which all of the particles are wetted. The consistency shall be such that the liquid will not separate from the mixture when the dish is tilted. Adjustments of the consistency may be obtained by the addition of pure butyl acetate or by evaporation of the solvent. An advisory procedure for preparing and loading the ignition charge is given in 6.4.

3.9 Ignition element inspection.

3.9.1 Visual inspection. The complete ignition element shall be free of visible defects noted in 4.6.5.

3.10 Bridgewire resistance. The bridge resistance of each completely assembled ignition element manufactured, when measured electrically as specified in 4.6.4, shall be not less than 0.08 ohm nor more than 0.14 ohm.

3.11. Tests.

3.11.1 Electrical sensitivity.

3.11.1.1 No-fire. The ignition element assembly shall not function when an electric current of 2.00 amperes is applied in accordance with 4.6.6.1. An ignition element which fires is considered defective and is sufficient cause for rejection of the lot represented.

3.11.1.2 All-fire. The ignition assembly shall fire when an electric current of 3.00 ampheres is applied in accordance with 4.6.6.2. An ignition element which does not fire is considered defective and is sufficient cause for rejection of the lot represented.

3.11.2 Functioning. Ignition elements from each production lot selected in accordance with 4.6.7 shall meet the requirements listed below when subjected to the test prescribed in 4.6.7.

3.11.2.1 Response time and output. When assembled in the firing test fixture prescribed in 4.6.7 the ignition element shall fire in a period of time not to exceed 15 milliseconds. When fired as prescribed in 4.6.7, the ignition element shall cause the puncture of a brass diaphragm 0.008 inch thick, Drawing 2302112, and subsequent thereto, successfully ignite a charge of approximately 0.080 gram of double base propellant, Drawing 838AS100. An ignition element which fails to fire in the prescribed time or to meet the output requirements shall be considered defective and shall cause rejection of the lot represented.

3.12 Workmanship. Ignition elements shall be constructed and finished in a manner to assure compliance with all requirements of this specification. Particular attention should be directed to dimensions, finishes and coatings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:38Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3)
b. Conformance inspection (see 4.4).

4.2 Sampling. Unless otherwise specified, and when applicable, the sampling plans and procedures used in the determination of the acceptability of products submitted by a supplier shall be in accordance with the provisions of ANSI/ASQC Z1.4. Unless otherwise specified in the contract, order, or requisition, all samples for test purposes shall be provided at the expense of the contractor.

4.2.1 Inspection lots. Inspection lot definition, formation, and size shall be in accordance with ANSI/ASQC Z1.4.

4.2.2 Production lots. The suggested production lot size is 1201 minimum and 3200 maximum. Ignition elements required for all test purposes are selected from the production lot and will not be applied as a part of the quantity specified for delivery by the contract. Only primary components from a single batch shall be used in a production lot of ignition elements. One primary component batch may be used in more than one ignition element production lot. Ignition elements selected for the functional test shall be delivered to the activity designated by the contracting agency.

4.3 First article inspection. Before entering into quantity production, an acceptable first article sample of 146 ignition elements shall be prepared. One hundred thirty-six of these ignition elements shall be expended in the tests listed below and 10 shall be retained for investigative purposes. A first article sample acceptable for environmental and functional testing shall be defined as a sample which has met the requirements of paragraphs 3.3 through 3.10 of this specification. The contractor shall deliver the ignition elements to the activity designated by the contracting agency for test. First article sample acceptance shall consist of the following tests as prescribed in table III of MIL-I-23659: vibration (12), 40-foot drop (6), temperature and humidity cycling (18), +70°F (50). No firing shall produce results outside the limits set forth in 3.11.2. In addition, 25 ignition elements shall be subjected to and meet the no-fire requirements of 3.11.1.1; also 25 ignition elements shall be subjected to and meet the all-fire requirements of 3.11.1.2. Failure of any ignition elements to meet the no-fire or all-fire requirements shall cause rejection of the first article lot represented. All ignition elements shall be fired in the test fixture, DL 613457. Any quantity production prior to notification by the contracting agency of first article sample acceptability shall be at the contractor's risk. The first article ignition elements will not be applied as a part of the quantity specified for delivery by the contract.

4.4 Conformance inspection. Production and acceptance inspection shall consist of verification of the characteristics classified on the drawings of DL 546659, and the tests and examinations of table I.

4.5 Classification of characteristics. The characteristics verified by the tests and examinations herein are classified as Critical, Major, or Minor in accordance with DOD-STD-2101. Tests and examinations that verify critical characteristics are identified by the symbol (C), and the major characteristic, by the symbol (M). The number following the classification symbol indicates the serial number of test or examination. Tests and examinations which are not annotated with a classification code are classified minor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:38Z
Check the source to verify that this is the current version before use.

TABLE I. Production tests and inspections.

Item	Nature of Test	Requirement	Test	Classification (DOD-STD-2101)
Primary Component	Single Batch Verification	3.3	4.3.3	(M101)
Primer Composition	Moisture Content	3.5	4.6.1	(C1)
Primer Composition	Drying Verification	3.5	-	(M102)
Inner Cup and Electrode Assembly	Insulation Resistance	3.6	4.6.2	(M103)
Bridgewire Assembly	Decomtamination	3.7.1	4.6.3	(C2)
Igniter Assembly	Loading Verification	3.8	-	(C3)
Igniter Assembly	Drying Verification	3.8	-	(M104)
Ignition Element	Visual Inspection	3.9.1	4.6.5	(M105)
Ignition Element	Bridgewire Resistance	3.10	4.6.4	(C4)
Ignition Element	No-Fire	3.11.1.1	4.6.6.1	(C5)
Ignition Element	All-Fire	3.11.1.2	4.6.6.2	(C6)
Ignition Element	Functioning	3.11.2	4.6.7	(C7)

4.6 Tests.

4.6.1 Determining moisture content. Transfer approximately 2.0 grams of the primer composition from the representative sample to a tared weighing dish, weigh to the nearest 0.1 milligram, calculate the weight of the sample, transfer weighing dish and sample to a vacuum drying oven, dry at +71°C ± 2°C and 28±2 inches of mercury vacuum until constant weight is obtained. The loss of weight is calculated as the percentage of moisture in the original sample.

4.6.2 Insulation resistance. Prior to assembly of the bridgewires, the insulation resistance shall be checked with an applied voltage of 500±25 volts d.c. This measurement shall be made between the electrode and the inner cup. Units which fail to meet the requirements of 3.6 shall be rejected.

4.6.3 Bridgewire assembly, decontamination. Before filling the cavity around the bridgewire with the ignition compound, the bridgewire sub-assembly shall be thoroughly cleaned to remove solder flux and contamination. Ultrasonic cleaning technique is recommended. Inspection for contaminates shall follow cleaning process.

4.6.4 Bridgewire resistance. Conformance with the bridge circuit resistance of 3.10 shall be ascertained by means of a test circuit which limits the bridge current to 25 milliamperes, maximum. A safety chamber with an interlock switch shall be used to protect the operator during the application of current. Instrumentation which is known to be accurate within 1% in the range of resistance specified shall be used to determine whether or not the requirement is being met. Units which fail to meet the requirements of 3.10 shall be rejected. The results of bridge circuit resistance measurements shall not be affected by resistance of the test circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:38Z
Check the source to verify that this is the current version before use.

4.6.5 Visual inspection. Examine each ignition element and reject for chips, burrs, cracks, split or perforated closure disc or for any other imperfections which would harmfully affect either assembly or functioning.

4.6.6 Electric sensitivity tests.

4.6.6.1 No-fire test. The number of ignition elements selected from each production lot for the no-fire test shall be in accordance with the requirements of table I of ANSI/ASQC Z1.4, Inspection Level 1. Each ignition element shall be conditioned at +70°F ± 5°F for a period 1 hour longer than that required to reach thermal equilibrium and tested in the firing test fixture, DL 613457. The firing circuit shall contain a resistor in series sufficient to regulate the current to 2.0 amperes measured to within an accuracy of 1.0%. This current shall be applied to the ignition element for a period of not less than 1 minute nor more than 1.1 minutes. An ignition element which fires shall be considered defective and shall cause rejection of the lot represented.

4.6.6.2 All-fire test. The number of ignition elements selected from each production lot for the all-fire test shall be in accordance with the requirements of table 1 of ANSI/ASQC Z1.4, Inspection Level I. The ignition element shall be conditioned at +70°F ± 5°F for a period 1 hour longer than that required to reach thermal equilibrium and fired in the test fixture, DL 613457. The firing circuit shall contain a resistor in series sufficient to regulate the current to 3.0 amperes measured to within an accuracy of 1.0%. Any ignition element which fails to fire within 100 milliseconds after current application shall be considered defective and shall cause rejection of the lot represented. As a precaution against obtaining an apparently defective ignition element due to high internal circuit resistance of the ignition element, it is recommended that the resistance of each ignition element be measured prior to conducting the test.

4.6.7 Functional test. The number of ignition elements selected from each production lot for the functional test shall be in accordance with the requirements of table I of ANSI/ASQC Z1.4, Inspection Level II. The ignition element shall be conditioned at +70°F ± 5°F for a period 1 hour longer than that required to reach thermal equilibrium and fired in the firing test fixture, DL 613457. In addition to the sample of ignition elements required for the test of 4.6.7, 10 additional ignition elements shall be furnished from the production lot for investigative purposes.

4.6.7.1 Criteria of acceptability.

4.6.7.1.1 Response time and output. Each ignition element shall be mounted in the firing test fixture, DL 613457, and the firing circuit shall contain a resistor in series sufficient to regulate the current to 5.0 amperes measured to within an accuracy of 1.0 percent. The firing interval between the application of current to the ignition element and the detection of explosive discharge (firing) shall be measured using an electronic timer or equally responsive instrument accurate to 1.0 percent. The timer is activated by an applied pulse to the ignition element and is stopped by photocell pickup of the explosive discharge of the double base propellant, Drawing 838AS100. The 0.008 inch thick brass diaphragm, Drawing 2302112, is used to measure the output, shall be located 2.810±015 inches from the face of the ignition element's closure disc when assembled in the test fixture. The 0.080 gram of double base propellant, Drawing 838AS100, shall be loaded in the test fixture as prescribed in DL 613457. Any ignition element which fails to meet the requirements of 3.11.2 shall be considered defective and shall cause rejection of the lot represented.

4.7 Retest. There shall be no retests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:38Z
Check the source to verify that this is the current version before use.

4.7.1 Test failure. If test failure is attributable to an assignable cause, excluding the test ignition elements, original test results should be discarded and the complete test reconducted.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When actual packaging of material is to be performed by DoD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Points packaging activity within the Military Department or Defense Agency, or within the Military Department's System Command. Packaging data retrieval is available from the managing Military Department's or Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful but is not mandatory.)

6.1 Intended use. The Mk 11 Mod 0 Ignition Element is intended for use in impulse cartridges used for stores separation. As the initiator is designed only for military aircraft, there is no commercial application for the Mk 11 Mod 0 Ignition Element.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number and date of this specification
b. Whether first article inspection is required and, if so, the test activity
c. Date and place of delivery
d. That revision A of MIL-I-23659 be used (see 4.3.2)
e. Lot size, if other than as specified (see 4.2.2)
f. Inspection conditions, if other than as specified in 4.4
g. That the safety precaution requirements of the "Contractors' Safety Manual for Ammunition, Explosives, and Related Dangerous Material," DOD 4145.26M, are applicable. NOTE: When this specification is used as part of the description of work to be accomplished by a Government activity, the safety precaution requirements of "Ammunition and Explosives Ashore," OP 5, are applicable.

6.3 First article. When a first article inspection is required, the item should be a first article sample. The first article should consist of 146 units. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirements for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract.

6.4 Advisory procedures for preparation and loading of ignition charge.

6.4.1 Preparation of ignition charge. Approximately 10 milliliters of the watered lead styphnate slurry as received are placed in a tared rubber dish. The styphnate is allowed to settle and the supernatant water

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:38Z
Check the source to verify that this is the current version before use.

is removed by decantation or by siphoning. Approximately 25 milliliters of ethanol are added and the mixture is stirred gently, allowed to settle, and the water siphoned off. An additional 25 milliliters of ethanol are added and the stirring, settling, and siphoning procedure repeated. The remaining mixture is air dried at ambient temperature for 2 hours and then oven dried for 12 hours at 90°F. The dry weight of the styphnate is then determined. In a separate container, dry cellulose nitrate equivalent to 2.0 percent of the dry weight of the lead styphnate is mixed with butyl acetate to make an approximate 0.5 percent solution. (A weighted quantity of gravimetrically standardized stock solution of approximately 0.5 percent cellulose nitrate concentration may be used to obtain the 2.0 percent of cellulose nitrate required.) This solution is added to the dry styphnate and mixed until the styphnate is thoroughly wetted.

6.4.2 Segregation and handling of ignition charge. The ignition charge is transferred to loading dishes in 2-gram batches. The loading dish should be constantly checked to prevent the mixture from becoming too dry, particularly around the edges and on top of the dish. If necessary, the operator may add butyl acetate and work the mixture to the proper buttering consistency. A maximum of 2 grams of mix should be present at each loading station and then only when an operator is present. Any spilled charge should be cleaned immediately with a cloth that has been wet with butyl acetate. The soiled cloth should be placed in a special explosives waste disposal container.

6.4.3 Operating precautions.

6.4.3.1 Lead styphnate. Dry lead styphnate is characterized by unusual sensitivity to electrical discharge. Except when absolutely necessary to obtain accurate weights, lead styphnate should never be handled in a dry state. Bulk lead styphnate should be stored under water or under butyl acetate. All loading, mixing, and handling of lead styphnate or compositions containing lead styphnate should be conducted in rooms kept at a relative humidity of 80 percent minimum.

6.4.3.1.1 Ignition charge and grounding. All mixing and loading of ignition charge should be done behind an approved safety shield. Fixture, equipment, benches, and floors should be properly grounded to prevent accidental ignition due to static discharge. This applies also to spatulas used in buttering operations which should be grounded by means of a wire connected directly to a grounded bus bar.

6.4.3.1.2 Butyl acetate. Butyl acetate, when used as a wetting agent, affords a degree of resistance to the initiation of the lead styphnate. Although not as effective as water, butyl acetate volatilizes rapidly to reduce the drying period. However, it should be note that this chemical is flammable and produces vapor which in itself is a fire hazard. Use of an exhaust system is recommended when performing buttering operations involving butyl acetate.

6.5 Gages. The contractor should provide himself with whatever gages are necessary to ensure that the material to which this specification applies will meet the dimensional requirements shown on the applicable drawings.

6.6 Subject term (keyword) listing.

Ejection systems, aircrew
Emergency escape systems, aircrew
Escape systems, aircrew
Life-saving systems, aircrew

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:38Z
Check the source to verify that this is the current version before use.

6.7 Changes from previous issue. Symbols are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Preparing activity:
Navy - OS
(Project 1377-0136)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:38Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.

2. The submitter of this form must complete blocks 4, 5, 6, and 7, and send to preparing activity.

3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	**1. DOCUMENT NUMBER** MIL-DTL-81530B(OS)	**2. DOCUMENT DATE (YYYYMMDD)** 20000824

3. DOCUMENT TITLE **IGNITION ELEMENT, ELECTRIC, MARK 11 MOD 0**

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME *(Last, First, Middle Initial)*	b. ORGANIZATION	
c. ADDRESS *(Include Zip Code)*	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON *(if applicable)*	**7.DATE SUBMITTED** (YYYYMMDD)

8. PREPARING ACTIVITY

a. NAME COMMANDER, INDIAN HEAD DIVISION, NAVAL SURFACE WARFARE CENTER	b. TELEPHONE *Include Area Code)* (1) Commercial (301) 744-4700 (2) AUTOVON 354-4700
c. ADDRESS *(Include Zip Code)* STANDARDIZATION TEAM (CODE 840M) 101 STRAUSS AVENUE INDIAN HEAD, MD 20640-5035	**IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:** Defense Standardization Program Office (DLSC-LM) 8725 John J. Kingman road, Suite 2533, Ft. Belvoir, VA 22060-2533 Telephone (703) 767-6888 AUTOVON 427-6888

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:38Z
Check the source to verify that this is the current version before use.