INCH-POUND

MIL-P-63234(AR)
AMENDMENT 3
12 JULY 1989
SUPERSEDING
AMENDMENT 2
8 June 1983

MILITARY SPECIFICATION

PROJECTILE, GUIDED, 155MM, XM712
ROLL RATE SENSOR FOR

This amendment forms a part of Military Specification MIL-P-63234(AR), dated 31 August 1979, and is approved for use within the US Army Armament Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Title: Add "M712" after the designation "XM712". Make this addition wherever "XM712" appears in the entire specification.

PAGE 3

3.2.1.4: Delete entire paragraph.

PAGE 4

3.2.2.2: Delete entire paragraph and substitute the following:

"3.2.2.2 Vibration.- The RRS shall be capable of withstanding a random vibration environment of 7.6 g rms, $0.04G^2/Hz$ power spectral density, 20 to 2000 Hz. During vibration the rate signal shall not exceed $\pm$ 5VDC and shall not exhibit a signal step change greater than $\pm$ 1 VDC. The RRS shall operate during random vibration of 2.4 g RMS at 20 to 2000 Hz and shall meet the performance during vibration of 3.2.1.3 for required data input."

3.2.2.3: Delete entire paragraph and substitute the following:

"3.2.2.3 Relative humidity.- The RRS shall withstand relative humidity exposures of greater than 90 percent at + 68°F to + 149°F."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.

* 4.4.1 Delete last sentence in its entirety and substitue the following:

"Lot size shall be no greater than one month's production and RRS Assemblies in the lot shall be from one manufacturer and have the same interfix number. There may be up to three consecutive subassembly configurations (denoted by the manufacturer's RRS modification number on the identification plates) within each Lot of RRS Assemblies, provided that the LAT sample contains a minimum of three RRS Assemblies from each of the subassembly configurations."

4.4.2.2: Add the following words to end of paragraph:

"Rejected lots shall be dispositioned in accordance with the applicable requirements of MIL-STD-105."

4.5.2.5: Delete entire paragraph.

4.5.3.3: Delete entire paragraph and substitute the following:

"4.5.3.3 Vibration test.- The vibration test shall be performed in two phases, gross operating vibration and performance vibration. Total operating time shall be seven minutes, five minutes for gross operating and two minutes for performance. The input vibration amplitude shall be reduced to zero between the two portions. The RRS shall have all input power removed for a minimum of 10 minutes prior to initiation of the Performance Vibration Test. Acceptance criteria shall be as specified in paragraph 3.2.2.2.

"4.5.3.3.1 Gross operating vibration.- The RRS shall be tested while operating during vibration per MIL-STD-810C, Method 5142, Procedure V, Part 2, Curve AF of Figure 514.2-5 at 7.6 g RMS. Power shall be applied per Figure 1 with the exception of the null store time which shall be 3.0 $\pm$ 2.0 sec instead of 1.6 $\pm$ 0.2 sec.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.

"4.5.3.3.2 Performance vibration.- The RRS shall be tested while operating with power application per Figure 1 during vibration per MIL-STD-810C, Method 514.2, Procedure V, Part 2, Figure 514.2-5, Curve AF except at 2.4 g RMS."

PAGE 8

4.5.3.4: Delete entire paragraph and substitute the following:

"4.5.3.4 Relative humidity test.- The RRS shall be tested in accordance with the humidity environment specified in MIL-STD-810, Method 507.1, Procedure V, one cycle only, and shall be tested at 72 $\pm$ 18°F for zero rate input to the requirement of 3.2.1.3 within 1 hour after humidity exposure."

PAGE 12

Replace Figure 1 with new Figure 1 attached.

PAGE 13

Replace Figure 2 with new Figure 2 attached.

PAGE 15

Replace Figure 4 with new Figure 4 attached.

PAGE 24

Table II, Major defect 105: Delete in its entirety.

PAGE 25

Table III, Para Ref/Insp Method: Delete in its entirety and substitute with the following:

"4.5.3.3, 4.5.2.1 thru 4.5.2.4."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.




Figure 1. Timing Sequence

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.




FIGURE 2. Roll Rate Output Boundaries

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.




Figure 4. Command Signal Drift Rate Boundaries

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections,deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no responsibility whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1320-AB30)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.