MILITARY
SPECIFICATION

MIL-R-55487(EL)
Amendment 1
10 JUNE 1966

# RECEIVER, RADIO R-1419( )/GR

This amendment forms a part of Specification MIL-R-55487(EL) dated 21 April 1966.

1. Page 5, add new paragraph 3.4.4.

3.4.4 Printed circuit boards.- All plug-in type printed circuit boards shall be so constructed that there can be no possibility of physically interchanging one board with any other board.

2. Page 5, add new paragraph 3.4.5.

3.4.5 Test points.- The existing test points shall be properly identified by marking the clearly on or near the actual test point. The marking shall be a suitable word, phrase, or abbreviation, indicating the circuit use or purpose of the test point. Each test point shall have provision for easy connection and removal of the test probes. A wire loop at each test point may provide this capability.

3. Page 10, paragraph 3.15.5.3 second line, delete "± 2.5 kc or 0.15 percent (whichever is larger)" and add "± 0.075 percent".

4. Page 13, paragraph 3.16.7, fifth line, change "BFO" to "audio chopper".

5. Page 14, change paragraph number "4.18" to "3.18".

6. Pages 24 and 26, delete paragraphs 4.5.3, 4.5.3.1, 4.5.3.2 and 4.5.4 and add new paragraphs.

4.5.3 Group C inspection.- This inspection shall consist of the tests specified in Table V and shall be performed on sample units that have been subjected to and met Groups A and B inspection. Sample units shall be selected in accordance with paragraph 4.5.3.1.

FSC 5820

Source: https://assist.dla.mil -- Downloaded: 202610-22T23:25Z
Check the source to verify that this is the current version before use.

4.5.3.1 Sampling for inspection.- Two sample units (excluding preproduction samples) shall be selected at random for the Group C inspection in Table V from the first 50 items produced and from each 100 items produced thereafter. The first samples selected shall be at the start of the contract from the first quality conformance inspection production lot. Two sample units are required so that different tests can be conducted at the same time. Both sample units are not to be subjected to the same tests. (See 4.5.3)

4.5.3 Noncompliance.- The contractor shall immediately report in writing each Group C failure occurrence, including details of the failure and characteristic affected. The contractor shall immediately investigate the cause of failure and further report the results of investigation and details of the proposed corrective action on (I) the process and materials, as applicable, and, (II) all units of product which were manufactured under the same conditions and which the Government considers subject to the same failure.. Reports shall be forwarded to the responsible technical activity designated in the contract through the Quality Assurance Representative. After corrective action has been taken, additional sample units shall be subjected to Group C inspection (all inspections, or the inspections which the sample failed, at the option of the Government) and Groups A and B inspection may be reinstituted; however, final acceptance and shipment will be withheld until Group C reinspection results have shown that the corrective action was effective.

4.5.4 Reinspection of Conforming Group C Sample Units.- Unless otherwise specified, sample units which have been subjected to and passed



Source: https://assist.dla.mil -- Downloaded: 202610-22T23:25Z
Check the source to verify that this is the current version before use.

Group C inspection may be accepted on the contract or order provided all damage is repaired and the sample units are resubjected to and pass Group A inspection.

7. Page 48, delete paragraph 6.4.

CUSTODIAN
Army-EL

PREPARING ACTIVITY
Army-EL

PROJECT NUMBER
5820-A348



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:25Z
Check the source to verify that this is the current version before use.