MILITARY SPECIFICATION

TEST SET, ELECTRONIC CIRCUIT PLUG-IN UNIT AN/ASM-152

This amendment forms a part of Military Specification MIL-T-81541(AS) dated 27 June 1967 and has been approved by the Naval Air Systems Command, Department of the Navy.

Page 1 paragraph 1.1: Add at end of the paragraph "of the A-4 aircraft."

Page 4 paragraph 3.4.3 Delete entire paragraph and substitute.

Page 4 paragraph 3.4.3: Interference Control The generation of radio interference by the equipment and the vulnerability of the equipment to radio interference shall be within the limits of MIL-I-6181 when loaded with appropriate CP-741(V)/A modules except that the limits of broadband switching transient interference are as follows:

Conducted: 30 db above 1 microvolt/mc
Radiated: 40 db above 1 microvolt/mc

Page 18 paragraph 3.6.1.2.8.3(2) last line. Change "XXI" to "XXIII".

Page 27 Delete "Table XXXII" and substitute the following revised Table.

Table XXXII

CONTROL MODULE Switch Position	Condition Obtained		Condition
	From	To	
All	J801-U	J801-H	0 to 0.5 ohm
All	J801-E	J801-L	0 to 0.5 ohm
All	J801-K	J801-C	0 to 0.5 ohm
13	J801-N connected to J801-T		WARN lamp lights
13	J801-P connected to J801-N		WARN lamp lights
13	J801-R connected to J801-N		WARN lamp lights
13	J801-S connected to J801-N		WARN lamp lights
All	J801-B connected to J801-T		WARN lamp lights
14	J801-P connected to J801-N		0 to 0.5 ohm
14	J801-D connected to J801-E		0 to 0.5 ohm
15	J801-P connected to J801-N		0 to 0.5 ohm
14	J801-M	J801-J (gnd)	27 ± 2.0 v d-c
15	J801-M	J801-J (gnd)	27 ± 2.0 v d-c

FSC 6625

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:39Z
Check the source to verify that this is the current version before use.