MILITARY SPECIFICATION

VEST, SURVIVAL, TYPE SV-2B

This amendment forms a part of Military Specification MIL-S-81523A(AS), dated 17 January 1969, and has been approved by the Naval Air Systems Command, Department of the Navy.

This amendment deletes "EQUIPMENT" from the title and changes "Type SV-2A" to "Type SV-2B" wherever they appear in this specification.

Page 1

SPECIFICATIONS:

(a) Under "Federal" delete "PPP-B-636" and add:

"V-T-295 Thread, Nylon"

(b) Add the following new category:

"Military

MIL-B-17757 Box, Fiber, Corrugated (Modular Sizes)"

Bottom of the page, lower right hand corner: Change "FSC 8475" to "FSC 8415."

Page 2

DRAWINGS: Under "Naval Air Systems Command" add:

"67A100D9 Securing Belt Assembly, Type SV-2B Survival Equipment Vest"

3.3.1 Cut edges: Delete the last sentence and substitute "The cut edges of the nylon duck cloth, except those that are completely covered by the nylon binding tape,

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:38Z
Check the source to verify that this is the current version before use.

Page 2 (Continued)

hook and pile fastener tapes, or are completely encased by the seam construction, shall be overedged stitched (serged)."

Page 3

Top of the page:

(a) Line 3: After "inch" add "The thread for all the overedge stitching shall conform to V-T-295, Type III, Size B, Class 1, Color Sage Green."

(b) Line 4: Change "6 to 8 stitches per inch" to "8 to 10 stitches per inch."

3.3.2.1 Sewing, line 3: After "inch" add "For stitching 1/16 inch from the seam edge, the tolerance shall be plus or minus 1/32 inch."

3.3.2.2 Bartacking: Delete in its entirety and substitute:

"3.3.2.2 Bartacking - A 1/2 inch long bartack shall contain a minimum of 28 stitches. A 3/4-inch bartack shall contain a minimum of 42 stitches. The location and length of the bartacks shall conform to the applicable drawings."

3.4 Color, line 2: After "in" add "3.3.2 and".

3.5 Dimensions, at the end of the paragraph: Add "Each pocket shall be capable of housing its intended survival equipment."

3.7 Workmanship, line 7: After "stain" add "Drill holes shall be not greater than 1/16 inch in diameter and shall be covered by the component assemblies."

Page 5

4.5.1.1 Vests:

(a) Line 3: After "specification" add "In addition, the radio, mirror, strobe light, shroud knife, pistol, knife, flare gun, and whistle pockets and sheath shall be examined for fit with the Defense Supply Agency Gage Number 610 (see 6.4)."

(b) Line 4: After "III" add "and IIIA".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:38Z
Check the source to verify that this is the current version before use.

Page 6

TABLE I, SAMPLE SIZE, ACCEPTANCE CRITERIA, EXAMINATIONS, AND TESTS OF THE VESTS: Add the following new horizontal column:

INSPECTION	PARAGRAPH		SAMPLE SIZE	ACCEPTANCE CRITERIA
	REQUIREMENT	METHOD		
"Fit examination	3.5	4.5.1.1, Table IIIA, and 4.5.2	Inspection Level S-2	An acceptable quality level of 2.5 defects per 100 units"

TABLE II, CLASSIFICATION OF DEFECTS FOR THE VISUAL EXAMINATION OF THE VESTS:

(a) Page 6, under "GENERAL", defect "a", line 1: After "hole" add "except drill holes."

(b) Page 7, under "GENERAL (Continued)" add the following new defect:

"l. Any drill hole more than 1/16 inch in diameter or not covered by any attached component". Insert "X" in the MINOR A column.

(c) Page 8, under "METALLIC COMPONENTS" add the following new defect:

"j. Any dot on any securing belt snap fastener not positioned as specified in 67A100D9". Insert "X" in the MAJOR column.

Page 11

Add the following new table:

"TABLE IIIA

LIST OF DEFECTS FOR FIT EXAMINATION OF THE POCKETS

EXAMINE	DEFECT
Fit of the applicable gage in the radio, mirror, strobe light, shroud knife, pistol, knife, flare gun, and whistle pockets and sheath.	Any pocket too small to accommodate the respective gage with the pocket in the closed position shall be enumerated as a fit examination defect."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:38Z
Check the source to verify that this is the current version before use.

Page 12

4.5.2 Procedure for measuring, at the end of the paragraph: Add "The gages shall be inserted into their respective pockets, the pockets shall be closed, and the fit of the gages observed."

5.1.1 Level A, line 5: Delete "13 by 9 inches" and substitute "11-3/4 by 7-1/2 inches".

Page 13

5.2.1 Level A:

(a) Line 1: Change "5.1" to "5.1.1"

(b) Delete the last sentence

5.2.2 Level B: Delete in its entirety and substitute:

"5.2.2 Level B - Twenty vests, packaged as specified in 5.1.1, shall be packed flat, two in length, two in width, and five in depth, within a fiberboard shipping container conforming to MIL-B-17757, Type CF, Domestic Class, Variety SW, Grade 200, Size 3A. The top and bottom of the contents of each shipping container shall be completely covered with a sheet of 30 pound minimum basis weight kraft paper conforming to UU-P-268, Grade B. The container shall be assembled, closed, and reinforced in accordance with MIL-B-17757, except that metal fasteners or stitches shall not be used. All the seams, corners, and manufacturer's joints shall be sealed with the tape conforming to PPP-T-45, Type III, Grade A, B, or C. The body joint and the top and bottom flaps shall be glued together as specified in MIL-B-17757.

Page 14

Add the following new paragraph:

"6.4 Fit examination gage - The Defense Supply Agency Gage Number 610 required by 4.5.1.1 will be supplied by the contracting officer. The gage shall consist of eight parts, radio, mirror, strobe light, shroud knife, pistol, knife, flare gun, and whistle."

Preparing activity:
Navy - AS
(Project No. 8415-N906)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:38Z
Check the source to verify that this is the current version before use.