INCH-POUND

MIL-B-49436/2B(ER)
10 December 1993
SUPERSEDING
MIL-B-49436/2A(ER)
29 March 1991

MILITARY SPECIFICATION SHEET

BATTERY, RECHARGEABLE, SEALED NICKEL CADMIUM, BB-588/U

This specification sheet is approved for use by the Army Research Laboratory, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-49436.




FIGURE 1. FRONT VIEW.

AMSC N/A FSC 6140

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:06Z
Check the source to verify that this is the current version before use.




FIGURE 2. TOP AND SIDE VIEW OF BB-588/U.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:06Z
Check the source to verify that this is the current version before use.

DRAWING NOTES:

1. All dimensions are in inches.

2. Tolerances on decimals: ±0.015 inch, unless otherwise specified.

3. Stencil (or equivalent) identification and charging instructions as shown. Color marking white.

4. Manufacturer must fill in applicable information in parenthesis.

5. Pressure relief mechanism typical location. It shall release gas before case damage is incurred.

6. Terminal marking shall be embossed or impressed. Positive terminal marking shall be colored red.

7. Last date of charge label shall be as shown on Figure 2.

8. Plastic shield around negative terminal to prevent connection of two (2) batteries together.

9. A vent cover which will allow the escape of gas (using the same type and color material as the case) shall be affixed in place when using a screw type vent valve. Vent valve shall not be removable by user.

REQUIREMENTS:

Rated capacity (C/5): 1.0 AH.

Voltage (Nominal): 13.2 Volts.

Weight (Maximum) 0.45 Kg (1.0 lb).

Connector: Snap type per MIL-B-18.

Number and type of cells: 11 sealed "4/5A" size or equal in series.

Charge rate for testing
and on battery (C/5 for 6-7 hrs): 0.20 amps.
(or when permitted, per 4.8.1.2)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:06Z
Check the source to verify that this is the current version before use.

Discharge Rates	5 Second Voltage(V)	Final Voltage(V)	Current (Amps)
C/5	-	11.0	0.2
C_5	-	11.0	1.0
3 C_5	12.1	11.0	3.0

Test	Discharge Rate	Capacity Requirement (AH)
Full Capacity Discharge	C_5	0.95
Cycle Life, 224 cycles	C_5	0.7
Overcharge, 24 hours	C_5	0.95
High Rate Discharge	3 C_5	0.72
Low Temperature Discharge at -30°C (-22°F)	C_5	0.50
Retention of Charge 7 days at 50°C (122°F)	C_5	0.60
Pulse Discharge	Not applicable	
Vibration	C/5	1.0

NOTES - 1. Unless otherwise specified, all values are minimum.
2. All charges and discharges shall be performed on fully assembled batteries through the terminals.

REQUIREMENTS:

Mounting screws for connector: Not applicable.

Connector: Battery connector shall be snap type terminal per MIL-B-18 which shall be capable of withstanding a minimum of 500 coupling and uncoupling with charging cable with no breakage, distortion or loss of electrical performance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:06Z
Check the source to verify that this is the current version before use.

Connector shield: A plastic shield shall be put around the negative terminal to prevent two BB-588/U batteries from being joined together at the snap type terminal.

Electrical leakage: Not applicable.

High rate pulse: Not applicable

Revision letters are not used to denote changes due to the extensiveness of the changes.

CONCLUDING MATERIAL:

Custodian:
ARMY-ER

Review Activities:
ARMY - CR, AV, GL

Preparing Activity:
ARMY-ER

(Project 6140-A782)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:06Z
Check the source to verify that this is the current version before use.