MILITARY SPECIFICATION

BODY ASSEMBLIES, GENERAL PURPOSE GRENADE: M73 AND M75 (PRACTICE)

This specification is approved for use by the U.S Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the quality assurance provisions and special requirements not covered by the drawings for parts and assembly of the metal parts for the Body Assemblies for the M73 and M75 (Practice) General Purpose Grenade.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078	Ammunition, Standard Quality Assurance Provisions, General Specification for

STANDARDS

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1167	Ammunition Data Card

FSC 1330

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:57Z
Check the source to verify that this is the current version before use.

2.1.2 Other government documents, drawings and publications. The following other Government documents, drawings and publications form a part of this specification to the extent specified herein.

DRAWINGS

U.S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND (ARRADCOM)

9334115	Body Assembly, M75
9335701	Body Assembly, M73
9335708	Box, Fiber, Inner
9342880	Box, Fiber, Outer
9352399	Box, Fiber, Outer

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with applicable drawings, specifications and standards.

3.2 Components and assembly. The parts and assembly shall comply with all requirements specified on Drawings (Dwg.) 9335701, 9334115 all associated drawings, and all requirements specified in applicable specifications and standards, unless otherwise specified.

3.3 Welded tubing. The welded body tubing shall be tested for weld integrity at tube fabrication in accordance with drawing 9342693.

3.4 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.5 Workmanship. All parts and assemblies shall be free of burrs, chips, sharp edges, cracks, unblended radii, surface blisters, excess flash, dirt, grease, rust, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part, nor shall the parts be contaminated by the

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:57Z
Check the source to verify that this is the current version before use.

cleaning agents. Exterior surface coatings shall be continuous except for minor scratches not exposing base material. The assembly operations shall be performed in a thorough, workmanlike manner consistent with the best practices of the industry. All required markings shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. First Article Inspection
b. Quality Conformance Inspection

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the contracting officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Part Description	Drawing	Quantity
Ring, Retaining	9335703	15
Cone	9335702	15
Body, M73 (without protective finish)	9335700	15
Cap	9335705	15
Ring, Filler	9335707	15
Body Assembly, M73	9335701	32
Body, M75 (without protective finish)	9334104	15
Body assembly, M75	9334115	32

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:57Z
Check the source to verify that this is the current version before use.

Two (2) samples of embossed stock each equivalent in length to the circumference of the embossing roll.

Two (2) samples of welded tube stock approximately 6 inches long.

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:57Z
Check the source to verify that this is the current version before use.

TABLE I. First Article Inspection.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63469(AR)

PARAGRAPH	TITLE		SHEET	DRAWING NUMBER
	Body Assembly, M73 General Purpose Grenade & M75 (Practice)		1 OF 2	See Below
				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH / PARAGRAPH REFERENCE /INSPECTION METHOD
	Cone (Dwg. 9335704)			
	Examination for defects	15		3.2 / 4.4.2.1
	Ring, Retaining (Dwg. 9335703)			
	Examination for defects	15		3.2 / 4.4.2.2
	Stock (Dwg. 9342694)			
	Examination for defects	2(a)		3.2 / 4.4.2.3
	Welded Tubing (Dwg. 9342693)			
	Examination for defects	1		3.3 / 4.4.2.4
	Flattening Test	1		3.3 / 4.5.2
	Flare Test	1		3.3 / 4.5.3
	Body, M73 (without protective finish) (Dwg. 9335700)			
	Examination for defects	15		3.2 / 4.4.2.5
	Body, M75 (without protective finish) (Dwg. 9334104)			
	Examination for defects	15		3.2 / 4.4.2.9

NOTES:

(a) Each sample equivalent in length to the circumference of the embossing roll.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil/ - Downloaded: 2026-10-23T02:57Z
Check the source to verify that this is the current version before use.

TABLE I. First Article Inspection.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63469(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
	Body Assembly, M73 General Purpose Grenade & M75 Practice				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Cap (Dwg. 9335705)				
	Examination for defects	15		3.2	4.4.2.6
	Ring, Filler (Dwg. 9335707)				
	Examination for defects	15		3.2	4.4.2.7
	Body Assembly, M73 General Purpose Grenade (Dwg. 9335701)				
	Examination for defects	32		3.2	4.4.2.8
	Leak Test of Ring & Cone Assembly with Body	32		3.2	4.5.5
	Cap Separation Test	32		3.2	4.5.6
	Pushout Force of Cone to Ring	32		3.2	4.5.7
	Pushout Force of Retaining Ring & Cone Assembly with Body	32		3.2	4.5.8
	Body Assembly (Dwg. 9334115)				
	Examination for defects	32		3.2	4.4.2.10
	Pushout test of retaining ring and cone assembly with body	32		3.2	4.5.8

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:57Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. See MIL-A-48078.

a. Sampling Plans. Unless otherwise specified in the Classification of Defects and Test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63469(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9335702
4.4.2.1	Cone				NEXT HIGHER ASSEMBLY 9335704
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Straightness		0.40%	3.2	Gage
102	Wall Thickness		0.40%	3.2	Gage
103	Wall Thickness Variation		0.40%	3.2	Gage
104	Height		0.40%	3.2	Gage
105	Outside Diameter		0.40%	3.2	Gage
Minor					
201	Evidence of Poor Workmanship		0.65%	3.5	Visual
202	Chamfer Missing or Improper		0.65%	3.2	Visual
203	Small Datum Height		0.65%	3.2	Gage
204	Large Datum Height		0.65%	3.2	Gage
205	Inside Diameter		0.65%	3.2	Gage

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63469(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.2	Ring, Retaining (Prior to Protective Finish)	1 OF 1	9335703
			NEXT HIGHER ASSEMBLY: 9335706

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Step Diameter		0.40%	3.2	Gage
102	Runout (Step Diameter to Outside Diameter)		0.40%	3.2	Gage
103	Step Height		0.40%	3.2	Gage
104	Outside Diameter		0.40%	3.2	Gage
Minor					
201	Evidence of Poor Workmanship		0.65%	3.5	Visual
202	Corner Break Missing or Improper		0.65%	3.2	Visual
203	Inside Diameter		0.65%	3.2	Gage
204	Flatness		0.65%	3.2	Gage
205	Thickness		0.65%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63469(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9342694
4.4.2.3	Embossed Stock				NEXT HIGHER ASSEMBLY 9342693
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major 101	Dimensional Inspection	2		3.2	4.5.1
Minor	None Defined				

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63469(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9342693
4.4.2.4	Welded Tubing				NEXT HIGHER ASSEMBLY 9335700
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Flattening Test	1		3.3	4.5.2
102	Flaring Test	1		3.3	4.5.3
103	Hydrostatic Test		100%	3.3	4.5.4
Minor	None Defined				

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63469(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.5	Body, M73 (Prior to Protective Finish)	1 OF 1	9335700
			NEXT HIGHER ASSEMBLY: 9335701

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	True Position (Largest Inside Diameter with Outside Diameter)		0.40%	3.2	Gage
102	Height		0.40%	3.2	Gage
103	Depth of Second Largest Inside Diameter		0.40%	3.2	Gage
104	Largest Outside Diameter		0.40%	3.2	Gage
105	True Position (Second Largest Inside Diameter with Largest Inside Diameter)		0.40%	3.2	Gage
106	True Position (Smallest Inside Diameter with Largest Inside Diameter)		0.40%	3.2	Gage
107	Largest Inside Diameter		0.40%	3.2	Gage
108	Smallest Inside Diameter		0.40%	3.2	Gage
109	Depth of Smallest Inside Diameter		0.40%	3.2	Gage
110	Slot Width (Small End)		0.40%	3.2	Gage
111	Slot Depth (Small End)		0.40%	3.2	Gage
Minor					
201	Evidence of Poor Workmanship		0.65%	3.5	Visual
202	Inside Radius Improper (2 places)		0.65%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63469(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.6	Cap				9335705
					NEXT HIGHER ASSEMBLY
					9335704
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Small Inside Diameter		0.40%	3.2	Gage
102	Angle		0.40%	3.2	Gage
103	Height to Small Inside Diameter		0.40%	3.2	Gage
Minor					
201	Evidence of Poor Workmanship		0.65%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:57Z
Check the source to verify that this is the current version before use.

MIL-B-63469(AR)

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.7	Ring, Filler				9335707
					NEXT HIGHER ASSEMBLY
					9335701
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Small Inside Diameter		0.40%	3.2	Gage
102	Large Inside Diameter		0.40%	3.2	Gage
103	Height to Small Inside Diameter		0.40%	3.2	Gage
Minor					
201	Evidence of Poor Workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63469(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.8	Body Assembly, M73 General Purpose Grenade	1 OF 1	9335701
			NEXT HIGHER ASSEMBLY: 9334103

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Largest Outside Diameter, Max.		0.40%	3.2	Gage
102	Lacquer Band Missing or Improper		0.40%	3.2	Visual
103	Leak Test of Ring & Cone Assembly with Body		100%	3.2	4.5.5
104	Cap Separation Test	32(a)		3.2	4.5.6
105	Pushout Force of Ring to Cone	32(a)		3.2	4.5.7
106	Pushout Force of Retaining Ring & Cone Assembly with Body	32(a)		3.2	4.5.8
107	Stack-up Height		0.40%	3.2	Gage
Minor					
201	Evidence of Poor Workmanship		0.65%	3.5	Visual
202	Ring Not Seated Properly		0.65%	3.2	Visual
203	Staking Improper		0.65%	3.2	Visual

NOTES:

(a) A total of thirty-two (32) body assemblies shall be selected from each lot and subjected to these tests in turn.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63469(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.9	Body, M75 (Prior to Protective Finish)	1 OF 1	9334104
			NEXT HIGHER ASSEMBLY: 9334115

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Fuze well diameter		0.40%	3.2	Gage
102	Fuze well depth		0.40%	3.2	Gage
103	Largest outside diameter		0.40%	3.2	Gage
104	Borerider slot depth max.		0.40%	3.2	Gage
Minor					
201	Ring seat diameter		0.65%	3.2	Gage
202	Ring seat location		0.65%	3.2	Gage
203	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63469(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9334115
4.4.2.10	Body Assembly, M75 General Purpose Grenade (Practice)				NEXT HIGHER ASSEMBLY 9334117
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major	None Defined				
Minor					
201	Pushout Test of retaining ring and cone assembly with body	32		3.2	4.5.8
202	Stack height		0.65%	3.2	Gage
203	Crimp spacing		0.65%	3.2	Visual
204	Retaining ring not fully seated against shoulder		0.65%	3.2	Visual
205	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:57Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein. The contractor shall submit all inspection equipment designs to the government for evaluation and approval prior to fabrication of such equipment.

4.5 Test methods and procedures.

4.5.1 Dimensional inspection of stock specimen. Two (2) stock specimens each comprised of the width of the stock to be used for production, and length as obtained from the circumference of the tool to be utilized for production, shall be selected from the coil of stock prior to forming the body. One sample shall be taken from the beginning of each coil, the other sample shall be taken from the end of each coil. An additional sample shall be taken whenever a new, repaired or altered tool is entered into production; each specimen shall be identified with an index position on the tool and for the direction of the roll. The specimen shall also be identified as being from the beginning or end of the coil. Fifteen (15) measurements shall be taken on each sample specimen for the .090 dimension and for the .13 dimension. There shall be three (3) points of measurement across the width of the specimen at five (5) places along the length. The spacing of the readings shall be approximately uniform, one (1) measurement for each characteristic shall be performed at each of the fifteen (15) measuring points on the specimen. An average value for each specimen shall be computed for each characteristic from the measurements obtained. In addition, measurements for the .232, 60° and .003R. dimensions shall be determined on the specimen from each new, repaired or adjusted rolling tool entering the production line. If the average of the fifteen (15) measurements for the .090 and .13 dimensions fails to comply, or if the direction of rolling does not comply with the requirement specified on the applicable drawing, the coil, or portion thereof, from which the sample was taken shall be rejected. Corrective action shall be performed prior to further production.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:57Z
Check the source to verify that this is the current version before use.

4.5.2 Flattening test of tubing weld seam. A minimum of one (1) section of tube four (4) to six (6) inches in length from each 2,500 feet of tubing welded from the same heat of steel shall be flattened between parallel plates with the weld at the point of maximum bending until opposite walls of the tubing meet. No opening in the weld shall take place until the distance between the plates is less than two thirds of the original outside diameter of the tubing. No cracks or breaks in the metal other than in the weld shall occur until the distance between the plates is less than one third of the original outside diameter of the tubing, but in no case less than five times the thickness of the tubing wall. Evidence of lamination or burnt material shall not develop during the flattening process, and the weld shall not show injurious defects. If a defect is found, the quantity represented by the sample shall be rejected.

NOTE: Tubing having a carbon content over 0.20 percent may be normalized prior to testing.

4.5.3 Flaring test of tubing weld seam. A minimum of one (1) section of tube, approximately four (4) inches in length from each 2,500 feet of tubing welded from the same heat of steel shall stand being flared with a tool having a 60 degree included angle until the tube at the mouth of the flare has been expanded 15 percent of the inside diameter, without cracking or showing flaws. If a defect is found, the quantity represented by the sample shall be rejected.

NOTE: Tubing having a carbon content over 0.20 percent may be normalized prior to testing.

4.5.4 Hydrostatic test of tubing. A hydrostatic test shall be performed on all tubes. The tubes shall be placed in an approved fixture with 1,000 psi of hydrostatic pressure applied. If any leakage is observed, the tube shall be rejected and removed from the lot.

4.5.5 Leak test of ring and cone assembly with body. Each body assembly shall be placed in an approved fixture and the internal air pressure specified on Dwg. 9335701 shall be applied. Any body assembly that fails the applicable acceptance criteria shall be rejected and removed from the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:57Z
Check the source to verify that this is the current version before use.

4.5.6 Cap separation test. Thirty-two (32) body assemblies shall be selected from each lot and subjected to this test. Apply a load perpendicular to the cap and in such a direction as to test the strength of the assembly of the cap to the cone. If any body assembly fails to comply with the requirement specified on drawing 9335704, the lot represented by the sample shall be rejected.

4.5.7 Pushout force of cone to retaining ring. After completion of test 4.5.6, subject the same body assemblies to this test. Apply a load circumferentially to the cone and in such a direction as to test the strength of the assembly of the cone to the rest of If any body assembly fails to comply with the requirement specified on drawing 9335706, the lot represented by the sample shall be rejected.

4.5.8 Pushout force of retaining ring and cone assembly with body. After completion of test 4.5.7 where applicable, subject the same body assemblies to this test, as described on the drawing. If any body assembly fails to comply with the requirement, the lot represented by the sample shall be rejected.

5. PACKAGING

5.1 Preservation and packaging. The body assemblies shall be preserved and packaged in accordance with Dwg. 9335708, Dwg. 9342880, and Dwg. 9352399 where applicable.

5.2 Packing. The body assemblies, preserved and packaged as specified in 5.1.1, shall be packed for shipment in accordance with Dwg. 9335708, Dwg. 9342880, and Dwg. 9352399 where applicable.

5.3 Marking. Marking shall be in accordance with Dwg. 9335708, Dwg. 9342880, and Dwg. 9352399 where applicable.

5.4 Shipping. When components from more than one lot are shipped as a carload, each lot shall be kept separate and the division between lots clearly indicated to prevent mixing of the lots in transit.

5.5 Ammunition data cards. Data card information shall be as specified in MIL-STD-1167.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:57Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The M73 body assembly is intended for use in the M73 General Purpose Grenade and M75 Body Assembly for use in the M75 Practice Grenade.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment for design approval. See 6.2.3 of MIL-A-48078. Submit equipment designs as required to Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAF-I, Dover, NJ 07801.

6.4 First article. When a first article is required for inspection and approval, see 3.4 and 4.3.

6.5 Source control and specification control drawings. Certificate of conformance from the supplier certifying that the item complies with the drawing requirements shall be provided to the government representative.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1330-A156)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:57Z
Check the source to verify that this is the current version before use.