MILITARY SPECIFICATION

CARTRIDGE, DELAY: M175 ASSEMBLY

This amendment forms a part of Military Specification MIL-C-60644(MU), dated 1 February 1968, and is approved for use within the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* 2.1 Delete: "MIL-E-5272 . . ." in its entirety.
Delete: "MIL-C-60539 . . ." in its entirety.
Delete: "MIL-STD-639 . . ." in its entirety.
Add: "MIL-A-8625 Anodic Coatings, for Aluminum and Aluminum Alloys".
Add: "MIL-STD-810 Environmental Test Methods and Engineering Guidelines".

PAGE 2

2.1: DRAWINGS: Delete "C8864169 - Carton, Outer Packing, Ammunition for Cartridge, Delay: M175" and substitute:

"C9214156 - Box, Packing Ammunition for Cartridge Initiator Delay M84, M85, M86, M87, M88, M89, M165, XM128, XM148, XM159, M174 or M175."

* Add: "2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the document which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer, Naval Ordnance Station, Standardization Branch (3730), Indian Head, MD 20640-5000.

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:52Z
Check the source to verify that this is the current version before use.

ANSI B46.1 Surface Texture (Surface Roughness, Waviness and Lay)

(Application for copies should be addressed to the American National Standards Institute (ANSI), 1430 Broadway, NY 10018)

(Nongovernment standards and other publications are normally available from the organization which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)"

* 3.2 Delete ". . . MIL-C-60539" and substitute ". . . MIL-A-8625".

* 3.3 Delete ". . . in MIL-E-5272, Procedure X11 . . ." and substitute: ". . . MIL-STD-810, Method 514.3, Test Procedure I. Test Condition I - 3.2.5 . . .".

PAGE 3

3.5.2., Table I, under "Delay Seconds", add:

"5.0 $\pm$ 0.3" second to 65° to 75° F. temperature range"

PAGE 4

4.2.1, line 4: Delete "50" and substitute:

"15" for carbon monoxide test.

4.2.1, Table II, under Sample Size: Delete "50" and substitute:

"15" for Carbon Monoxide Test.

PAGE 5

* 4.3.2 Delete: "The Ordnance Standard Finish Blocks prescribed in MIL-STD-639 . . ." and substitute: "The roughness comparison standards prescribed in ANSI B46.1 . . .".

PAGE 6

4.3.2.1 Paragraph title: Change "XM45" to "M45".

PAGE 8

4.3.2.4, under MAJOR Defects: Delete Defect "103" in its entirety and substitute: "103. Location of crimp with delay element ..... Gage".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:52Z
Check the source to verify that this is the current version before use.

PAGE 9

4.3.2.6: Delete paragraph title in its entirety and substitute: "Box, Packing Ammunition for Cartridge Initiator Delay, M175, Drawing C9214156".

PAGE 10

4.3.3.5, line 1: Delete "Fifty" and substitute: "Fifteen".

* 4.4.1 Delete ". . . MIL-C-60539" and substitute: ". . . MIL-A-8625".

* 4.4.4 Delete ". . . in MIL-E-5272, Procedure XII . . ." and substitute: " . . . in MIL-STD-810, Method 514.3, Test Procedure I, Test Condition I-3.2.5 . . ."

4.4.6: Delete and substitute:

"4.4.6 Sealant application. The cartridge shall be disassembled in such a manner that determination can be made that the sealant has been applied for the full length (360°) of the joining surfaces at the junction of the "O" Ring and case sidewall and that the propellant cavity is free of sealant."

5.1, line 2: Delete "C8864169" and substitute: "C9214156"

6.2 Changes from previous issue. The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Preparing Activity:
Navy - OS
Project No. 1377-N885

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:52Z
Check the source to verify that this is the current version before use.