MIL-C-63130(AR)
AMENDMENT 4
20 March 1979
SUPERSEDING
AMENDMENT 3
2 November 1978

MILITARY SPECIFICATION

CARTRIDGE, 40MM, GREEN SMOKE, GROUND MARKER, M715
LOADING, ASSEMBLING AND PACKING

This amendment forms a part of Military Specification MIL-C-63130(AR), dated 14 March 1977.

PAGE 4

Add the following paragraph:

"3.7 X-ray examination of ballistic samples. - Prior to forwarding the sample cartridges for ballistic testing, they shall be x-rayed for critical and major defects. A Critical defect is defined as no delay assembly or delay assembly above face of fuze support."

PAGE 4 AND 5

Paragraph 4.3.3.1. -

e. Delete "Mean velocity or standard deviation fail the applicable requirement (average)" and substitute "e Mean velocity or standard deviation fail the applicable requirement at ambient phase only. Informational at hot and cold phases."

FSC: 1310

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:17Z
Check the source to verify that this is the current version before use.

PAGE 8

Paragraph 4.4.2.1. - Add the following Major Defect characteristic:

"105 - Stake missing or improper 0.40% 3.2 visual. "
(prior to assembling tape)

PAGE 9

Paragraph 4.4.2.2. -

Major 102. Delete "50 2.50%" and substitute 4 per hr. **."

Under NOTES add:

"** If any sample fails to comply with the drawing requirement, the hours production represented by the sample shall be rejected."

* Add the following QUALITY CONFORMANCE INSPECTION Paragraph 4.4.2.6.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:17Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63130(AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.6	Projectile Loaded (Green Smoke)	1	1	9323263
				NEXT HIGHER ASSEMBLY 9323264

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major					
101.	Total depth of cavity		0.40%	3.2	Gage
102.	Diameter of cavity		0.40%	3.2	Gage
103.	Conentricity of cavity with bourrelet		0.40%	3.2	Gage
104.	Seating surface for base not visible for 360°		0.40%	3.2	Visual
Minor:	None defined				

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:17Z
Check the source to verify that this is the current version before use.

PAGE 13

Paragraph 4.4.3.1. -

(a) Delete "moisture content" throughout and substiute "total volatiles"

(b) After eight (8) delete "of each"

Paragraph 4.4.3.3. - Delete "examined visually with," and substitute "examined visually without"

PAGE 17

Add the following paragraph:

"4.4.3.10. X-ray examination of ballistic samples. - Prior to forwarding the sample cartridges for ballistic testing, they shall be x-rayed for critical and major defects. If any critical defect is found, the sample shall be removed and the lot rejected including the ballistic samples and 100% x-ray examination of the lot shall be performed prior to submitting a new ballistic sample. If any major defect is found, it shall be noted and the sample forwarded for testing."

PAGE 14 and 15

Paragraph 4.4.3.5.4. -

e. Delete "Mean velocity or standard deviation fail the applicable requirement (average)" and substitute "e Mean velocity or standard deviation fail the applicable requirement at ambient phase only. Informational at hot and cold phases."

PAGE 16 and 17

Paragraph 4.4.3.9.4. -

e. Delete "Mean velocity or standard deviation fail the applicable requirement (average)" and substitute "e Mean velocity or standard deviation fail the applicable requirement at ambient phase only. Informational at hot and cold phases."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:17Z
Check the source to verify that this is the current version before use.

Paragraph 4.5.1 and 4.5.1.1. - Delete "moisture contenet" throughout and substiute "total volatiles"

PAGE 19

Add the following paragraph:

"4.5.8 X-ray examination of ballistic samples. - The sample cartridges prior to forwarding for ballistic testing, shall be subjected to x-ray examination using approved x-ray equipment.'

* The margins of this amendment are marked with an asterisk to indicate where changes (additions, modification, correction, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requriements of this document based on the entire content irrespective of the marginal notations and relationship to the previous amendment.

Custodian:
Army-AR

Preparing Activity
Army-AR

Project Number: 1310-A-217

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:17Z
Check the source to verify that this is the current version before use.