MILITARY SPECIFICATION SHEET

FITTINGS, WIRE REINFORCED HYDRAULIC HOSE AND CLAMP-HALVES: FIELD ATTACHABLE (REUSABLE), SCREW-ON TO 37° FLARE FEMALE SWIVEL, STRAIGHT, FOR USE WITH TYPE 100RE FOUR-SPIRAL-WRAP REINFORCEMENT HOSE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the fittings described herein shall consist of this specification and the latest issue of specification MIL-F-52525.

REQUIREMENTS:

1. The fittings shall conform to figure 1 and table I.

FSC 4730

AMSC N/A

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:23Z
Check the source to verify that this is the current version before use.

TABLE I. Dimensions for type 100RE fittings, straight.

Specification part number	Hose dash number	Hose I.D		Hose O.D		Tube dash number	Tube O.D		Nominal Thread size
		inch	mm	inch	mm		inch	mm	
M52525/31-12-12	12	.75	19.05	1.26	32.00	12	.75	19.05	1-1/16-12
M52525/31-16-16	16	1.00	25.4	1.51	38.35	16	1.00	25.4	1-5/16-12

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:23Z
Check the source to verify that this is the current version before use.

TABLE I. Dimensions for type 100RE fittings, straight. - Continued

Specification part number	Hose dash number	H Nominal hex size	L		M		N	
			Maximum		Minimum		+.030 -.015	+0.8 -0.4
		inch	inch	mm	inch	mm	inch	mm
M52525/31-12-12	12	1.25	1.88	47.75	.469	11.91	.562	14.27
M52525/31-16-16	16	1.50	2.31	58.67	.563	14.30	.594	15.09

Source: https://assist.dla.mil -- Downloaded: 202640-22T21:23Z
Check the source to verify that this is the current version before use.

TABLE I. Dimensions for type 100RE fittings, straight. - Continued

Specification part number	Hose dash number	P		Q		C	
		±.005	±0.13	Minimum		Maximum	
		inch	mm	inch	mm	inch	mm
M52525/31-12-12	12	.850	21.59	.61	15.49	5.95	151.13
M52525/31-16-16	16	1.100	27.94	.78	19.81	6.37	161.80

Source: https://assist.dla.mil -- Downloaded: 2026/10-22T21:23Z
Check the source to verify that this is the current version before use.

2. The maximum working pressures shall be as specified in table II.

TABLE II. Maximum working pressures of fittings.

Hose I.D. (REF) (inch)	Pounds per square inch (PSI)	Megapascals (MPa)
.75	6250	43.1
1.00	5000	34.5

3. The over-tightening torque for swivel nuts shall be as specified in table III.

TABLE III. Over-tightening torque for swivel nut.

Nominal tube O.D. (REF) (inch)	Torque	
	Inch pounds	Newton meter (N·m)1/
.75	900	101.7
1.00	1200	135.6

1/Torque is expressed as Newton meter per radian (N·/rad) rad = N·m.

4. Marking shall include the manufacturer's name or trademark, size, and hose identifier 100RE. Location of marking is optional.

5. Method of fabrication and assembly and of swivel nut is optional.


6. This item must be listed on QPL-52525.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:23Z
Check the source to verify that this is the currentversion before use.

INTENDED USE: Type 100RE fittings are for use with four-spiral-wrap reinforced hose conforming to MIL-H-52471, type 100RE.

CATALOGING DATA: The military specification part number is a definitive part number which corresponds to the size fitting covered by this specification sheet. The military specification number, the military specification sheet number, code number for size of hose, and code number for size of tube are combined to form the military specification part number.

EXAMPLE: Military specification part number



The approved item name of this item, in accordance with the Federal Item Name Directory for the Federal Catalog System, Handbook H6, Section A, is Adapter.

Custodian:
Army - ME

Review activities:
Army - GL
DLA - CS


User activities:

Air Force - 99

Preparing activity:
Army - ME

Project 4730-0657

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:23Z
Check the source to verify that this is the current version before use.



(a) DIMENSION P TO BE CONCENTRIC WITH DIMENSION Q WITHIN 0.015 F I M.

FIGURE 1. Fitting, screw-on to 37° flare, straight.

X-3355A

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:23Z
Check the source to verify that this is the current version before use.