INCH-POUND

MIL-DTL-60996B(AR)
25 December 2025
SUPERSEDING
MIL-C-60996A(PA)
15 August 1974

DETAIL SPECIFICATION

CHARGE, DEMOLITION ROLL, M186
PARTS, LOADING, ASSEMBLING AND PACKING

This specification is approved for use by the U.S. Army Armaments Center and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE.

1.1 Scope. This specification covers the parts, loading, assembling and packing for one type of demolition charge designated as Charge, Demolition Roll, M186.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3, 4, and 5 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents cited in sections 3, 4, and 5 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

Comments, suggestions, or questions on this document should be addressed to: U.S. Army DEVCOM Armaments Center, ATTN: FCDD-ACE-QSA, Picatinny Arsenal, New Jersey 07806-5000, or emailed to usarmy.pica.devcom-ac.list.ardec-stdzn-branch@army.mil. Since contact information can change, you may want to verify the currency of this information using ASSIST Online database at https://assist.dla.mil.

AMSC N/A FSC 1375

Distribution Statement A. Approved for public release: distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:08Z
Check the source to verify that this is the current version before use.

DEPARTMENT OF DEFENSE SPECIFICATION

MIL-DTL-15011	–	Pallets, Material Handling, Wood: Post Construction, 4-Way Entry
MIL-PRF-46676	–	Flexible Explosive

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-1168	–	Ammunition Lot Numbering and Ammunition Data Card
MIL-STD-1916	–	DoD Preferred Methods for Acceptance of Product
MIL-STD-2073-1E	–	Standard Practice for Military Packaging

(Copies of these documents are available online at (https://quicksearch.dla.mil/.)

2.2.2 Other Government documents, drawings and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract (see 6.2).

U.S. ARMY ARMAMENTS CENTER DRAWINGS

8887302	–	Holder, Blasting Cap, M8
9211459	–	Charge, Demolition Roll, M186
9211460	–	Explosive, Flexible, For Charge, Demolition Roll, M186
9211461	–	Parts Assy, Charge, Demolition Roll, M186
9214256	–	Core
9214259	–	Disk
9216714	–	Bag, Packing, Ammunition, For Charge Demo Roll, M186
9216715	–	Box, Wirebound, Packing, Ammunition for Charge, Demolition Roll, M186
9297231	–	Charge, Demolition Assembly M186
9297232	–	Bag, Packing, For Holder Blasting Cap, M8
9298299	–	Bag Assembly, With Blasting Cap Holder
13021068	–	Disk (Alternative)

(Copies of these drawings may be requested via email at usarmy.pica.devcom-ac.list.drawing-request-help-desk@army.mil.)

U.S. Army Defense Ammunition Center Drawings

19-48-4116/120F	–	Unitization Procedures for Boxed Ammunition and Components on 4-Way Entry Pallets

(Copies of these drawings may be obtained at https://defenseammunitioncenter.army.mil/.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:08Z
Check the source to verify that this is the current version before use.

2.3 Non-Government standards and publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents are those cited in the solicitation or contract.

ASTM INTERNATIONAL

ASTM E18 – Standard Test Methods for Rockwell Hardness of Metallic Materials

(Copies of these documents are available from https://www.astm.org/.)

2.4 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Required inspections.

3.1.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection in accordance with 4.2.

3.1.2 Conformance. A sample shall be subject to conformance inspection in accordance with 4.3.

3.2 Materials and assemblies. Materials and assemblies shall be in accordance with Drawing 9297231 and all subsidiary drawings and specifications.

3.2.1 Reclaimed material. A blend of reclaimed and virgin plastic material may be used provided the requirements of this specification are met. The blend shall be limited to not less than 70 percent virgin material. The reclaimed material shall be clean scrap, free from any type of foreign material not related to the blend. Floor sweepings shall not be accepted as clean scrap.

3.2.2 M8 blasting cap holder. M8 blasting cap holders shall be in accordance with Drawing 8887302.

3.2.2.1 Hardness of M8 blasting cap holder. The M8 blasting cap holder shall have a hardness meeting the requirement on Drawing 8887302.

3.2.3 Heat seal test. Bags containing M8 blasting cap holders shall meet the heat seal strength defined in MIL-STD-2073-1E (see Drawing 9298299).

3.2.4 Susceptibility to cracking. The parts assembly (Drawing 9211461) shall not crack or separate when subjected to temperature conditioning at –65 ± 5˚F for a period of not less than 24 hours.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:08Z
Check the source to verify that this is the current version before use.

3.3 Marking. All required markings shall be neat and sharply defined.

3.4 Workmanship. All parts and assemblies shall be clean and free of burrs, sharp edges, unblended radii, surface defects, chips, dirt, grease and oil, holes, tears, voids, porosity, warpage, excess flush, cracks, chipped edges, blisters, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part or assembly nor shall be contaminated by the cleaning agent. Exterior surface coating shall be continuous except for a few light scratches not exposing base material.

4. VERIFICATION

TABLE I. Requirements/verification cross reference matrix.

Methods of verification 1 – Analysis 2 – Demonstration		3 – Examination 4 – Test				Classes of verification A – First article B – Conformance		
Section 3 Requirement	Description	Verification Methods				Verification Class		Section 4 Verification
		1	2	3	4	A	B	
3.1.1	First article			X		X		4.2
3.1.2	Conformance			X			X	4.3
3.2	Materials and assemblies			X		X	X	4.3 thru 4.5
3.2.1	Reclaimed material			X		X	X	4.3.2.1 thru 4.3.2.3
3.2.2	M8 blasting cap holder			X	X	X	X	4.3.2.6, 4.4.2
3.2.2.1	Hardness of M8 blasting cap holder				X	X	X	4.4.2
3.2.3	Heat seal test			X		X	X	4.4.3
3.2.4	Susceptibility to cracking			X		X	X	4.4.1
3.3	Marking			X		X	X	4.3.2.5, 4.3.2.7 thru 4.3.2.9, 10, 4.4.1
3.4	Workmanship			X		X	X	4.3.2.1 thru 4.3.2.14
5.1	Packaging			X		X	X	4.3.2.12 thru 4.3.2.13
5.2	Marking			X		X	X	4.3.2.12 thru 4.3.2.14
5.3	Unitization			X		X	X	4.3.2.14

4.1 Classification of inspection. The inspection requirements specified herein are classified as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:08Z
Check the source to verify that this is the current version before use.

a. First article inspection (see paragraph 4.2).
b. Conformance inspection (see paragraph 4.3).

4.2 First article inspection. A sample shall be subjected to first article verification in accordance with Table II. The first article sample shall consist of parts and sub-assemblies which have been produced by the contractor or furnished by supplier and which have been manufactured using the same production processes, procedures and equipment which shall be used in regular production.

TABLE II. First article acceptance tests.

Examination or test	Conformance criteria	Requirement paragraph	Inspection method
Core (Drawing 9214256) 1/			
Examination for defects	25	3.2	4.3.2.1
Disk (Drawing 9214259) 1/			
Examination for defects	25	3.2	4.3.2.2
Disk (alternative) (Drawing 13021068) 1/			
Examination for defects	25	3.2	4.3.2.3
Parts assembly, charge demo roll, M186 (Drawing 9211461)			
Susceptibility to cracking	25	3.2.4	4.4.1
Examination for defects	25	3.2, 3.3	4.3.2.4
Explosive, flexible (Drawing 9211460)			
Examination for defects	25	3.2, 3.3	4.3.2.5
Holder, blasting cap, M8 (Drawing 8887302)			
Hardness	25	3.2.2.1	4.4.2
Salt spray test	Per drawing	3.2	Per drawing
Examination for defects	25	3.2.2	4.3.2.6
Charge, demolition roll, M186 (Drawing 9211459)			
Examination for defects	25	3.2, 3.3	4.3.2.7
Bag, packing, ammunition, for charge demo roll, M186 (Drawing 9216714)			
Examination for defects	25	3.2, 3.3	4.3.2.8
Bag, packing, for holder blasting cap, M8 (Drawing 9297232)			
Examination for defects	25	3.2, 3.3	4.3.2.9

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:08Z
Check the source to verify that this is the current version before use.

TABLE II. First article acceptance tests - Continued.

Examination or test	Conformance criteria	Requirement paragraph	Inspection method
Bag assembly, with blasting cap holder (Drawing 9298299)			
Heat seal test	2	3.2.3	4.4.3
Examination for defects	25	3.2, 3.3	4.3.2.10
Charge demolition assembly M186 (Drawing 9297231)			
Examination for defects	25	3.2	4.3.2.11
Box, wirebound, packing (prior to close) (Drawing 9216715)			
Examination for defects	8	3.2	4.3.2.12
Box, wirebound, packing sealed (Drawing 9216715)			
Examination for defects	8	5.1 thru 5.3	4.3.2.13
Unitization (Drawing 19-48-4116/120F)			
Examination for defects	1	5.2, 5.3	4.3.2.14
Notes: 1/ The parts assembly (Drawing 9211461) may be assembled by either a Core and two Disks, or by assembling two Disks (alternative).			

4.2.1 Rejection. If any sample fails to comply with any of the applicable requirements the first article quantity shall be rejected.

4.3 Conformance inspection.

4.3.1 Lot formation. Lot formation shall be in accordance with the lot formation requirements of MIL-STD-1916. Ammunition lot numbers shall be assigned in accordance with MIL-STD-1168. In addition, each lot of demolition charge rolls shall contain the following:

a. Parts of one kind from one supplier
b. Flexible explosive from one lot

4.3.2 Examination. The examinations listed in the following tables and subparagraphs shall be performed on inspection lots of the components or assemblies designated in the Classification of Defects and Test tables or paragraphs. Unless otherwise specified in the Conformance Inspection, sampling plans for Major and Minor defects shall be in accordance with MIL-STD-1916, Verification Level IV for Major defects and Verification Level II for Minor defects. Unless otherwise noted, any assembly, subassembly, material, or component which fails to comply with the conformance inspection requirements shall reject the batch/lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:08Z
Check the source to verify that this is the current version before use.

4.3.2.1 Core.			Drawing Number 9214256 Next Higher Assembly 9211461	
Classification	Examination or Test	Conformance Criteria	Requirement Paragraph	Inspection Method
Critical	None defined			
Major				
101	Outside diameter across web, maximum (max.)	VL-IV	3.2	AIE
102	Length of web pilot, minimum (min.)	VL-IV	3.2	AIE
103	Crack or split	VL-IV	3.2	Visual
Minor				
201	Thickness of rim	VL-II	3.2	AIE
202	Inside diameter of hub	VL-II	3.2	AIE
203	Length of rim	VL-II	3.2	AIE
204	Width of slot	VL-II	3.2	AIE
205	Percentage of reclaimed material	Once per lot	3.2.1	Examination of objective evidence
206	Evidence of poor workmanship	VL-II	3.4	Visual

4.3.2.2 Disk.			Drawing Number 9214259 Next Higher Assembly 9211461	
Classification	Examination or Test	Conformance Criteria	Requirement Paragraph	Inspection Method
Critical	None defined			
Major				
101	Crack or split	VL-IV	3.2	Visual
102	Length of hub	VL-IV	3.2	AIE
103	Width of slit of hub	VL-IV	3.2	AIE
104	Thickness of hub	VL-IV	3.2	AIE
105	Perpendicularity of hub with respect to base	VL-IV	3.2	AIE
Minor				
201	Outside diameter	VL-II	3.2	AIE
202	Inside diameter	VL-II	3.2	AIE
203	Thickness of base	VL-II	3.2	AIE
204	Percentage of reclaimed material	Once per lot	3.2.1	Examination of objective evidence
205	Evidence of poor workmanship	VL-II	3.4	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:08Z
Check the source to verify that this is the current version before use.

4.3.2.3 Disk (alternative).			Drawing Number 13021068 Next Higher Assembly 9211461	
Classification	Examination or Test	Conformance Criteria	Requirement Paragraph	Inspection Method
Critical	None defined			
Major				
101	Crack or split	VL-IV	3.2	Visual
102	Outside diameter of disk	VL-IV	3.2	AIE
103	Outside diameter of hub	VL-IV	3.2	AIE
104	Height of hub	VL-IV	3.2	AIE
105	Thickness of disk	VL-IV	3.2	AIE
106	Inner diameter of hub	VL-IV	3.2	AIE
107	Distance from height of hub to step of tab	VL-IV	3.2	AIE
108	Width of slot	VL-IV	3.2	AIE
Minor				
201	Percentage of reclaimed material	Once per lot	3.2.1	Examination of objective evidence
202	Evidence of poor workmanship	VL-II	3.4	Visual

4.3.2.4 Parts assembly, charge demo roll, M186.			Drawing Number 9211461 Next Higher Assembly 9211459	
Classification	Examination or Test	Conformance Criteria	Requirement Paragraph	Inspection Method
Critical	None defined			
Major				
101	Parts improperly or inadequately secured	VL-IV	3.2	Visual
102	Susceptibility to cracking	25	3.2.4	4.4.1
Minor				
201	Distance between disks, min.	VL-II	3.2	AIE
202	Perpendicularity of sides of disk with hub	VL-II	3.2	AIE
203	Evidence of poor workmanship	VL-II	3.4	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:08Z
Check the source to verify that this is the current version before use.

4.3.2.5 Flexible explosive.			Drawing Number 9211460 Next Higher Assembly 9211459	
Classification	Examination or Test	Conformance Criteria	Requirement Paragraph	Inspection Method
Critical	None defined			
Major				
101	Pressure sensitive tape missing or improperly applied	VL-IV	3.2	Visual
102	Flexible explosive IAW MIL-PRF-46676	Once per lot	3.2	Examination of objective evidence
Minor				
201	Total length, min.	VL-II	3.2	AIE
202	Width	VL-II	3.2	AIE
203	Thickness, min.	VL-II	3.2	AIE
204	Markings missing or incorrect	VL-II	3.3	Visual
205	Evidence of poor workmanship	VL-II	3.4	Visual

4.3.2.6 Holder, blasting cap, M8.			Drawing Number 8887302 Next Higher Assembly 9211459	
Classification	Examination or Test	Conformance Criteria	Requirement Paragraph	Inspection Method
Critical	None defined			
Major				
101	Small width of explosive charge opening	VL-IV	3.2	AIE
102	Blasting cap retaining dimples missing or inadequate	VL-IV	3.2	Visual
103	Raised nibs missing or deformed	VL-IV	3.2	Visual
104	Hardness	20	3.2.2	4.4.2
Minor				
201	Width of clip opening, max.	VL-II	3.2	AIE
202	Length of blasting cap clip	VL-II	3.2	AIE
203	Diameter of blasting cap clip	VL-II	3.2	AIE
204	Overall width of holder	VL-II	3.2	AIE
205	Overall length of holder	VL-II	3.2	AIE
206	Evidence of poor workmanship	VL-II	3.4	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:08Z
Check the source to verify that this is the current version before use.

4.3.2.7 Charge, demolition roll, M186.			Drawing Number 9211459 Next Higher Assembly 9297231	
Classification	Examination or Test	Conformance Criteria	Requirement Paragraph	Inspection Method
Critical	None defined			
Major	None defined			
Minor				
201	Explosive improperly coiled	VL-II	3.2	Visual
202	Carrying rope missing	VL-II	3.2	Visual
203	Carrying rope knot improper	VL-II	3.2	Visual
204	Markings missing or incorrect	VL-II	3.4	Visual
205	Evidence of poor workmanship	VL-II	3.4	Visual

4.3.2.8 Bag, packing, ammunition, for charge demo roll, M186.			Drawing Number 9216714 Next Higher Assembly 9297231	
Classification	Examination or Test	Conformance Criteria	Requirement Paragraph	Inspection Method
Critical	None defined			
Major	None defined			
Minor				
201	Snap fasteners missing, improperly located or inadequately attached	VL-II	3.2	AIE/ Visual
202	Pull tabs missing or improperly attached	VL-II	3.2	Visual
203	Carrying straps improperly attached	VL-II	3.2	Visual
204	Stitching improper or incomplete	VL-II	3.2	Visual
205	Improper thread	VL-II	3.2	Visual
206	Markings missing or incorrect	VL-II	3.2	Visual
207	Evidence of poor workmanship	VL-II	3.4	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:08Z
Check the source to verify that this is the current version before use.

4.3.2.9 Bag, packing, for holder blasting cap, M8.			Drawing Number 9297232 Next Higher Assembly 9298299	
Classification	Examination or Test	Conformance Criteria	Requirement Paragraph	Inspection Method
Critical	None defined			
Major	None defined			
Minor				
201	Bag height	VL-II	3.2	AIE
202	Bag width	VL-II	3.2	AIE
203	Location of lettering from base of bag	VL-II	3.2	AIE
204	Lettering height	VL-II	3.2	AIE
205	Markings missing or incorrect	VL-II	3.2	Visual
206	Evidence of poor workmanship	VL-II	3.4	Visual

4.3.2.10 Bag assembly, with blasting cap holder.			Drawing Number 9298299 Next Higher Assembly 9297231	
Classification	Examination or Test	Conformance Criteria	Requirement Paragraph	Inspection Method
Critical	None defined			
Major				
101	Heat seal test	13	3.2.3	4.4.3
102	Incorrect number of blasting cap holders	VL-IV	3.2	Visual
103	Sealing strip incomplete or badly wrinkled (see 6.7)	VL-IV	3.2	Visual
104	Bag punctured, torn or cut	VL-IV	3.2	Visual
Minor				
201	Evidence of poor workmanship	VL-II	3.4	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:08Z
Check the source to verify that this is the current version before use.

4.3.2.11 Charge demolition assembly M186.			Drawing Number 9297231 Next Higher Assembly ------	
Classification	Examination or Test	Conformance Criteria	Requirement Paragraph	Inspection Method
Critical	None defined			
Major				
101	Snap fasteners improperly secured	VL-IV	3.2	Visual
Minor				
201	Any component missing from bag	VL-II	3.2	Visual
202	Evidence of poor workmanship	VL-II	3.4	Visual

4.3.2.12 Box, wirebound, packing (prior to close).			Drawing Number 9216715 Next Higher Assembly ------	
Classification	Examination or Test	Conformance Criteria	Requirement Paragraph	Inspection Method
Critical	None defined			
Major				
101	Incorrect number of demolition charges	VL-IV	5.1	Visual
Minor				
201	Evidence of poor workmanship	VL-II	3.4	Visual

4.3.2.13 Box, wirebound, packing sealed.			Drawing Number 9216715 Next Higher Assembly ------	
Classification	Examination or Test	Conformance Criteria	Requirement Paragraph	Inspection Method
Critical	None defined			
Major				
101	Box damaged to extent that contents are exposed or liable to become exposed	VL-IV	5.1	Visual
Minor				
201	Car seal missing, unsealed or improperly positioned	VL-II	5.1	Visual
202	Content loose	VL-II	5.1	Visual / Manual
203	Markings missing or incorrect	VL-II	5.2	Visual
204	Evidence of poor workmanship	VL-II	3.4	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:08Z
Check the source to verify that this is the current version before use.

4.3.2.14 Unitization.			Drawing Number 19-48-4116/120F Next Higher Assembly ------	
Classification	Examination or Test	Conformance Criteria	Requirement Paragraph	Inspection Method
Critical	None defined			
Major				
101	Boxes aligned or stacked incorrectly	VL-II	5.3.2	Visual
102	Strapping missing, broken or loose	VL-II	5.3.2	Visual / Manual
103	Heat treatment stamps missing or incorrect	VL-II	5.2	Visual
104	Pallet incorrect	VL-II and MIL-DTL-15011	5.3.1	MIL-DTL-15011
Minor				
201	Contents loose	VL-I	5.3	Visual / Manual
202	Markings missing or incorrect	VL-I	5.2	Visual
203	Evidence of poor workmanship	VL-I	3.4	Visual

4.4 Testing.

4.4.1 Susceptibility to cracking. The parts assembly shall be placed in a cold temperature chamber in such a manner that no external mechanical stresses are applied. The assembly shall be maintained at a temperature of -65 ± 5˚F for a period of not less than 24 hours. Observation shall be made for evidence of cracks, including hairline cracks, as evidence of noncompliance with 3.3. If one or more assemblies fail to comply with the specified requirements, the first article or lot shall be rejected. Samples complying with the requirement may be returned to the lot.

4.4.2 Hardness of M8 blasting cap holder. The blasting cap holder shall be tested for hardness as specified in ASTM E18. If any holder fails to comply with the applicable requirement, the heat-treated batch represented by the sample shall be rejected. Samples complying with the requirement may be returned to the lot.

4.4.3 Heat seal test of sealed bag. Sampling, acceptance criteria and test procedures for this test shall be as required in MIL-STD-2073-1E.

5. PACKAGING

5.1 Packaging. The demolition charge shall be packaged in accordance with Drawing

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:08Z
Check the source to verify that this is the current version before use.

9216715.

5.2 Marking. Markings shall be in accordance with Drawing 9216715.

5.3 Unitization.

5.3.1 Pallet. The pallet used in the unit load packaging shall conform to MIL-DTL-15011.

5.3.2 Unit load. The unit load shall conform to Drawing 19-48-4116/120F, shall be securely strapped, and shall contain all subcomponents, subassemblies and marking conforming to requirements.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The M186 Charge Demolition Roll is intended for use as a cutting charge which requires use of lengths longer than twelve inches.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number and date of this specification.
b. Provisions for submission/resubmission of first article samples.
c. Quantity required and delivery schedules.
d. Packaging requirements (see 5.1).
e. Requirements for submission of acceptance inspection equipment.
f. Certificate(s) of Analysis reporting the test results for the flexible explosive batches/lots used.
g. Requirements for distribution of ammunition data cards.
h. Acceptance Inspection Equipment (AIE) requirements.
i. Acceptance and description sheet for propellants and explosives in accordance with MIL-STD-1171.
j. Compatibility testing between flexible explosive with marking ink and/or adhesive tape.

6.3 Technical agency. US Army DEVCOM Armaments Center is the technical agency that is responsible for the preparation and revision of the specification. All correspondence to the Technical Agency should be submitted through the contracting officer to: U.S. Army DEVCOM Armaments Center, Attn: FCDD-ACE-QEE, Picatinny Arsenal, NJ 07806-5000.

6.4 Approval of equivalent test methods. Prior approval by the Contracting Officer should be required for use of equivalent test methods and/or instruments. A description of the proposed method and/or instrumentation should be submitted through the Contracting Officer to the Technical Agency (see 6.3). This description should include but not be limited to the

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:08Z
Check the source to verify that this is the current version before use.

procedures used, the accuracy and precision of the method, test data to demonstrate the accuracy and precision, and drawings of any special equipment required.

6.5 Submission of alternative conformance inspection provisions. Unless otherwise specified in the contract, proposed alternative conformance inspection provisions should be submitted by the contractor for evaluation by the Technical Agency (see 6.3) responsible for preparation of this specification.

6.6 Changes incorporated. ECP R25B2005 revised MIL-C-60996A and incorporated outstanding approved changes. Details of these changes are documented in the ECPs listed below.

Specification ID	ECP
MIL-C-60996A	-
-	R08Q2051
-	R10B2016
MIL-DTL-60996B	R25B2005

6.7 Visual standards. Visual standards and levels of acceptable/defective workmanship should be established or provided at the start of each contract. The Technical Agency (see 6.3) should approve visual standards.

6.8 Subject term (key word) listing.

Flexible explosive
Sheet explosive
Taggant
Spool

6.9 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

CONCLUDING MATERIAL

Custodians:
Army - AR

Preparing Activity:
Army - AR
(Project 1375-2026-001)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:08Z
Check the source to verify that this is the current version before use.