MIL-D-50836(MU)
20 December 1972

MILITARY SPECIFICATION

DISC, CASE SUPPORT, TRAINING

1. SCOPE

1.1 This specification covers requirements, quality assurance provisons, and the preparation for delivery criteria for one type of disc, case support, training used on 423 projectile loading assembly.

SPECIFICATIONS

MILITARY

MIL-P-116 - Preservation, Methods of

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1167 - Ammunition Data Cards
MIL-STD-1168 - Lot Numbering of Ammunition
MIL-STD-1169(MU) - Packaging, Packing and Marking for Shipments of Inert Ammunition Components

DRAWINGS

ORDNANCE CORPS

8808362 - Packing and Marking for Storage and Shipments
8787207 - Disc, Case Support, Training
8883538 - Bag, Packing for Repair Parts
EL-8787207 - Equipment List

FSC-1110

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:40Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The disc shall comply with all requirements specified on the drawing (dwg) 8787207, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawings and herein.

3.3 Serialization. The contractor shall assign serial numbers as required by drawings. The contractor may select any number which complies with the drawing requirement. These numbers shall not be duplicated.

3.4 Workmanship.

3.4.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.4.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.4.3 Burrs. Parts shall be free from burrs.

3.4.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.4.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection. "Not applicable"

4.3 Product acceptance inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:40Z
Check the source to verify that this is the current version before use.

4.3.1 Lot formation. Lot formation shall be in accordance with MIL-STD-1168. Changes in lot numbers shall be recorded on Ammunition Data Cards in accordance with MIL-STD-1167 and MIL-STD-1168.

4.3.1.1 Inspection lot. An inspection lot shall be the quantity of parts, subassemblies or assemblies from the same lot, which are submitted to inspection for Government acceptance.

4.3.2 Product inspection examination. Critical characteristics shall require 100 percent inspection of all items in the inspection lot. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Table I
Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

TABLE II
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-9	all	14-16	12	28-33	16	77-121	20
10	9	17-18	13	34-41	17	122-273	21
11	10	19-22	14	42-54	18	over 273	22
12-13	11	23-27	15	55-76	19		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:40Z
Check the source to verify that this is the current version before use.

4.3.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Disc, case support, training (see dwg 8787207).

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Pitch diameter of thread	Gage
102.	Major diameter of thread	Gage
103.	Chamfer present	Visual
104.	Outside diameter	Gage
105.	Length of outside diameter	Gage
106.	Total length	Gage
107.	Presence of holes	Visual
108.	Material (see 3.1)	Visual
109.	Objective evidence (see 6.2) for protective finish in accordance with dwg 8787207	Visual
Minor:		
201.	Surface finish	Visual
202.	Stamping	Visual
203.	Serialization (see 3.3)	Visual
204.	Workmanship (see 3.4)	Visual/Manual

4.3.2.1.2 Preparation for delivery (see 5.1).

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Preservation, packaging, packing and marking in accordance with MIL-STD-1169(MU)	Visual/Manual
Minor:		
201.	Workmanship (see 3.4)	Visual/Manual

4.3.2.1.3 Bag, packing, for repair parts (see dwg 8883538 covering part number 8883538-4 and 5.2).

Categories	Characteristics	Method of Inspection
Critical: None defined.		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:40Z
Check the source to verify that this is the current version before use.

Major:
101. Material (see 3.1).....Visual
102. Length before packing, min.....*Measure
103. Width before packing, min.....*Measure
104. Proper heat seal.....Visual/Manual
105. Objective evidence (see 6.2) for heat seal test in accordance with MIL-P-116.....Visual
106. Properly packed.....Visual
107. No tear, split, crack or hole in bag.....Visual

*Measure with suitable scale.

Minor:
201. Marking.....Visual
202. Workmanship (see 3.4).....Visual/Manual

4.3.2.1.4 Packing and marking for storage and shipments (see dwg 8808362 and 5.2).

Categories	Characteristics	Method of Inspection

Critical: None defined.

Major:
101. Gross load weight, max.....*Measure
102. Contents tight in package.....Manual
103. Correctly packed.....Visual/Manual
104. Packaging material (see 3.1).....Visual

*Determine weight with suitable scale.

Minor:
201. Marking.....Visual
202. Workmanship (see 3.4).....Visual/Manual

4.3.3 Testing. Not applicable.
4.3.4 Acceptance inspection equipment.
4.3.4.1 Critical and major characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions, and calibration instructions specified on the Equipment Lists (EL) (See EL-8787207). When either of the conditions listed below exist, the contractor shall design required equipment or specify suitable commercial equipment and obtain approval prior to use on the contract.

a. Any deviation from equipment or procedures specified on the EL is desired (see 6.3).
b. The code "CD" is listed in the "Part or Identifying Number" column on the EL (see 6.1.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:40Z
Check the source to verify that this is the current version before use.

4.3.4.2 Minor characteristics and tests. Acceptance inspection equipment for minor characteristics is not specified on ELs. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.4 Test methods. Not applicable.

5. PREPARATION FOR DELIVERY

5.1 Production items.

5.1.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1.1 Level A. The disc shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU).

5.1.1.2 Level C. The disc shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU).

5.1.2 Packing.

5.1.2.1 Levels A and C. The disc shall be packed in accordance with the applicable instructions contained in MIL-STD-1169(MU).

5.1.3 Marking. Marking shall be in accordance with MIL-STD-1169(MU).

5.2 Repair parts.

5.2.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.2.1.1 Level A. The disc shall be packaged in accordance with dwgs 8883538 and 8808362 using the specified moisture barrier.

5.2.1.2 Level C. The disc shall be packaged in accordance with dwg 8808362 except that the moisture barrier may be omitted.

5.2.2 Packing.

5.2.2.1 Level A and C. The disc shall be packed in accordance with dwgs 8883538 and 8808362.

5.2.3 Marking. Marking shall be as specified in accordance with dwgs 8883538 and 8808362.

5.3 Data cards. Data cards shall be prepared in accordance with MIL-STD-1167.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

6.1.1 Procurement requirements.

a. Title, number, and date of this specification.
b. Production or Repair Part.
c. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:40Z
Check the source to verify that this is the current version before use.

6.1.2 Contract data requirements (see 4.3.4.1 and 5.3). Data specified in 4.3.4.1 and 5.3 will be delivered as identified on a numbered DD Form 1667 when specified on DD Form 1423 incorporated in the contract.

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.3.4.1). The contractor shall obtain approval from the Commanding Officer, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SMUPA-QA-N-I

6.4 Supersession data. This specification supersedes the requirements of Purchase Description PA-PD-1129 (Rev 3). dated 27 October 1960.

Custodian:
Army - MU

Preparing activity:
Army - MU

Project No. 1110-A040

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:40Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

MIL-D-50836(MU) Disc, Case Support, Training

ORGANIZATION

CITY AND STATE	CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*	DATE

DD FORM 1 JAN 66 1426 REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:40Z
Check the source to verify that this is the current version before use.