MILITARY SPECIFICATION

PIN AND LANYARD ASSEMBLY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the inspection and test of the parts of the pin and lanyard assembly used with the SUU-13 D/A dispensers.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550 - Ammunition, General Specification For
MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1169 - Packaging, Packing and Marking for Shipment for Inert Ammunition Components

DRAWINGS

U.S. ARMY PICATINNY ARSENAL

9287745 - Pin and Lanyard Assembly

FSC: 1345

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer).

3. REQUIREMENTS

3.1 Material. - Materials shall be in accordance with the applicable drawings and specifications.

3.2 Assembly. - The assembly shall comply with all requirements specified on Drawing (dwg.) 9287745 and all associated drawings and with all requirements specified in applicable specifications.

3.3 Workmanship. - All parts and assemblies shall be fabricated and finished in a thorough workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust, corrosion products, and other foreign matter. The cleaning agent or method used shall not be injurious to any part, nor shall the part be contaminated by the cleaning agents.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. - Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspection. - The following type of inspection shall be conducted on this item:

a. First Article Inspection

b. Quality Conformance Inspection

4.3 First article inspection

4.3.1 Submission. - The contractor shall submit a first article sample (Sect 6.2b) as designated by the Contracting Officer. The first article sample shall consist of ten (10) complete sets of parts and ten (10) assemblies. The first article shall be evaluated in accordance with the provisions of 4.3.2 and 4.3.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

4.3.2 Inspections to be performed. - See MIL-A-48078 and paragraph 4.4.2.1, testing per paragraph 4.4.3.

4.3.3 Rejection. - (See MIL-A-48078).

4.4 Quality conformance inspection

4.4.1 Inspection lot formation. - Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. - (See MIL-A-48078) Unless otherwise specified in the classification of defects and test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

4.4.3 Testing

4.4.3.1 Lanyard Assembly Pull Test. (See dwg. 9287745) - Major A defect. - Ten (10) assemblies shall be randomly selected from each lot and tested for the specified requirement in accordance with 4.5.1. The lot shall be rejected if one (1) or more assemblies are classed defective (Destructive Test).

4.4.3.2 Spindle Hardness Test. (See dwg. 9287745) - Major A defect. - Ten (10) spindles shall be randomly selected from each heat treat lot and tested for the specified requirement in accordance with 4.5.2. The lot shall be rejected if one (1) or more samples are classed defective (Non-destructive Test).

4.4.3.3 Spring, Spring Rate Test. (See Dwg. 9287745) - Major B defect. - Ten (10) springs shall be randomly selected from each heat treat lot and tested for the specified requirements in accordance with 4.5.3. The lot shall be rejected if one (1) or more samples are classed defective (Non-destructive Test).

4.4.4 Inspection equipment. - The inspection equipment required to perform the inspections and tests prescribed in this specification is identified in the 'Paragraph Reference/ Inspection Method' column in the tables starting with 4.4.2.1, and the test method paragraphs (see 4.5). The contractor shall submit for approval, inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078, and section 6.3 herein.

4.5 Test method and procedures

4.5.1 Lanyard Assembly Pull Test. - The pin assembly shall be secured in a Government approved test fixture and theforce shall be applied in the direction shown on the applicable drawing. The force shall also be applied using the application rate specified. Any assembly that fails to comply with all of the specified requirements shall be classed defective.

4.5.2 Spindle Hardness Test. - The spindle shall be tested for the specified hardness requirement at 3 equally spaced points along the spindle axis using Government approved test equipment and procedures. Any spindle failing to comply with all of the specified requirements shall be classed defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

4.5.3 Spring, Spring Rate Test. - The spring shall be loaded with the specified loads and the heights shall be measured at each load. Any spring failing to comply with all of the specified requirements shall be classed defective.

5. PREPARATION FOR DELIVERY

5.1 Preservation and Packaging

5.1.1 Level C. - The pin and lanyard assemblies shall be packaged in accordance with MIL-STD-1169.

5.2 Packing

5.2.1 Level C. - The pin and lanyard assemblies shall be packed for assembly in accordance with MIL-STD-1169.

5.3 Marking

5.3.1 Marking of the carton shall comply with MIL-STD-1169.

5.4 Shipping. - When assemblies of more than one lot are shipped together, each lot shall be kept separate and the division between lots clearly indicated to prevent mixing of lots in transit.

6. NOTES

6.1 Intended use. - The components and assemblies covered by this specification are intended for use with the Dispenser, Bomb SUU-13D/A.

6.2 Ordering data. - See MIL-A-48078.

6.3 Submission of inspection equipment designs for approval. - See MIL-A-48078. Submit equipment designs as required to Commander: Picatinny Arsenal, ATTN: SARPA-QA-T-T, Dover, New Jersey 07801.

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 1345-A-128

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-48850 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Pin and Lanyard Assembly				9287745
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Pallet diameter		0.40	3.2	Gage
102	Bushing diameter		0.40	3.2	Gage
Major B	Overall assembled spring length		0.40	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65		Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

* U.S. GOVERNMENT PRINTING OFFICE: 1975-603-766:2139