MILITARY SPECIFICATION

WINDOW, OBSERVATION

1. SCOPE

1.1 This specification covers requirements, quality assurance provisions, and the preparation for delivery criteria for one type of window used on M455 and M455E1 training projectiles.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-P-116 - Preservation, Methods of.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-1169 - Packaging, Packing and Marking for Shipments of Inert Ammunition Components.

DRAWINGS

PICATINNY ARSENAL

8808362 - Packing and Marking for Storage and Shipments.
8865078 - Window.
8883536 - Bag, Packing, for Repair Parts.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:21Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The window shall comply with all requirements specified on the drawing (dwg) 8865078, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 Workmanship.

3.3.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.3.2 Burrs. Parts shall be free from burrs.

3.3.3 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.3.4 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Quality conformance inspection.

4.2.1 Inspection lot formation. All items in each inspection lot shall be from one production line, one shift, one batch of products, one manufacturer of raw material or components, one production method or manufacturing operation. The entire lot shall be submitted as a unit for inspection.

4.2.2 Product inspection examination. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table (see Table I and Table II), and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:21Z
Check the source to verify that this is the current version before use.

Table I
Major Characteristics

LQ=.10 Acceptance No = 0 Consumer's risk =.05

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131			

Table II
Minor Characteristics

LQ=.10 Acceptance No = 0 Consumer's risk =.10

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-9	all	14-16	12	28-33	16	77-121	20
10	9	17-18	13	34-41	17	122-273	21
11	10	19-22	14	42-54	18	over 273	22
12-13	11	23-27	15	55-76			

4.2.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.2.2.1.1 Window (see dwg 8865078).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Location of 2 small holes	Gage
102.	Location of large hole	Gage
103.	Radii present	Visual
104.	Width of transparent section (.25)	Gage
105.	Width (2.645)	Gage
106.	Distance from center of large hole to transparent section (.74)	Gage
107.	Distance from center of large hole to end of transparent section (1.82)	Gage
108.	Length (2.936)	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:21Z
Check the source to verify that this is the current version before use.

109. Curvature of curved section.....Gage
110. Thickness at thin end (.415).....Gage
111. Thickness at thick end (.784).....Gage
112. Diameter of counterbore on small holes (.1910).....Gage
113. Diameter of counterbore on small holes (.125).....Gage
114. Diameter of small holes (.1285).....Gage
115. Diameter of large hole (.360).....Gage
116. Depth of counterbore on large hole (.410).....Gage
117. Diameter of counterbore on large hole (.75).....Gage
118. Proper transparency in transparent section.....Visual

Minor:
201. Scribe lines present, correct, identifiable and properly filled.....Visual
202. Enamel present no bare spots.....Visual
203. Marking.....Visual
204. Workmanship (see 3.3).....Visual-Manual

4.2.2.1.2 Preparation for delivery (see 5.1).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Preservation, packaging, packing and marking in accordance with MIL-STD-1169(MU)	Visual-Manual
Minor:	None defined.	

4.2.2.1.3 Bag, packing, for repair parts (see dwg 8883536 covering dwg part number 8883536-7 and 5.2).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Material (see 3.1)	Visual
	102. Length before packing, min	*Measure
	103. Width before packing, min	*Measure

*Measure with suitable scale.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:21Z
Check the source to verify that this is the current version before use.

104. Properly packed.....Visual-Manual
105. Proper heat seal.....Visual-Manual
106. No crack or hole in bag.....Visual-Manual
107. Objective evidence (see 6.2) for heat seal test in accordance with MIL-P-116.....Visual

Minor:
201. Marking.....Visual
202. Workmanship (see 3.3).....Visual-Manual

4.2.2.1.4 Packing and marking for storage and shipments (see dwg 8808362).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Gross load weight (max).....	*Measure
	102. Contents tight in package.....	Manual
	103. Properly packed.....	Visual-Manual
	104. Material (see 3.1).....	Visual

*Measure with suitable scale.

Minor:
201. Marking.....Visual
202. Workmanship (see 3.3).....Visual-Manual

4.2.3 Testing. Not applicable.
4.2.4 Acceptance inspection equipment.
4.2.4.1 Major characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions and calibration instructions designed or specified by the contractor. The contractor shall obtain approval of such designs, operating instructions and calibration instructions prior to use on the contract from Commander, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SARPA-QA-N-I as specified on DI-R-1714 (see 6.1.2).
4.2.4.2 Minor characteristics and tests. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.
4.3 Test methods. Not applicable.

5. PREPARATION FOR DELIVERY

5.1 Production items.
5.1.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).
5.1.1.1 Level A. The window shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:21Z
Check the source to verify that this is the current version before use.

5.1.1.2 Level C. The window shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU).

5.1.2 Packing.

5.1.2.1 Levels A and C. The window shall be packed in accordance with the applicable instructions contained in MIL-STD-1169(MU).

5.1.3 Marking. Marking shall be in accordance with MIL-STD-1169(MU).

5.2 Repair parts.

5.2.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.2.1.1 Level A. The window shall be packaged in accordance with dwg 8883536 and 8808362 using the specified moisture barrier.

5.2.1.2 Level C. The window shall be packaged in accordance with dwg 8808362 except that the moisture barrier may be omitted.

5.2.2 Packing.

5.2.2.1 Level A and C. The window shall be packed in accordance with dwg 8883536 and 8808362.

5.2.3 Marking. Marking shall be as specified in accordance with dwg 8883536 and 8808362 as applicable.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

6.1.1 Procurement requirements.

a. Title, number, and date of this specification.
b. Production or Repair Parts.
c. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.1.2 Contract data requirements (see 4.2.4.1). Data specified in 4.2.4.1 will be listed directly on a DD Form 1423 incorporated in the contract.

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

Custodian:
Army - PA

Preparing activity:
Army - PA

Project No. 1110-A043

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:21Z
Check the source to verify that this is the current version before use.

ENGINEERING RELEASE RECORD

SARPA-QA-N-Q

1. ERR NO.	2. DATE	3. SHEET OF SHEETS
7301240-2	11-26-73	1 of 1

4. BASELINE ESTABLISHED OR CHANGED

[ ] FUNCTIONAL [ ] ALLOCATED [X] PRODUCT

5. TYPE OF RELEASE

[ ] INITIAL [X] CHANGE

6. ECP NO. _____

DATE APPROVED _____

7. FUNCTIONAL ASSEMBLY NOMENCLATURE

Window, Observation

8. SYSTEM/OR CONFIGURATION ITEM NOMENCLATURE

M-454 Projectile

9. REMARKS/MISCELLANEOUS

10. DATA RELEASED OR REVISED

a CODE ID	DOCUMENT b TYPE	c NUMBER	d SH OF SHEETS	REVISION f LTR	g DATE	h RELEASE IR	h RELEASE NAR	i CHANGE CH	i CHANGE CAN	j OTHER
	SQ	8865078		B	08-10-66				X	
		MIL-W-48302(PA)	7	Orig	11-26-73	X				

11. SUBMITTED BY

12. APPROVED BY

AMC Form 1724R
26 Feb 1970

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:21Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

MIL-W-48302(PA) Window, Observation

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426 REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:21Z
Check the source to verify that this is the current version before use.