INCH-POUND

MIL-M-28787/526
AMENDMENT 1
29 September 1993

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

DIRECT MEMORY INTERFACE I MODULE, KEY CODE DWG

This amendment forms a part of Military Specification MIL-M-28787/526, dated 29 March 1991, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

TABLE I: Delete and substitute new table I as printed on page 3 of this amendment.

PAGES 39 AND 40

TABLE II: Insert the following new test condition and renumber test conditions A44-A46 to A45-A47:

Test cond	Test description	Connect		25 ± 5°C Initial limits		Units	Notes
		A to pin	B to pin	Min	Max		
A44	Isolation, unused to unused pins	94	95,96,97,63	10	INF	MOhm	1-8

PAGE 41

TABLE II, NOTES, Isolation test tolerance table, Test condition column: Delete "A1-A46" (two places) and substitute "A1-A47" (two places).

AMSC N/A FSC 5963
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:34Z
Check the source to verify that this is the current version before use.

PAGE 43

TABLE III, Test conditions B9 and B10, Max column: Delete "1" and substitute "3".

TABLE III, NOTES, Continuity test tolerance table: Delete and substitute the following:

Condition	Value	Accuracy	Test condition
Continuity measurement	NA	± 0.05 Ohm ± 0.15 Ohm	B1-B8 B9,B10

PAGE 89

TABLE XIX, Test condition T2, Pin no. column: Delete "51" and substitute "50".

Custodians:
Army - ER
Navy - NW
Air Force - 85

Review activities:
Army - AT
Navy - AS, MC
Air Force - 13, 19
DLA - ES

Preparing activity:
Navy - NW

(Project 5963-0287)

Source: https://assist.dla.mil -- Downloaded: 20260-20T18:34Z
Check the source to verify that this is the current version before use.

TABLE I. Module electrical requirements.

Test cond	Parameter 5/	Ref test table	Test type 1/-3/	25 ± 5°C 4/		0 ± 5°C 4/		60 ± 5°C 4/		Units
				Min	Max	Min	Max	Min	Max	
A1	Isolation	II	S	10	INF	10	INF	10	INF	MOhm
	End-of-life	II	S	1	INF	1	INF	1	INF	MOhm
A2-A47	Isolation	II	X	10	INF	10	INF	10	INF	MOhm
	End-of-life	II	X	1	INF	1	INF	1	INF	MOhm
B1-B8	Continuity	III	X	0	1	0	1	0	1	Ohm
B9,B10	Continuity	III	X	0	3	0	3	0	3	Ohm
C	Power supply stress	IV	Q	------Module shall pass all remaining tests--						
D1	Ibd	V	S	0.0	0.1	0.0	0.1	0.0	0.1	mA
D2	Ibd	V	S	0.0	0.2	0.0	0.2	0.0	0.2	mA
D3-D13	Ibd	V	S	0.0	0.1	0.0	0.1	0.0	0.1	mA
E1-E16	Ios	VI	S	-150.0	-60.0	150.0	-60.0	-150.0	-60.0	mA
F1	Iih	VII	X	-0.60	0.02	-0.60	0.02	-0.60	0.02	mA
F2	Iih	VII	X	-2.60	0.04	-2.60	0.04	-2.60	0.04	mA
F3-F12	Iih	VII	X	-0.60	0.02	-0.60	0.02	-0.60	0.02	mA
F13-F19	Iih	VII	X	-1.70	0.12	-1.70	0.12	-1.70	0.12	mA
F20	Iih	VII	X	-1.10	0.12	-1.10	0.12	-1.10	0.12	mA
F21	Iih	VII	X	-0.60	0.02	-0.60	0.02	-0.60	0.02	mA
G1	Iil	VIII	X	-0.60	0.02	-0.60	0.02	-0.60	0.02	mA
G2	Iil	VIII	X	-2.60	0.04	-2.60	0.04	-2.60	0.04	mA
G3-G12	Iil	VIII	X	-0.60	0.02	-0.60	0.02	-0.60	0.02	mA
G13-G19	Iil	VIII	X	-1.70	0.12	-1.70	0.12	-1.70	0.12	mA
G20	Iil	VIII	X	-1.10	0.12	-1.10	0.12	-1.10	0.12	mA
G21	Iil	VIII	X	-0.60	0.02	-0.60	0.02	-0.60	0.02	mA

- See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-02-20T18:34Z
Check the source to verify that this is the current version before use.