INCH-POUND

MIL-M-28787/537(SH)
AMENDMENT 1
3 August 1994

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

RS 232C INTERFACE ADAPTER MODULE, KEY CODE AML

This amendment forms a part of Military Specification MIL-M-28787/537(SH), dated 20 October 1989, and is approved for use by the Crane Division, Naval Surface Warfare Center, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

TABLE I, Test condition A: Delete and substitute new section of table I as printed on page 4 of this amendment.

PAGE 5

TABLE I, Test condition N3, Min limit (all temperatures): Delete "-9.4" (three places) and substitute "-10.6" (three places).

TABLE I, Test condition N3, Max limit (all temperatures): Delete "-3.9" (three places) and substitute "-5.1" (three places).

PAGE 17

6.3.1, Input parameters, Signals D ST RDY N and D ST RDY N+1, Vil max (V) column: Delete "NA" and substitute "-4.0".

6.3.1, Input parameters, Signals D ST RDY N and D ST RDY N+1, Vih min (V) column: Delete "NA" and substitute "4.0".

PAGE 18

6.3.2, Output parameters, Signal LP TEST N, D TM RDY N, NEW SYNC N, RQ TO SD N, XMT D N and LP TEST N+1, Voh min (V) column: Delete "6.0" and substitute "5.0".

AMSC N/A FSC 5963
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:40Z
Check the source to verify that this is the current version before use.

6.3.2, Output parameters, Signals LP TEST N, D TM RDY N, NEW SYNC N, RQ TO SD N, XMT D N and LP TEST N+1, Vol max (V) column: Delete "-6.0" and substitute "-5.0".

6.3.2, Output parameters, Signals LP TEST N, D TM RDY N, NEW SYNC N, RQ TO SD N, XMT D N and LP TEST N+1, Ioh max (mA) column: Delete "-0.4" and substitute "-1.6".

6.3.2, Output parameters, Signals LP TEST N, D TM RDY N, NEW SYNC N, RQ TO SD N, XMT D N and LP TEST N+1, Iol max (mA) column: Delete "6.0" and substitute "1.6".

PAGE 19

6.3.2, Output parameters, Signals D TM RDY N+1, NEW SYNC N+1, RQ TO SD N+1 and XMT D N+1, Voh min (V) column: Delete "6.0" and substitute "5.0".

6.3.2, Output parameters, Signals D TM RDY N+1, NEW SYNC N+1, RQ TO SD N+1 and XMT D N+1, Vol max (V) column: Delete "-6.0" and substitute "-5.0".

6.3.2, Output parameters, Signals D TM RDY N+1, NEW SYNC N+1, RQ TO SD N+1 and XMT D N+1, Ioh max (mA) column: Delete "-0.4" and substitute "-1.6".

6.3.2, Output parameters, Signals D TM RDY N+1, NEW SYNC N+1, RQ TO SD N+1 and XMT D N+1, Iol max (mA) column: Delete "6.0" and substitute "1.6".

PAGE 33

TABLE IV, Power supplies V2 and V3, Vin (V) column: Delete "17.5" (two places) and substitute "17.4" (two places).

TABLE IV, Test tolerance table, Power supply V2, Value column: Delete "17.5" and substitute "17.4".

TABLE IV, Test tolerance table, Power supply V2, Accuracy column: Delete "-175" and substitute "-174".

TABLE IV, Test tolerance table, Power supply V3, Value column: Delete "-17.5" and substitute "-17.4".

TABLE IV, Test tolerance table, Power supply V3, Accuracy column: Delete "+175" and substitute "+174".

Source: https://assist.dla.mil -- Downloaded: 20260-20T18:40Z
Check the source to verify that this is the current version before use.

PAGE 35

FIGURE 8, Items P01-2 and P01-3: Delete "17.5V" and substitute "17.4V".

PAGE 47

FIGURE 9, Logic load circuit, Note 4, Pin numbers 53, 54, 55, 56, 57, 59, 82, 83, 84 and 89, R2 (Ohms) column: Delete "6200" and substitute "3125".

FIGURE 9, Logic load circuit, Note 4, Pin numbers 53, 54, 55, 56, 57, 59, 82, 83, 84 and 89, Iol (mA) column: Delete "6.0" and substitute "1.6".

FIGURE 9, Logic load circuit, Note 4, Pin numbers 53, 54, 55, 56, 57, 59, 82, 83, 84 and 89, Vol (Volts) column: Delete "-6.0" and substitute "-5.0".

PAGE 54

TABLE XIII, Test condition N3, Min limit: Delete "-9.4" and substitute "-10.6".

TABLE XIII, Test condition N3, Max limit: Delete "-3.9" and substitute "-5.1".

PAGE 59

TABLE XV, Dynamic test, Note 2(b), Pin number column: Delete pin numbers 91 and 92 from the row of 2.4 V (VH)/ 0.4 V (VL) and insert pin numbers 91 and 92 into the row of 4.0 V (VH)/ -4.0 V (VL).

PAGE 60

TABLE XV, Dynamic test, Note 4(c): Delete pins 91 and 92.

TABLE XV, Dynamic test, Note 4(d): Add pins 91 and 92.

Preparing activity:
Navy - NW

(Project 5963-N866)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:40Z
Check the source to verify that this is the current version before use.

TABLE I. Module electrical requirements.

Test cond	Parameter 5/	Ref test table	Test type 1/ - 3/	25 ± 5°C 4/		Class I 4/ 0 ± 5°C 60 ± 5°C		Class II 4/ -55 ± 5°C 85 ± 5°C		Units
				Min	Max	Min	Max	Min	Max	
A1	Isolation	II	S	10	INF	10	INF	10	INF	MOhm
	End-of-life	II	S	1	INF	1	INF	1	INF	MOhm
A2-A35	Isolation	II	X	10	INF	10	INF	10	INF	MOhm
	End-of-life	II	X	1	INF	1	INF	1	INF	MOhm
B1-B6	Continuity	III	X	0	1	0	1	0	1	Ohm
C	Power supply stress	IV	S	---------Module shall pass all remaining tests----------						
D1,D2	Ibd	V	S	0.0	0.1	0.0	0.1	0.0	0.1	mA
E1,E2	Ios	VI	S	-100.0	-15.0	-100.0	-15.0	-100.0	-15.0	mA
E3-E6	Ios	VI	S	-100.0	-20.0	-100.0	-20.0	-100.0	-20.0	mA
F1-F7	Iih	VII	X	-1.6	0.04	-1.6	0.04	-1.6	0.04	mA
F8	Iih	VII	X	-0.8	0.04	-0.8	0.04	-0.8	0.04	mA
F9	Iih	VII	X	-1.6	0.04	-1.6	0.04	-1.6	0.04	mA
F10	Iih	VII	X	-0.8	0.04	-0.8	0.04	-0.8	0.04	mA
G1-G7	Iil	VIII	X	-1.6	0.04	-1.6	0.04	-1.6	0.04	mA
G8	Iil	VIII	X	-0.8	0.04	-0.8	0.04	-0.8	0.04	mA
G9	Iil	VIII	X	-1.6	0.04	-1.6	0.04	-1.6	0.04	mA
G10	Iil	VIII	X	-0.8	0.04	-0.8	0.04	-0.8	0.04	mA
H1-H6	Voh	IX	X	2.4	4.5	2.4	4.5	2.4	4.5	V
J1-J6	Vol	X	X	0.0	0.5	0.0	0.5	0.0	0.5	V
L1,L2	Vic	XI	S	-1.5	0.0	-1.5	0.0	-1.5	0.0	V
M1	PSFC	XII	S	1.4	2.6	1.4	2.6	1.4	2.6	µF
M2	PSFC	XII	S	3.0	5.6	3.0	5.6	3.0	5.6	µF
M3	PSFC	XII	S	0.9	1.7	0.9	1.7	0.9	1.7	µF
M4	PSFC	XII	S	1.5	2.7	1.5	2.7	1.5	2.7	µF

- See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-02-20T18:40Z
Check the source to verify that this is the current version before use.