|INCH-POUND|

MIL-M-28787/538
AMENDMENT 1
29 September 1993

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

MIL-STD-188C/VACALES INTERFACE ADAPTER MODULE, KEY CODE APC

This amendment forms a part of Military Specification MIL-M-28787/538(SH), dated 27 December 1989, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

TABLE I: Delete and substitute new table I as printed on page 3 of this amendment.

PAGE 21

6.3.2: Signals DCT A (N), DCT D (N), DCT F (N), DCT G (N), XMT D (N), and DCT A (N+1), Voh column: Delete "6.0" and substitute "5.0".

6.3.2: Signals DCT A (N), DCT D (N), DCT F (N), DCT G (N), XMT D (N), and DCT A (N+1), Vol column: Delete "-6.0" and substitute "-5.0".

6.3.2: Signals DCT A (N), DCT D (N), DCT F (N), DCT G (N), XMT D (N), and DCT A (N+1), Ioh column: Delete "-0.16" and substitute "-1.6".

AMSC N/A FSC 5963
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 20260410-20T18:41Z
Check the source to verify that this is the current version before use.

PAGE 22

6.3.2: Signals DCT D (N+1), DCT F (N+1), DCT G (N+1), and XMT D (N+1), Voh column: Delete "6.0" and substitute "5.0".

6.3.2: Signals DCT D (N+1), DCT F (N+1), DCT G (N+1), and XMT D (N+1), Vol column: Delete "-6.0" and substitute "-5.0".

6.3.2: Signals DCT D (N+1), DCT F (N+1), DCT G (N+1), and XMT D (N+1), Ioh column: Delete "-0.16" and substitute "-1.6".

PAGE 35

TABLE III, Test condition B7, Max column: Delete "1" and substitute "3".

TABLE III, Note 1, Continuity test tolerance table, Test condition column and Accuracy column: In the test condition column, change "B1-B7" to "B1-B6" and add "B7" below. In the accuracy column, add "± 0.15 Ohm" for test condition B7.

PAGE 53

FIGURE 9, NOTE 4, Pin numbers 53, 54, 55, 56, 57, 59, 82, 83, 84, and 89, R2 column: Delete "16000" and substitute "3000".

FIGURE 9, NOTE 4, Pin numbers 53, 54, 55, 56, 57, 59, 82, 83, 84, and 89, Vol column: Delete "-6.0" and substitute "-5.0".

Custodians:
Army - ER
Navy - NW
Air Force - 85

Review activities:
Army - AT
Navy - AS, MC
Air Force - 13, 19
DLA - ES

Preparing activity:
Navy - NW

(Project 5963-0289)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:41Z
Check the source to verify that this is the current version before use.

TABLE I. Module electrical requirements

Test cond	Parameter 5/	Ref test table	Test type 1/,3/	25 ± 5°C 4		Class I 4/ 0 ± 5°C 60 ± 5°C		Class II 4/ -55 ± 5°C 85 ± 5°C		Units
				Min	Max	Min	Max	Min	Max	
A1	Isolation	II	S	10	INF	10	INF	10	INF	MOhm
	End-of-Life	II	S	1	INF	1	INF	1	INF	MOhm
A2-A23	Isolation	II	X	10	INF	10	INF	10	INF	MOhm
	End-of-Life	II	X	1	INF	1	INF	1	INF	MOhm
B1-B6	Continuity	III	X	0	1	0	1	0	1	Ohm
B7	Continuity	III	X	0	3	0	3	0	3	Ohm
C	Power supply stress	IV	S	---------- Module shall pass all remaining tests ----------						
D1	Ibd	V	S	-0.11	0.81	-0.11	0.81	-0.11	0.81	mA
D2,D3	Ibd	V	S	0.0	0.1	0.0	0.1	0.0	0.1	mA
E1	Ios	VI	S	-100.0	-15.0	-100.0	-15.0	-100.0	-15.0	mA
E2	Ios	VI	S	-100.0	-20.0	-100.0	-20.0	-100.0	-20.0	mA
E3	Ios	VI	S	-100.0	-15.0	-100.0	-15.0	-100.0	-15.0	mA
E4-E9	Ios	VI	S	-100.0	-20.0	-100.0	-20.0	-100.0	-20.0	mA
F1-F5	Iih	VII	X	-1.6	0.04	-1.6	0.04	-1.6	0.04	mA
F6	Iih	VII	X	-8.41	-2.83	-8.41	-2.83	-8.41	-2.83	mA
F7-F9	Iih	VII	X	-1.6	0.04	-1.6	0.04	-1.6	0.04	mA
F10	Iih	VII	X	-0.8	0.04	-0.8	0.04	-0.8	0.04	mA
F11-F14	Iih	VII	X	-1.6	0.04	-1.6	0.04	-1.6	0.04	mA
F15	Iih	VII	X	-0.8	0.04	-0.8	0.04	-0.8	0.04	mA
G1-G6	Iil	VIII	X	-1.6	0.04	-1.6	0.04	-1.6	0.04	mA
G6	Iil	VIII	X	-8.41	-2.83	-8.41	-2.83	-8.41	-2.83	mA
G7-G9	Iil	VIII	X	-1.6	0.04	-1.6	0.04	-1.6	0.04	mA
G10	Iil	VIII	X	-0.8	0.04	-0.8	0.04	-0.8	0.04	mA

- See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 20260-20T18:41Z
Check the source to verify that this is the current version before use.