INCH-POUND

MIL-M-28787/539(NW)
AMENDMENT 1
3 August 1994

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

HIGH PERFORMANCE ADDRESS GENERATION MODULE, KEY CODE CWK

This amendment forms a part of Military Specification MIL-M-28787/539, dated 5 May 1989, and is approved for use by the Crane Division, Naval Surface Warfare Center, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGES 4 THROUGH 10

TABLE I: Delete and substitute new table I as printed on pages 2 through 6 of this amendment.

PAGES 22 AND 23

6.3.1, Input parameters: Delete and substitute new section of 6.3.1 as printed on pages 7 and 8 of this amendment.

PAGES 26 THROUGH 30

6.3.2, Output parameters, Ios max (mA) column: Delete Ios max (mA) column.

PAGES 66 THROUGH 73

TABLE VI: Delete and substitute new table VI as printed on pages 9 through 14 of this amendment.

PAGES 104 THROUGH 106

TABLE XII: Delete and substitute new table XII as printed on pages 15 and 16 of this amendment.

Preparing activity:
Navy - NW

(Project 5963-N861)

AMSC N/A FSC 5963
DISTRIBUTION STATEMENT A Approved for public release, distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:42Z
Check the source to verify that this is the current version before use.

TABLE I. Module electrical requirements.

Test cond.	Parameter 5/	Ref test table	Test type 1/ - 3/	25° ± 5°C 4/		Class I 4/ 0° ± 5°C 60° ± 5°C		Class II 4/ -55° ± 5°C 85° ± 5°C		Units
				Min	Max	Min	Max	Min	Max	
A1	Isolation	II	S	10	INF	10	INF	10	INF	MOhm
	End-of-life	II	S	1	INF	1	INF	1	INF	MOhm
A2	Isolation	II	X	10	INF	10	INF	10	INF	MOhm
	End-of-life	II	X	1	INF	1	INF	1	INF	MOhm
B1-B6	Continuity	III	X	0	1	0	1	0	1	Ohm
C	Vcc stress	IV	S	--------Module shall pass all remaining tests------						
D1	Ibd	V	S	0.0	2.0	0.0	2.0	0.0	2.0	mA
D2	Ibd	V	S	0.0	2.1	0.0	2.1	0.0	2.1	mA
D3	Ibd	V	S	0.0	2.0	0.0	2.0	0.0	2.0	mA
D4	Ibd	V	S	0.0	1.1	0.0	1.1	0.0	1.1	mA
D5	Ibd	V	S	0.0	1.0	0.0	1.0	0.0	1.0	mA
D6	Ibd	V	S	0.0	1.1	0.0	1.1	0.0	1.1	mA
D7,D8	Ibd	V	S	0.0	1.0	0.0	1.0	0.0	1.0	mA
D9-D12	Ibd	V	S	0.0	2.1	0.0	2.1	0.0	2.1	mA
D13	Ibd	V	S	0.0	3.1	0.0	3.1	0.0	3.1	mA
D14	Ibd	V	S	0.0	1.0	0.0	1.0	0.0	1.0	mA
D15,D16	Ibd	V	S	0.0	2.3	0.0	2.3	0.0	2.3	mA
D17	Ibd	V	S	0.0	0.1	0.0	0.1	0.0	0.1	mA
D18	Ibd	V	S	0.0	8.1	0.0	8.1	0.0	8.1	mA
D19	Ibd	V	S	0.0	1.5	0.0	1.5	0.0	1.5	mA
D20	Ibd	V	S	0.0	0.2	0.0	0.2	0.0	0.2	mA
D21	Ibd	V	S	0.0	2.0	0.0	2.0	0.0	2.0	mA
D22	Ibd	V	S	0.0	0.3	0.0	0.3	0.0	0.3	mA
D23	Ibd	V	S	0.0	2.1	0.0	2.1	0.0	2.1	mA
D24	Ibd	V	S	0.0	0.4	0.0	0.4	0.0	0.4	mA
D25	Ibd	V	S	0.0	0.6	0.0	0.6	0.0	0.6	mA
E1-E100	Ios	VI	S	-------Module shall pass all remaining tests-------						

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:42Z
Check the source to verify that this is the current version before use.

TABLE I. Module electrical requirements - Continued.

Test cond.	Parameter 5/	Ref test table	Test type 1/ 3/	25° ± 5°C 4/		Class I 4/ 0° ± 5°C 60° ± 5°C		Class II 4/ -55° ± 5°C 85° ± 5°C		Units
				Min	Max	Min	Max	Min	Max	
F1	Iih	VII	X	-0.5	0.05	-0.5	0.05	-0.5	0.05	mA
F2	Iih	VII	X	-1.1	0.07	-1.1	0.07	-1.1	0.07	mA
F3	Iih	VII	X	-0.5	0.05	-0.5	0.05	-0.5	0.05	mA
F4	Iih	VII	X	-2.6	0.07	-2.6	0.07	-2.6	0.07	mA
F5,F6	Iih	VII	X	-1.72	0.28	-1.72	0.28	-1.72	0.28	mA
F7-F12	Iih	VII	X	-1.93	0.31	-1.93	0.31	-1.93	0.31	mA
F13	Iih	VII	X	-0.25	0.03	-0.25	0.03	-0.25	0.03	mA
F14	Iih	VII	X	-0.9	0.06	-0.9	0.06	-0.9	0.06	mA
F15-F22	Iih	VII	X	-0.27	0.09	-0.27	0.09	-0.27	0.09	mA
F23,F24	Iih	VII	X	-0.25	0.03	-0.25	0.03	-0.25	0.03	mA
F25-F28	Iih	VII	X	-0.9	0.07	-0.9	0.07	-0.9	0.07	mA
F29	Iih	VII	X	-1.15	0.10	-1.15	0.10	-1.15	0.10	mA
F30	Iih	VII	X	-2.0	0.05	-2.0	0.05	-2.0	0.05	mA
F31,F32	Iih	VII	X	-2.3	0.11	-2.3	0.11	-2.3	0.11	mA
F33	Iih	VII	X	-0.6	0.02	-0.6	0.02	-0.6	0.02	mA
F34	Iih	VII	X	-16.6	0.42	-16.6	0.42	-16.6	0.42	mA
F35	Iih	VII	X	-3.8	0.15	-3.8	0.15	-3.8	0.15	mA
F36-F43	Iih	VII	X	-0.24	0.06	-0.24	0.06	-0.24	0.06	mA
F44	Iih	VII	X	-1.2	0.04	-1.2	0.04	-1.2	0.04	mA
F45	Iih	VII	X	-0.5	0.05	-0.5	0.05	-0.5	0.05	mA
F46	Iih	VII	X	-0.6	0.06	-0.6	0.06	-0.6	0.06	mA
F47	Iih	VII	X	-1.1	0.07	-1.1	0.07	-1.1	0.07	mA
F48	Iih	VII	X	-0.8	0.08	-0.8	0.08	-0.8	0.08	mA
F49	Iih	VII	X	-6.0	0.12	-6.0	0.12	-6.0	0.12	mA
G1	Iil	VIII	X	-0.5	0.05	-0.5	0.05	-0.5	0.05	mA
G2	Iil	VIII	X	-1.1	0.07	-1.1	0.07	-1.1	0.07	mA
G3	Iil	VIII	X	-0.5	0.05	-0.5	0.05	-0.5	0.05	mA
G4	Iil	VIII	X	-2.6	0.07	-2.6	0.07	-2.6	0.07	mA
G5,G6	Iil	VIII	X	-1.72	0.28	-1.72	0.28	-1.72	0.28	mA
G7-G12	Iil	VIII	X	-1.93	0.31	-1.93	0.31	-1.93	0.31	mA
G13	Iil	VIII	X	-0.25	0.03	-0.25	0.03	-0.25	0.03	mA
G14	Iil	VIII	X	-0.9	0.06	-0.9	0.06	-0.9	0.06	mA

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:42Z
Check the source to verify that this is the current version before use.

TABLE I. Module electrical requirements - Continued.

Test cond.	Parameter 5/	Ref test table	Test type 1/ - 3/	25° ± 5°C 4/		Class I 4/ 0° ± 5°C 60° ± 5°C		Class II 4/ -55° ± 5°C 85° ± 5°C		Units
				Min	Max	Min	Max	Min	Max	
G15-G22	III	VIII	X	-0.27	0.09	-0.27	0.09	-0.27	0.09	mA
G23,G24	III	VIII	X	-0.25	0.03	-0.25	0.03	-0.25	0.03	mA
G25-G28	III	VIII	X	-0.9	0.07	-0.9	0.07	-0.9	0.07	mA
G29	III	VIII	X	-1.15	0.10	-1.15	0.10	-1.15	0.10	mA
G30	III	VIII	X	-2.0	0.05	-2.0	0.05	-2.0	0.05	mA
G31,G32	III	VIII	X	-2.3	0.11	-2.3	0.11	-2.3	0.11	mA
G33	III	VIII	X	-0.6	0.02	-0.6	0.02	-0.6	0.02	mA
G34	III	VIII	X	-16.6	0.42	-16.6	0.42	-16.6	0.42	mA
G35	III	VIII	X	-3.8	0.15	-3.8	0.15	-3.8	0.15	mA
G36-G43	III	VIII	X	-0.24	0.06	-0.24	0.06	-0.24	0.06	mA
G44	III	VIII	X	-1.2	0.04	-1.2	0.04	-1.2	0.04	mA
G45	III	VIII	X	-0.5	0.05	-0.5	0.05	-0.5	0.05	mA
G46	III	VIII	X	-0.6	0.06	-0.6	0.06	-0.6	0.06	mA
G47	III	VIII	X	-1.1	0.07	-1.1	0.07	-1.1	0.07	mA
G48	III	VIII	X	-0.8	0.08	-0.8	0.08	-0.8	0.08	mA
G49	III	VIII	X	-6.0	0.12	-6.0	0.12	-6.0	0.12	mA
H1-H100	Voh	IX	X	2.4	4.5	2.4	4.5	2.4	4.5	V
J1-J100	Vol	X	X	0.0	0.5	0.0	0.5	0.0	0.5	V
K1-K17	Iozh	XI	X	-0.05	0.05	-0.05	0.05	-0.05	0.05	mA
K18-K34	Iozl	XI	X	-0.05	0.05	-0.05	0.05	-0.05	0.05	mA
L1-L3	Vic	XII	S	-1.2	0.0	-1.2	0.0	-1.2	0.0	V
L4-L8	Vic	XII	S	-1.5	0.0	-1.5	0.0	-1.5	0.0	V
L9-L13	Vic	XII	S	-1.2	0.0	-1.2	0.0	-1.2	0.0	V
L14,L15	Vic	XII	S	-1.5	0.0	-1.5	0.0	-1.5	0.0	V
L16	Vic	XII	S	-1.2	0.0	-1.2	0.0	-1.2	0.0	V
M1	PSFC	XIII	S	3.9	7.4	3.9	7.4	3.9	7.4	µF
M2	PSFC	XIII	S	2.3	4.4	2.3	4.4	2.3	4.4	µF

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:42Z
Check the source to verify that this is the current version before use.

TABLE I. Module electrical requirements - Continued.

Test cond.	Parameter 5/	Ref test table	Test type 1/ 3/	25° ± 5°C 4/		Class I 4/ 0° ± 5°C 60° ± 5°C		Class II 4/ -55° ± 5°C 85° ± 5°C		Units
				Min	Max	Min	Max	Min	Max	
N	Icc	XIV	X	892	2139	892	2139	892	2139	mA
P1,P2	Functional	XV	X	----------		See table XV		See table XV		
Q1,Q2	Dynamic	XVI	S	----------		See table XVI		See table XVI		
Q3,Q4	Dynamic	XVI	Q	----------		See table XVI		See table XVI		
R1-R3	Ci/o	XVIII	Q	2	75	2	75	2	75	pF
R4	Ci/o	XVIII	Q	2	100	2	100	2	100	pF
R5	Ci/o	XVIII	Q	2	75	2	75	2	75	pF
R6	Ci/o	XVIII	Q	4	100	4	100	4	100	pF
R7	Ci/o	XVIII	Q	2	125	2	125	2	125	pF
R8	Ci/o	XVIII	Q	2	75	2	75	2	75	pF
R9	Ci/o	XVIII	Q	6	100	6	100	6	100	pF
R10-R12	Ci/o	XVIII	Q	6	75	6	75	6	75	pF
R13	Ci/o	XVIII	Q	2	175	2	175	2	175	pF
R14	Ci/o	XVIII	Q	2	50	2	50	2	50	pF
R15	Ci/o	XVIII	Q	4	150	4	150	4	150	pF
R16	Ci/o	XVIII	Q	10	125	10	125	10	125	pF
R17	Ci/o	XVIII	Q	2	75	2	75	2	75	pF
R18	Ci/o	XVIII	Q	18	175	18	175	18	175	pF
R19	Ci/o	XVIII	Q	6	175	6	175	6	175	pF
R20	Ci/o	XVIII	Q	4	100	4	100	4	100	pF
R21	Ci/o	XVIII	Q	4	125	4	125	4	125	pF
R22	Ci/o	XVIII	Q	4	150	4	150	4	150	pF
R23	Ci/o	XVIII	Q	6	100	6	100	6	100	pF
R24	Ci/o	XVIII	Q	4	125	4	125	4	126	pF
R25	Ci/o	XVIII	Q	8	150	8	150	8	150	pF
R26,R27	Ci/o	XVIII	Q	4	75	4	75	4	75	pF
R28-R33	Ci/o	XVIII	Q	2	75	2	75	2	75	pF
R34-R37	Ci/o	XVIII	Q	4	75	4	75	4	75	pF
R38-R45	Ci/o	XVIII	Q	2	75	2	75	2	75	pF
R46	Ci/o	XVIII	Q	2	50	2	50	2	50	pF

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:42Z
Check the source to verify that this is the current version before use.

TABLE I. Module electrical requirements - Continued.

Test cond.	Parameter 5/	Ref test table	Test type 1/ - 3/	25° ± 5°C 4/		Class I 4/ 0° ± 5°C 60° ± 5°C		Class II 4/ -55° ± 5°C 85° ± 5°C		Units
				Min	Max	Min	Max	Min	Max	
R47	C I/o	XVIII	Q	2	75	2	75	2	75	pF
R48-R61	C I/o	XVIII	Q	6	100	6	100	6	100	pF
R62	C I/o	XVIII	Q	6	125	6	125	6	125	pF
T1,T2	PSTA	XIX	Q	0	400	0	400	0	400	mV

- See footnotes on next page.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:42Z
Check the source to verify that this is the current version before use.

6.3.1 Input parameters.

Signal	Vic min (V)	Vil max (V)	Vih min (V)	Iil min (mA)	Iih max (mA)	Ibd max (mA)	Cin max (pF)
MICRO IR 00	NA	0.4	2.4	-0.5	0.05	2.0	75
MICRO IR 01	-1.2	0.4	2.4	-1.1	0.07	2.1	75
MICRO IR 02	NA	0.4	2.4	-0.5	0.05	2.0	75
DEST CLK HLD	-1.2	0.4	2.4	-2.6	0.07	1.1	100
NDRO BIT MDE	NA	0.4	2.4	-0.25	0.03	1.0	75
LDPGRG 12-15	-1.2	0.4	2.4	-0.9	0.06	1.1	100
BOOT PRESENT	NA	0.4	2.4	-0.25	0.03	1.0	125
JMP CND TRUE	NA	0.4	2.4	-0.25	0.03	1.0	75
MCRO 28 (D4)	-1.5	0.4	2.4	-0.9	0.07	2.1	100
MCRO 27 (D3)	-1.5	0.4	2.4	-0.9	0.07	2.1	75
MCRO 26 (D2)	-1.5	0.4	2.4	-0.9	0.07	2.1	75
MCRO 25 (D1)	-1.5	0.4	2.4	-0.9	0.07	2.1	75
MCRO 24 (D0)	-1.5	0.4	2.4	-1.15	0.10	3.1	175
CB CLOCK	-1.2	0.4	2.4	-2.0	0.05	1.0	50

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:42Z
Check the source to verify that this is the current version before use.

6.3.1 Input parameters - Continued.

Signal	Vic min (V)	Vil max (V)	Vih min (V)	Iil min (mA)	Iih max (mA)	Ibd max (mA)	Cin max (pF)
MCRO 23(SA2)	NA	0.4	2.4	-2.3	0.11	2.3	150
MICRO IR 10	NA	0.4	2.4	-2.3	0.11	2.3	125
MICRO IR 05	-1.2	0.4	2.4	-0.6	0.02	0.1	75
CP CLOCK	-1.2	0.4	2.4	-16.6	0.42	8.1	175
2ND RNK FULL	-1.2	0.4	2.4	-3.8	0.15	1.5	175
ENBADRSGENSC	-1.2	0.4	2.4	-1.2	0.04	0.2	100
CBMCRCNTFMT	NA	0.4	2.4	-0.5	0.05	2.0	125
ENBL WR DATA	-1.5	0.4	2.4	-0.6	0.06	0.3	150
MCRO 16(SB0)	NA	0.4	2.4	-1.1	0.07	2.1	100
INCR PC/SPC	-1.5	0.4	2.4	-0.8	0.08	0.4	125
ENBCBAD/WRDA	-1.2	0.4	2.4	-6.0	0.12	0.6	150
PG SET-SEL 1	NA	0.4	2.4	-1.72	0.28	NA	NA
PG SET-SEL 0	NA	0.4	2.4	-1.72	0.28	NA	NA
INST CNTR 10	NA	0.4	2.4	-1.93	0.31	NA	NA

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:42Z
Check the source to verify that this is the current version before use.

TABLE VI. Output short circuit current test.

Test cond	Signal name	Pin no.	Vout (V)	25 ± 5°C Initial limits	Notes
E1	NDRO SEL LTC	6	0.0	Module shall pass all remaining tests.	1-4
E2	SR1 04	7			
E3	SR1 05	8			
E4	PG SET-SEL 1	9			
E5	PG SET-SEL 1	9			
E6	PG SET-SEL 0	11			
E7	PG SET-SEL 0	11			
E8	INST CNTR 10	12			
E9	INST CNTR 10	12			
E10	INST CNTR 10	12			
E11	INST CNTR 10	12			
E12	INST CNTR 11	13			
E13	INST CNTR 11	13			
E14	INST CNTR 11	13			
E15	INST CNTR 11	13			
E16	INST CNTR 12	14			
E17	INST CNTR 12	14			
E18	INST CNTR 12	14			
E19	INST CNTR 12	14			
E20	INST CNTR 13	15	0.0	Module shall pass all remaining tests.	1-4

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:42Z
Check the source to verify that this is the current version before use.

TABLE VI. Output short circuit current test - Continued.

Test cond	Signal name	Pin no.	Vout (V)	25 ± 5°C Initial limits	Notes
E21	INST CNTR 13	15	0.0	Module shall pass all remaining tests.	1-4
E22	INST CNTR 13	15			
E23	INST CNTR 13	15			
E24	INST CNTR 14	16			
E25	INST CNTR 14	16			
E26	INST CNTR 14	16			
E27	INST CNTR 14	16			
E28	INST CNTR 15	17			
E29	INST CNTR 15	17			
E30	INST CNTR 15	17			
E31	INST CNTR 15	17			
E32	EXEC LCKOUT	18			
E33	WRITE LCKOUT	19			
E34	READ LCKOUT	20			
E35	STREISTKHIT	23			
E36	CBAD/WRDBT17	24			
E37	CBAD/WRDBT16	26			
E38	CBAD/WRDBT15	27			
E39	CBAD/WRDBT14	28			
E40	CBAD/WRDBT13	29	0.0	Module shall pass all remaining tests.	1-4

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:42Z
Check the source to verify that this is the current version before use.

TABLE VI. Output short circuit current test - Continued.

Test cond	Signal name	Pin no.	Vout (V)	25 ± 5°C Initial limits	Notes
E41	CBAD/WRDBT12	30	0.0	Module shall pass all remaining tests.	1-4
E42	CBAD/WRDBT11	32			
E43	CBAD/WRDBT10	33			
E44	PRGM CNTR 15	34			
E45	PRGM CNTR 15	34			
E46	PRGM CNTR 14	35			
E47	PRGM CNTR 14	35			
E48	PRGM CNTR 13	36			
E49	PRGM CNTR 13	36			
E50	PRGM CNTR 12	37			
E51	PRGM CNTR 12	37			
E52	PRGM CNTR 11	38			
E53	PRGM CNTR 11	38			
E54	PRGM CNTR 10	39			
E55	PRGM CNTR 10	39			
E56	PRGM CNTR 09	41			
E57	PRGM CNTR 09	41			
E58	PRGM CNTR 08	42			
E59	PRGM CNTR 08	42			
E60	CBAD/WRDBT18	43	0.0	Module shall pass all remaining tests.	1-4

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:42Z
Check the source to verify that this is the current version before use.

TABLE VI. Output short circuit current test - Continued.

Test cond	Signal name	Pin no.	Vout (V)	25 ± 5°C Initial limits	Notes
E61	CBAD/WRDBT19	44	0.0	Module shall pass all remaining tests.	1-4
E62	CBAD/WRDBT20	45			
E63	CBAD/WRDBT21	46			
E64	CBAD/WRDBT08	47			
E65	CBAD/WRDBT09	48			
E66	NDRO SELECT	49			
E67	SR1 14 (GSS)	61			
E68	LD P HISTORY	64			
E69	FRCE I FETCH	65			
E70	LDSHDWPRGCTR	66			
E71	SR1 00 DMAEN	69			
E72	SR1 01 CLIEN	71			
E73	SR1 02 CIIEN	72			
E74	SR1 03 CIIIE	73			
E75	PRGM CNTR 07	74			
E76	PRGM CNTR 07	74			
E77	PRGM CNTR 06	76			
E78	PRGM CNTR 06	76			
E79	PRGM CNTR 05	77			
E80	PRGM CNTR 05	77	0.0	Module shall pass all remaining tests.	1-4

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:42Z
Check the source to verify that this is the current version before use.

TABLE VI. Output short circuit current test - Continued.

Test cond	Signal name	Pin no.	Vout (V)	25 ± 5°C Initial limits	Notes
E81	PRGM CNTR 04	78	0.0	Module shall pass all remaining tests.	1-4
E82	PRGM CNTR 04	78			
E83	PRGM CNTR 03	79			
E84	PGRM CNTR 03	79			
E85	PRGM CNTR 02	80			
E86	PRGM CNTR 02	80			
E87	PRGM CNTR 01	82			
E88	PRGM CNTR 01	82			
E89	PRGM CNTR 00	83			
E90	PRGM CNTR 00	83			
E91	MDRO FULL	87			
E92	KILL PIPE	89			
E93	CBAD/WRDBT00	93			
E94	CBAD/WRDBT01	94			
E95	CBAD/WRDBT02	95			
E96	CBAD/WRDBT03	96			
E97	CBAD/WRDBT04	97			
E98	CBAD/WRDBT05	98			
E99	CBAD/WRDBT06	99			
E100	CBAD/WRDBT07	100	0.0	Module shall pass all remaining tests.	1-4

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:42Z
Check the source to verify that this is the current version before use.

NOTES:

1. Output short circuit current test tolerance table.

Condition	Value	Accuracy	Test condition
Power supply, (Vcc)	5.5 V	± 55 mV	E1-E100
Power supply current limit	3.20 A	NA	E1-E100
Forcing voltage, (Vout)	0.0 V	± 50 mV	E1-E100
Pattern voltage, high, (VH)	3.0 V	± 100 mV	E1-E100
low, (VL)	0.0 V	± 100 mV	E1-E100

2. The following procedure is required to perform this test:

(a) The module power supply and ground pins shall be connected as specified in the power supply stress test table. The power supply voltage, including overshoot, shall not exceed the value specified in the power supply stress test tolerance table.

(b) Precondition the module under test to achieve the required state and make the indicated test at the appropriate pattern line.

(c) When making the test indicated on a pin, insure that the pin is disconnected from any drivers or comparators except those called for in the test.

(d) The forcing voltage shall be applied to the pin specified in the appropriate test conditions in table VI. The forcing voltage undershoot shall not exceed 100 mV.

3. When performing this test, no measurements are taken. Only one output shall be tested at a time, and the duration of momentarily grounding each output shall not exceed 1 second.

4. Abbreviations used are defined in 6.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:42Z
Check the source to verify that this is the current version before use.

TABLE XII. Input clamp diode voltage test.

Test cond	Signal name	Pin no.	Iin (mA)	25 ± 5°C Initial limits Min	Max	Units	Notes
L1	MICRO IR 01	3	-18.0	-1.2	0.0	V	1-3
L2	DEST CLK HLD	5					
L3	LDPGRG 12-15	22		-1.2			
L4	MCRO 28 (D4)	53		-1.5			
L5	MCRO 27 (D3)	54					
L6	MCRO 26 (D2)	55					
L7	MCRO 25 (D1)	56					
L8	MCRO 24 (D0)	57		-1.5			
L9	CB CLOCK	58		-1.2			
L10	MICRO IR 05	67					
L11	CP CLOCK	68					
L12	2ND RNK FULL	70					
L13	ENBADRSGENSC	84		-1.2			
L14	ENBL WR DATA	86		-1.5			
L15	INCR PC/SPC	91		-1.5			
L16	ENBCBAD/WRDA	92	-18.0	-1.2	0.0	V	1-3

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:42Z
Check the source to verify that this is the current version before use.

NOTES:

1. Input clamp diode voltage test tolerance table.

Condition	Value	Accuracy	Current limit	Test condition
Power supply, (Vcc)	Off	NA	NA	L1-L16
Forcing current, (Iin)	-18 mA	± 1.8 mA	NA	L1-L16
Pattern voltage high, (VH)	NA	NA	NA	L1-L16
low, (VL)	NA	NA	NA	L1-L16
Input voltage measurement	NA	± 60 mV	NA	L1-L3
	|	± 75 mV	|	L4-L8
	|	± 60 mV	|	L9-L13
	|	± 75 mV	|	L14,L15
	NA	± 60 mV	NA	L16

2. The following procedure is required to perform this test:

(a) No power shall be applied to the module.

(b) When making the test indicated on a pin, insure that the pin is disconnected from any drivers or comparators except those called for in the test.

(c) The forcing current shall be applied to the pin specified in the appropriate test conditions in table XII and the voltage then measured.

3. Abbreviations used are defined in 6.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:42Z
Check the source to verify that this is the current version before use.