|INCH-POUND|

MIL-M-28787/540
AMENDMENT 1
29 September 1993

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

HIGH PERFORMANCE EMULATION CONTROL I, KEY CODE EWAH

This amendment forms a part of Military Specification MIL-M-28787/540, dated 10 May 1989, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

TABLE I, Test condition A: Add End-of-life limits below the isolation test limits with a minimum limit of 1 MOhm (all temperatures) and a maximum limit of INF MOhm (all temperatures).

TABLE I, Test conditions E18-E21, Min limit (all temperatures): Delete "-85.0" (three places) and substitute "-160.0" (three places).

PAGE 6

TABLE I, Test conditions G63,G64, Max columns (all temperatures): Delete "0.22" (three places) and substitute "0.02" (three places).

PAGE 8

TABLE I, Test condition R65, Max columns (all temperatures): Delete "75" (three places) and substitute "50" (three places).

AMSC N/A FSC 5963
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:43Z
Check the source to verify that this is the current version before use.

PAGE 28

6.3.2, Signal BUS BIT 6, Cout column: Delete "75" and substitute "50".

PAGE 60

TABLE VI, Test conditions E18-E21, Min column: Delete "-85.0" and substitute "-160.0".

PAGE 62

TABLE VI, NOTES, Test tolerance table, Output current measurement accuracy, Test conditions E18-E21: Delete "3.65" and substitute "7.4".

PAGE 65

TABLE VII, Test condition F29, Vih column: Delete "0.0" and substitute "2.4".

PAGE 72

TABLE VIII, Test condition G63, Max column: Delete "0.22" and substitute "0.02".

PAGE 73

TABLE VIII, Test condition G64, Max column: Delete "0.22" and substitute "0.02".

PAGE 74

TABLE VIII, NOTES, Test tolerance table, Input current measurement accuracy, Test conditions G63,G64: Delete "31.0" and substitute "21.0".

PAGE 116

TABLE XVIII, Test condition R65, Max column: Delete "75" and substitute "50".

PAGE 118

TABLE XVIII, NOTES, Test tolerance table, Capacitance measurement accuracy, Test condition R65: Delete "3.65" and substitute "2.4".

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:43Z
Check the source to verify that this is the current version before use.

Custodians:
Army - ER
Navy - NW
Air Force - 85

Review activities:
Army - AT
Navy - AS, MC
Air Force - 13, 19
DLA - ES

Preparing activity:
Navy - NW

(Project 5963-0290)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:43Z
Check the source to verify that this is the current version before use.