INCH-POUND

MIL-M-28787/540
AMENDMENT 2
3 August 1994
SUPERSEDING
AMENDMENT 1
29 September 1993

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

HIGH PERFORMANCE EMULATION CONTROL I, KEY CODE EWAH

This amendment forms a part of Military Specification MIL-M-28787/540, dated 10 May 1989, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGES 4, 5, 6, 7, 8 AND 9

* TABLE I: Delete and substitute new table I as printed on pages 4, 5, 6, 7, 8 and 9 of this amendment.

PAGE 23

* 6.3.1, Input parameters, Vic column, Signals "EC1 DEST", "IR BIT 26", "IR BIT 25", and "IR BIT 24": Delete "-1.5" (four places) and substitute "NA" (four places).

PAGES 26, 27 AND 28

* 6.3.2, Output parameters, Ios column: Delete Ios column.

PAGE 28

6.3.2, Output parameters, Cout column, Signal "BUS BIT 6": Delete "75" and substitute "50".

PAGES 60, 61, 62 AND 63

* TABLE VI: Delete and substitute new table VI as printed on pages 10, 11 and 12 of this amendment.

AMSC N/A FSC 5963
DISTRIBUTION STATEMENT A Approved for public release, distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:43Z
Check the source to verify that this is the current version before use.

PAGE 65

TABLE VII, Test condition F29, Vih column: Delete "0.0" and substitute "2.4".

PAGE 72

TABLE VIII, Test condition G63, Max limit: Delete "0.22" and substitute "0.02".

PAGE 73

TABLE VIII, Test condition G64, Max limit: Delete "0.22" and substitute "0.02".

PAGE 74

TABLE VIII, Test tolerance table, Input current measurement accuracy, Test conditions G63,G64: Delete "31.0" and substitute "21.0".

PAGES 87, 88, 89 AND 90

* TABLE XII: Delete and substitute new table XII as printed on pages 13, 14, 15 and 16 of this amendment.

PAGE 116

TABLE XVIII, Test condition R65, Max limit: Delete "75" and substitute "50".

PAGE 118

TABLE XVIII, Test tolerance table, Capacitance measurement accuracy, Test condition R65: Delete "3.65" and substitute "2.4".

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:43Z
Check the source to verify that this is the current version before use.

NOTE: The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - ER
Navy - NW
Air Force - 85

Review activities:
Army - AT
Navy - AS, MC
Air Force - 13, 19
DLA - ES

Preparing activity:
Navy - NW

(Project 5963-0294)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:43Z
Check the source to verify that this is the current version before use.

TABLE I Module electrical requirements

Test cond	Parameter 5/	Ref test table	Test type 1/ - 3/	25 ± 5°C 4/		Class I 4/ 0 ± 5°C 60 ± 5°C		Class II 4/ -55 ± 5°C 85 ± 5°C		Units
				Min	Max	Min	Max	Min	Max	
A	Isolation	II	S	10	INF	10	INF	10	INF	MOhm
	End-of-life	II	S	1	INF	1	INF	1	INF	MOhm
B1 B6	Continuity	III	X	0	1	0	1	0	1	Ohm
C	Vcc Stress	IV	S	--------Module shall pass all remaining tests-- ---						
D1,D2	Ibd	V	S	0 0	0.2	0 0	0 2	0 0	0 2	mA
D3	Ibd	V	S	0 0	1 3	0 0	1 3	0 0	1 3	mA
D4	Ibd	V	S	0 0	0.3	0 0	0.3	0 0	0 3	mA
D5	Ibd	V	S	0 0	2 1	0 0	2 1	0 0	2 1	mA
D6,D7	Ibd	V	S	0 0	0.1	0 0	0.1	0 0	0 1	mA
D8	Ibd	V	S	0 0	1.2	0 0	1.2	0 0	1 2	mA
D9	Ibd	V	S	0 0	0 1	0 0	0 1	0 0	0.1	mA
D10-D17	Ibd	V	S	0 0	0.2	0.0	0.2	0 0	0.2	mA
D18-D23	Ibd	V	S	0 0	0.4	0 0	0 4	0 0	0.4	mA
D24-D27	Ibd	V	S	0.0	1.0	0.0	1.0	0 0	1 0	mA
D28	Ibd	V	S	0 0	8.0	0 0	8 0	0 0	8.0	mA
D29-D36	Ibd	V	S	0 0	0.2	0 0	0.2	0 0	0 2	mA
D37	Ibd	V	S	0 0	1 3	0 0	1 3	0 0	1 3	mA
D38-D40	Ibd	V	S	0 0	0.1	0 0	0 1	0 0	0.1	mA
D41	Ibd	V	S	0 0	0 4	0 0	0 4	0 0	0.4	mA
D42	Ibd	V	S	0 0	1 2	0 0	1.2	0 0	1.2	mA
D43,D44	Ibd	V	S	0 0	0.2	0 0	0 2	0.0	0 2	mA
D45	Ibd	V	S	0 0	0 1	0 0	0 1	0 0	0.1	mA
D46	Ibd	V	S	0 0	0.2	0 0	0.2	0.0	0 2	mA
D47,D48	Ibd	V	S	0 0	0.3	0 0	0.3	0.0	0 3	mA
D49	Ibd	V	S	0 0	0.2	0 0	0.2	0.0	0 2	mA
* E1-E41	Ios	VI	S	-------Module shall pass all remaining tests-------						

- See footnotes at end of table

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:43Z
Check the source to verify that this is the current version before use.

TABLE I. Module electrical requirements - Continued

Test cond	Parameter 5/	Ref-test table	Test type 1/ - 3/	25 ± 5°C 4/		Class I 4/ 0 ± 5°C 60 ± 5°C		Class II 4/ -55 ± 5°C 85 ± 5°C		Units
				Min	Max	Min	Max	Min	Max	
F1 F4	Iih	VII	X	-0 25	0.07	-0.25	0 07	-0 25	0 07	mA
F5 F8	Iih	VII	X	-1 15	0.12	-1.15	0 12	-1 15	0 12	mA
F9,F10	Iih	VII	X	-0 4	0 04	-0 4	0 04	-0 4	0.04	mA
F11	Iih	VII	X	-2.05	0.085	-2.05	0 085	-2.05	0.085	mA
F12	Iih	VII	X	-1.8	0.06	-1.8	0 06	-1.8	0.06	mA
F13	Iih	VII	X	-1 1	0.07	-1.1	0 07	-1 1	0.07	mA
F14,F15	Iih	VII	X	-0 6	0 02	-0.6	0 02	-0 6	0.02	mA
F16	Iih	VII	X	-1 45	0 065	-1 45	0 065	-1.45	0 065	mA
F17	Iih	VII	X	-0.6	0.02	-0.6	0 02	-0.6	0.02	mA
F18 F25	Iih	VII	X	-1.0	0.04	-1.0	0 04	-1 0	0.04	mA
F26	Iih	VII	X	-2.4	0 08	-2.4	0.08	-2.4	0.08	mA
F27,F28	Iih	VII	X	-1 6	0 08	-1 6	0.08	-1 6	0.08	mA
F29	Iih	VII	X	-3 2	0 16	-3.2	0 16	-3.2	0.16	mA
F30,F31	Iih	VII	X	-1.6	0 08	-1 6	0.08	-1.6	0.08	mA
F32 F35	Iih	VII	X	-0.25	0.025	-0.25	0.025	-0.25	0.025	mA
F36	Iih	VII	X	-16 0	0 4	-16 0	0 4	-16.0	0.4	mA
F37-F44	Iih	VII	X	-1.0	0.04	-1.0	0.04	-1.0	0.04	mA
F45	Iih	VII	X	-2 05	0 085	-2.05	0.085	-2 05	0 085	mA
F46	Iih	VII	X	-0 4	0.02	-0.4	0.02	-0.4	0.02	mA
F47-F54	Iih	VII	X	-0 85	0.09	-0.85	0.09	-0.85	0.09	mA
F55-F62	Iih	VII	X	-1.05	0.11	-1.05	0 11	-1 05	0.11	mA
F63,F64	Iih	VII	X	-0 4	0.02	-0.4	0 02	-0.4	0.02	mA
F65	Iih	VII	X	-2 4	0.08	-2.4	0 08	-2 4	0 08	mA
F66	Iih	VII	X	-1.45	0.065	-1.45	0 065	-1.45	0.065	mA
F67,F68	Iih	VII	X	-1.2	0 04	-1.2	0.04	-1.2	0.04	mA
F69	Iih	VII	X	-0.6	0 02	-0 6	0 02	-0.6	0.02	mA
F70	Iih	VII	X	-1 2	0.04	-1 2	0 04	-1.2	0.04	mA
F71,F72	Iih	VII	X	-1 8	0.06	-1.8	0.06	-1.8	0.06	mA
F73	Iih	VII	X	-1 2	0.04	-1.2	0 04	-1 2	0 04	mA
G1-G4	Iil	VIII	X	-0 25	0.07	-0.25	0 07	-0 25	0.07	mA
G5-G8	Iil	VIII	X	-1 15	0 12	-1.15	0.12	-1.15	0.12	mA
G9,G10	Iil	VIII	X	-0 4	0.04	-0.4	0 04	-0.4	0.04	mA

See footnotes at end of table

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:43Z
Check the source to verify that this is the current version before use.

TABLE I Module electrical requirements - Continued.

Test cond	Parameter 5/	Ref test table	Test type 1/ - 3/	25 ± 5°C 4/		Class I 4/ 0 ± 5°C 60 ± 5°C		Class II 4/ -55 ± 5°C 85 ± 5°C		Units
				Min	Max	Min	Max	Min	Max	
G11	III	VIII	X	-2 05	0.085	-2 05	0 085	-2.05	0.085	mA
G12	III	VIII	X	-1 8	0.06	-1.8	0 06	-1.8	0.06	mA
G13	III	VIII	X	-1 1	0 07	-1 1	0 07	-1.1	0.07	mA
G14,G15	III	VIII	X	-0 6	0 02	-0 6	0.02	-0.6	0.02	mA
G16	III	VIII	X	-1 45	0 065	-1.45	0.065	-1.45	0.065	mA
G17	III	VIII	X	-0 6	0 02	-0 6	0.02	-0 6	0 02	mA
G18-G25	III	VIII	X	-1 0	0.04	-1.0	0.04	-1 0	0 04	mA
G26	III	VIII	X	-2 4	0.08	-2 4	0.08	-2 4	0 08	mA
G27,G28	III	VIII	X	-1 6	0 08	-1 6	0.08	-1.6	0.08	mA
G29	III	VIII	X	-3 2	0 16	-3.2	0 16	-3.2	0 16	mA
G30,G31	III	VIII	X	-1 6	0 08	-1.6	0.08	-1 6	0.08	mA
G32 G35	III	VIII	X	-0 25	0 025	-0.25	0.025	-0 25	0 025	mA
G36	III	VIII	X	-16 0	0.4	-16.0	0.4	-16.0	0.4	mA
G37 G44	III	VIII	X	-1 0	0 04	-1 0	0.04	-1.0	0.04	mA
G45	III	VIII	X	-2 05	0.085	-2.05	0.085	-2.05	0 085	mA
G46	III	VIII	X	-0 4	0 02	-0 4	0 02	-0 4	0 02	mA
G47-G54	III	VIII	X	-0 85	0.09	-0 85	0.09	-0 85	0.09	mA
G55-G62	III	VIII	X	-1 05	0.11	-1.05	0.11	-1.05	0.11	mA
G63,G64	III	VIII	X	-0 4	0 02	-0.4	0.02	-0.4	0 02	mA
G65	III	VIII	X	-2 4	0.08	-2.4	0.08	-2.4	0 08	mA
G66	III	VIII	X	-1 45	0 065	-1.45	0.065	-1 45	0 065	mA
G67,G68	III	VIII	X	-1 2	0.04	-1.2	0.04	-1.2	0.04	mA
G69	III	VIII	X	-0 6	0 02	-0 6	0.02	-0 6	0 02	mA
G70	III	VIII	X	-1.2	0.04	-1.2	0.04	-1 2	0.04	mA
G71,G72	III	VIII	X	-1 8	0 06	-1.8	0 06	-1 8	0 06	mA
G73	III	VIII	X	-1.2	0.04	-1.2	0.04	-1.2	0 04	mA
H1 H41	Voh	IX	X	2 4	4.5	2.4	4.5	2 4	4 5	V

See footnotes at end of table

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:43Z
Check the source to verify that this is the current version before use.

TABLE I. Module electrical requirements - Continued.

Test cond	Parameter 5/	Ref test table	Test type 1/ - 3/	25 ± 5°C 4/		Class I 4/ 0 ± 5°C 60 ± 5°C		Class II 4/ -55 ± 5°C 85 ± 5°C		Units
				Min	Max	Min	Max	Min	Max	
J1-J41	Vol	X	X	0 0	0.5	0.0	0.5	0 0	0.5	V
K1-K12	Iozh	XI	X	-0 05	0.05	-0.05	0 05	-0 05	0.05	mA
K13-K24	Iozl	XI	X	-0.05	0 05	-0.05	0.05	-0.05	0 05	mA
L1,L2	Vic	XII	S	-1.5	0.0	-1.5	0.0	-1 5	0 0	V
L3-L18	Vic	XII	S	-1 2	0 0	-1 2	0 0	-1 2	0 0	V
* L19-L23	Vic	XII	S	-1.5	0.0	-1.5	0 0	-1 5	0.0	V
* L24 L33	Vic	XII	S	-1 2	0 0	-1 2	0 0	-1 2	0 0	V
* L34-L36	Vic	XII	S	-1 5	0.0	-1.5	0.0	-1 5	0 0	V
* L37-L45	Vic	XII	S	-1 2	0 0	-1 2	0 0	-1 2	0 0	V
M1	PSFC	XIII	S	3 2	6 1	3 2	6 1	3 2	6 1	uF
M2	PSFC	XIII	S	2 6	4 9	2 6	4 9	2 6	4 9	uF
N1	Icc	XIV	X	870	2088	870	2088	870	2088	mA
P1,P2	Functional	XV	X	See table XV						
Q1,Q2	Dynamic	XVI	S	See table XVI						
Q3,Q4	Dynamic	XVI	Q	See table XVI						
R1,R2	Ci/o	XVIII	Q	4	100	4	100	4	100	pF
R3,R4	Ci/o	XVIII	Q	4	150	4	150	4	150	pF
R5	Ci/o	XVIII	Q	4	125	4	125	4	125	pF
R6,R7	Ci/o	XVIII	Q	2	50	2	50	2	50	pF
R8	Ci/o	XVIII	Q	6	125	6	125	6	125	pF
R9	Ci/o	XVIII	Q	2	100	2	100	2	100	pF

-See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:43Z
Check the source to verify that this is the current version before use.

TABLE I Module electrical requirements - Continued

Test cond	Parameter 5/	Ref test table	Test type 1/ - 3/	25 ± 5°C 4/		Class I 4/ 0 ± 5°C 60 ± 5°C		Class II 4/ -55 ± 5°C 85 ± 5°C		Units
				Min	Max	Min	Max	Min	Max	
R10-R17	Ci/o	XVIII	Q	4	75	4	75	4	75	pF
R18	Ci/o	XVIII	Q	8	125	8	125	8	125	pF
R19,R20	Ci/o	XVIII	Q	8	100	8	100	8	100	pF
R21	Ci/o	XVIII	Q	8	125	8	125	8	125	pF
R22,R23	Ci/o	XVIII	Q	8	100	8	100	8	100	pF
R24 R27	Ci/o	XVIII	Q	2	50	2	50	2	50	pF
R28	Ci/o	XVIII	Q	16	125	16	125	16	125	pF
R29,R30	Ci/o	XVIII	Q	4	75	4	75	4	75	pF
R31,R32	Ci/o	XVIII	Q	4	100	4	100	4	100	pF
R33 R35	Ci/o	XVIII	Q	4	75	4	75	4	75	pF
R36	Ci/o	XVIII	Q	4	100	4	100	4	100	pF
R37	Ci/o	XVIII	Q	2	175	2	175	2	175	pF
R38	Ci/o	XVIII	Q	2	100	2	100	2	100	pF
R39	Ci/o	XVIII	Q	2	75	2	75	2	75	pF
R40	Ci/o	XVIII	Q	2	125	2	125	2	125	pF
R41	Ci/o	XVIII	Q	8	125	8	125	8	125	pF
R42	Ci/o	XVIII	Q	2	100	2	100	2	100	pF
R43,R44	Ci/o	XVIII	Q	4	75	4	75	4	75	pF
R45	Ci/o	XVIII	Q	2	50	2	50	2	50	pF
R46	Ci/o	XVIII	Q	4	75	4	75	4	75	pF
R47	Ci/o	XVIII	Q	6	75	6	75	6	75	pF
R48	Ci/o	XVIII	Q	6	100	6	100	6	100	pF
R49 R53	Ci/o	XVIII	Q	4	75	4	75	4	75	pF
R54-R57	Ci/o	XVIII	Q	4	100	4	100	4	100	pF
R58	Ci/o	XVIII	Q	2	75	2	75	2	75	pF
R59-R64	Ci/o	XVIII	Q	2	50	2	50	2	50	pF
R65	Ci/o	XVIII	Q	2	50	2	50	2	50	pF
R66	Ci/o	XVIII	Q	2	50	2	50	2	50	pF

See footnotes at end of table

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:43Z
Check the source to verify that this is the current version before use.

TABLE I Module electrical requirements - Continued

Test cond	Parameter 5/	Ref test table	Test type 1/ - 3/	25 ± 5°C 4/		Class I 4/ 0 ± 5°C 60 ± 5°C		Class II 4/ -55 ± 5°C 85 ± 5°C		Units
				Min	Max	Min	Max	Min	Max	
R67	Ci/o	XVIII	Q	4	100	4	100	4	100	pF
R68-R70	Ci/o	XVIII	Q	4	125	4	125	4	125	pF
R71	Ci/o	XVIII	Q	2	75	2	75	2	75	pF
R72-R74	Ci/o	XVIII	Q	2	50	2	50	2	50	pF
R75,R76	Ci/o	XVIII	Q	6	100	6	100	6	100	pF
R77	Ci/o	XVIII	Q	6	75	6	75	6	75	pF
R78-R82	Ci/o	XVIII	Q	6	100	6	100	6	100	pF
R83	Ci/o	XVIII	Q	2	150	2	150	2	150	pF
R84-R86	Ci/o	XVIII	Q	2	175	2	175	2	175	pF
R87,R88	Ci/o	XVIII	Q	2	150	2	150	2	150	pF
R89,R90	Ci/o	XVIII	Q	2	175	2	175	2	175	pF
S	Vic latch up	XIX	S	-1 2	2 4	-1.2	2 4	-1.2	2 4	V
T1,T2	PSTA	XX	Q	0	400	0	400	0	400	mV

-See footnotes on next page

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:43Z
Check the source to verify that this is the current version before use.

TABLE VI. Output short circuit current test.

Test cond	Signal name	Pin no.	Vout (V)	25 ± 5°C Initial limits	Notes
E1	PIPE BIT 7	2	0.0	Module shall pass all remaining tests.	1-4
E2	PIPE BIT 6	3			
E3	PIPE BIT 5	4			
E4	PIPE BIT 4	5			
E5	PIPE BIT 3	6			
E6	PIPE BIT 2	7			
E7	PIPE BIT 1	8			
E8	PIPE BIT 0	9			
E9	BUS BIT 10	36			
E10	BUS BIT 0	52			
E11	BUS BIT 1	53			
E12	BUS BIT 2	54			
E13	BUS BIT 3	55			
E14	BUS BIT 4	56			
E15	BUS BIT 5	57			
E16	BUS BIT 6	58			
E17	BUS BIT 7	59			
E18	DATA BUS 12	63			
E19	DATA BUS 13	64			
E20	DATA BUS 14	65	0.0	Module shall pass all remaining tests.	1-4

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:43Z
Check the source to verify that this is the current version before use.

TABLE VI. Output short circuit current test - Continued.

Test cond	Signal name	Pin no.	Vout (V)	25 ± 5°C Initial limits	Notes
E21	DATA BUS 15	66	0.0	Module shall pass all remaining tests.	1-4
E22	BOOT PRES	67			
E23	EMUL BIT 0	68			
E24	EMUL BIT 1	69			
E25	EMUL BIT 2	70			
E26	EMUL BIT 3	71			
E27	EMUL BIT 4	72			
E28	EMUL BIT 5	73			
E29	EMUL BIT 6	74			
E30	EMUL BIT 7	76			
E31	EMUL BIT 8	77			
E32	EMUL BIT 9	78			
E33	EMUL BIT 10	79			
E34	EMUL BIT 11	80			
E35	EMUL BIT 12	82			
E36	EMUL BIT 13	83			
E37	EMUL BIT 14	84			
E38	EMUL BIT 15	85			
E39	BUS BIT 8	95			
E40	BUS BIT 9	96			
E41	JMP COND T	100	0.0	Module shall pass all remaining tests.	1-4

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:43Z
Check the source to verify that this is the current version before use.

TABLE XII. Input clamp diode voltage test.

Test cond	Signal name	Pin no.	Iin (mA)	25 ± 5°C Initial limits Min	25 ± 5°C Initial limits Max	Units	Notes
L1	CLK Y REG	11	-18.0	-1.5	0.0	V	1-3
L2	CLK MDRI	12		-1.5			
L3	INTR PEND	13		-1.2			
L4	CLK PIPE	14					
L5	IR BIT 15	15					
L6	IR BIT 16	16					
L7	IR BIT 17	17					
L8	CTRL FRMT	18					
L9	PWR FAULT	19					
L10	DAT BIT 3	20					
L11	DAT BIT 2	21					
L12	DAT BIT 1	22					
L13	DAT BIT 0	23					
L14	DAT BIT 7	24					
L15	DAT BIT 6	26					
L16	DAT BIT 5	27					
L17	DAT BIT 4	28					
L18	CB/I STACK	29		-1.2			
L19	STACK R1	30		-1.5			
L20	STACK R0	32					
L21	CLK STACK	33	-18.0	-1.5	0.0	V	1-3

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:43Z
Check the source to verify that this is the current version before use.

TABLE XII. Input clamp diode voltage test - Continued.

	Test cond	Signal name	Pin no.	Iin (mA)	25 ± 5°C Initial limits Min	25 ± 5°C Initial limits Max	Units	Notes
	L22	STACK W1	34	-18.0	-1.5	0.0	V	1-3
	L23	STACK W0	35		-1.5			
*	L24	PH N CLK	42		-1.2			
*	L25	DAT BIT 8	43					
*	L26	DAT BIT 9	44					
*	L27	DAT BIT 10	45					
*	L28	DAT BIT 11	46					
*	L29	DAT BIT 12	47					
*	L30	DAT BIT 13	48					
*	L31	DAT BIT 14	49					
*	L32	DAT BIT 15	50					
*	L33	J MAP OE	61		-1.2			
*	L34	STOP KEY 2	62		-1.5			
*	L35	STOP KEY 1	86					
*	L36	BT 1/ BT 2	87		-1.5			
*	L37	EN SB 18-1B	88		-1.2			
*	L38	IR BIT 14	89					
*	L39	ALU NEG	91					
*	L40	ALU ZERO	92					
*	L41	ALU CARRY	93	-18.0	-1.2	0.0	V	1-3

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:43Z
Check the source to verify that this is the current version before use.

TABLE XII. Input clamp diode voltage test - Continued.

	Test cond	Signal name	Pin no.	Iin (mA)	25 ± 5°C Initial limits Min	Max	Units	Notes
*	L42	ALU OVERFL	94	-18.0	-1.2	0.0	V	1-3
*	L43	IR BIT 12	97					
*	L44	IR BIT 13	98					
*	L45	IR BIT 41	99	-18.0	-1.2	0.0	V	1-3

NOTES:

1. Input clamp diode voltage test tolerance table.

Condition	Value	Accuracy	Current limit	Test condition
Power supply, (Vcc)	Off	NA	NA	L1-L45
Forcing current, (Iin)	-18 mA	± 1.8 mA	NA	L1-L45
Pattern voltage high, (VH)	NA	NA	NA	L1-L45
low, (VL)	NA	NA	NA	L1-L45
Input voltage measurement	NA	± 75 mV	NA	L1,L2
		± 60 mV		L3-L18
		± 75 mV		L19-L23
		± 60 mV		L24-L33
		± 75 mV		L34-L36
	NA	± 60 mV	NA	L37-L45

2. The following procedure is required to perform this test:

(a) No power shall be applied to the module.

(b) When making the test indicated on a pin, insure that the pin is disconnected from any drivers or comparators except those called for in the test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:43Z
Check the source to verify that this is the current version before use.

NOTES: - Continued.

(c) The forcing current shall be applied to the pin specified in the appropriate test conditions in table XII and the voltage then measured.

3. Abbreviations used are defined in 6.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:43Z
Check the source to verify that this is the current version before use.

TABLE XII. Input clamp diode voltage test - Continued.

	Test cond	Signal name	Pin no.	Iin (mA)	25 ± 5°C Initial limits Min	Max	Units	Notes
*	L42	ALU OVERFL	94	-18.0	-1.2	0.0	V	1-3
*	L43	IR BIT 12	97					
*	L44	IR BIT 13	98					
*	L45	IR BIT 41	99	-18.0	-1.2	0.0	V	1-3

NOTES:

1. Input clamp diode voltage test tolerance table.

Condition	Value	Accuracy	Current limit	Test condition
Power supply, (Vcc)	Off	NA	NA	L1-L45
Forcing current, (Iin)	-18 mA	± 1.8 mA	NA	L1-L45
Pattern voltage high, (VH)	NA	NA	NA	L1-L45
low, (VL)	NA	NA	NA	L1-L45
Input voltage measurement	NA	± 75 mV	NA	L1,L2
		± 60 mV		L3-L18
		± 75 mV		L19-L23
		± 60 mV		L24-L33
		± 75 mV		L34-L36
	NA	± 60 mV	NA	L37-L45

2. The following procedure is required to perform this test:

(a) No power shall be applied to the module.

(b) When making the test indicated on a pin, insure that the pin is disconnected from any drivers or comparators except those called for in the test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:43Z
Check the source to verify that this is the current version before use.