INCH-POUND

MIL-M-28787/542(NW)
AMENDMENT 1
3 August 1994

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

HIGH PERFORMANCE EMULATION CONTROL III MODULE, KEY CODE FWB

This amendment forms a part of Military Specification MIL-M-28787/542, dated 5 May 1989, and is approved for use by the Crane Division, Naval Surface Warfare Center, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGES 4 THROUGH 9

TABLE I: Delete and substitute new table I as printed on pages 2 through 6 of this amendment.

PAGES 22 AND 23

6.3.1, Input parameters: Delete and substitute new section of 6.3.1 as printed on pages 7 and 8 of this amendment.

PAGES 25 THROUGH 27

6.3.2, Output parameters, Ios max (mA) column: Delete Ios max (mA) column.

PAGES 54 THROUGH 57

TABLE VI: Delete and substitute new table VI as printed on pages 9 through 11 of this amendment.

PAGES 81 THROUGH 84

TABLE XII: Delete and substitute new table XII as printed on pages 12 through 14 of this amendment.

Preparing activity:
Navy - NW

(Project 5963-N862)

AMSC N/A FSC 5963
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:45Z
Check the source to verify that this is the current version before use.

TABLE I Module electrical requirements

Test cond.	Parameter 5/	Ref test table	Test type 1/ - 3/	25 ± 5°C 4/		Class I 4/ 0 ± 5°C 60 ± 5°C		Class II 4/ -55 ± 5°C 85 ± 5°C		Units
				Min	Max	Min	Max	Min	Max	
A	Isolation	II	S	10	INF	10	INF	10	INF	MOhm
	End-of-life	II	S	1	INF	1	INF	1	INF	MOhm
B1-B6	Continuity	III	X	0	1	0	1	0	1	Ohm
C	Vcc stress	IV	S	--------Module shall pass all remaining tests------						
D1	Ibd	V	S	0.0	0.1	0.0	0.1	0.0	0.1	mA
D2	Ibd	V	S	0.0	0.2	0.0	0.2	0.0	0.2	mA
D3-D5	Ibd	V	S	0.0	0 1	0.0	0.1	0 0	0.1	mA
D6,D7	Ibd	V	S	0.0	0.2	0.0	0.2	0.0	0.2	mA
D8	Ibd	V	S	0.0	3.0	0.0	3.0	0.0	3.0	mA
D9	Ibd	V	S	0.0	2.5	0.0	2.5	0.0	2.5	mA
D10	Ibd	V	S	0.0	0 4	0.0	0.4	0.0	0.4	mA
D11-D13	Ibd	V	S	0.0	0.1	0.0	0.1	0.0	0.1	mA
D14	Ibd	V	S	0.0	1.0	0.0	1.0	0 0	1.0	mA
D15,D16	Ibd	V	S	0.0	0.1	0.0	0.1	0.0	0.1	mA
D17	Ibd	V	S	0.0	0.2	0.0	0.2	0.0	0.2	mA
D18-D20	Ibd	V	S	0.0	1.0	0.0	1.0	0.0	1.0	mA
D21	Ibd	V	S	0.0	2 1	0.0	2.1	0 0	2.1	mA
D22	Ibd	V	S	0.0	1.0	0.0	1.0	0.0	1.0	mA
D23	Ibd	V	S	0.0	2.0	0.0	2.0	0.0	2.0	mA
D24	Ibd	V	S	0 0	3 0	0.0	3.0	0.0	3.0	mA
D25	Ibd	V	S	0.0	2.0	0.0	2.0	0.0	2.0	mA
D26	Ibd	V	S	0.0	1.2	0.0	1.2	0.0	1.2	mA
D27	Ibd	V	S	0.0	1.0	0.0	1.0	0.0	1.0	mA
D28	Ibd	V	S	0.0	2.0	0.0	2.0	0.0	2.0	mA
D29-D33	Ibd	V	S	0.0	1.0	0.0	1.0	0.0	1.0	mA
D34	Ibd	V	S	-0.25	0.346	-0.25	0.346	-0.25	0.346	mA
D35-D41	Ibd	V	S	0.0	0.1	0.0	0.1	0.0	0.1	mA
D42,D43	Ibd	V	S	0 0	0 2	0.0	0.2	0.0	0.2	mA
D44	Ibd	V	S	0.0	0.1	0.0	0.1	0.0	0.1	mA
D45,D46	Ibd	V	S	0.0	1.0	0.0	1.0	0.0	1.0	mA
D47	Ibd	V	S	0.0	0.1	0.0	0.1	0.0	0.1	mA

- See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:45Z
Check the source to verify that this is the current version before use.

TABLE I. Module electrical requirements - Continued.

Test cond.	Parameter 5/	Ref test table	Test type 1/ - 3/	25 ± 5°C 4/		Class I 4/ 0 ± 5°C 60 ± 5°C		Class II 4/ -55 ± 5°C 85 ± 5°C		Units
				Min	Max	Min	Max	Min	Max	
E1-E42	Ios	VI	S	-------Module shall pass all remaining tests-------						
F1	Ilh	VII	X	-0.6	0.02	-0.6	0.02	-0.6	0.02	mA
F2	Ilh	VII	X	-1.2	0.04	-1.2	0.04	-1.2	0.04	mA
F3-F5	Ilh	VII	X	-0.6	0.02	-0.6	0.02	-0.6	0.02	mA
F6	Ilh	VII	X	-1.4	-0.54	-1.4	-0.54	-1.4	-0.54	mA
F7,F8	Ilh	VII	X	-1.2	0.04	-1.2	0.04	-1.2	0.04	mA
F9	Ilh	VII	X	-6.0	0.15	-6.0	0.15	-6.0	0.15	mA
F10	Ilh	VII	X	-7.0	0.2	-7.0	0.2	-7.0	0.2	mA
F11	Ilh	VII	X	-6.0	0.08	-6.0	0.08	-6.0	0.08	mA
F12-F14	Ilh	VII	X	-0.6	0.02	-0.6	0.02	-0.6	0.02	mA
F15	Ilh	VII	X	-2.0	0.05	-2.0	0.05	-2.0	0.05	mA
F16,F17	Ilh	VII	X	-0.6	0.02	-0.6	0.02	-0.6	0.02	mA
F18	Ilh	VII	X	-1.2	0.04	-1.2	0.04	-1.2	0.04	mA
F19-F21	Ilh	VII	X	-0.25	0.025	-0.25	0.025	-0.25	0.025	mA
F22	Ilh	VII	X	-1.1	0.07	-1.1	0.07	-1.1	0.07	mA
F23	Ilh	VII	X	-0.25	0.025	-0.25	0.025	-0.25	0.025	mA
F24	Ilh	VII	X	-0.5	0.05	-0.5	0.05	-0.5	0.05	mA
F25	Ilh	VII	X	-0.75	0.075	-0.75	0.075	-0.75	0.075	mA
F26	Ilh	VII	X	-0.5	0.05	-0.5	0.05	-0.5	0.05	mA
F27	Ilh	VII	X	-1.05	0.065	-1.05	0.065	-1.05	0.065	mA
F28	Ilh	VII	X	-0.25	0.025	-0.25	0.025	-0.25	0.025	mA
F29	Ilh	VII	X	-0.5	0.05	-0.5	0.05	-0.5	0.05	mA
F30-F34	Ilh	VII	X	-0.25	0.025	-0.25	0.025	-0.25	0.025	mA
F35	Ilh	VII	X	-11.7	-6.1	-11.7	-6.1	-11.7	-6.1	mA
F36-F39	Ilh	VII	X	-0.6	0.02	-0.6	0.02	-0.6	0.02	mA
F40	Ilh	VII	X	-0.2	0.02	-0.2	0.02	-0.2	0.02	mA
F41,F42	Ilh	VII	X	-0.6	0.02	-0.6	0.02	-0.6	0.02	mA
F43,F44	Ilh	VII	X	-1.2	0.04	-1.2	0.04	-1.2	0.04	mA
F45	Ilh	VII	X	-0.6	0.02	-0.6	0.02	-0.6	0.02	mA
F46,F47	Ilh	VII	X	-2.0	0.05	-2.0	0.05	-2.0	0.05	mA
F48	Ilh	VII	X	-0.6	0.02	-0.6	0.02	-0.6	0.02	mA

- See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:45Z
Check the source to verify that this is the current version before use.

TABLE I. Module electrical requirements - Continued.

Test cond.	Parameter 5/	Ref test table	Test type 1/ - 3/	25 ± 5°C 4/		Class I 4/ 0 ± 5°C 60 ± 5°C		Class II 4/ -55 ± 5°C 85 ± 5°C		Units
				Min	Max	Min	Max	Min	Max	
G1	III	VIII	X	-0.6	0.02	-0.6	0.02	-0.6	0 02	mA
G2	III	VIII	X	-1.2	0.04	-1.2	0.04	-1.2	0.04	mA
G3-G5	III	VIII	X	-0.6	0 02	-0.6	0.02	-0.6	0.02	mA
G6	III	VIII	X	-1.4	-0.54	-1.4	-0.54	-1.4	-0.54	mA
G7,G8	III	VIII	X	-1.2	0.04	-1.2	0.04	-1.2	0.04	mA
G9	III	VIII	X	-6.0	0.15	-6.0	0.15	-6.0	0.15	mA
G10	III	VIII	X	-7.0	0 2	-7.0	0.2	-7.0	0.2	mA
G11	III	VIII	X	-6.0	0.08	-6.0	0.08	-6.0	0.08	mA
G12-G14	III	VIII	X	-0.6	0.02	-0.6	0.02	-0.6	0.02	mA
G15	III	VIII	X	-2.0	0.05	-2.0	0 05	-2.0	0.05	mA
G16,G17	III	VIII	X	-0.6	0.02	-0.6	0.02	-0.6	0.02	mA
G18	III	VIII	X	-1 2	0.04	-1.2	0.04	-1.2	0.04	mA
G19-G21	III	VIII	X	-0.25	0.025	-0.25	0.025	-0.25	0.025	mA
G22	III	VIII	X	-1 1	0.07	-1.1	0.07	-1 1	0.07	mA
G23	III	VIII	X	-0.25	0.025	-0.25	0.025	-0.25	0.025	mA
G24	III	VIII	X	-0 5	0.05	-0.5	0.05	-0.5	0.05	mA
G25	III	VIII	X	-0.75	0.075	-0.75	0.075	-0.75	0.075	mA
G26	III	VIII	X	-0.5	0.05	-0.5	0.05	-0.5	0.05	mA
G27	III	VIII	X	-1.05	0.065	-1.05	0.065	-1.05	0.065	mA
G28	III	VIII	X	-0.25	0.025	-0.25	0.025	-0.25	0.025	mA
G29	III	VIII	X	-0.5	0.05	-0.5	0.05	-0.5	0.05	mA
G30-G34	III	VIII	X	-0.25	0.025	-0.25	0.025	-0.25	0.025	mA
G35	III	VIII	X	-11.7	-6.1	-11.7	-6.1	-11.7	-6.1	mA
G36-G39	III	VIII	X	-0.6	0.02	-0.6	0.02	-0.6	0.02	mA
G40	III	VIII	X	-0.2	0.02	-0.2	0.02	-0.2	0.02	mA
G41,G42	III	VIII	X	-0.6	0.02	-0.6	0.02	-0.6	0.02	mA
G43,G44	III	VIII	X	-1.2	0.04	-1.2	0.04	-1.2	0.04	mA
G45	III	VIII	X	-0.6	0.02	-0.6	0.02	-0.6	0.02	mA
G46,G47	III	VIII	X	-2.0	0.05	-2.0	0.05	-2.0	0.05	mA
G48	III	VIII	X	-0.6	0.02	-0.6	0.02	-0.6	0.02	mA

-See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:45Z
Check the source to verify that this is the current version before use.

TABLE I. Module electrical requirements - Continued

Test cond.	Parameter 5/	Ref test table	Test type 1/ - 3/	25 ± 5°C 4/		Class I 4/ 0 ± 5°C 60 ± 5°C		Class II 4/ -55 ± 5°C 85 ± 5°C		Units
				Min	Max	Min	Max	Min	Max	
H1-H42	Voh	IX	X	2.4	4.5	2.4	4.5	2.4	4.5	V
J1-J42	Vol	X	X	0.0	0.5	0.0	0.5	0.0	0.5	V
K1-K7	Iozh	XI	X	-0.05	0.05	-0.05	0.05	-0.05	0.05	mA
K8-K14	Iozl	XI	X	-0.05	0.05	-0.05	0.05	-0.05	0.05	mA
L1-L21	Vic	XII	S	-1.2	0.0	-1.2	0.0	-1.2	0.0	V
L22	Vic	XII	S	-1.5	0.0	-1.5	0.0	-1.5	0.0	V
L23-L30	Vic	XII	S	-1.2	0.0	-1.2	0.0	-1.2	0.0	V
M1	PSFC	XIII	S	3.7	6.9	3.7	6.9	3.7	6.9	µF
M2	PSFC	XIII	S	3.1	5.8	3.1	5.8	3.1	5.8	µF
N	Icc	XIV	X	480	1150	480	1150	480	1150	mA
P1,P2	Functional	XV	X	----------		See table XV		----------		
Q1,Q2	Dynamic	XVI	S	----------		See table XVI		----------		
Q3,Q4	Dynamic	XVI	G	----------		See table XVI		----------		
R1	Ci/o	XVIII	G	2	75	2	75	2	75	pF
R2	Ci/o	XVIII	G	4	150	4	150	4	150	pF
R3	Ci/o	XVIII	G	2	75	2	75	2	75	pF
R4	Ci/o	XVIII	G	2	50	2	50	2	50	pF
R5	Ci/o	XVIII	G	2	75	2	75	2	75	pF
R6,R7	Ci/o	XVIII	G	4	75	4	75	4	75	pF
R8	Ci/o	XVIII	G	6	75	6	75	6	75	pF
R9	Ci/o	XVIII	G	10	175	10	175	10	175	pF
R10	Ci/o	XVIII	G	4	100	4	100	4	100	pF
R11	Ci/o	XVIII	G	2	50	2	50	2	50	pF
R12,R13	Ci/o	XVIII	G	2	75	2	75	2	75	pF
R14,R15	Ci/o	XVIII	G	2	50	2	50	2	50	pF
R16	Ci/o	XVIII	G	2	75	2	75	2	75	pF

-See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:45Z
Check the source to verify that this is the current version before use.

TABLE I. Module electrical requirements - Continued.

Test cond.	Parameter 5/	Ref test table	Test type 1/ - 3/	25 ± 5°C 4/		Class I 4/ 0 ± 5°C 60 ± 5°C		Class II 4/ -55 ± 5°C 85 ± 5°C		Units
				Min	Max	Min	Max	Min	Max	
R17	C1/o	XVIII	Q	4	75	4	75	4	75	pF
R18,R19	C1/o	XVIII	Q	2	50	2	50	2	50	pF
R20	C1/o	XVIII	Q	6	125	6	125	6	125	pF
R21	C1/o	XVIII	Q	2	75	2	75	2	75	pF
R22	C1/o	XVIII	Q	4	75	4	75	4	75	pF
R23	C1/o	XVIII	Q	6	100	6	100	6	100	pF
R24	C1/o	XVIII	Q	4	75	4	75	4	75	pF
R25	C1/o	XVIII	Q	6	125	6	125	6	125	pF
R26	C1/o	XVIII	Q	2	75	2	75	2	75	pF
R27	C1/o	XVIII	Q	4	100	4	100	4	100	pF
R28-R30	C1/o	XVIII	Q	2	50	2	50	2	50	pF
R31	C1/o	XVIII	Q	2	75	2	75	2	75	pF
R32	C1/o	XVIII	Q	2	100	2	100	2	100	pF
R33	C1/o	XVIII	Q	4	75	4	75	4	75	pF
R34-R36	C1/o	XVIII	Q	2	50	2	50	2	50	pF
R37,R38	C1/o	XVIII	Q	2	75	2	75	2	75	pF
R39,R40	C1/o	XVIII	Q	2	50	2	50	2	50	pF
R41	C1/o	XVIII	Q	4	75	4	75	4	75	pF
R42	C1/o	XVIII	Q	4	100	4	100	4	100	pF
R43	C1/o	XVIII	Q	2	50	2	50	2	50	pF
R44,R45	C1/o	XVIII	Q	2	125	2	125	2	125	pF
R46	C1/o	XVIII	Q	2	75	2	75	2	75	pF
R47	C1/o	XVIII	Q	6	125	6	125	6	125	pF
R48-R54	C1/o	XVIII	Q	2	75	2	75	2	75	pF
R55	C1/o	XVIII	Q	6	100	6	100	6	100	pF
R56	C1/o	XVIII	Q	2	50	2	50	2	50	pF
R57	C1/o	XVIII	Q	2	100	2	100	2	100	pF
R58	C1/o	XVIII	Q	6	100	6	100	6	100	pF
R59	C1/o	XVIII	Q	2	50	2	50	2	50	pF
T1,T2	PSTA	XIX	Q	0	400	0	400	0	400	mV

- See footnotes on next page.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:45Z
Check the source to verify that this is the current version before use.

6.3.1. Input parameters.

Signal	Vic min (V)	Vil max (V)	Vih min (V)	Iil min (mA)	Iih max (mA)	Ibd max (mA)	Cin max (pF)
WR LOCKOUT	-1.2	0.4	2.4	-0.6	0.02	0.1	50
EXEC LOCKOUT	-1.2	0.4	2.4	-0.6	0.02	0.1	75
READ LOCKOUT	-1.2	0.4	2.4	-1.2	0.04	0.2	75
IR BIT 02	NA	0.4	2.4	-0.25	0.025	1.0	50
IR BIT 01	NA	0.4	2.4	-0.25	0.025	1.0	50
IR BIT 00	NA	0.4	2.4	-0.25	0.025	1.0	50
COM BUS CTRL	NA	0.4	2.4	-1.1	0.07	2.1	125
IR BIT 10	NA	0.4	2.4	-0.25	0.025	1.0	75
CB CTRL CD F	NA	0.4	2.4	-0.5	0.05	2.0	75
FRC INS FTCH	NA	0.4	2.4	-0.75	0.075	3.0	100
IR BIT 05	NA	0.4	2.4	-0.5	0.05	2.0	75
KILL PIPE	NA	0.4	2.4	-1.05	0.065	1.2	125
BUS BIT 00	NA	0.4	2.4	-0.25	0.025	1.0	75
IR BIT 06	NA	0.4	2.4	-0.5	0.05	2.0	100

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:45Z
Check the source to verify that this is the current version before use.

6.3.1. Input parameters - Continued.

Signal	Vic min (V)	Vil max (V)	Vih min (V)	Iil min (mA)	Iih max (mA)	Ibd max (mA)	Cin max (pF)
IR BIT 04	NA	0.4	2.4	-0.25	0.025	1.0	50
IR BIT 03	NA	0.4	2.4	-0.25	0.025	1.0	50
BYTE POINTER	NA	0.4	2.4	-0.25	0.025	1.0	50
EN PROTECT A	NA	0.4	2.4	-0.25	0.025	1.0	75
DEST CLK HLD	NA	0.4	2.4	-0.25	0.025	1.0	100
STOP	NA	0.4	2.4	-11.7	-6.1	0.346	75
IR BIT 09	-1.2	0.4	2.4	-0.6	0.02	0.1	50
IR BIT 08	-1.2	0.4	2.4	-0.6	0.02	0.1	50
IR BIT 07	-1.2	0.4	2.4	-0.6	0.02	0.1	50
CBDATA TMOUT	-1.2	0.4	2.4	-0.6	0.02	0.1	75
BRKPT ABR 0	-1.5	0.4	2.4	-0.2	0.02	0.1	75
SET ISTA EMP	-1.2	0.4	2.4	-0.6	0.02	0.1	50
ISTACK FULL	-1.2	0.4	2.4	-0.6	0.02	0.1	50
ISTA TO YREG	-1.2	0.4	2.4	-1.2	0.04	0.2	75

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:45Z
Check the source to verify that this is the current version before use.

TABLE VI. Output short circuit current test.

Test cond.	Signal name	Pin no.	Vout (V)	25 ± 5°C Initial limits	Notes
E1	E START	2	0.0	Module shall pass all remaining tests.	1-4
E2	ORIG RDY TP	5			
E3	EN PG W DATA	9			
E4	CB FUNC BIT0	11			
E5	CB FUNC BIT1	12			
E6	CB ORIG RDY	13			
E7	INSTR FETCH	14			
E8	CB FUNC BIT2	15			
E9	CB FUNC BIT3	16			
E10	CB WRITE EN	17			
E11	CB CYC ABORT	18			
E12	PAGING BUSY	19			
E13	EN CB AD/WR	20			
E14	(TP) 1	22			
E15	AD BUS MASTR	23			
E16	CB REQ3 (CP)	27			
E17	2ND RNK FULL	28			
E18	(TP) 2	29			
E19	CLK 3RD RANK	30			
E20	CLK IN MDR	32			
E21	(TP) 3	34	0.0	Module shall pass all remaining tests.	1-4

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:45Z
Check the source to verify that this is the current version before use.

TABLE VI. Output short circuit current test - Continued.

Test cond.	Signal name	Pin no.	Vout (V)	25 ± 5°C Initial limits	Notes
E22	CB CLK BUF	35	0.0	Module shall pass all remaining tests.	1-4
E23	(TP) 4	36			
E24	TNT DT BS MR	37			
E25	DT BS MASTR	38			
E26	CLK Y	42			
E27	LD PG B15-12	43			
E28	EN INCR PC	46			
E29	CLK BRKPT ST	47			
E30	CLK PIPE	48			
E31	IN MDR FULL	50			
E32	KIL PI 4 RNK	52			
E33	SEL ISTA/SEL	74			
E34	RESUME ERROR	76			
E35	BRKPT 4 RANK	77			
E36	PTCT ER 4 RK	78			
E37	CLOCK ISTACK	86			
E38	INCR ISTA WR	88			
E39	2 WD READ	91			
E40	Y REG FULL	95			
E41	PIPE FULL	96			
E42	INCR ISTA RD	100	0.0	Module shall pass all remaining tests.	1-4

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:45Z
Check the source to verify that this is the current version before use.

NOTES:

1. Output short circuit current test tolerance table.

Condition	Value	Accuracy	Test condition
Power supply, (Vcc)	5.5 V	± 55 mV	E1-E42
Power supply current limit	1.73 A	NA	E1-E42
Forcing voltage, (Vout)	0.0 V	± 50 mV	E1-E42
Pattern voltage, high, (VH) low, (VL)	3.0 V 0.0 V	± 100 mV ± 100 mV	E1-E42 E1-E42

2. The following procedure is required to perform this test:

(a) The module power supply and ground pins shall be connected as specified in the power supply stress test table. The power supply voltage, including overshoot, shall not exceed the value specified in the power supply stress test tolerance table.

(b) Precondition the module under test to achieve the required state and make the indicated test at the appropriate pattern line.

(c) When making the test indicated on a pin, insure that the pin is disconnected from any drivers or comparators except those called for in the test.

(d) The forcing voltage shall be applied to the pin specified in the appropriate test conditions in table VI. The forcing voltage undershoot shall not exceed 100 mV.

3. When performing this test, no measurements are taken. Only one output shall be tested at a time, and the duration of momentarily grounding each output shall not exceed 1 second.

4. Abbreviations used are defined in 6.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:45Z
Check the source to verify that this is the current version before use.

TABLE XII. Input clamp diode voltage test.

Test cond.	Signal name	Pin no.	Iin (mA)	25 ± 5°C Initial limits Min	25 ± 5°C Initial limits Max	Units	Notes
L1	IR BIT 11	3	-18.0	-1.2	0.0	V	1-3
L2	CB ADR TMOUT	4					
L3	CLR2 RNK FULL	6					
L4	CP MA CL SNC	7					
L5	CB ADDR TERM	8					
L6	CB GRANT 3	21					
L7	OTPT MDR FUL	26					
L8	CB CLOCK 2	33					
L9	CP CLOCK 1	39					
L10	FL INSTR STA	41					
L11	CB BUSY	44					
L12	CB DATA TERM	45					
L13	RESET IN MDR	49					
L14	NDRO SEL LAT	53					
L15	WR LOCKOUT	54					
L16	EXEC LOCKOUT	55					
L17	READ LOCKOUT	56					
L18	IR BIT 09	80					
L19	IR BIT 08	82					
L20	IR BIT 07	83					
L21	CBDATA TMOUT	84	-18.0	-1.2	0.0	V	1-3

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:45Z
Check the source to verify that this is the current version before use.

TABLE XII. Input clamp diode voltage test - Continued.

Test cond.	Signal name	Pin no.	Iin (mA)	25 ± 5°C Initial limits Min	25 ± 5°C Initial limits Max	Units	Notes
L22	BRKPT ABR 0	85	-18.0	-1.5	0.0	V	1-3
L23	SET ISTA EMP	87		-1.2			
L24	ISTACK FULL	89					
L25	ISTA TO YREG	92					
L26	ISTA TO PIPE	93					
L27	RESET Y FULL	94					
L28	J MAP OE	97					
L29	IR BIT 41	98					
L30	B/DESTN CLK	99	-18.0	-1.2	0.0	V	1-3

NOTES:

1. Input clamp diode voltage test tolerance table.

Condition	Value	Accuracy	Test condition
Power supply, (Vcc)	Off	NA	L1-L30
Power supply current limit	NA	NA	L1-L30
Forcing current, (Iin)	-18 mA	± 1.8 mA	L1-L30
Pattern voltage, high, (VH)	NA	NA	L1-L30
Pattern voltage, low, (VL)	NA	NA	L1-L30

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:45Z
Check the source to verify that this is the current version before use.

NOTES: - Continued.

Condition	Value	Accuracy	Test condition
Input voltage measurement	NA	± 60 mV	L1-L21
	|	± 75 mV	L22
	NA	± 60 mV	L23-L30

2. The following procedure is required to perform this test:

(a) No power shall be applied to the module.

(b) When making the test indicated on a pin, insure that the pin is disconnected from any drivers or comparators except those called for in the test.

(c) The forcing voltage shall be applied to the pin specified in the appropriate test conditions in table XII and the voltage then measured.

3. Abbreviations used are defined in 6.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T18:45Z
Check the source to verify that this is the current version before use.