INCH-POUNDS

MIL-DTL-28731/15F
17 May 2016
SUPERSEDING
MIL-C-28731/15E
4 June 1985

DETAIL SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, INSERT (INSULATOR), MALE RECTANGULAR, POLARIZED, CENTER SCREW LOCK, FOR 90 REMOVABLE CONTACTS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-28731.





FIGURE 1. Connector, male rectangular.

AMSC N/A


FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:57Z
Check the source to verify that this is the current version before use.



Keying position on both polarizing pins can be rotated to desired position by loosening spanner nut (counter-clockwise), resetting pin in one of six positions then retightening spanner nut (clockwise).

NOTE: Overtightening of spanner nut can fracture connector. Spanner keying wrench shown below.



Configuration A – Connector polarization guide (layout)

FIGURE 1. Connector, male rectangular – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:57Z
Check the source to verify that this is the current version before use.





FIGURE 1. Connector, male rectangular – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:57Z
Check the source to verify that this is the current version before use.



Configuration B – Contact hole detail

Inches	mm	Inches	mm	Inches	mm	Inches	mm
.005	0.13	.075	1.90	.250	6.35	1.710	43.43
.022	0.71	.090	2.29	.412	10.46	1.900	48.26
.03	0.8	.110	2.79	.468	11.89	1.950	49.53
.035	0.89	.120	3.05	.495	12.57	2.280	57.91
.040	1.02	.128	3.25	.650	16.51	2.576	65.43
.043	1.12	.130	3.30	.681	17.30	2.592	65.84
.044	1.12	.133	3.38	.790	20.07	3.187	80.95
.045	1.14	.138	3.51	.798	20.27		
.050	1.27	.140	3.56	.910	23.11		
.055	1.40	.150	3.81	1.00	25.4		
.060	1.52	160	4.06	1.015	25.78		
.062	1.57	.187	4.75	1.140	28.96		
.070	1.70	.234	5.94	1.37	34.8		

FIGURE 1. Connector, male rectangular – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:57Z
Check the source to verify that this is the current version before use.

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Tolerances between any two contact centers shall be ± .004 (0.10 mm).
4. Flatness, squareness, and parallelism shall be within dimensional tolerances.
5. Contact hole details shall be in accordance with configuration B.
6. Mating connector information:
   M28731/15-0073, and M28731/15-0075 mate with M28731/16-0074, M28731/16-0076, and M29731/16-0077. M28731/15-0074, M28731/15-0076 and M28731/15-0077 mate with M28731/16-0073, and M28731/16-0075. M28731/15-0078, M28731/15-0079 and M28731/15-0080 mate with M28731/16-0078 and M28731/16-0079.
7. Polarization information: Polarization pins are provided for indexing to preclude intermixing of adjacent connectors. By using a standard type spanner wrench, polarization pins can be rotated to desired position. For parts supplied directly to the government, polarization will be in the 1-1 position. For other polarization positions see connector polarization guide configuration A (see marking, note 13d). For direct government acquisition a tool is supplied in the unit package for polarization socket adjustment.
8. Contact and terminal designations: Contacts and terminals shall be designated on the insulator using letters in the location shown on figure 1.
9. Tolerance shall be ± .010 (0.25 mm) unless otherwise specified.
10. Patent notice: Patent No. 3,248,686 owned by Elco Corporation. The government has a royalty-free license under the above patent for the benefit of manufacturers of items called for in this specification, either for the government or for use in equipment to be delivered to the government.
11. For direct government acquisition crimp contacts M28731/20-0001 are furnished in a plastic bag in each unit package (see marking, note 13a).
12. For direct government acquisition wrappost contacts are M28731/26-001 (see table I) and are factory installed in connector body (see marking, note 13a).
13. Marking:
    a. Connectors supplied directly to the government shall be marked with the military Part or Identifying Number (PIN) (see table I). Example: M28731/15-0073.
    b. Connectors supplied with contacts to government end users shall be marked with the military PIN (see table I). Example: M28731/15-0073.
    c. Connectors supplied without contacts to government end users shall be marked as follows: Example: M28731/15F (socket type from table I). The user shall complete the remaining portion of the military PIN as shown in table I based upon contact type he assembles. Example: M28731/15F-0073.
    d. Polarization position marking is not required unless otherwise specified. When required polarization marking shall be in accordance with the connector polarization guide (see configuration A). The marking shall appear following the PIN.
14. Applicable contact insertion and removal tools:
    Insertion – SAE AS81969/13, PIN: M81969/13-01
    Removal – SAE AS81969/11, PIN: M81969/11-01
15. When double wire crimp contact MIL-DTL-28731/23 is required for use with connector, it shall be ordered separately.
16. Rectangular shields shall conform to MIL-DTL-28731/19-0011 -0012, -0019 and -0020 must be ordered separately.
17. Recommended hardware (not furnished) for panel mounting (4) .112-40 UNC-2A (length to suit) bolt with No. 4 washer and mating nut.

FIGURE 1. Connector, male rectangular – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:57Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

Mating and unmating forces (torque): 185 inch-ounces, maximum.

Dielectric withstanding voltage. 1,250 V rms, 60 Hz, minimum.

Mechanical shock (specified pulse): High impact shock applicable.

PIN: See table I.

TABLE I. PIN information.

PIN	Actuating hardware	Polarizing pin position		Contact type
		A .140 DIA	B .120 DIA	
M28731/15-0073	Jackscrew type G	1	1	Crimp, MIL-DTL-28731/20 1/
M28731/15-0074	Fixed socket type F	1	1	Crimp, MIL-DTL-28731/20 1/
M28731/15-0077	Fixed socket type F	1	1	Wrappost MIL-DTL-28731/26 2/
M28731/15-0078	Fixed screw type E	1	1	Crimp, MIL-DTL-28731/20 1/
M28731/15-0080	Fixed screw type E	1	1	Wrappost MIL-DTL-28731/26 2/

1/ See figure 1, note 11.
2/ See figure 1, note 12.

Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Referenced documents. In addition to MIL-DTL-28731, this document references the following:

MIL-DTL-28731/19
MIL-DTL-28731/20
MIL-DTL-28731/23
MIL-DTL-28731/26
SAE AS81969/11
SAE AS81969/13

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:57Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army – CR
Navy – EC
Air Force – 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5935-2016-050)

Review activities:
Army – AR, AT, CR4, MI
Navy – AS, MC, OS
Air Force – 19, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:57Z
Check the source to verify that this is the current version before use.