[INCH-POUND]
A-A-468A
May 12, 1993
SUPERSEDING
A-A-468
October 27, 1982

COMMERCIAL ITEM DESCRIPTION

SCOOP, KITCHEN

The General Services Administration has authorized the use of this commercial item description as a replacement for Federal Specifications RR-S-131 and RR-K-260 which have been canceled.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This commercial item description covers aluminum and corrosion-resisting steel food service scoops.

1.2 Classification. The scoops shall be of the following types.

Type I - Aluminum alloy
Type II - Corrosion-resisting steel

2. APPLICABLE DOCUMENTS

2.1 The documents referenced in this commercial item description shall be the issues in effect on the date of issuance of the invitation for bids or request for proposal unless otherwise specified. These documents form a part of this commercial item description to the extent specified. In the event of a conflict between this commercial item description and a document referenced herein, this commercial item description shall take precedence.

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any other data which may improve this document should be sent to: General Services Administration, Engineering Group (7FXEE), 819 Taylor Street, Fort Worth, TX 76102.

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

FSC 7330

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:08Z
Check the source to verify that this is the current version before use.

c. The backing, backing, and marking desired.

Federal Standard:

FED-STD-376 - Preferred Metric Units for General Use by The Federal Government.

Copies of Federal standards are available from the General Services Administration Business Service Centers in Boston, MA; New York, NY; Philadelphia, PA; Washington, DC; Atlanta, GA; Chicago, IL; Kansas City, MO; Fort Worth, TX; Denver, CO; San Francisco, CA; Seattle, WA, and the GSA Specifications Unit (3FBP-W), Suite 8100, 470 E. L'Enfant Plaza, S.W., Washington, DC 20407.

Military Standard:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

Copies of military standards may be obtained from Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.

American Iron and Steel Institute:

Handbook - Finishes for Stainless Steel.

Application for copies of AISI handbooks should be addressed to the Committee of Stainless Steel Producers, American Iron and Steel Institute, 1000 16th Street, N.W., Washington, DC 20036.

ASTM Standard:

E 29 - Standard Practice For Using Significant Digits in Test Data to Determine Conformance with Specifications.

Application for copies of ASTM standards should be addressed to ASTM, 1916 Race Street, Philadelphia, PA 19103.

National Sanitation Foundation (NSF):

Standard No. 2 - Food Service Equipment.
Annual Listing - Food Service Equipment and Related Products, Components and Materials.

Application for NSF documents should be addressed to the National Sanitation Foundation, 3475 Plymouth Road, P.O. Box 1468, Ann Arbor, MI 48106.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:08Z
Check the source to verify that this is the current version before use.

3. SALIENT CHARACTERISTICS

3.1 Material.

3.1.1 Type I, Aluminum. The type I scoop shall be an integral casting of aluminum alloy.

3.1.2 Type II, Corrosion-resisting steel. The type II scoop shall be formed from a 300-series corrosion-resisting steel.

3.2 Design and construction. The body of the scoop shall be a half-cylinder measuring 8 inches (20.3 cm) in length and 5 inches (12.7 cm) in diameter with an overall length of 12 inches (30.5 cm). The tolerances shall be ± 1 inch (2.54 cm). The handle shall be positioned at an angle of 8 to 20 degrees to the scoop from the horizontal position for the type I scoop and 25 to 35 degrees for the type II scoop.

3.2.1 Type I. The body of the scoop shall have a minimum average thickness of 0.055 inch (1.4 mm) when measured in four different locations around the edge of the body. The handle shall be cast integral with the body.

3.2.2 Type II. The body of the scoop shall have a minimum average thickness of 0.035 inch (0.9 mm) when measured in four different locations around the edge of the body. The body shall be fitted with a handle. The handle shall be fastened to the body by one of the following two methods.

1. Flanged to the diameter and securely attached to the body of the scoop by spotwelding or continuous welding around the outside diameter of the flange.

2. Continuously welded to a shield of the same material as the body. The shield shall not be less than 0.040 inch (1.0 mm) thick and shall be attached to the body of the scoop by spotwelding or continuous welding.

3.3 Finish.

3.3.1 Type I. The scoop shall have a smooth finish as defined in National Sanitation Foundation Standard No. 2.

3.3.2 Type II. The scoop shall have a polished finish equivalent to a No. 2B or better as defined by the American Iron and Steel Institute handbook, "Finishes for Stainless Steel."

3.4 Marking. The scoop shall be marked with the manufacturer's name, trade name, or trademark of such known character that the source may be readily determined.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:08Z
Check the source to verify that this is the current version before use.

3.5 Workmanship. The scoop shall be free from sharp edges, slivers, burrs, deep scratches, pits and tool marks. Welding shall be complete, free from burnholes, cracks, fractures, slag inclusion, and undercut. Welds shall be correctly fused, smooth, and uniform. There shall be no defects which impair the durability, appearance, or serviceability of the item.

3.6 NSF Compliance. Prior to approval of first shipment, the contractor shall submit to the contracting officer or his authorized representative satisfactory evidence that the items offered meet the applicable requirements of NSF Standard No. 2. Satisfactory evidence of this compliance may be any of the following:

(1) A listing in the current edition of the NSF "Listing of Food Service Equipment" and display of the NSF seal on the finished item, or

(2) A certification issued by NSF under the special one-time contract evaluation/certification service, or

(3) A certified test report from a recognized independent testing laboratory acceptable to the contracting officer or authorized representative of the service for which the items are being procured, indicating that the item has been tested and conforms to NSF No. 2.

3.7 Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 as amended to the maximum extent practicable.

3.8 Measurement system. The values stated in inch-pound units are to be regarded as the standard. The values stated in parentheses are for informational purposes only.

3.9 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, providing they fall within tolerances specified using conversion tables contained in the latest revision of FED-STD-376, and all other requirements of this document are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the specification preparing activity for changes to this document.

3.10 Commercial item. The use of the term "commercial item description" in this document does not imply that any item or items offered are not required to conform with all requirements specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:08Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Certification. The contractor shall certify, and maintain objective quality evidence, that the product offered meets this commercial item description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The government reserves the right to require proof of such conformance prior to the first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

4.2 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.3 Sampling. The levels of inspection and acceptable quality levels (AQL's) shall be in accordance with MIL-STD-105.

4.4 Lot formation. All scoops from the same manufacturer of the same type offered for delivery at one time shall be considered a lot for purposes of inspection.

4.5 Sampling for visual and dimensional examination. A random sample of scoops shall be selected from each lot in accordance with inspection level S-4, AQL 4.0 expressed in terms of defects per hundred units (dhu). The sample unit shall be one scoop. The sample scoop shall be visually and dimensionally examined to verify compliance with table I and the remainder of this commercial item description. All dimensions are absolute as defined in ASTM E 29.

4.6 Examination for preparation for delivery. A random sample of shipping containers shall be selected from each lot for examination of the unit, intermediate, and shipping containers (as applicable) for conformance with the packaging, packing, and marking required in the contract or order. Samples shall be selected in accordance with inspection level S-2, AQL 6.5 (dhu).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:08Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects for visual and dimensional defects.

Examine	Defect
Finish	Area of corrosion, stain or discoloration
	Not as specified
Construction and Workmanship	Scratch or tool mark 1/
	Any sharp edge, sliver, rough tool or die mark, or burr
	Any component fractured, split, bent, buckled, punctured or otherwise impaired
	Handle not securely attached
	Dimensions not as specified
Marking	Missing, incomplete, illegible

1/ - An unacceptable scratch is one that will catch a fingernail when run across it.

5. PREPARATION FOR DELIVERY

5.1 Packaging, packing, and marking. The packaging, packing, and marking shall be as specified in the contract or order.

6. NOTES

6.1 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents (if applicable).

a. Title, number, and date of this commercial item description.
b. Type required.
c. The packaging, packing, and marking required.

6.2 National Stock Numbers (NSN's). The following is a list of NSN's assigned which correspond to this cid. The list may not be indicative of all possible NSN's associated with the cid.

7330-00-680-2766 - Type I 7330-00-153-9760 - Type II

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:08Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

Military Coordinating Activity:

Army - GL

Custodians:

Army - GL
Navy - SA
Air Force - 99

Review Activities:

Army - MD, TS
Air Force - 84, 50

User Activity:

Navy - MC

Civil Agency Coordinating Activity:

VA - OSS

Preparing Activity:

GSA - FSS

(DoD Project Number 7330-0657)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:08Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:08Z
Check the source to verify that this is the current version before use.