INCH-POUND

A-A-55201

14 April 1993

COMMERCIAL ITEM DESCRIPTION

TROUSERS, DISPOSABLE

The General Services Administration has authorized the use of this Commercial Item Description in preference to MIL-T-87020.

Abstract. This Commercial Item Description covers the requirements for a disposable trouser of nonwoven, coated, spunbonded olefin fabric, intended primarily for use as part of a protective ensemble used to protect torpedo handlers from exposure to otto fuels.

Classification. The disposable trousers shall be of one type.

Description. The disposable trousers of a nonwoven coated, spunbonded olefin fabric shall be straight leg with an elasticized rubber tape waistband and with no fly opening. The color shall be white. The seams shall be formed by super-imposing two plies of material, folding both the edges back over the body of material and overedging. The minimum and maximum number of stitches per inch shall be 6 and 8 respectively, including the elastic tape waistband fully extended. The stitch gauge and stitch length shall produce adequately durable seams throughout the garment.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Defense Personnel Support Center, Clothing and Textiles Directorate, Attn: DPSC-FSSC, 2800 South 20th Street, Philadelphia, PA 19101-8419, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC 8415

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:44Z
Check the source to verify that this is the current version before use.

Material.
The basic material shall be white polyethylene coated spunbonded (nonwoven), nonperforated olefin fabric conforming to type II, class B of MIL-C-87019. The coated side of the fabric shall be the face side.

Thread. The sewing thread shall be commercial type, suitable for the purpose intended. The color of the thread shall be white. Skipped stitches and thread breaks shall be repaired by stitching not less than 1/2 inch beyond each end of the defect.

Waistband, elastic. The elastic waistband shall be a minimum of 3/8 inch wide and shall be either a cut rubber tape, or a woven, braided, or knitted elastic webbing. The color shall be white.

Sizes. The trousers shall be provided in the following sizes.

extra-small, small, medium, large, extra-Large, and extra-extra-large

NOTE: The sizes extra small, small, medium, large, extra-large and extra-extra-large may be abbreviated as XSM, MED, LG, XLG and XXLG.

Label/marking. Each pair of trousers shall have a combination identification, size and cautionary statement label marked or adhered to the inside back of the trousers, approximately 1 1/2 inches below the top edge and adjacent to the center back seam, bearing the inscription specified below. The label can be directly marked on the material by direct printing, marking, stamping or stencilling or the inscription can be printed on a heat sealable, adhesive coated cloth label of cotton, polyester or polyester/cotton blend.

TROUSERS, DISPOSABLE
CONTRACT NO:
STOCK NO:
SIZE:
NAME OF CONTRACTOR:

CAUTION
THIS GARMENT SHALL NOT BE REUSED AND
MUST BE DISCARDED WHEN OTTO FUEL
STAINS ARE OBSERVED

The cautionary statement shall be printed in larger letters than all other lettering on the label.

Patterns. The government shall furnish a single size pattern. The contractor is responsible for grading patterns for additional sizes. The pattern generally provides for a seam allowance of 3/8 to 1/2 inch for joining seams. The government patterns shall be used to make the contractor's working patterns. Commercial patterns may be used in

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:44Z
Check the source to verify that this is the current version before use.

lieu of the government furnished pattern provided they conform to the cited design and finished measurements.

Sizes and Measurements. The finished trousers shall conform to the measurements below. All measurements and tolerances are expressed in inches.

	A	B
Sizes	Waist	Inseam
XSM	21	32
SM	22	32
MED	24	33 1/2
LG	26	33 1/2
XLG	28	35
XXLG	29	35
Tolerance	± 1	± 1/2

Measurement (A) shall be taken from side seam to side seam at waist, with the elastic tape waistband fully extended.

Measurement (B) shall be taken from crotch to bottom open edge of leg.

Workmanship. The finished trousers shall conform to the quality of product established by this document. The occurrence of defects shall not exceed the applicable acceptable quality levels.

Product Demonstration Model. When required, offerers shall submit samples of their intended production. The Product Demonstration Model will consist of units independently developed. Product Demonstration Models will be analyzed and evaluated by the government. Evaluation criteria and basis for award are contained in the solicitation. Product Demonstration Models will be retained by the government. One (1) Product Demonstration Model approved by DPSC under the resultant contract will serve as a manufacturing standard for the corresponding production items delivered under this contract.
Offerers are advised that the Product Demonstration Model does not relieve the successful offerer of his responsibility to perform in accordance with the Commercial Item Description specified above.

Quality Assurance

Certification. The contractor shall certify that the product offered meets the salient characteristics and material requirements of this description and that the product conforms to the producer's own drawings, specifications, standards and quality assurance practices. The government reserves the right to require proof of such conformance prior to the first delivery and thereafter as may be otherwise provided for, under the provisions of the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:44Z
Check the source to verify that this is the current version before use.

Examination. Trousers lots shall be inspected in accordance with "Sampling Procedures and Tables for Inspection by Attributes", ANSI/ASQC Z1.4, published by the American Society for Quality Control.

Visual Examination. The trousers shall be examined for the defects listed below. The lot size shall be expressed in units of trousers. The sample unit is one trouser. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5.

Defects

The trousers shall be examined for the following defects:

Assembly: color not as specified; any spot or stain (outside); Waistband not color, width, or material specified; coated side of cloth on inside of garment; any component part misplaced or not securely affixed, e.g. elastic tape waistband loosely attached to trousers.

Cloth: any hole, cut, tear, mend or burn; Any imbedded foreign matter; Any evidence of delamination of the coating; overall cleanness, objectionable odor.

Label: Missing, incorrect, illegible or misplaced, cautionary statement lettering not larger than all other lettering, not size specified.

Seams and Stitching: open seams, pleated or puckered stitching seriously effecting serviceability,; stitching excessively loose or tight, ends of continuous line of stitching overlapped less than 1/2 inch; thread breaks not repaired or stitched less than 1/2 inch beyond each end of break. Stitches per inch more or less than specified.

Measurements: Any measurement deviating from nominal dimensions and tolerances specified. Leg inseam lengths uneven by 1 inch or more.

Dimensional Examination. The finished trousers shall conform to the dimensions specified. Any dimension that is not within the established tolerance shall be classified as a defect. The sample unit shall be one trouser; the inspection level shall be S-3 and the AQL shall be 4.0.

Packaging Examination. The fully packaged shipping containers shall be examined in accordance with defects listed below. The lot size shall be the number of shipping containers in the inspection lot. The inspection level shall be S-1 and AQL shall be 6.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:44Z
Check the source to verify that this is the current version before use.

EXAMINE	DEFECT
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, or method of application
Materials	Any component missing, damaged, or not as specified
Workmanship	Inadequate application of components, such as: incomplete closure of container flaps, loose strapping, improper taping, or inadequate stapling
Content	Number of items in container is more or less than required
	NSN shown on one or more items not as specified on shipping container
Palletization	Length, width, or height exceeds specified maximum requirements
	Pallet type not as specified
	Load not bonded as specified

Regulatory Requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

Regulatory Requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

Preservation, Packing, and Marking. The preservation, packing, and marking shall be as specified in the contract or order.

Source of Government Documents. Copies of Military and Federal documents are available from:

Standardization Documents Order Desk
Bldg. 4D
700 Robbins Avenue
Philadelphia, PA 19111-5094

Sources of Nongovernment Documents.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:44Z
Check the source to verify that this is the current version before use.

ANSI/ASQC Z1.4 - Sampling Procedures and Tables For Inspection By Attributes

(Applications for copies should be addressed to American National Standards Institute, 1430 Broadway, New York, NY 10018-3308.)

ASTM-D 3951 - Standard Practice for Commercial Packaging

(Applications for copies should be addressed to American Society For Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

Custodian:
Navy - NU

Civil Agency Coordinating Activity:
GSA - FSS

Review Activity:

Navy -OS

Preparing Activity:
DLA - CT

User Activity:
Navy - SH

Project No. 8415-0885

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:44Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER A-A-55201	2. DOCUMENT DATE (YYMMDD) 14 April 1993

3. DOCUMENT TITLE
trousers, Disposable

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME Defense Personnel Support Center ATTN: DPSC-FSSD (12-3-D) - DLA-CT	b. TELEPHONE (Include Area Code) (1) Commercial: 215-737-8105 (2) AUTOVON - DSN: 444-8105
c. ADDRESS (Include Zip Code) 2800 South 20th Street P. O. Box 8419 Philadelphia, Pennsylvania 19101-8419	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil/online/start/ 20240610-26T09:44Z
Check the source to verify that this is the current version before use.