INCH-POUND

A-A-55215

20 June 1993

COMMERCIAL ITEM DESCRIPTION

PILLOW, PASSENGER, HEADREST, AIRLINE TYPE

The General Services Administration has authorized the use of this Commercial Item Description in preference to MIL-P-83777.

Abstract. This document covers the requirements for fiber-filled airline-type head rest pillows. These pillows are intended for use in aircraft as a comfort accessory.

SALIENT CHARACTERISTICS

General Description. The airline-type head rest pillow shall be rectangular in shape without risers or boxes and shall conform to the finished dimensions and weight listed in Table I. The polyester fiberfill shall be garnetted and inserted with a compression chute. The case of the pillow shall consist of one piece of material which shall be assembled with a single needle lockstitch and turned in the plain edge method. The stitching shall have not less than 10 or more than 15 stitches per inch, with a minimum seam allowance of 1/4 inch

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Defense Personnel Support Center, Clothing and Textiles Directorate, Attn: DPSC-FSSC, 2800 South 20th Street, Philadelphia, PA 19101-8419, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC 7210

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:44Z
Check the source to verify that this is the current version before use.

The closing seam shall be along one end of the width dimension of the pillow, with a minimum turn-under of 1/4 inch and stitching no less than 1/8 inch from the edge. All ends of stitching shall be securely backstitched a minimum of 1/2 inch when not caught in another seam or row of stitching. The pillow shall be machine washable.

Sheeting. The sheeting for the pillow case shall be bleached, preshrunk cotton muslin conforming to Type III of A-A-50155.

Fiber Filling. The filling shall be new, washable, synthetic fibers consisting of 6 denier, hollow core polyester fiber, treated with silicone to repel water. Colored, stained and oily fibers will not be acceptable.

Thread. The thread used for sewing shall be polyester covered polyester core, Ticket No. 40, conforming to Type II of A-A-50199.

Label/marking. The label shall be in accordance with commercial practice and shall conform to the legal requirements of the state in which the pillows are manufactured. The label shall contain fiber content, cleaning instructions, contractor's name; and shall be integrally sewn into the end seam of the pillow, equidistant from the sides of the pillow The printing or marking on the label shall show Grade 4 colorfastness to laundering when tested as specified in AATCC Test Method 61, Test 3A (3 complete cycles, specimens must be dried after each cycle; use 10 steel balls and multifiber test fabric).

Size and Weight The pillow shall have the finished dimensions and weight listed in Table I.

TABLE I - PILLOW SIZE AND WEIGHT

Dimension	Finished Measurement	Tolerance
Overall Width (Inches)	11	-0 +1/2 1/
Overall Length (Inches)	15	-0 +1 1/
Thickness (Inches)	2-3/4 Min.	-0 2/
Total Weight (Ounces)	5.75 Min. 6.25 Max.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:44Z
Check the source to verify that this is the current version before use.

1/ Length and width of filled and closed pillow shall be measured from seam to opposing seam.
2/ The pillow shall be laid on a clean, flat surface and a square, flat piece of methyl methacrylate plastic, 18 X 18 X 1/4 inches (weighing 3-1/2 lbs. ± 1/4 lbs.) shall be gently placed on the pillow in a manner that the approximate center of the piece of plastic is over the approximate center of the pillow The pillow shall not be either fluffed or compressed prior to the foregoing procedure. The thickness shall be taken as the average of the measurements of free height under each of the four corners of the square piece of plastic. The measurements shall be made to the nearest 1/16 inch and taken within one minute after placement of the plastic square on the pillow.

Workmanship. The finished pillow shall conform to the quality of product established by this document The occurrence of defects shall not exceed the applicable acceptable quality levels.

Regulatory Requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

Product Demonstration Model When required, offerers shall submit samples of their intended production. The Product Demonstration Model shall consist of units independently developed. Product Demonstration Models shall be analyzed and evaluated by the government Evaluation criteria and basis for award are contained in the solicitation Product Demonstration Models shall be retained by the government. One (1) Product Demonstration Model approved by DPSC under the resultant contract shall serve as a manufacturing standard for the corresponding production items delivered under this contract Offerers are advised that the Product Demonstration Model does not relieve the successful offerer of his responsibility to perform in accordance with the Commercial Item Description specified above.

QUALITY ASSURANCE

Certification The contractor shall certify that the product offered meets the salient characteristics of this description and that the product conforms to the producer's own drawings, specifications, standards and quality assurance practices. The government reserves the right to require proof of such conformance prior to the first delivery and thereafter as may be otherwise provided for, under the provisions of the contract. Reliance on contractor QA systems shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the government for acceptance comply with all requirements of the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:44Z
Check the source to verify that this is the current version before use.

Examination. Pillow lots shall be inspected in accordance with "Sampling Procedures and Tables for Inspection by Attributes", ANSI/ASQC Z1.4, published by the American Society for Quality Control.

Visual Examination. The pillows shall be examined for the defects listed below. The lot size shall be expressed in units of pillows. The sample unit is one pillow. The inspection level shall be I and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 1.5.

Defects. The pillows shall be examined for the defects in Table II.

TABLE II - END ITEM VISUAL DEFECTS

Examination	Defect
Material and Workmanship	Any hole, cut or tear, slubs, or broken threads Needle chews, folds, mends, seam puckering or twisting, open seams Stitching or seam allowances not as specified Objectionable lumps, fiberfill protruding through seams or sheeting Evidence of risers or boxes
Cleanness	Spot, stain, thread ends not trimmed, rancid odor
Label	Omitted, incorrect, illegible or misplaced

Dimensional Examination. The finished pillows shall conform to the dimensions specified Any dimension that is not within the established tolerance shall be classified as a defect The sample unit shall be one pillow; the inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Packaging Examination. The fully packaged shipping containers shall be examined in accordance with defects listed below. The lot size shall be the number of shipping containers in the inspection lot. The inspection level shall be S-2 and AQL, expressed in terms of defects per hundred units, shall be 2.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:44Z
Check the source to verify that this is the current version before use.

EXAMINATION	DEFECT
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, or method of application.
Materials	Any component missing, damaged, or not as specified.
Workmanship	Inadequate application of components such as: incomplete closure of container flaps, loose strapping, improper taping, or inadequate stapling.
Content	Number of items per container is more or less than required.
	NSN shown on one or more items not as specified on shipping container.
Palletization	Length, width, or height exceeds specified maximum requirements.
	Pallet type not as specified.
	Load not bonded as specified.

End Item Performance Testing. The finished pillow shall conform to the following requirements when tested as specified in AATCC Test Method 135 Washing method I III, Drying method A III:

Fiberfill lumping shall be at a minimum; there shall not be sections of very thick lumps of fiber and sections of no fiber.

No fiberfill shall protrude through the pillow ticking.

The sheeting fabric shall show a minimum of No. 4 rating when evaluated for pilling according to ASTM Test Method 3511.

The seams shall show a minimum of SS-3 rating when evaluated for puckering according to AATCC Test Method 88B.

Preservation, Packing, and Marking. The preservation, packing, and marking shall be as specified in the contract or order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:44Z
Check the source to verify that this is the current version before use.

Source of Government Documents. Copies of Military and Federal documents are available from:

Standardization Documents Order Desk
Bldg. 4D
700 Robbins Avenue
Philadelphia, PA 19111-5094

Sources of Nongovernment Documents.

ANSI/ASQC Z1.4 - Sampling Procedures and Tables For Inspection By Attributes

(Applications for copies should be addressed to American National Standards Institute, 11 West 42nd Street, New York, NY 10036-8002.)

ASTM-D 3511 - Standard Test Method for Pilling Resistance and Other Related Surface Changes of Textile Fabrics Brush Pilling Tester Method

(Applications for copies should be addressed to American Society For Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

AATCC Method 61 - Colorfastness to Laundering, Home and Commercial: Accelerated

AATCC Method 135 - Dimensional Changes in Automatic Home Laundering of Woven or Knit Fabrics

AATCC Method 88B - Appearance of Seams in Durable Press Items After Repeated Home Laundering

(Applications for copies should be addressed to American Association of Textile Chemists and Colorists, P.O. Box 12215, Research Triangle Park, N.C 27709-2215.)

Custodian:
Air Force - 99

Review Activity:
Air Force - 82

User Activity:
Air Force - 45

Civil Agency Coordinating Activity:
GSA - FSS

Preparing Activity:
DLA - CT

Project No.
7210-0316

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:44Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1 The preparing activity must complete blocks 1, 2, 3, and 8 In block 1, both the document number and revisio letter should be given

2 The submitter of this form must complete blocks 4, 5, 6, and 7

3 The preparing activity must provide a reply within 30 days from receipt of the form

NOTE This form may not be used to request copies of documents, nor to request waivers, or clarification o requirements on current contracts Comments submitted on this form do not constitute or imply authorization t waive any portion of the referenced document(s) or to amend contractual requirements

I RECOMMEND A CHANGE:	1 DOCUMENT NUMBER A-A-55215	2 DOCUMENT DATE (YYMMDD) 93/6/20

3 DOCUMENT TITLE
Pillow, Passenger, Headrest, Airline Type

4 NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible Attach extra sheets as needed.)

5 REASON FOR RECOMMENDATION

6 SUBMITTER

a NAME	b ORGANIZATION
c ADDRESS (Include Zip Code)	d TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)
	7 DATE SUBMITTED (YYMMDD)

8 PREPARING ACTIVITY

a NAME Defense Personnel Support Center ATTN: DPSC-FSSD (12-3-D)	b TELEPHONE (Include Area Code) (1) Commercial: 215-737-8105 (2) AUTOVON: 444-8105
c ADDRESS (Include Zip Code) 2800 South 20Th Street P.O. Box 8419 Philadelphia, PA 19101-8419	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403 Falls Church VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil - Downloaded: 2026-10-26T09:44Z
Check the source to verify that this is the current version before use.