INCH-POUND

MIL-D-83531
AMENDMENT 2
24 Oct 1990
SUPERSEDING
AMENDMENT 1
10 March 1989

MILITARY SPECIFICATION

DELAY LINES, PASSIVE,

GENERAL SPECIFICATION FOR

This amendment forms a part of MIL-D-83531, dated 31 March 1987, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

3.3.1b, delete and substitute the following:

"3.3.1b The manufacturer is required to document training."

3.4.7, delete and substitute the following:

"3.4.7 Passive circuit elements. Capacitors shall be qualified or screened to MIL-C-123 or MIL-C-55681. Resistors shall be qualified or screened to MIL-R-55342. The inductor shall be so designed as to allow the delay line to meet the requirements specified herein."

PAGE 4

*3.8.4, last line: Delete "±10 percent" and substitute "±15 percent".

PAGE 10

4.3.1.5c, delete and substitute the following:

"4.3.1.5c Calculate delay line output pulse distortions $(S_o)_b$, $(S_o)_c$, $(S_o)_d$ using worst case conditions (see RS-242).

$$(S_o)_b\% = \frac{|b|}{E} \times 100 \qquad (S_o)_c\% = \frac{|c|}{E} \times 100 \qquad (S_o)_d\% = \frac{|d|}{E} \times 100$$ "

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:42Z
Check the source to verify that this is the current version before use.

Table II, subgroup I: Delete "Delay time variation with temperature (output only)" and associated information, in its entirety

Subgroup II, following "DC resistance" add:

Inspection	Requirement paragraph	Test method paragraph	AQL (percent defective)	
			Major	Minor
"Delay time variation with temperature (output only)	3.8.5	4.6.6.1.5	100%	100% "

4.6.5, delete and substitute the following:

"4.6.5 Seal. Delay lines shall be immersed for 2 to 3 minutes in a bath of water, or any other suitable liquid of no greater density and surface tension, maintained at a temperature of at least 85 degrees Celsius. The temperature of the delay line shall not exceed 40 degrees Celsius at the time of immersion."

4.6.9: Delete "MIL-STD-202." and substitute "MIL-STD-202, except step 7b, which is not applicable."

The margins of this amendment are marked with asterisks to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:42Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Air Force - 11, 19, 99
DLA - ES

User activities:
Navy - AS, CG, MC, SH

Preparing activity:
Air Force - 85

Agent:
DLA - ES

(Project 5999-0285)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:42Z
Check the source to verify that this is the current version before use.