INCH-POUND

MIL-D-83532A
AMENDMENT 1
5 Feb 1993

MILITARY SPECIFICATION

DELAY LINES, ACTIVE

GENERAL SPECIFICATION FOR

This amendment forms a part of MIL-D-83532A, dated 30 December 1991, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

Add the following new paragraph:

"3.3.4.1 ESD identifier/index mark. Delay lines supplied to this specification are considered to be ESD class 1 devices susceptible to ESD voltages of 0 to 1,999 volts. Delay lines shall be marked on top, over pin 1, with a single equilateral triangle (Δ) ESD identifier (see 3.20.2c)."

PAGE 4

Add the following new paragraph:

"3.4.6.2 Meniscus. Leads shall be free of case meniscus and other foreign material and shall be solderable for a minimum of .010 inch (0.25 mm) above the seating plane of the delay line."

PAGE 6

3.20.2, delete and substitute the following:

"3.20.2 Part marking. Delay lines shall be marked on the top in accordance with method I of MIL-STD-1285 (except item c) with the following, as a minimum:

a. JAN marking (see 3.20.1).

b. PIN (see 1.2.1).

c. ESD identifier/index mark. The mark shall be in accordance with 3.3.4.1 herein. The MIL-STD-1285 ESD mark shall not be used.

d. Manufacturer's source code or logo.

e. Date of manufacture code."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:42Z
Check the source to verify that this is the current version before use.

TABLE III, delete and substitute the following:

TABLE III. Group B inspection.

"

Inspection	Requirement paragraph	Method paragraph
Subgroup I (4 units)		
Resistance to solvents	3.7	4.6.5
Solderability	3.6	4.6.4
Salt spray (metal cases only)	3.12	4.6.10
Shock	3.14	4.6.12
Electrical characteristics	3.11	4.6.9
Subgroup II (4 units)		
Life	3.18	4.6.16
Terminal strength	3.9	4.6.7
Electrical characteristics	3.11	4.6.9

"

4.5.2.1.1, delete and substitute the following:

"4.5.2.1.1 Sampling plan. Every 12 months, eight sample units of any total delay value of each specification sheet produced during the 3-month period prior to the annual inspection shall be subjected to the group B inspection. If, during a 12-month period, qualification testing has been successfully completed on delay lines covered by extent of qualification (see 4.4.4), the group B inspection for that 12-month period may be omitted."

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Air Force - 19, 99
DLA - ES

User activities:
Navy - AS, CG, MC, SH

Preparing activity:
Air Force - 85

Agent:
DLA - ES

(Project 5999-0304)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:42Z
Check the source to verify that this is the current version before use.