MILITARY SPECIFICATION

ALTIMETER, PRESSURE AAU-2A

This amendment forms a part of MIL-A-27391B(USAF), dated 1 Aug 1979, and is approved for use within the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Delete "2.1" and add: "2.1 Government documents."

Add:
"2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation."

Under Specifications, Federal, delete "QQ-P-416".

Under Specifications, Military, delete "MIL-E-5272" and add: "MIL-C-83488 Coating, Aluminum Ion Vapor Deposited".

Change address in beneficial comments block to "Oklahoma City Air Logistics Center/MMEDO, Tinker AFB OK 73145-5990."

PAGE 2

Under Standard, Military, delete "MIL-STD-831" and add: "MIL-STD-810" Environmental Test Methods and Engineering Guidelines".

Add:
"2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation."

ASTM D3951 Packaging, Commercial

(Application for copies should be addressed to: ASTM, 1916 Race St, Philadelphia, PA 19103.)

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)"

PAGE 3

Add:
"3.3.7 Recovered materials. Recovered materials shall be used to the maximum extent possible without jeopardizing the end use of the item."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:39Z
Check the source to verify that this is the latest version.

PAGE 11

Delete "3.16.4" and add:
"3.16.4 Steel parts. Steel parts shall be coated with ion vapor depositied aluminum, where practicable, in accordance with MIL-C-83488, type I or II as applicable and of a class that is adequate to achieve the degree of protection required. Other protective coating, in lieu of MIL-C-83488, may be used if demonstrated to be satisfactory and approved by the preparing activity. Cadmium plating must be avoided when satisfactory alternative processes can be used."

PAGE 12

Add:
"4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material."

PAGE 13

Delete "4.4.2" "a" and "b".

PAGE 19

4.6.11 Line 2 delete "procedure II of MIL-E-5272" and add: "method 502.1, procedure I of MIL-STD-810."

PAGE 20

4.6.12 Line 2 delete "procedure II, high temperature test, of MIL-E-5272" and add: "method 501.1, procedure I of MIL-STD-810."

4.6.13 Line 2 delete "procedure I of MIL-E-5272" and add: "method 507.1, procedure I of MIL-STD-810."

4.6.14 Line 2, delete "procedure I of MIL-E-5272" and add: "method 509.1, procedure I of MIL-STD-810."

4.6.16 Line 2, delete procedure V of MIL-E-5272" and add: "method 514.2 procedure IA of MIL-STD-810."

4.6.17 Line 2, delete "procedure I of MIL-E-5272" and add: "method 508.1, procedure I of MIL-STD-810."

4.6.18 Line 2, delete "procedure II of MIL-E-5272" and add: "method 506.1, procedure II of MIL-STD-810."

PAGE 21

4.6.19 Line 2, delete "procedure I of MIL-E-5272" and add: "method 510.1,

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:39Z
Check the source to verify that this is the current version before use.

procedure I of MIL-STD-810."

4.6.20 Delete and add: "4.6.20 Acceleration. The altimeter shall be subjected to an acceleration test in accordance with method 513.2, procedure I of MIL-STD-810."

4.6.21 Line 10, delete "procedure I of MIL-E-5272" and add: "method 503.1, procedure I of MIL-STD-810."

PAGE 23

Delete Section 5 in its entirety and add:

"5. PACKAGING.

5.1. Preservation-packaging. Preservation-packaging shall be level A, C, or Industrial, as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Cleaning. Altimeter shall be cleaned in accordance with process C-1 or MIL-P-116.

5.1.1.2 Drying. Altimeter shall be dried in accordance with process D-4 of MIL-P-116.

5.1.1.3 Preservation application. Not applicable.

5.1.1.4 Unit packaging. Unless otherwise specified by the contracting activity, each altimeter shall be packaged in quantity unit packs of one each in accordance with Method IA8 of MIL-P-116. Overbox completed pack in PPP-B-636 container. Apply sufficient cushioning material between bag and unit container of a type, density, and thickness to insure shock transmission does not exceed peak values in G's established for the altimeter when completed packs are subjected to the rough handling drop tests of MIL-P-116.

5.1.2 Level C. Each altimeter shall be clean, dry, and individually packaged in a manner that will afford adequate protection against corrosion, deterioration, and physical damage during shipment from supply source to the first receiving activity.

5.1.3 Industrial. The Industrial preservation of altimeter shall be in accordance with ASTM D3951.

5.2 Packing. Packing shall be level A, B, C, or Industrial as specified (see 6.2).

5.2.1 Level A. Altimeter packaged as specified in 5.1.1. shall be packed in shipping containers conforming to PPP-B-601, Styles A or B, Class overseas, unless otherwise specified by the contracting activity. Insofar as practical, exterior shipping container shall be of uniform shape, size, minimum tare and cube consistant with the protection required.

5.2.2 Level B. Altimeter packaged as specified in 5.1.1 shall be packed in shipping containers conforming to PPP-B-636, class weather-resistant, unless otherwise specified by the contracting activity. Other requirements as specified in 5.2.1 apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:39Z
Check the source to verify that this is the current version before use.

5.2.3 Level C. Packing shall be applied which affords adequate protection during domestic shipment from the supply source to the first receiving activity for immediate use. This level shall conform to applicable carrier rules and regulations.

5.2.4 Industrial. The packaged altimeter shall be packed in accordance with ASTM D3951.

5.3 Marking. In addition to any other markings required by the contract or order (see 6.2), interior and exterior containers shall be marked in accordance with MIL-STD-129."

Delete "6.7".

Delete "6.8".

Custodian:
Air Force - 99

Preparing Activity:
Air Force - 71

Project Number:
6610 - F132

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:39Z
Check the source to verify that this is the current version before use.