MIL-M-27386D
28 September 1979
SUPERSEDING
MIL-M-27386C
31 May 1974

MILITARY SPECIFICATION

MANIFOLD ASSEMBLIES, HOSE-LINE: FUELING: 4-INCH, QUICK-COUPLING TYPE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers two types of 4-inch, quick-disconnect-coupling type, hose-line manifold assemblies.

1.2 Classification. The manifold assemblies shall be of the following types, as specified (see 6.2):

Type I - with two tee fittings (Drawing C13200E0068).
Type II - with one tee fitting (Drawing C13200E0803).

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

FSC 4730

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Mobility Equipment Research and Development Command, ATTN: DRDME-DS, Fort Belvoir, VA 22060 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:39Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

QQ-S-781	- Strapping, Steel, and Seals.
PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-621	- Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636	- Boxes, Shipping, Fiberboard.

MILITARY

MIL-P-116	- Preservation-Packaging, Methods of.
MIL-T-704	- Treatment and Painting of Materiel.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-130	- Identification Marking of US Military Property.
MIL-STD-1188	- Commercial Packaging of Supplies and Equipment.

DRAWINGS

ME

MA132O2E2860	- Manifold Line Assembly.
B132O2E2860	- Manifold Line Assembly.
PL132O2E2860	- Parts List for Manifold Line Assembly.
C132OOE0068	- Manifold Assembly, Type I.
PL132OOE0068	- Parts List for Manifold Assembly, Type I.
C132OOE0003	- Manifold Assembly, Type II.
PL132OOE0003	- Parts List for Manifold Assembly, Type II.

(Copies of specifications, standards and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:39Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Description. The manifold assemblies are as shown on drawing B13202E2860 along with top assembly drawing TA13202E2860 and parts list drawing PL13202E2860 and shall be in accordance with drawings C13200E0066 and PL13200E0066 for a Type I manifold assembly or drawings C13200E0803 and PL13200E0803 for a Type II manifold assembly, and as specified herein.

3.1.1 Drawings. The drawings forming a part of this specification are end product drawings. No deviation from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Where tolerances could cumulatively result in incorrect fits, the contractor shall provide tolerances within those prescribed on the drawings to insure correct fit, assembly, and operation of the manifold assemblies. Any data (e.g., shop drawings, layouts, flow sheets, processing procedures, etc.) prepared by the contractor or obtained from a vendor to support fabrication and manufacture of the preproduction item shall be made available, upon request, for inspection by the contracting officer or his designated representative.

3.2 Material. Material shall be as specified herein and as shown on the applicable drawings. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification (see 6.5).

3.3 Working pressure and hydrostatic pressure. The manifold assemblies shall have a working pressure of 125 pounds per square inch (psi) and shall withstand a hydrostatic pressure of 300 psi without leakage or permanent deformation.

3.4 Identification marking. The manifold assemblies shall be identified in accordance with MIL-STD-130.

3.5 Treatment and painting. Treatment and painting shall be in accordance with MIL-T-704, Type A, Color, Forest Green.

3.6 Government-loaned property. Unless otherwise specified (see 6.2), the following property in the quantities indicated will be loaned by the Government (see 6.3):

Item No.	Description	Identification	Quantity
1.	Plug, Quick Disconnect	NSN 4730-00-640-6168	4
2.	Cap, Quick Disconnect	NSN 4730-00-640-6156	3

Source: https://assist.dla.mil -- Downloaded: 20260-20T11:39Z
Check the source to verify that this is the currentversion before use.

3.7 Workmanship. All parts and components of the manifold assemblies, including castings, forgings, molded parts, stampings, bearings, seals, machined surfaces, and welded parts, shall be clean and free from sand, dirt, fins, pits, sprues, scale, flux, and other harmful extraneous material. All edges shall be rounded or chamfered.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. The contractor is responsible for insuring that components and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards, as applicable.

4.1.2 Disassembly inspection. The manifold assemblies failing a performance test shall be disassembled. Each disassembled part shall be inspected in detail for compliance with this specification and referenced drawings in regard to materials, dimensions, and tolerances. Parts not complying with such requirements shall be rejected. Reassembly with replacement parts and retesting shall be the responsibility of the contractor. Government-loaned property shall be excluded from the requirements of this paragraph.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) Quality conformance inspection (see 4.3).
(b) Inspection of packaging (see 4.5).

4.3 Quality conformance inspection.

4.3.1 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.3.2 Examination. Samples selected in accordance with 4.3.1 shall be examined as specified in 4.4.1. AQL shall be 1.5 percent defective.

Source: https://assist.dla.mil -- Downloaded: 202640-20T11:39Z
Check the source to verify that this is the currentversion before use.

4.3.3 Tests.

4.3.3.1 Individual. Each manifold assembly shall be tested as specified in 4.4.2. Failure of the test shall be cause for performing the inspection specified in 4.1.2.

4.4 Inspection procedure.

4.4.1 Examination. The manifold assemblies shall be examined as specified herein for the following defects:

101. Dimensions not as specified.
102. Components missing.
103. Seating surfaces not as specified.
104. Material not as specified.
105. Identification marking missing, incomplete, or not legible.
106. Treatment and painting not as specified.
107. Workmanship not as specified.

4.4.2 Tests.

4.4.2.1 Hydrostatic pressure. After being plugged and capped using the Government-loaned plug and cap (see 3.6), each manifold assembly shall be subjected to a hydrostatic pressure of 300 psi for a period of 10 seconds. The test fluid shall be water. Evidence of leakage, permanent deformation, or holes in the castings shall constitute failure of this test.

4.5 Inspection of packaging.

4.5.1 Quality conformance inspection of pack.

4.5.1.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.5.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.5.1.3 Examination. Samples selected in accordance with 4.5.1.2 shall be examined for the following defects. AQL shall be 2.5 percent defective.

Source: https://assist.dla.mil -- Downloaded: 202640-20T11:39Z
Check the source to verify that this is the currentversion before use.

108. Materials, methods, or containers not as specified. Each incorrect material, method, or container shall constitute one defect.
109. Fiberboard boxes not closed Method V, as specified.
110. Strapping not as specified.
111. Marking illegible, incomplete, incorrect, or missing.

5. PACKAGING

5.1 Preservation. Preservation shall be Level A or Commercial, as specified (see 6.2).

5.1.1 Level A. Each manifold assembly complete with technical publication, valves, tees, coupler and adapter shall be preserved in accordance with MIL-P-116, Method III in a close-fitting box conforming to PPP-B-636, Class Weather-Resistant, style optional. Closure of the box shall be Method V, in accordance with the appendix to the box specification.

5.1.2 Commercial. Each complete manifold assembly with technical publication shall be preserved in accordance with MIL-STD-1188.

5.2 Packing. Packing shall be Level A, Level B, or Commercial, as specified (see 6.2).

5.2.1 Level A. The manifold assemblies, preserved as specified in 5.1, shall be packed in close-fitting boxes conforming to PPP-B-601, Overseas Type, style optional, Grade B or PPP-B-621, Class 2. Strapping shall conform to QQ-S-781, Class 1, Type I or IV, size as applicable. Unless otherwise specified (see 6.2), strapping shall be Finish B. When specified (see 6.2), strapping shall be Finish A.

5.2.2 Level B. The manifold assemblies, preserved as specified in 5.1, shall be packed as specified in 5.2.1, except that boxes shall be Domestic Type and strapping shall be Finish A.

5.2.3 Commercial. The manifold assemblies, preserved as specified in 5.1, shall be packed in accordance with MIL-STD-1188.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:39Z
Check the source to verify that this is the current version before use.

5.3 Marking.

5.3.1 Military packaging. Marking shall be in accordance with MIL-STD-129.

5.3.2 Commercial packaging. Marking shall be in accordance with MIL-STD-1186.

6. NOTES

6.1 Intended use. The manifold assemblies are intended for use in attaching hose-line assemblies conforming to MIL-H-370, or connecting the manifold assembly to a collapsible tank fuel storage system.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Type of manifold assembly required (see 1.2).
(c) When Government-loaned property is not required (see 3.6).
(d) Degree of preservation and degree of packing required (see 5.1 and 5.2).
(e) When Finish A strapping is required (see 5.2.1).

6.3 Government-loaned property. The contracting officer should arrange to loan the equipment listed in 3.6.

6.4 Data requirements. The contracting officer should include requirements for such data as technical publications, instructional materials, illustrated parts lists, and contractor's maintenance and operation manual to be furnished with each manifold assembly.

6.5 Recycled material. It is encouraged that recycled material be used, when practical, as long as it meets the requirements of this specification (see 3.2).

Source: https://assist.dla.mil -- Downloaded: 20261O-20T11:39Z
Check the source to verify that this is the current version before use.

Custodians:
Army - ME
Air Force - 99

Review activity:
DLA - CS

User activities:
Army - CE
Navy - MC, YD

Preparing activity:
Army - ME

Project No. 4730-0947

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:39Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval No. 22-R086

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE: MIL-M-27386D Manifold Assemblies, Hose-Line: Fueling: 4-Inch, Quick-Coupling Type

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO (If "Yes", in what way?)

4. REMARKS

SUBMITTED BY (Printed or typed name and address - Optional)

TELEPHONE NO.

DATE

DD FORM 1426, JAN 72 REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:39Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
USA Mobility Equipment R&D Command
ATTN: DRDME-DS
Ft. Belvoir, VA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:39Z
Check the source to verify that this is the current version before use.