NOT MEASUREMENT SENSITIVE

MIL-DTL-3628/108
25 September 1996
SUPERSEDING
MIL-I-3575/48E
23 May 1995

DETAIL SPECIFICATION SHEET

BADGE, OCCUPATIONAL, DENTIST, AIR FORCE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3628 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

DASH NO.
-1: Dentist
-2: Senior Dentist
-3: Chief Dentist

MATERIAL: Red Brass or Nickel Silver

FINISH: Nickel Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 16.

DIMENSIONS:
HEIGHT (Overall):
-1: 11/16 inch (1.75 cm) (REF)
-2: 1 inch (2.54 cm) (REF)
-3: 1-1/16 inches (2.70 cm) (REF)
WIDTH (Overall): 5/8 inch (1.59 cm) (REF)
THICKNESS (At Thickest Point): 0.120 inch ± 0.005 inch (0.304 cm ± 0.012 cm)

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:36Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to measurements taken from the Government furnished hub or die.

2. Attaching device shall be prong and clutch type. Prongs shall be located on the vertical center line, equidistant from each end and the following distance apart:

-1: 7/16 inch ± 1/64 inch (1.11 cm ± 0.04 cm) apart.
-2, -3: 11/16 inch ± 1/64 inch (1.75 cm ± 0.04 cm) apart.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH
Air Force - 45

Preparing activity:
Army - IH

Review activities:
Air Force - 32, 82, 99
DLA - CT

(Project No. 8455-0862)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:36Z
Check the source to verify that this is the current version before use.