NOT MEASUREMENT SENSITIVE

MIL-DTL-3628/111
25 September 1996
SUPERSEDING
MIL-I-3575/51E
23 May 1995

DETAIL SPECIFICATION SHEET

# BADGE, OCCUPATIONAL, DEPARTMENT OF THE JUDGE ADVOCATE GENERAL, AIR FORCE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3628 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.




MATERIAL: Red Brass or Nickel Silver

FINISH: Nickel Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 16.

DIMENSIONS:
HEIGHT (Overall): 3/4 inch (1.91 cm) (REF)
WIDTH (Overall): 1-1/8 inch (2.86 cm) (REF)
THICKNESS (At Thickest Point): 0.075 inch ± 0.005 inch (0.190 cm ± 0.012 cm)

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.


Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:37Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to measurements taken from the Government furnished hub or die.

2. Piercing shall be as indicated.

3. Attaching device shall be prong and clutch type. Prongs shall be located on the vertical center line, equidistant from each end and 3/4 inch ± 1/64 inch (1.91 cm ± 0.04 cm) apart.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH
Air Force - 45

Preparing activity:
Army - IH

Review activities:
Air Force - 32, 82, 99
DLA - CT

(Project No. 8455-0862)


Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:37Z
Check the source to verify that this is the current version before use.