METRIC

DOD-C-63976 (AR)
AMENDMENT 4
30 MARCH 1989
SUPERSEDING
AMENDMENT 3
03 November 1986

MILITARY SPECIFICATION

CASE, CARTRIDGE, 30MM AMMUNITION
FOR M788, M789 AND M799
SERIES OF 30MM AMMUNITION

This Amendment forms a part of Military Specification DOD-C-63976 (AR), dated 14 May 1982 and is approved for use within the U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.1: Add "MIL-STD-1235 - Single and Multi-Level Continuous Sampling Procedures and Tables for Inspection by Attributes" to the end of the paragraph.

* Delete "FED-STD-115" and substitute "FED-STD-151".

2.1.2: Under "Drawings":
Delete "11825969 - Test Barrel, 30MM Mann (6.5)" and substitute "9390627 - Barrel, Test 30MM (A.D.E.N. Barrel)"

PAGE 3

3.2.1: Delete "Drawing 11825969" and substitute "Drawing 9390627"

PAGE 5

Note 1/: Delete "4.5.3.10.2" and substitute "4.5.3.10.1".

PAGE 8

3.2.3.1.3: Delete "MIL-STD-331, Method 107" and substitute "MIL-STD-810, Method 509".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:07Z
Check the source to verify that this is the current version before use.

PAGE 12

Table III: Delete Sample size "20" and substitute "Sample size "60" for case extraction".

PAGE 13

4.4.2a: Add at the end of the sentence "or MIL-STD-1235."

PAGE 14

4.4.2.1: Delete "3/" from Major 104 and add "3/" to Majors 101, 102, 103.

PAGE 15

4.4.2.1: Minor 222: Delete "3.3.3" and substitute "3.5".

PAGE 16

Note 3/: Delete "Min. sample size 315 no defects allowed" and substitute "Sample size determined by .25 AQL (315 min sample size) zero defects allowed."

PAGE 20

4.5.1.1: Delete "Drawing 11825959" and substitute "Drawing 9390627"

4.5.1.1.1: Delete "chamber pressure" and substitute "case mouth pressure" wherever applicable.

PAGE 21

4.5.2.3:

Delete "MIL-STD-331 test method 107" and substitute "MIL-STD-810 test method 509 (Slight Mouth Erosion Permissible)".

Delete "4.3.2" and substitute "4.5.2".

PAGE 22

4.5.3.4.1:

Third sentence: Delete "hole" and substitute "hold".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:07Z
Check the source to verify that this is the current version before use.

Delete last sentence of last paragraph and substitute "All mechanical properties test results shall be reported".

PAGE 23

4.5.3.4.2:

Third sentence: Delete "avioded" and substitute "avoided".

Delete last sentence and substitute "All hardness test results shall be reported".

PAGE 24

4.5.3.5: Delete last sentence and substitute "The thickness values obtained by both methods should be reported."

4.5.3.4.2: Delete last sentence and substitute "The coating weight data obtained will be reported".

PAGE 25

4.5.3.6: Delete "3.5.3" and substitute "3.5".

4.5.3.7.1: Delete in its entirety and substitute the following.

"4.5.3.7.1 External defects, case sidewall. Examination of the case sidewall for logitudinal cracks or seams shall be performed using the five diopter magnifier or a (NDT) device capable of detecting external cracks or seams. Prior to the examination the entire surface of each case will be examined for random gross defects. When using the optical method, adequate lighting must be available and higher magnification can be used to differentiate between a scratch or a crack. When it is still questionable whether or not a crack exists, then die penetrant testing per MIL-I-6866 can be employed. Any case found to have a crack in excess of 38.1mm long by .19mm deep shall be considered as a defect. The cross sectioning technique may be used to verify the depth of a crack identified visually.

When a (NDT) method is used, sufficient standards will be available to verify that cracks or seams in excess of .19mm deep by 6mm long can be reliably identified. Any cracks or seams in excess of .19mm deep by 6mm long shall be considered as defects. The area of inspection to be included in the NDT technique shall extend from 15.25mm to 85.00mm when measured from the head end of the case."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:07Z
Check the source to verify that this is the current version before use.

PAGE 26

4.5.3.7.2:

Delete: "Binocular microscope using a minimum of 7x magnification" and substitute "five diopter magnifier".

Delete "Refer to 6.7" from the end of paragraph 1 and add "Refer to 6.7" to the end of the second paragraph.

4.5.3.7.3, last sentence, second paragraph: Delete "For definition, refer to 6.3.7".

4.5.3.8: Delete last sentence and substitute "The individual values thus obtained shall be reported".

PAGE 27

4.5.3.10: Delete "6.3.8" and substitute "6.8".

PAGE 29

6.3: Add sentence to the end of paragraph as follows: "The letter of submittal shall state contractor, contract number, specification number, item nomenclature and classification of defects or test paragraph."

6.5: Delete in its entirety and substitute the following:

"6.5 Data report. All data obtained from testing as described in 4.4.3.4 and 4.4.3.6 shall be reported.

6.7: Delete first sentence and substitute "The contractor and supplier shall establish defect standards for use in the NDT test defined in 4.3.3.7.1, 4.3.3.7.2 and 4.3.3.7.3".

PAGE 30

6.10: Delete "4.3.4" and substitute "4.5.1 and 4.5.2".

6.11: Delete in its entirety.

The margins of this amendment are marked with an asterisk or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:07Z
Check the source to verify that this is the current version before use.

and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian
Army-AR

Preparing activity:
Army-AR

(Project 1305-AD09)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:07Z
Check the source to verify that this is the current version before use.