MIL-P-53065(ME)
AMENDMENT 3
30 June 1987
SUPERSEDING
AMENDMENT 2
16 March 1987

MILITARY SPECIFICATION

PUMPING UNIT, FRAME MOUNTED, 1-1/2 INCH

ELECTRIC MOTOR DRIVEN, 35 GPM AT

25 FEET TOTAL HEAD

This amendment forms a part of MIL-P-53065(ME), dated 8 October 1986, and is approved for use within the USA Belvoir Research, Development, and Engineering Center, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

2.2, under AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM), delete the following:

"B 26 - Aluminum Alloy Sand Castings, Spec for.
B 210 - Aluminum-Alloy Drawn Seamless Tubes.
B 221 - Aluminum and Aluminum-Alloy Extruded Bars, Rods, Wire, Shaped, and Tubes.
B 584 - Cooper Alloy Sand Castings for General Application, Spec for."

PAGE 5

3.4.1, add at the end of paragraph: "It shall also operate under adverse weather conditions such as rain, dust, high humidity, salt fog and solar radiation.

3.5, add at the end of paragraph: "The pump shall comply with applicable safety and health requirements and shall not present any uncontrolled hazards to user personnel throughout its life cycle."

3.6, add at the end of paragraph: "The pump shall be operable in reduced visibility without protection, with a minimum of illumination, by the 5th through 95th percentile soldier, and by two vehicle crewmen in MOPP IV protective ensemble."

AMSC N/A FSC 4320

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:57Z
Check the source to verify that this is the current version before use.

PAGE 6

3.8, line 2, delete "with minimum flow of 35 GPM at 25 feet of total head" and substitute: "capable of transferring from 25 to 50 GPM of diesel fuel viscosity range of 1.3 cs to 5.0 cs at 20 °C at 20 feet of head."

3.8.4.1, lines 1 and 2, delete first sentence and substitute: "The pump case and volute shall be a one piece casting of a nonsparking material compatible with diesel fuel."

3.8.4.2, line 2, delete "constructed from 356-T6 aluminum."

3.8.4.3, delete in its entirety and substitute:

"3.8.4.3 Impeller. The impeller shall be of a nonsparking material compatible with diesel fuel."

After 3.8.4.5, add:

* "3.8.4.6 Physical characteristics. A maximum size of 28 inches long, 18 inches wide and 18 inches high, with a maximum weight of 80 pounds is permissible."

"3.8.5 Nuclear biological chemical (NBC) contamination. The pump and assembly shall be NBC contamination survivable."

PAGE 7

3.10, line 1, delete "tubular aluminum".

Lines 2 and 3, delete second sentence in its entirety.

3.13, add at the end of paragraph: "The pump and hose fittings shall be standard cam-lock, 1-1/2 inches in diameter."

PAGE 9

* After 3.19.5, add:

"3.20 Government-loaned property. The following property in the quantity indicated will be loaned by the Government (see 6.7).

Item	Description	Quantity
1	Army MOPP IV protective mask and cold weather clothing	As required"

PAGE 10

4.3, line 2, delete "one complete unit" and substitute: "three complete units"

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:57Z
Check the source to verify that this is the current version before use.

PAGE 11

4.6, after "Tests", add: "The hydrostatic test (see 4.6.1) and the performance test (see 4.6.3) shall be conducted on three complete pump and fitting setups and the evaluation of each in accordance with the stated requirements."

* 4.6.3.4, line 6, after sentence ending "of any component.", add "Operator performing functional operational test shall be dressed in Army MOPP IV protective mask and cold weather clothing."

PAGE 12

4.6.3.6.1, line 2, delete "method 501.1, procedure I." and substitute "method 501.2, procedure I."

4.6.3.6.2, line 2, delete "method 502.1" and substitute: "method 502.2"

4.6.5, add at the end of paragraph: "Operation will be verified by personnel representing the 5th through 95th percentile soldier. This will address compatibility with NBC protective clothing and equipment and ease of use under conditions of reduced visibility."

After 4.6.7, add:

"4.6.8 Physical characteristics. The pumping unit's weight and dimensions shall be determined. Nonconformance to 3.8.4.6 shall constitute failure.

"4.6.9 NBC contamination. The pumping unit must be capable of withstanding five cycles of contamination/decontamination with degradation. It must be functional after these cycles."

PAGE 15

* After 6.6, add:

"6.7 Government-loaned property. The contracting officer should arrange to lend the property listed in 3.20."

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army - ME

Preparing activity:
Army - ME

Project 4320-A271

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:57Z
Check the source to verify that this is the current version before use.