NOT MEASUREMENT SENSITIVE


MIL-DTL-3628/159D
5 October 2020
SUPERSEDING
MIL-DTL-3628/159C
4 December 2015

DETAIL SPECIFICATION SHEET

BADGE, QUALIFICATION, AVIATION, AVIATOR, MASTER, U.S. ARMY

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3628.



DASH NO.
-1: Regular Size
-2: Miniature Size
-3: Dress Miniature Size
-4: Regular Size, Subdued

MATERIAL:
-1, -2, -3: Red Brass 85/15 (UNS Alloy No. C-230) or Nickel Silver 65/35 (UNS Alloy No.C-752)

-4: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH:
-1, -2, and -3: Nickel plated, Mirror-like Polished and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 16. Reverse shall be bright and clean.

-4: Dull, Flat Black Enamel Finish and shall match TIOH Metal Finish Chip Number 21.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:53Z
Check the source to verify that this is the current version before use.

DIMENSIONS:
HEIGHT (Overall):
-1, -4: 7/8 inch (REF)
-2: 23/32 inch (REF)
-3: 15/32 inch (REF)
WIDTH (Overall):
-1, -4: 2-1/2 inches (REF)
-2: 2 inches (REF)
-3: 1-1/4 inches (REF)
THICKNESS (At lowest edge):
-1, -4: 0.110 inch ± 0.005 inch
-2, -3: 0.095 inch ± 0.005 inch

ATTACHING DEVICE:
1. Attaching device shall be prong and wing type clutch.

2. The prongs shall be located on the horizontal center line, equidistant from each end and the following distance apart. For -1 and -4 1-3/4 inches ± 1/32 inch For-2 1-1/2 inches ± 1/32 inch. For -3 7/8 inch ± 1/32 inch

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Piercing shall be as indicated. The piercing shown is for -1, -2, and -4 only. The piercing for -2 is identical except the area between the star and the top of the shield is not pierced. There is no piercing for -3.

3. When specified in acquisition documents, an astronaut device may be embossed to the shield portion of the badge in accordance with MIL-DTL-3628/166 and The Institute of Heraldry drawing B-5-84.

4. -1, -2, and -3: Silver Plated Oxidized Buffed Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 14, May be used for commercial sale.

5. A mock forcer may be used to bring up the design of the shield for -1, -2 and -4 only.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2020-569)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:53Z
Check the source to verify that this is the current version before use.