NOT MEASUREMENT SENSITIVE

MIL-DTL-3628/163A
1 April 1999
SUPERSEDING
MIL-DTL-3628/163
15 November 1996

DETAIL SPECIFICATION SHEET

BADGE, QUALIFICATION, AVIATION, AIRCRAFT CREWMAN, ARMY

Inactive for new design after 13 January 1999.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3628 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

MATERIAL:

-1, -2, -3: Red Brass or Nickel Silver
-4: Red Brass

DASH NO.

-1: Regular Size
-2: Miniature Size
-3: Dress Miniature Size
-4: Regular Size, Subdued

FINISH:

-1, -2, -3: Nickel Plated (Red Brass only), Silver Plated, Oxidized, Relieved, Matte Finish with the Highlights of the Shield Mirror-like Polished and shall match TIOH Metal Finish Chip number 15.
-4: Dull, Flat Black Enamel.

DIMENSIONS:

HEIGHT (overall):
-1, -4: 3/4 inch (REF)
-2: 19/32 inch (REF)
3: 21/64 inch (REF)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:55Z
Check the source to verify that this is the current version before use.

WIDTH (overall):
-1, -4: 2-1/2 inches (REF)
-2: 2 inches (REF)
-3: 1-1/4 inch (REF)
THICKNESS (at thickest point of wings):
-1, -4: 0.110 inch ± 0.005 inch
-2, -3: 0.090 inch ± 0.005 inch

NOTES:

1. The term (REF) refers to measurements taken from the Government furnished hub or die.

2. Piercing shall be as indicated.

3. Attaching device shall be prong and clutch type. The prongs shall be located on the horizontal center line, equidistant from each end and the following distance apart.

Dash No. -1 and -4: 1-3/4 inches ± 1/32 inch
Dash No. -2: 1-1/2 inches ± 1/32 inch
Dash No. -3: 7/8 inch ± 1/32 inch

4. A mock forcer may be used to bring up the design of the shield for Dash No. -1, -2 and -4 only.

5. The dull flat black enamel for Dash No. -4 shall match FED-STD-595, Chip No. 37038.

6. When specified in acquisition documents, an astronaut device may be embossed to the shield portion of the badge in accordance with MIL-DTL-3628/166 and TIOH drawing B-5-84.

7. Dash No. -1, -2, and -3 may be nickel or rhodium plated with a mirror-like polished finish matching TIOH Metal Finish Chip number 16 for commercial sale only. The silver plating requirement shall not apply with this finish.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0973)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:55Z
Check the source to verify that this is the current version before use.