INCH-POUND

MIL-DTL-3628/164C
10 July 2007
SUPERSEDING
MIL-DTL-3628/164B
23 May 2000

DETAIL SPECIFICATION SHEET

BADGE, QUALIFICATION, AVIATION, SENIOR, ARMY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3628.



MATERIAL:

-1, -2, -3: Red Brass or Nickel Silver
-4: Red Brass

DASH NO.

-1: Regular Size
-2: Miniature Size
-3: Dress Miniature Size
-4: Regular Size, Subdued

FINISH:

-1, -2, -3: Nickel Plated (Red Brass only), Silver Plated, Oxidized, Buffed Relieved, Matte Finish and shall match the Institute of Heraldry (TIOH) Metal Finish Chip number 14.
-4: Dull, Flat Black Enamel.

DIMENSIONS:

HEIGHT (overall):
-1, -4: 27/32 inch (REF)
-2: 11/16 inch (REF)
-3: 13/32 inch (REF)
WIDTH (overall):
-1, -4: 2-1/2 inches (REF)
-2: 2 inches (REF)
-3: 1-1/4 inch (REF)

THICKNESS (at thickest point of wings):

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:55Z
Check the source to verify that this is the current version before use.

-1, -4: 0.110 inch ± 0.005 inch
-2, -3: 0.090 inch ± 0.005 inch

NOTES:

1. The term (REF) refers to measurements taken from the Government furnished hub or die.

2. Piercing shall be as indicated.

3. Attaching device shall be prong and clutch type. The prongs shall be located on the horizontal center line, equidistant from each end and the following distance apart.

Dash No. -1 and -4: 1-3/4 inches ± 1/32 inch
Dash No. -2: 1-1/2 inches ± 1/32 inch
Dash No. -3: 7/8 inch ± 1/32 inch

4. A mock forcer may be used to bring up the design of the shield for Dash No. -1, -2 and -4 only.

5. The dull flat black enamel for Dash No. -4 shall match FED-STD-595, Chip No. 37038.

6. When specified in acquisition documents, an astronaut device may be embossed to the shield portion of the badge in accordance with MIL-DTL-3628/166 and TIOH drawing B-5-84.

7. Dash No. -1, -2, and -3 may be nickel or rhodium plated with a mirror-like polished finish matching TIOH Metal Finish Chip number 16 for commercial sale only. The silver plating requirement shall not apply with this finish.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH
(Project No. 8455-2007-116)

Review activities:
DLA - CT

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:55Z
Check the source to verify that this is the current version before use.