NOT MEASUREMENT SENSITIVE


MIL-DTL-3628/164F(IH)
20 February 2026
SUPERSEDING
MIL-DTL-3628/164E(IH)
5 October 2020

DETAIL SPECIFICATION SHEET

BADGE, QUALIFICATION, AVIATION, SENIOR, ARMY

This specification is approved for use by all
Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3628.



DASH NO.
-1: Regular Size
-2: Miniature Size
-3: Dress Miniature Size
-4: Regular Size Subdued

MATERIAL:
-1, -2, -3: Red Brass 85/15 (UNS Alloy No. C-230) or Nickel Silver 65/35 (UNS Alloy No. C-752)

-4: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH:
-1, -2, and -3: Nickel plated, Mirror-like Polished and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 16. Reverse shall be bright and clean.

-4: Dull, Flat Black Enamel Finish and shall match TIOH Metal Finish Chip Number 21.

DIMENSIONS:
HEIGHT (Overall):
-1, -4: 27/32 inch (REF)
-2: 11/16 inch (REF)
-3: 13/32 inch (REF)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:55Z
Check the source to verify that this is the current version before use.

WIDTH (Overall):
-1, -4: 2-1/2 inches (REF)
-2: 2 inches (REF)
-3: 1-1/4 inch (REF)
THICKNESS (At thickest point of wings):
-1, -4: 0.110 inch ± 0.010 inch
-2, -3: 0.090 inch ± 0.005 inch

ATTACHING DEVICE:
-1: Attaching device shall be prong and wing clutch type.

-2: The prongs shall be located on the horizontal center line, equidistant from each end and the following distance apart. For -1 and -4: 1-3/4 inches ± 1/32 inch, -2: 1-1/2 inches ± 1/32 inch and -3: 7/8 inch ± 1/32 inch

NOTES:
1. The term (REF) refers to measurements taken from the Government furnished hub or die.

2. Piercing shall be as indicated.

3. A mock forcer may be used to bring up the design of the shield for -1, -2 and -4 only.

4. When specified in acquisition documents, an astronaut device may be embossed to the shield portion of the badge in accordance with MIL-DTL-3628/166 and TIOH drawing B-5-84.

5. -1, -2, and -3: Silver Plated Oxidized Buffed Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 14, May be used for commercial sale.

CHANGES FROM PREVIOUS ISSUE: The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2026-123)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:55Z
Check the source to verify that this is the current version before use.