INCH-POUND

A-A-59324
14 September 1998

COMMERCIAL ITEM DESCRIPTION

MAINTENANCE PLATFORM, SELF-PROPELLED, ELECTRIC

The General Services Administration has authorized the use of this commercial item description (CID) by all federal agencies.

1 SCOPE. The maintenance platform is civil engineering equipment for use in the inspection and maintenance of electrical, heating and ventilating utilities and Air Force buildings such as aircraft hangers.

2. SALIENT CHARACTERISTICS. The equipment shall be capable of operation and be bid sample tested within the accuracy, limits, and specifications herein.

2.1. Physical description. The maintenance platform shall be a standard commercial product except that minor changes may be made to comply with the requirements provided that significant performance, reliability, durability, and safety characteristics are not adversely affected.

2.1.1 Maintenance platform dimensions. The overall width of the unit shall be a maximum of 51 inches. The overall height of the unit with guardrails of the platform extended shall be 86 inches. The overall height with guardrails lowered shall be a maximum of 74 inches and the overall length of the unit shall be 91 inches maximum.

2.1.2 Platform. The platform size shall be a maximum of 48 inches by 89 inches and a minimum of 30 inches by 82 inches inside the toe boards. Safety bars shall be provided around the platform.

2.1.3 Height. The working heights shall be a minimum of 25 feet. The maximum platform height, as measured to the base floor to the bottom of the platform shall be 19 feet. The minimum platform height of the platform shall be 40 inches.

2.1.4 Weight. The weight of the maintenance platform shall be less than 3800 pounds.

2.1.5 Capacity. The unit shall have a maximum platform capacity of 1,000 pounds during lift operations up to a working height of 25 feet. The minimum cantilever cage or fold down deck capacity shall be 250 pounds.

2.1.6 Speed. The speed of the unit shall be from 0 to 2 miles per hour with the platform lowered and from 0 to 0.7 with the platform raised.

2.1.7 Power source. The unit shall be powered by a 24 volt DC battery pack with a 4 HD electric motor and four 220 ampere hour batteries. The battery charge shall be 25 amp and the battery duty cycle shall be 25% for 8 hours. Battery shelf life shall be 2 years. The unit shall be provided with a battery recharging unit capable of operating from 110/220 volt AC power outlet.

Beneficial comments, recommendations, additions, deletions, clarifications, Etc., and any data which may improve this document should be sent to: SA-ALC/TILDD, 485 Quentin Roosevelt Rd., Bldg. 171, Kelly AFB, TX 78241-6425, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 4940

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:10Z
Check the source to verify that this is the current version before use.

2.1.8 Lift system. The lift system shall be by means of hydraulic lift cylinder or chain operated mast system. The lift system shall be by means of 2 single stage lift cylinders.

2.1.9 Control system. Toggle switches shall provide control for all functions. The unit shall be controlled by means of a 2 speed lever or stick - forward and reverse.

2.1.10 Horizontal drive. The unit shall be powered by a dual front wheel hydraulic motor.

2.1.11 Tires. The tires shall be 16 inches diameter solid rubber with optional type of tires being 16.5 x 6.5 x 6 polyurethane filled. The wheel base shall be 63 inches maximum and 60 inches minimum.

2.1.12 Braking. Service brakes shall be automatically applied when the unit is not in the drive mode. Braking shall be spring applied, hydraulic release type parking brakes and shall hold on a 20% flat, smooth incline.

2.1.13 Mobility. The unit shall have an inside turning radius of 24 inches. The grade ability of the unit shall be a minimum of 25%.

2.1.14 Safety. Holding valves in the hydraulic-system shall maintain the work platform position in the event of power loss and shall have an auxiliary means of lowering and retracting the platform in the event of power loss. It shall meet the latest issue requirements of ANSI A92.6.

3. REGULATORY REQUIREMENT.

3.1 The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4. QUALITY ASSURANCE PROVISIONS.

4.1 Product conformance. The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards, and quality assurance practices and be the same product offered for sale in the commercial market. The Government reserves the right to require proof of such conformance.

4.2 Market acceptability. The unit shall be designed and constructed by a manufacturer with at least two years of experience in the manufacture and sale of the units. All workmanship and design shall conform to the applicable industrial standard.

5. PACKAGING.

5.1 Packaging. Preservation, packing, and marking shall be as specified in the contract or order.

6. NOTES.

6.1 Bid samples. The Government will request bid samples if the literature submitted does not appear to be adequate for acceptance. The contractor shall submit bid samples within 30 days after notification that their literature is not sufficient for acceptance. A 14 to 30 day evaluation of each bid sample will be made by SA-ALC/LDEE, Kelly AFB, TX 78241-5000.

6.2 Ordering data. Acquisition documents must specify the following:

a. Title, Number and date of this document.
b. Power source (see 2.1.2)
c. Lift System (see 2.1.8)
d. Control system (see 2.1.2

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:10Z
Check the source to verify that this is the current version before use.

e. Tires (see 2.1.11)
f. Packaging requirements, as specified (see 4.1)

6.3 Source of non-Government documents.

6.3.1 ANSI Standards are available from the American National Standards Institute, 11 West 42nd Street, New York, NY 10036.

MILITARY INTERESTS:

Custodians:
Air Force - 99
Army - AL

Review activities:
OSD – SO
AF-01

CIVIL AGENCY COORDINATING ACTIVITY:
GSA-FSS

Preparing Activity:
Air Force - 82

(Project No. 4940-0648)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:10Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	**1. DOCUMENT NUMBER** A-A-59324	**2. DOCUMENT DATE (YYMMDD)** 980914

3. DOCUMENT TITLE
MAINTENANCE PLATFORM, SELF-PROPELLED, ELECTRIC

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME *(Last, First, Middle Initial)*	b. Organization	
c. ADDRESS *(Include zip code)*	**d. TELEPHONE** *(Include Area Code)* (1) Commercial (2) DSN *(if applicable)*	**7. DATE SUBMITTED (YYMMDD)**

8. PREPARING ACTIVITY

a. NAME **San Antonio Air Logistics Center/TILDD**	**b. TELEPHONE** *(Include Area Code)* (1) Commercial **(210) 925-6314 (2) DSN 945-6314**
c. ADDRESS ***(Include Zip Code)*** **485 Quentin Roosevelt Rd., Bldg 171** **Kelly AFB, TX 78241-6524**	**IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:** **Defense Quality and Standardization Office** **5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466** **Telephone (703) 756-2340 DSN 289-2340**

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:10Z
Check the source to verify that this is the current version before use.